

TEST DATA OF EAC-06-□□□/ESC-06-□□□

Noise Filter

Nov. 30, 2010

Approved by : Toshio Watanabe Toshio Watanabe Design Manager

COSEL CO.,LTD.





CONTENTS

1.Attenuation Characteristics	1
2.Pulse Attenuation Characteristics	4
3.Leakage Current	6
4.Figure of Testing Circuitry	7

(Final Page 8)


COSEL





COSEL

COSEL

Model	EAC-06-□□□/ESC-06-□□□	Temperature Testing Circuitry	25°C Figure A
Item	Attenuation Characteristics		
Object	_____		



COSEL

COSEL



Model	EAC-06-□□□/ESC-06-□□□	Temperature Testing Circuitry Figure C
Item	Leakage Current	
Object	_____	

1. Results


[mA]

Model	Standards	Input Volt.				Note
		100 [V]	125 [V]	230 [V]	250 [V]	
EAC-06-681 ESC-06-681	UL1283	0.031	0.040	0.082	0.093	
EAC-06-102 ESC-06-102	UL1283	0.044	0.056	0.110	0.120	
EAC-06-222 ESC-06-222	UL1283	0.090	0.120	0.230	0.250	
EAC-06-332 ESC-06-332	UL1283	0.130	0.170	0.340	0.370	
EAC-06-472 ESC-06-472	UL1283	0.190	0.240	0.480	0.520	

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL



Attenuation = $20\log(U_{01}/U_{02})$ [dB]
 U_{01} : Voltage in state without filters
 U_{02} : Voltage in state which added filters
N.A. : Network Analyzer




Figure A - 1 Differential mode attenuation measurement



Attenuation = $20\log(U_{01}/U_{02})$ [dB]
 U_{01} : Voltage in state without filters
 U_{02} : Voltage in state which added filters
N.A. : Network Analyzer




Figure A - 2 Common mode attenuation measurement

COSEL




Figure B Pulse attenuation measurement




Figure C Leakage current measurement (UL1283)