

DATA SHEET		Date	May.21,2001
Model	CDS600	Temp.	25 °C
Test	Vibration/impact test 振動・衝撃試験	Humid.	45 %Rh
		Tested by	H.Nakayama

  

1. Method  
Vibration/impact test complies with JIS C 0911 (Vibration), JIS C 0912 (Impact)  
JIS C 0911 (振動), JIS C 0912 (衝撃) に準ずる
  
2. Conditions
  - (1) Vibration : 10～55 Hz  
振動 3 minutes period  
1 hour each X,Y and Z axis
  
  - (2) Impact : 11mS  
衝撃 once each X, Y and Z axis
  
3. Conditions of Acceptability
  - (1) No degradation of performance or loss of function after test.  
試験後、諸機能が正常であること
  
  - (2) No remakably damage of appearance.  
外観上著しい損傷がないこと
  
  - (3) No looseness or a crack at solder joint.  
はんだ付け、圧着など電氣的接合部分にクラックや緩みの発生がないこと
  
4. Result
  - (1) Vibration limit test
 

No.	Gravity [m/s <sup>2</sup> ]	Result	Note
1	49.0	OK	
2	—	—	

All are satisfactory to item 3:      OK
  
  - (2) Impact test
 

No.	Gravity [m/s <sup>2</sup> ]	Result	Note
1	196.1	OK	
2	—	—	

All are satisfactory to item 3:      OK