

DATA SHEET		Date	Jul.13,1999
Model	DBS400B03	Temp.	25 °C
Test	Vibration/Impact test 振動・衝撃試験	Humid.	45 %Rh
		Tested by	H.Senda

1. Method

Vibration/impact test complies with JIS C 0911 (Vibration), JIS C 0912 (Impact)
JIS C 0911(振動), JIS C 0912(衝撃)に準ずる

2. Conditions

- (1) Vibration : 10~55 Hz
振動 3 minutes period
1 hour each X, Y and Z axis
- (2) Impact : 11mS
衝撃 once each X, Y and Z axis

3. Conditions of Acceptability

- (1) No degradation of performance or loss of function after test.
試験後、諸機能が正常であること
- (2) No remarkably damage of appearance.
外観上著しい損傷がないこと
- (3) No looseness or a crack at solder joint.
はんだ付け、圧着など電氣的接合部分にクラックや緩みの発生がないこと

4. Result

(1) Vibration limit test

No.	Gravity [m/S ²]	Result	Note
1	49.0 (5G)	OK	
2	—	—	

All are satisfactory to item 3: OK

(2) Impact test

No.	Gravity [m/S ²]	Result	Note
1	196.1 (20G)	OK	
2	—	—	

All are satisfactory to item 3: OK