



M T B F

(E I A J R C R - 9 1 0 2)

| | |
|-------|------------|
| Model | FSB-40-693 |
|-------|------------|

| No. | P a r t s | | Q' ty of Device | Failure rate [$10^{-6}/H$] | Re f e r e n c e |
|------------------------------------|---|------------|-----------------|------------------------------|------------------|
| 1 | I C | Monolithic | 0 | 0.0000 | |
| 2 | | Hybrid | 0 | 0.0000 | |
| 3 | T r a n s i s t o r s | | 0 | 0.0000 | |
| 4 | D i o d e s | | 0 | 0.0000 | |
| 5 | LED·Optocouplers | | 0 | 0.0000 | |
| 6 | R e s i s t o r s | | 9 | 0.0279 | |
| 7 | C a p a c i t o r s | | 16 | 0.1328 | |
| 8 | T r a n s f o r m e r · C h o k e C o i l | | 2 | 0.0460 | |
| 9 | C o n n e c t o r s | | 102 | 0.4358 | |
| 10 | O t h e r s | | 1 | 0.0030 | |
| Total Failure Rate [$10^{-6}/H$] | | | | 0.6455 | |

| | | |
|---------------------|------|-----------|
| M T B F | [H] | 1,549,000 |
| Ambient Temperature | [°C] | — |
| Load Factor | [%] | — |