



# M T B F

(EIAJ RCR-9102B)

Model	GT3.5W-12
-------	-----------

No.	Parts	Q'ty of Device	Failure rate [10 <sup>-6</sup> /H]	Reference
1	IC Linear	4	0.0960	
2	Transistors NPN/PNP	0	0.0000	
3	Transistors Power NPN/PNP	2	0.0840	
4	FET MOS FET	2	0.1980	
5	Diodes FR	6	0.1320	
6	Diodes Zener	4	0.0960	
7	Diodes bridge	4	0.2640	
8	Resistors Metal Film	35	0.5600	
9	Resistors Power Film	6	0.2460	
10	Resistors variable	2	0.0320	
11	Capacitors Aluminum Electrolytic	16	0.3040	
12	Capacitors Film	10	0.0840	
13	Transformer Power	1	0.3600	
14	Fuses	3	0.0600	
15	Connectors Printed Circuit Board	7	0.3640	
16	Connection Hand Solder	29	0.0754	
17	Connection Flow Solder	318	0.1654	
18	Connection Crimp	35	0.0217	
19	Connection Screw	10	0.0100	
20	Printed Circuit Board Through Hole	4	0.1800	
Total Failure Rate [10 <sup>-6</sup> /H]			3.3325	

M T B F	[H]	300,000
Ambient Temperature	[°C]	-
Load Factor	[%]	-