

Temperature increase of main components: 主要部品温度上昇

Model: GT3W

1. Conditions

- (1) Input :AC 90 ~ 110 [V]
- (2) Output :Rated output
- (3) Mounting method :Shown as Fig.1.1

2. Result

No.	Parts name	Symbol No.	Increase (ΔT)						Rated temp. [°C]	Reference
			[deg]							
			±12	±15						
1	Rectifier(Main-Input)	SS1	64	56				150	Junction Temp.	
2	Rectifier(Sub-Input)	SS21	23	21				150	Junction Temp.	
3	Transformer	T1	41	39				120		
4	Input Capacitor(Main)	C2	27	24				105		
5	Input Capacitor(Sub)	C21	24	22				105		
6	Fet(Main)	TR1	42	39				150	Junction Temp.	
7	Transistor(Sub)	TR21	28	27				150	Junction Temp.	
8	Voltage Regulator	IC21	27	25				150	Junction Temp.	
9	Power Control Ic	IC22	38	35				150	Junction Temp.	
10	Output Capacitor	C4	23	22				105		
11										
12										
13										
14										
15										
16										
17										
18										
19										
20										




Fig.1.1 Mounting method (Normal position)

*All information presented herein are not guaranteed.
 *本資料は参考資料であり、その内容を保証するものではありません。