



M T B F

(EIAJ RCR-9102)

| | |
|-------|-----------|
| Model | LCA15S-24 |
|-------|-----------|

| No. | P a r t s | | Q'ty of Device | Failure rate [$10^{-6}/H$] | Reference |
|------------------------------------|------------------------|------------|----------------|------------------------------|-----------|
| 1 | I C | Monolithic | 1 | 0.0240 | |
| 2 | | Hybrid | 0 | 0.0000 | |
| 3 | T r a n s i s t o r s | | 2 | 0.1001 | |
| 4 | D i o d e s | | 7 | 0.2135 | |
| 5 | LED·Optocouplers | | 1 | 0.0700 | |
| 6 | R e s i s t o r s | | 17 | 0.4536 | |
| 7 | C a p a c i t o r s | | 12 | 0.1828 | |
| 8 | Transformer·Choke Coil | | 3 | 0.0690 | |
| 9 | C o n n e c t o r s | | 116 | 0.0598 | |
| 10 | O t h e r s | | 4 | 0.0650 | |
| Total Failure Rate [$10^{-6}/H$] | | | | 1.2378 | |

| | | |
|---------------------|------|---------|
| M T B F | [H] | 808,000 |
| Ambient Temperature | [°C] | — |
| Load Factor | [%] | — |