



Certificate of Compliance

Certificate: 1075041

Master Contract: 174688

Project: 80061533

Date Issued: November 19, 2020

Issued to: Cosel Co., Ltd.
1-6-43 Kamiakae-machi
Toyama-shi, Toyama 930-0816
JAPAN
Attention: Mr. Shinichi Yokoyama

The products listed below are eligible to bear the CSA Mark shown



Issued by:

Masato Endo

PRODUCTS

CLASS 5311 11 - POWER SUPPLIES - Component Type (CSA 60950-1-07-2nd Ed)

Model LDC60F-1, level 3, Input rated: 100-240Vac, 1.4A or 110-370Vdc 0.8A, 50-60Hz;
Output rated (dc): 5V, 5A; +12V, 2.5A; -12Vdc 0.5A.

Model LDC60F-2, level 3, Input rated: 100-240Vac, 1.4A or 110-370Vdc 0.8A, 50-60Hz;
Output rated (dc): 5V, 5A; +15V, 2.0A; -15Vdc 0.5A.

Model LDC60F-1-SXYMH, level 3, Input rated: 100-240Vac, 1.4A or 110-370Vdc 0.8A, 50-60Hz;
Output rated (dc): 5V, 5A; +12V, 2.5A; -12Vdc 0.5A.

Model LDC60F-2-SXYMH, level 3, Input rated: 100-240Vac, 1.4A or 110-370Vdc 0.8A, 50-60Hz;
Output rated (dc): 5V, 5A; +15V, 2.5A; -12Vdc 0.5A.

Notes:

1. Component type power supplies for use with Information Technology and Electrical Business Equipment where the suitability of the combination is determined by the CSA International.
2. Evaluation for Resistance to Abnormal Heat (Ball Pressure) Test, Continuity Test and Limited Short-circuit Test shall be performed in the end equipment.

Model LDC60F-1,-2 only

3. May be followed by suffix S or SN or G. Suffix "S" indicates optional chassis provided. Suffix "SN" indicates optional chassis and cover provided.
4. Suffix "G" indicates capacitors C104, C105, rated 250V, 470pF.



Certificate: 1075041
Project: 80061533

Master Contract: 174688
Date Issued: November 19, 2020

APPLICABLE REQUIREMENTS

- CAN/CSA C22.2 No. 0-M91 - General Requirements - Canadian Electrical Code, Part II
- No 0.4 M1982 - Bonding and Grounding of Electrical Equipment (Protective Grounding)
- CAN/CSA C22.2 No. 60950-1-07 - Information Technology Equipment - Safety - Part 1: General Requirements