



M T B F

(E I A J R C R - 9 1 0 2)

| | |
|-------|------------|
| Model | LHA100F-12 |
|-------|------------|

| No. | P a r t s | | Q'ty of Device | Failure rate [$10^{-6}/H$] | Reference |
|------------------------------------|------------------------|------------|----------------|------------------------------|-----------|
| 1 | I C | Monolithic | 4 | 0.1460 | |
| 2 | | Hybrid | 0 | 0.0000 | |
| 3 | T r a n s i s t o r s | | 12 | 0.6985 | |
| 4 | D i o d e s | | 31 | 0.4540 | |
| 5 | LED·Optocouplers | | 2 | 0.1400 | |
| 6 | R e s i s t o r s | | 106 | 0.3906 | |
| 7 | C a p a c i t o r s | | 60 | 0.5380 | |
| 8 | Transformer·Choke Coil | | 7 | 0.1610 | |
| 9 | C o n n e c t o r s | | 429 | 0.0928 | |
| 10 | O t h e r s | | 4 | 0.1580 | |
| Total Failure Rate [$10^{-6}/H$] | | | | 2.7789 | |

| | | |
|---------------------|------|---------|
| M T B F | [H] | 360,000 |
| Ambient Temperature | [°C] | — |
| Load Factor | [%] | — |