



M T B F

(E I A J R C R - 9 1 0 2)

| | |
|-------|-----------|
| Model | MHFS61205 |
|-------|-----------|

| No. | P a r t s | | Q'ty of Device | Failure rate [$10^{-6}/H$] | Reference |
|------------------------------------|------------------------|------------|----------------|------------------------------|-----------|
| 1 | I C | Monolithic | 3 | 0.0720 | |
| 2 | | Hybrid | 0 | 0.0000 | |
| 3 | T r a n s i s t o r s | | 6 | 0.2024 | |
| 4 | D i o d e s | | 11 | 0.2350 | |
| 5 | LED•Optocouplers | | 1 | 0.0700 | |
| 6 | R e s i s t o r s | | 33 | 0.3264 | |
| 7 | C a p a c i t o r s | | 22 | 0.1628 | |
| 8 | Transformer•Choke Coil | | 3 | 0.0460 | |
| 9 | C o n n e c t o r s | | 72 | 0.0097 | |
| 10 | O t h e r s | | 2 | 0.2200 | |
| Total Failure Rate [$10^{-6}/H$] | | | | 1.3443 | |

| | | |
|---------------------|------|---------|
| M T B F | [H] | 744,000 |
| Ambient Temperature | [°C] | — |
| Load Factor | [%] | — |