



PJMA1000F series Reliability test results

Feb 1, 2021
DESIGN DEPT.

Approved : Takashi Kajii

Prepared : Akihisa Mukai

No.	Test Item	Testing conditions	Conditions of acceptability	Number of samples	Number of failures
1	Heat cycle test	(1) -40° C ~ 125° C 30minutes each (2) 800cycles	(1)No degradation of electric characteristics after test.	1	0
2	High temperature/ High humidity bias test	(1) Ta=85°C, RH=85% (2) At rated input (3) Load 0% (4) 1000hours	(1)No degradation of electric characteristics after test.	1	0
3	Vibration test	(1) f=10~150Hz, 29.4m/s ² (5G) (2) 3minutes period (3) 60minutes each X, Y and Z axis	(1)No degradation of electric characteristics after test. (2)No crack at solder joint. (3)No mechanical damage of appearance.	3	0
4	Impact test	(1) 294.2m/s ² (30G), 11ms (2) Once each X, Y and Z axis	(1)No degradation of electric characteristics after test. (2)No crack at solder joint. (3)No thermal damage of appearance.	3	0
5	Static electricity immunity test	(1) Applied voltage ±8kV (2) At rated input and load	(1)No protection circuit fail. (2)No output voltage drop with control circuit fail. (3)No any other function fail.	1	0