



M T B F

(E I A J R C R - 9 1 0 2)

| | |
|-------|-------------|
| Model | SFLS15481R2 |
|-------|-------------|

| No. | P a r t s | | Q' ty of Device | Failure rate [$10^{-6}/H$] | Reference |
|------------------------------------|------------------------|------------|-----------------|------------------------------|-----------|
| 1 | I C | Monolithic | 2 | 0.0390 | |
| 2 | | Hybrid | 0 | 0.0000 | |
| 3 | T r a n s i s t o r s | | 23 | 0.8085 | |
| 4 | D i o d e s | | 20 | 0.2820 | |
| 5 | LED·Optocouplers | | 0 | 0.0000 | |
| 6 | R e s i s t o r s | | 92 | 0.0184 | |
| 7 | C a p a c i t o r s | | 43 | 0.3182 | |
| 8 | Transformer·Choke Coil | | 2 | 0.0460 | |
| 9 | C o n n e c t o r s | | 462 | 0.0636 | |
| 10 | O t h e r s | | 1 | 0.1100 | |
| Total Failure Rate [$10^{-6}/H$] | | | | 1.6857 | |

| | | |
|---------------------|------|---------|
| M T B F | [H] | 594,000 |
| Ambient Temperature | [°C] | — |
| Load Factor | [%] | — |