



M T B F

(EIAJ RCR-9102)

| | |
|-------|----------|
| Model | ZUW62415 |
|-------|----------|

| No. | P a r t s | | Q'ty of Device | Failure rate [$10^{-6}/H$] | Reference |
|------------------------------------|------------------------|------------|----------------|------------------------------|-----------|
| 1 | I C | Monolithic | 0 | 0.0000 | |
| 2 | | Hybrid | 0 | 0.0000 | |
| 3 | T r a n s i s t o r s | | 5 | 0.0873 | |
| 4 | D i o d e s | | 14 | 0.2040 | |
| 5 | LED·Optocouplers | | 1 | 0.0700 | |
| 6 | R e s i s t o r s | | 21 | 0.0042 | |
| 7 | C a p a c i t o r s | | 13 | 0.0892 | |
| 8 | Transformer·Choke Coil | | 4 | 0.0920 | |
| 9 | C o n n e c t o r s | | 140 | 0.0193 | |
| 10 | O t h e r s | | 2 | 0.1300 | |
| Total Failure Rate [$10^{-6}/H$] | | | | 0.6960 | |

| | | |
|---------------------|------|-----------|
| M T B F | [H] | 1,440,000 |
| Ambient Temperature | [°C] | — |
| Load Factor | [%] | — |