

# Industrial Computer ATX Series



## 600W/750W/850W Multiple Output Active PFC Data Sheet

For the latest revision, please visit [power.liteon.com](http://power.liteon.com)

### Description

This is a high-power factor (PF), multiple-output AC to DC switching mode power supply unit which can provide up to 600/750/850 watts continuous with forced cooling by a smart FSC (fan speed control) circuitry. There is a built-in auxiliary converter (5VSB) for better energy saving. It complies with 80+gold as well as worldwide safety and EMC regulations (refer to details below). It is suitable for various industrial PC applications.

### Features

- \* Full AC input voltage range design.
- \* High power factor and less fictitious power.
- \* Withstand 300Vac surge voltage for 5 seconds.
- \* Full Protections: Short-circuit/ Over-voltage/ Over-current/ Over temperature.
- \* INTEL® standard ATX form factor.
- \* Meet 80+gold and support 200% peak power (note#6).
- \* IEC/EN 62368-1 design compliance.
- \* Up to 5000 meters operating altitude (note#4)
- \* High efficiency and high reliability.
- \* REM\_ON/OFF and PWR\_OK signal



### Electrical Specification

Model Name	PS-5601-60LG / PS-5751-60LG / PS-5851-60LG				
Output					
Rated power	600W / 750W / 850W				
Rated voltage	12V	5V	3.3V	-12V	5Vsb
Rated current	50A/62.5A/70.8A	20A	20A	0.3A	3A
Ripple & Noise(max.) (note #2)	120mV	50mV	50mV	120mV	50mV
Line & load regulation	±5%	±5%	±5%	±10%	±5%
Hold-up time(typ.) (note #5)	16ms				
Timing: AC ON delay / rising (max.)	2 sec / 20ms				
Input					
Rated voltage range	100~240Vac				
Operated voltage range	90~264Vac, 300Vac for 5 sec				

Current range (max.)	8A/100Vac (600W); 10A/100Vac (750W); 10A/100Vac (850W)
Inrush current	No component damaged ( $<I^2 \cdot t$ ).
Frequency range	50-60Hz
Leakage current (max.)	3.5mA at 240Vac
Efficiency (min.)	87% - 90% - 87% (at 20% - 50% - 100% of rated loading)
Standby power saving (min.)	Pin<1W at 5Vsb/0.1A Pin<0.5W at Po=0.25W (at REM_OFF, efficiency>50%)
<b>Protection Function</b>	
Over voltage (max.)	140% of rated voltage, latch-off protection (for +12V/+5V/+3.3V)
Over current (max.)	Latch-off protection (for +12V/+5V/+3.3V)
Short circuit at O/P	Latch-off protection (for +12V/+5V/+3.3V)
Over temperature	Latch-off protection
<b>Others</b>	
MTBF (min.) (note#3)	700K hours @ rated load
<b>Environment</b>	
Temperature (note#5)	(operating) 0~40°C / (storage) -40~85°C
Humidity	(operating) 10~90% RH non-condensing / (storage) 5~95% RH
Altitude (max.)	5000 meters
<b>Mechanical</b>	
Dimension	150(L)*140(W)*86(H) mm
Vibration	10~500 Hz, 5G 20min./1cycle per axis for all axes (X, Y, Z)
Weight (typ.)	1.9kg
<b>Safety</b>	
Standard	CB/IEC62368-1,TUV62368-1,UL62368-1,EN62368-1
Withstand voltage	Input-Output: 4242VDC / Input-FG: 2150VDC
Isolation resistance(min.)	Input-Output: 100Mohm @ 500VDC, 25°C, 70%RH
<b>EMC</b>	
EN55032 (CISPR32)	Conducted EMI: class B / Radiated EMI: class B
FCC	Conducted EMI: class B / Radiated EMI: class B
EN61000-3-2	Harmonic distortion: Class D
EN61000-4-2	ESD: ±8KV contact discharge / ±15KV contact discharge
EN61000-4-3	Radiated RF immunity: 3V/m
EN61000-4-4	EFT: ±1KV (AC port)
EN61000-4-5	Surge: ±1KV DM / ±2KV CM
EN61000-4-6	Conducted RF immunity: 3V/m
EN61000-4-8	Magnetic field immunity: 3A/m
EN61000-4-11	Voltage dip immunity

## Notes

#1: All specification defined at 230Vac/50Hz, rated power and 25°C ambient temperature if not mentioned specifically.

#2: Ripple noise is measured with 0.1uF MLCC & 10uF low ESR capacitor.

#3: Calculated by Telcordia SR332 at 25°C ambient temperature.

#4: When operating altitude is higher than 2000m, the environment temperature derating factor is  $0.36^{\circ}\text{C}/100\text{m}$ .

#5: Hold up time will be evaluated at 80% of rated load.

#6: With 12V-2x6 connector, it can support 200% peak power. Without 12V-2x6 connector, it can support 150% peak power.

## Mechanical Specification

