

適合ハーネス一覧

機種名	ハーネス型番	用途
FEシリーズ	H-SN-47	CN1、CN2の機能を全て使う場合に使用（片側ハウジング）
	H-SN-55	CN1、CN2の機能を全て使う場合に使用（両側ハウジング）
	H-PA-12	並列運転する場合に使用
	H-PA-13	並列運転を行い、CN1、CN2の機能を使う場合に使用

標準価格(税抜)

<p>●型番 <b>H-SN-47</b> ハウジング： PUDP-12V-S （日本圧着端子） 接 触 子： SPUD-002T-P0.5 （日本圧着端子） 質 量： 13g max</p>	<p>●形状</p>	<p>●使用電線</p> <table border="1"> <thead> <tr> <th>コネクタ ピン 番号</th> <th>電線番号</th> <th>AWG</th> <th>色</th> <th>長さ ℓ [mm]</th> </tr> </thead> <tbody> <tr><td>1</td><td>UL1061</td><td>28</td><td>白</td><td>500</td></tr> <tr><td>2</td><td>UL1061</td><td>28</td><td>桃</td><td>500</td></tr> <tr><td>3</td><td>UL1061</td><td>28</td><td>茶</td><td>500</td></tr> <tr><td>4</td><td>UL1061</td><td>28</td><td>黄</td><td>500</td></tr> <tr><td>5</td><td>UL1061</td><td>28</td><td>灰</td><td>500</td></tr> <tr><td>6</td><td>UL1061</td><td>28</td><td>橙</td><td>500</td></tr> <tr><td>7</td><td>UL1061</td><td>28</td><td>紫</td><td>500</td></tr> <tr><td>8</td><td>UL1061</td><td>28</td><td>赤</td><td>500</td></tr> <tr><td>9</td><td>UL1061</td><td>28</td><td>黒</td><td>500</td></tr> <tr><td>10</td><td>UL1061</td><td>28</td><td>青</td><td>500</td></tr> <tr><td>11</td><td>UL1061</td><td>28</td><td>黄</td><td>500</td></tr> <tr><td>12</td><td>UL1061</td><td>28</td><td>緑</td><td>500</td></tr> </tbody> </table>	コネクタ ピン 番号	電線番号	AWG	色	長さ ℓ [mm]	1	UL1061	28	白	500	2	UL1061	28	桃	500	3	UL1061	28	茶	500	4	UL1061	28	黄	500	5	UL1061	28	灰	500	6	UL1061	28	橙	500	7	UL1061	28	紫	500	8	UL1061	28	赤	500	9	UL1061	28	黒	500	10	UL1061	28	青	500	11	UL1061	28	黄	500	12	UL1061	28	緑	500	<p>¥400</p>
コネクタ ピン 番号	電線番号	AWG	色	長さ ℓ [mm]																																																																
1	UL1061	28	白	500																																																																
2	UL1061	28	桃	500																																																																
3	UL1061	28	茶	500																																																																
4	UL1061	28	黄	500																																																																
5	UL1061	28	灰	500																																																																
6	UL1061	28	橙	500																																																																
7	UL1061	28	紫	500																																																																
8	UL1061	28	赤	500																																																																
9	UL1061	28	黒	500																																																																
10	UL1061	28	青	500																																																																
11	UL1061	28	黄	500																																																																
12	UL1061	28	緑	500																																																																
<p>●型番 <b>H-SN-55</b> ハウジング： PUDP-12V-S （日本圧着端子） 接 触 子： SPUD-002T-P0.5 （日本圧着端子） チューブ： E-651U-1 （ニッカン工業） 質 量： 12g max</p>	<p>●形状</p>	<p>●使用電線</p> <table border="1"> <thead> <tr> <th>コネクタ ピン 番号</th> <th>電線番号</th> <th>AWG</th> <th>色</th> <th>長さ ℓ [mm]</th> </tr> </thead> <tbody> <tr><td>1</td><td>UL10368</td><td>28</td><td>赤</td><td>200</td></tr> <tr><td>2</td><td>UL10368</td><td>28</td><td>白</td><td>200</td></tr> <tr><td>3</td><td>UL10368</td><td>28</td><td>白</td><td>200</td></tr> <tr><td>4</td><td>UL10368</td><td>28</td><td>白</td><td>200</td></tr> <tr><td>5</td><td>UL10368</td><td>28</td><td>白</td><td>200</td></tr> <tr><td>6</td><td>UL10368</td><td>28</td><td>白</td><td>200</td></tr> <tr><td>7</td><td>UL10368</td><td>28</td><td>白</td><td>200</td></tr> <tr><td>8</td><td>UL10368</td><td>28</td><td>白</td><td>200</td></tr> <tr><td>9</td><td>UL10368</td><td>28</td><td>白</td><td>200</td></tr> <tr><td>10</td><td>UL10368</td><td>28</td><td>白</td><td>200</td></tr> <tr><td>11</td><td>UL10368</td><td>28</td><td>白</td><td>200</td></tr> <tr><td>12</td><td>UL10368</td><td>28</td><td>白</td><td>200</td></tr> </tbody> </table>	コネクタ ピン 番号	電線番号	AWG	色	長さ ℓ [mm]	1	UL10368	28	赤	200	2	UL10368	28	白	200	3	UL10368	28	白	200	4	UL10368	28	白	200	5	UL10368	28	白	200	6	UL10368	28	白	200	7	UL10368	28	白	200	8	UL10368	28	白	200	9	UL10368	28	白	200	10	UL10368	28	白	200	11	UL10368	28	白	200	12	UL10368	28	白	200	<p>¥800</p>
コネクタ ピン 番号	電線番号	AWG	色	長さ ℓ [mm]																																																																
1	UL10368	28	赤	200																																																																
2	UL10368	28	白	200																																																																
3	UL10368	28	白	200																																																																
4	UL10368	28	白	200																																																																
5	UL10368	28	白	200																																																																
6	UL10368	28	白	200																																																																
7	UL10368	28	白	200																																																																
8	UL10368	28	白	200																																																																
9	UL10368	28	白	200																																																																
10	UL10368	28	白	200																																																																
11	UL10368	28	白	200																																																																
12	UL10368	28	白	200																																																																
<p>●型番 <b>H-PA-12</b> ハウジング： PUDP-12V-S （日本圧着端子） 接 触 子： SPUD-002T-P0.5 （日本圧着端子） 質 量： 5g max</p>	<p>●形状</p>	<p>●使用電線</p> <table border="1"> <thead> <tr> <th>コネクタ ピン 番号</th> <th>電線番号</th> <th>AWG</th> <th>色</th> <th>長さ ℓ [mm]</th> </tr> </thead> <tbody> <tr><td>1</td><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>2</td><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>3</td><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>4</td><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>5</td><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>6</td><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>7</td><td>UL1061</td><td>28</td><td>紫</td><td>210</td></tr> <tr><td>8</td><td>UL1061</td><td>28</td><td>赤</td><td>210</td></tr> <tr><td>9</td><td>UL1061</td><td>28</td><td>黒</td><td>210</td></tr> <tr><td>10</td><td>UL1061</td><td>28</td><td>青</td><td>210</td></tr> <tr><td>11</td><td>UL1061</td><td>28</td><td>黄</td><td>210</td></tr> <tr><td>12</td><td>UL1061</td><td>28</td><td>緑</td><td>210</td></tr> </tbody> </table>	コネクタ ピン 番号	電線番号	AWG	色	長さ ℓ [mm]	1	—	—	—	—	2	—	—	—	—	3	—	—	—	—	4	—	—	—	—	5	—	—	—	—	6	—	—	—	—	7	UL1061	28	紫	210	8	UL1061	28	赤	210	9	UL1061	28	黒	210	10	UL1061	28	青	210	11	UL1061	28	黄	210	12	UL1061	28	緑	210	<p>¥400</p>
コネクタ ピン 番号	電線番号	AWG	色	長さ ℓ [mm]																																																																
1	—	—	—	—																																																																
2	—	—	—	—																																																																
3	—	—	—	—																																																																
4	—	—	—	—																																																																
5	—	—	—	—																																																																
6	—	—	—	—																																																																
7	UL1061	28	紫	210																																																																
8	UL1061	28	赤	210																																																																
9	UL1061	28	黒	210																																																																
10	UL1061	28	青	210																																																																
11	UL1061	28	黄	210																																																																
12	UL1061	28	緑	210																																																																
<p>●型番 <b>H-PA-13</b> ハウジング： PUDP-12V-S （日本圧着端子） 接 触 子： SPUD-002T-P0.5 （日本圧着端子） 質 量： 16g max</p>	<p>●形状</p> <p>※CN1、CN2のコネクタピン番号1～6の ハーネス先端は開放 ※CN1のコネクタピン番号7～12はCN2の 同一番号コネクタピンとハーネスで接続</p>	<p>●使用電線</p> <table border="1"> <thead> <tr> <th>コネクタ ピン 番号</th> <th>電線番号</th> <th>AWG</th> <th>色</th> <th>長さ ℓ [mm]</th> </tr> </thead> <tbody> <tr><td>1</td><td>UL1061</td><td>28</td><td>白</td><td>500</td></tr> <tr><td>2</td><td>UL1061</td><td>28</td><td>桃</td><td>500</td></tr> <tr><td>3</td><td>UL1061</td><td>28</td><td>茶</td><td>500</td></tr> <tr><td>4</td><td>UL1061</td><td>28</td><td>黄</td><td>500</td></tr> <tr><td>5</td><td>UL1061</td><td>28</td><td>灰</td><td>500</td></tr> <tr><td>6</td><td>UL1061</td><td>28</td><td>橙</td><td>500</td></tr> <tr><td>7</td><td>UL1061</td><td>28</td><td>紫</td><td>210</td></tr> <tr><td>8</td><td>UL1061</td><td>28</td><td>赤</td><td>210</td></tr> <tr><td>9</td><td>UL1061</td><td>28</td><td>黒</td><td>210</td></tr> <tr><td>10</td><td>UL1061</td><td>28</td><td>青</td><td>210</td></tr> <tr><td>11</td><td>UL1061</td><td>28</td><td>黄</td><td>210</td></tr> <tr><td>12</td><td>UL1061</td><td>28</td><td>緑</td><td>210</td></tr> </tbody> </table>	コネクタ ピン 番号	電線番号	AWG	色	長さ ℓ [mm]	1	UL1061	28	白	500	2	UL1061	28	桃	500	3	UL1061	28	茶	500	4	UL1061	28	黄	500	5	UL1061	28	灰	500	6	UL1061	28	橙	500	7	UL1061	28	紫	210	8	UL1061	28	赤	210	9	UL1061	28	黒	210	10	UL1061	28	青	210	11	UL1061	28	黄	210	12	UL1061	28	緑	210	<p>¥500</p>
コネクタ ピン 番号	電線番号	AWG	色	長さ ℓ [mm]																																																																
1	UL1061	28	白	500																																																																
2	UL1061	28	桃	500																																																																
3	UL1061	28	茶	500																																																																
4	UL1061	28	黄	500																																																																
5	UL1061	28	灰	500																																																																
6	UL1061	28	橙	500																																																																
7	UL1061	28	紫	210																																																																
8	UL1061	28	赤	210																																																																
9	UL1061	28	黒	210																																																																
10	UL1061	28	青	210																																																																
11	UL1061	28	黄	210																																																																
12	UL1061	28	緑	210																																																																