



EXTRA TEST DATA OF AEA600F-32

Regulated DC Power Supply
Apr, 11, 2023

COSEL CO.,LTD.






CONTENTS

1.Inrush Current (enlargement)	1
2.Dynamic Line Regulation	2
3.Hiccup cycle (by Overcurrent Protection)	3
4.Power Consumption (by Input Voltage)	4
5.Figure of Testing Circuitry	5

(Final Page 5)




COSEL

Model	AEA600F-32	Temperature	25°C
Item	Inrush Current (enlargement)	Testing Circuitry	A
Object	<hr/>		






COSEL

Model	AEA600F-32	Temperature Testing Circuitry Object	25°C A
Item	Dynamic Line Regulation		
Object	_____		




COSEL

Model	AEA600F-32	Temperature Testing Circuitry A	25°C
Item	Hiccup cycle (by Overcurrent Protection)		
Object	_____		
Load	: Short		

Output Current
[25A/div]Output Current
[25A/div]

COSEL

Model	AEA600F-32	Temperature	25°C													
Item	Input voltage - Power consumption	Testing Circuitry	-													
Object	_____	Load	: 0%													
1.Graph			2.Values													
 <p>The graph plots Power consumption [W] on the Y-axis (0.00 to 5.00) against Input Voltage [V] on the X-axis (50 to 300). The data points show a U-shaped curve, indicating minimum power consumption around 230V.</p> <table><thead><tr><th>Input Voltage [V]</th><th>Power consumption [W]</th></tr></thead><tbody><tr><td>85</td><td>4.11</td></tr><tr><td>100</td><td>3.21</td></tr><tr><td>115</td><td>3.63</td></tr><tr><td>200</td><td>3.26</td></tr><tr><td>230</td><td>3.18</td></tr><tr><td>264</td><td>3.25</td></tr></tbody></table>			Input Voltage [V]	Power consumption [W]	85	4.11	100	3.21	115	3.63	200	3.26	230	3.18	264	3.25
Input Voltage [V]	Power consumption [W]															
85	4.11															
100	3.21															
115	3.63															
200	3.26															
230	3.18															
264	3.25															

Reducing standby power is possible by OFF signal
of the remote control.


COSEL

Figure A