



DATA SHEET		Date	14-Jan-21
Model	AEA600F-36	Temp.	25 degreeC
Test	EMI	Humid.	40 %RH
	Line conduction & Radiated emission	Tested by	M.Tosu




Frequency MHz	Line	Level dB(μV)		Limit dB(μV)		Margin dB		Pass/Fail	Remark
		QP	AV	QP	AV	QP	AV		
18.707	N	47.7	38.6	60	50	12.3	11.4	Pass	
18.835	L1	48.4	38.9	60	50	11.6	11.1	Pass	




Frequency MHz	Polarization	Stability	Level dB(μV/m)	Limit dB(μV/m)	Margin dB	Pass/Fail	Height cm	Angle deg	Remark
			QP	QP	QP				
131.887	H	Stable	27.4	40	12.6	Pass	200	359.7	
116.64	V	Stable	28.5	40	11.5	Pass	100	308.2	

DATA SHEET		Date	14-Jan-21
Model	Circuit used for measurement	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	40 %RH
		Tested by	M.Tosu

1. Line conduction



2. Radiated emission




Conditions

Test : EMI

Model Name : AEA600F

○Photographs of Test Set-Up

1.LINE CONDUCTION



2.RADIATED EMISSION

