

# TEST DATA OF BRFS150

Regulated DC Power Supply  
February 20, 2018

Approved by : Yoshimichi Hirokawa  
Yoshimichi Hirokawa                                  Design Manager

Prepared by : Yohei Urayama  
Yohei Urayama                                  Design Engineer

**COSEL CO.,LTD.**

## CONTENTS


1.Input Current (by Input Voltage) . . . . .	1
2.Input Current (by Load Current) . . . . .	2
3.Input Power (by Load Current) . . . . .	3
4.Efficiency (by Input Voltage) . . . . .	4
5.Efficiency (by Load Current) . . . . .	5
6.Line Regulation . . . . .	6
7.Load Regulation . . . . .	7
8.Dynamic Load Response . . . . .	8
9.Ripple Voltage (by Load Current) . . . . .	9
10.Ripple-Noise . . . . .	10
11.Ripple Voltage (by Ambient Temperature) . . . . .	11
12.Ambient Temperature Drift . . . . .	12
13.Output Voltage Accuracy . . . . .	13
14.Time Lapse Drift . . . . .	14
15.Rise and Fall Time . . . . .	15
16.Minimum Input Voltage for Regulated Output Voltage . . . . .	16
17.Overcurrent Protection . . . . .	17
18.Figure of Testing Circuitry . . . . .	18

(Final Page 18)

Model	BRFS150	Temperature Testing Circuitry 25°C Figure A																																																																															
Item	Input Current (by Input Voltage)																																																																																
Object	+1.2V																																																																																
1.Graph		2.Values																																																																															
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>At 1.2V output, refer to the specifications 2.6(2).</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>2.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.039</td><td>0.038</td><td>0.038</td></tr> <tr><td>4.5</td><td>0.038</td><td>0.039</td><td>0.039</td></tr> <tr><td>4.6</td><td>0.351</td><td>22.273</td><td>49.476</td></tr> <tr><td>5.0</td><td>0.346</td><td>20.283</td><td>44.468</td></tr> <tr><td>5.2</td><td>0.344</td><td>19.422</td><td>42.576</td></tr> <tr><td>6.0</td><td>0.317</td><td>16.939</td><td>36.524</td></tr> <tr><td>8.0</td><td>0.266</td><td>12.440</td><td>26.161</td></tr> <tr><td>10.0</td><td>0.232</td><td>9.874</td><td>20.569</td></tr> <tr><td>12.0</td><td>0.207</td><td>8.223</td><td>16.970</td></tr> <tr><td>14.0</td><td>0.189</td><td>7.141</td><td>14.746</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	2.0	0.000	0.000	0.000	4.0	0.039	0.038	0.038	4.5	0.038	0.039	0.039	4.6	0.351	22.273	49.476	5.0	0.346	20.283	44.468	5.2	0.344	19.422	42.576	6.0	0.317	16.939	36.524	8.0	0.266	12.440	26.161	10.0	0.232	9.874	20.569	12.0	0.207	8.223	16.970	14.0	0.189	7.141	14.746	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																
	Load 0%	Load 50%	Load 100%																																																																														
0.0	0.000	0.000	0.000																																																																														
2.0	0.000	0.000	0.000																																																																														
4.0	0.039	0.038	0.038																																																																														
4.5	0.038	0.039	0.039																																																																														
4.6	0.351	22.273	49.476																																																																														
5.0	0.346	20.283	44.468																																																																														
5.2	0.344	19.422	42.576																																																																														
6.0	0.317	16.939	36.524																																																																														
8.0	0.266	12.440	26.161																																																																														
10.0	0.232	9.874	20.569																																																																														
12.0	0.207	8.223	16.970																																																																														
14.0	0.189	7.141	14.746																																																																														
--	-	-	-																																																																														
--	-	-	-																																																																														
--	-	-	-																																																																														
--	-	-	-																																																																														
--	-	-	-																																																																														
--	-	-	-																																																																														

Model	BRFS150
Item	Input Current (by Load Current)
Object	+1.2V

Temperature 25°C  
Testing Circuitry Figure A



## 2.Values

Load Current [A]	Input Current [A]		
	Input Volt. 5[V]	Input Volt. 12[V]	Input Volt. 14[V]
0	0.346	0.207	0.189
30	7.885	3.341	2.883
60	15.971	6.564	5.717
90	24.673	9.897	8.570
120	34.106	13.363	11.564
150	44.468	16.970	14.746
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

At 1.2V output, refer to the specifications 2.6(2).

Model	BRFS150	Temperature 25°C Testing Circuitry Figure A																																																				
Item	Input Power (by Load Current)																																																					
Object	+1.2V																																																					
1.Graph	<p>—△— Input Volt. 5V      - - -□- - Input Volt. 12V      - ·○- - Input Volt. 14V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>5V [W]</th> <th>12V [W]</th> <th>14V [W]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0</td><td>0</td><td>0</td></tr> <tr><td>30</td><td>45</td><td>90</td><td>105</td></tr> <tr><td>60</td><td>90</td><td>180</td><td>150</td></tr> <tr><td>90</td><td>135</td><td>270</td><td>225</td></tr> <tr><td>120</td><td>180</td><td>360</td><td>300</td></tr> <tr><td>150</td><td>225</td><td>450</td><td>375</td></tr> </tbody> </table>	Load Current [A]	5V [W]	12V [W]	14V [W]	0	0	0	0	30	45	90	105	60	90	180	150	90	135	270	225	120	180	360	300	150	225	450	375																									
Load Current [A]	5V [W]	12V [W]	14V [W]																																																			
0	0	0	0																																																			
30	45	90	105																																																			
60	90	180	150																																																			
90	135	270	225																																																			
120	180	360	300																																																			
150	225	450	375																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 5[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 14[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>1.7</td><td>2.5</td><td>2.7</td></tr> <tr><td>30</td><td>39.4</td><td>40.1</td><td>40.4</td></tr> <tr><td>60</td><td>79.8</td><td>78.7</td><td>80.0</td></tr> <tr><td>90</td><td>123.2</td><td>118.7</td><td>119.9</td></tr> <tr><td>120</td><td>170.4</td><td>160.3</td><td>161.9</td></tr> <tr><td>150</td><td>222.0</td><td>203.6</td><td>206.3</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 5[V]	Input Volt. 12[V]	Input Volt. 14[V]	0	1.7	2.5	2.7	30	39.4	40.1	40.4	60	79.8	78.7	80.0	90	123.2	118.7	119.9	120	170.4	160.3	161.9	150	222.0	203.6	206.3	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 5[V]	Input Volt. 12[V]	Input Volt. 14[V]																																																			
0	1.7	2.5	2.7																																																			
30	39.4	40.1	40.4																																																			
60	79.8	78.7	80.0																																																			
90	123.2	118.7	119.9																																																			
120	170.4	160.3	161.9																																																			
150	222.0	203.6	206.3																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			


Note: Slanted line shows the range of the rated load current.

At 1.2V output, refer to the specifications 2.6(2).

Model	BRFS150
Item	Efficiency (by Input Voltage)
Object	+1.2V

Temperature 25°C  
Testing Circuitry Figure A

## 1.Graph



## 2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
5	89.2	81.2
6	90.4	83.8
8	91.5	87.3
10	91.9	88.6
12	91.7	88.7
14	90.5	87.5
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated input voltage.


At 1.2V output, refer to the specifications 2.6(2).

Model	BRFS150	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Efficiency (by Load Current)																																																					
Object	+1.2V																																																					
1.Graph	<p>—△— Input Volt. 5V        - - -□- - Input Volt. 12V        - - ○ - - Input Volt. 14V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [5V] (%)</th> <th>Efficiency [12V] (%)</th> <th>Efficiency [14V] (%)</th> </tr> </thead> <tbody> <tr><td>30</td><td>91.8</td><td>90.2</td><td>89.6</td></tr> <tr><td>60</td><td>90.5</td><td>91.8</td><td>90.3</td></tr> <tr><td>90</td><td>87.8</td><td>91.3</td><td>90.4</td></tr> <tr><td>120</td><td>84.6</td><td>90.1</td><td>89.2</td></tr> <tr><td>150</td><td>81.2</td><td>88.7</td><td>87.5</td></tr> </tbody> </table>			Load Current [A]	Efficiency [5V] (%)	Efficiency [12V] (%)	Efficiency [14V] (%)	30	91.8	90.2	89.6	60	90.5	91.8	90.3	90	87.8	91.3	90.4	120	84.6	90.1	89.2	150	81.2	88.7	87.5																											
Load Current [A]	Efficiency [5V] (%)	Efficiency [12V] (%)	Efficiency [14V] (%)																																																			
30	91.8	90.2	89.6																																																			
60	90.5	91.8	90.3																																																			
90	87.8	91.3	90.4																																																			
120	84.6	90.1	89.2																																																			
150	81.2	88.7	87.5																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 5[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 14[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>30</td><td>91.8</td><td>90.2</td><td>89.6</td></tr> <tr><td>60</td><td>90.5</td><td>91.8</td><td>90.3</td></tr> <tr><td>90</td><td>87.8</td><td>91.3</td><td>90.4</td></tr> <tr><td>120</td><td>84.6</td><td>90.1</td><td>89.2</td></tr> <tr><td>150</td><td>81.2</td><td>88.7</td><td>87.5</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 5[V]	Input Volt. 12[V]	Input Volt. 14[V]	0	-	-	-	30	91.8	90.2	89.6	60	90.5	91.8	90.3	90	87.8	91.3	90.4	120	84.6	90.1	89.2	150	81.2	88.7	87.5	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 5[V]	Input Volt. 12[V]	Input Volt. 14[V]																																																			
0	-	-	-																																																			
30	91.8	90.2	89.6																																																			
60	90.5	91.8	90.3																																																			
90	87.8	91.3	90.4																																																			
120	84.6	90.1	89.2																																																			
150	81.2	88.7	87.5																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.


At 1.2V output, refer to the specifications 2.6(2).

Model	BRFS150	Temperature	25°C																																
Item	Line Regulation	Testing Circuitry	Figure A																																
Object	+1.2V150A																																		
1.Graph	<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: ---□--- Load 50% —△— Load 100%</p>																																		
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>5</td><td>1.199</td><td>1.199</td></tr> <tr> <td>6</td><td>1.200</td><td>1.199</td></tr> <tr> <td>8</td><td>1.200</td><td>1.200</td></tr> <tr> <td>10</td><td>1.201</td><td>1.201</td></tr> <tr> <td>12</td><td>1.201</td><td>1.200</td></tr> <tr> <td>14</td><td>1.200</td><td>1.200</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	5	1.199	1.199	6	1.200	1.199	8	1.200	1.200	10	1.201	1.201	12	1.201	1.200	14	1.200	1.200	--	-	-	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
5	1.199	1.199																																	
6	1.200	1.199																																	
8	1.200	1.200																																	
10	1.201	1.201																																	
12	1.201	1.200																																	
14	1.200	1.200																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
Note:	Slanted line shows the range of the rated input voltage.																																		
At 1.2V output, refer to the specifications 2.6(2).																																			

Model	BRFS150	Temperature Testing Circuitry 25°C Figure A																																																			
Item	Load Regulation																																																				
Object	+1.2V150A																																																				
1.Graph	<p>—△— Input Volt. 5V        - - -□- - Input Volt. 12V        - - ○ - - Input Volt. 14V</p>  <p>Output Voltage [V]</p> <p>Load Current [A]</p>	2.Values																																																			
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 5[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 14[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>1.201</td> <td>1.202</td> <td>1.202</td> </tr> <tr> <td>30</td> <td>1.200</td> <td>1.202</td> <td>1.202</td> </tr> <tr> <td>60</td> <td>1.199</td> <td>1.202</td> <td>1.201</td> </tr> <tr> <td>90</td> <td>1.199</td> <td>1.201</td> <td>1.200</td> </tr> <tr> <td>120</td> <td>1.199</td> <td>1.201</td> <td>1.200</td> </tr> <tr> <td>150</td> <td>1.199</td> <td>1.200</td> <td>1.200</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 5[V]	Input Volt. 12[V]	Input Volt. 14[V]	0	1.201	1.202	1.202	30	1.200	1.202	1.202	60	1.199	1.202	1.201	90	1.199	1.201	1.200	120	1.199	1.201	1.200	150	1.199	1.200	1.200	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																				
	Input Volt. 5[V]	Input Volt. 12[V]	Input Volt. 14[V]																																																		
0	1.201	1.202	1.202																																																		
30	1.200	1.202	1.202																																																		
60	1.199	1.202	1.201																																																		
90	1.199	1.201	1.200																																																		
120	1.199	1.201	1.200																																																		
150	1.199	1.200	1.200																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		

Note: Slanted line shows the range of the rated load current.

At 1.2V output, refer to the specifications 2.6(2).

**COSEL**

**COSSEL**


Model BRFS150

Item Ripple Voltage (by Load Current)

Object +1.2V150A

## 1. Graph

—▲— Input Volt. 5V  
 - - ○ - - Input Volt. 12V



Measured by 20 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]




Fig.Complex Ripple Wave Form

Temperature 25°C  
Testing Circuitry Figure C


## 2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 5 [V]	Input Volt. 12 [V]
0	4	6
30	5	6
60	5	6
90	5	6
120	5	6
150	5	6
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

**COSEL**

Model	BRFS150
Item	Ripple-Noise
Object	+1.2V150A

## 1. Graph



Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C  
Testing Circuitry Figure C

## 2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 5 [V]	Input Volt. 12 [V]
0	14	18
30	16	20
60	16	22
90	16	22
120	16	22
150	17	24
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

**COSEL**

Model	BRFS150
Item	Ripple Voltage (by Ambient Temp.)
Object	+1.2V150A

## Testing Circuitry Figure C

## 1.Graph



## 2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	11	11
-20	10	9
0	9	8
25	8	8
60	8	9
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 20 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	BRFS150
Item	Ambient Temperature Drift
Object	+1.2V150A



Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 5[V]	Input Volt. 12[V]	Input Volt. 14[V]
-40	1.198	1.200	1.199
-20	1.198	1.199	1.199
0	1.198	1.201	1.200
25	1.199	1.200	1.200
60	1.202	1.201	1.201
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.

At 1.2V output, refer to the specifications 2.6(2).

Model	BRFS150	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+1.2V150A	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 60°C

Input Voltage : 5 - 14V (At 1.2V output, refer to the specifications 2.6(2).)

Load Current : 0 - 150A


\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	60	5	0	1.203	±3	±0.3
Minimum Voltage	-40	5	150	1.198		

**COSEL**

Model	BRFS150	Temperature Testing Circuitry 25°C Figure A																						
Item	Time Lapse Drift																							
Object	+1.2V150A																							
1.Graph		2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 12V Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>1.200</td></tr> <tr><td>0.5</td><td>1.200</td></tr> <tr><td>1.0</td><td>1.200</td></tr> <tr><td>2.0</td><td>1.200</td></tr> <tr><td>3.0</td><td>1.200</td></tr> <tr><td>4.0</td><td>1.200</td></tr> <tr><td>5.0</td><td>1.200</td></tr> <tr><td>6.0</td><td>1.200</td></tr> <tr><td>7.0</td><td>1.200</td></tr> <tr><td>8.0</td><td>1.200</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	1.200	0.5	1.200	1.0	1.200	2.0	1.200	3.0	1.200	4.0	1.200	5.0	1.200	6.0	1.200	7.0	1.200	8.0	1.200
Time since start [H]	Output Voltage [V]																							
0.0	1.200																							
0.5	1.200																							
1.0	1.200																							
2.0	1.200																							
3.0	1.200																							
4.0	1.200																							
5.0	1.200																							
6.0	1.200																							
7.0	1.200																							
8.0	1.200																							

**COSEL**


Model BRFS150

Item Rise and Fall Time

Object +1.2V150A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		9.5	2.9	12.4	0.1	0.3	
100 %		9.5	3.1	12.6	0.1	0.3	



Model	BRFS150	Testing Circuitry Figure A																																						
Item	Minimum Input Voltage for Regulated Output Voltage																																							
Object	+1.2V150A																																							
1.Graph		2.Values																																						
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-40</td><td>4.31</td><td>4.34</td></tr> <tr><td>-20</td><td>4.32</td><td>4.35</td></tr> <tr><td>0</td><td>4.32</td><td>4.34</td></tr> <tr><td>25</td><td>4.33</td><td>4.35</td></tr> <tr><td>60</td><td>4.34</td><td>4.34</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-40	4.31	4.34	-20	4.32	4.35	0	4.32	4.34	25	4.33	4.35	60	4.34	4.34	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-40	4.31	4.34																																						
-20	4.32	4.35																																						
0	4.32	4.34																																						
25	4.33	4.35																																						
60	4.34	4.34																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>At 1.2V output, refer to the specifications 2.6(2).</p>																																								

**COSEL**

Model	BRFS150	Temperature Testing Circuitry	25°C Figure A																																																							
Item	Overcurrent Protection																																																									
Object	+1.2V150A																																																									
1.Graph		2.Values																																																								
<p>Output Voltage [V]</p> <p>Load Current [A]</p>		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 5[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 14[V]</th> </tr> </thead> <tbody> <tr><td>1.20</td><td>169.77</td><td>172.78</td><td>174.32</td></tr> <tr><td>1.14</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.08</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.96</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.84</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.72</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.60</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.48</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.36</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.24</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.12</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]			Input Volt. 5[V]	Input Volt. 12[V]	Input Volt. 14[V]	1.20	169.77	172.78	174.32	1.14	-	-	-	1.08	-	-	-	0.96	-	-	-	0.84	-	-	-	0.72	-	-	-	0.60	-	-	-	0.48	-	-	-	0.36	-	-	-	0.24	-	-	-	0.12	-	-	-	0.00	-	-	-
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 5[V]	Input Volt. 12[V]	Input Volt. 14[V]																																																							
1.20	169.77	172.78	174.32																																																							
1.14	-	-	-																																																							
1.08	-	-	-																																																							
0.96	-	-	-																																																							
0.84	-	-	-																																																							
0.72	-	-	-																																																							
0.60	-	-	-																																																							
0.48	-	-	-																																																							
0.36	-	-	-																																																							
0.24	-	-	-																																																							
0.12	-	-	-																																																							
0.00	-	-	-																																																							
<p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when overcurrent protection is activated.</p> <p>At 1.2V output, refer to the specifications 2.6(2).</p>																																																										



Data Acquisition/Control Unit

Figure A




Figure B




Figure C