



M T B F (E I A J R C R - 9 1 0 2)

| | |
|-------|--------|
| Model | BRFS60 |
|-------|--------|

| No. | P a r t s | | Q' ty of Device | Failure rate [10 ⁻⁶ /H] | R e f e r e n c e |
|--|------------------------|---------------------|-----------------|------------------------------------|-------------------|
| 1 | I C | M o n o l i t h i c | 7 | 0.2090 | |
| 2 | | H y b r i d | 0 | 0.0000 | |
| 3 | T r a n s i s t o r s | | 9 | 0.5973 | |
| 4 | D i o d e s | | 3 | 0.0390 | |
| 5 | LED•Optocouplers | | 0 | 0.0000 | |
| 6 | R e s i s t o r s | | 91 | 0.6578 | |
| 7 | C a p a c i t o r s | | 61 | 0.4514 | |
| 8 | Transformer•Choke Coil | | 2 | 0.0460 | |
| 9 | C o n n e c t o r s | | 474 | 0.0653 | |
| 1 0 | O t h e r s | | 1 | 0.1100 | |
| Total Failure Rate [10 ⁻⁶ /H] | | | | 2.1758 | |

| | |
|--------------------------|---------|
| M T B F [H] | 460,000 |
| Ambient Temperature [°C] | — |
| Load Factor [%] | — |