

COSEL

TEST DATA OF CBS1002405

(24V INPUT)

Regulated DC Power Supply
Mar. 12, 2002

Approved by : Isao Yasuda Isao Yasuda Design Manager

Prepared by : Kouichi Kinoshita Kouichi Kinoshita Design Engineer

コーワセル株式会社
COSEL CO.,LTD.

CONTENTS

1. Line Regulation	1
静的入力変動	
2. Input Current (by Input Voltage)	2
入力電流 (入力電圧特性)	
3. Input Current (by Load Current)	3
入力電流 (負荷特性)	
4. Input Power (by Load Current)	4
入力電力 (負荷特性)	
5. Efficiency (by Input Voltage)	5
効率 (入力電圧特性)	
6. Efficiency (by Load Current)	6
効率 (負荷特性)	
7. Load Regulation	7
静的負荷変動	
8. Ripple Voltage (by Load Current)	8
リップル電圧 (負荷特性)	
9. Ripple-Noise	9
リップルノイズ	
10. Overcurrent Protection	10
過電流保護	
11. Overvoltage Protection	11
過電圧保護	
12. Dynamic Load Response	12
動的負荷変動	
13. Rise and Fall Time	13
立上り、立下り時間	
14. Ambient Temperature Drift	14
周囲温度変動	
15. Minimum Input Voltage for Regulated Output Voltage	15
最低レギュレーション電圧	
16. Ripple Voltage (by Ambient Temperature)	16
リップル電圧 (周囲温度特性)	
17. Time Lapse Drift	17
経時ドリフト	
18. Output Voltage Accuracy	18
定電圧精度	
19. Condensation	19
結露特性	
20. Line Noise Tolerance	20
入力雑音耐量	
21. Figure of Testing Circuitry	21
測定回路図	

(Final Page 21)

COSEL

Model	CBS1002405	Temperature	25°C																																
Item	Line Regulation 静的の入力変動	Testing Circuitry	Figure A																																
Object	+5V20A																																		
1. Graph			2. Values																																
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line), Load 100% (solid line)</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>17</td><td>5.045</td><td>5.045</td></tr> <tr><td>18</td><td>5.045</td><td>5.045</td></tr> <tr><td>20</td><td>5.045</td><td>5.045</td></tr> <tr><td>24</td><td>5.045</td><td>5.045</td></tr> <tr><td>30</td><td>5.045</td><td>5.045</td></tr> <tr><td>36</td><td>5.045</td><td>5.045</td></tr> <tr><td>40</td><td>5.045</td><td>5.045</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	17	5.045	5.045	18	5.045	5.045	20	5.045	5.045	24	5.045	5.045	30	5.045	5.045	36	5.045	5.045	40	5.045	5.045	--	--	--	--	--	--
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
17	5.045	5.045																																	
18	5.045	5.045																																	
20	5.045	5.045																																	
24	5.045	5.045																																	
30	5.045	5.045																																	
36	5.045	5.045																																	
40	5.045	5.045																																	
--	--	--																																	
--	--	--																																	

Note: Slanted line shows the range of the rated input voltage.


(注) 斜線は定格入力電圧範囲を示す。

COSEL

Model	CBS1002405	Temperature 25°C Testing Circuitry Figure A																																																																					
Item	Input Current (by Input Voltage) 入力電流 (入力電圧特性)																																																																						
Object	—																																																																						
1. Graph	<p style="text-align: center;"> △ — Load 100% □ --- Load 50% ○ - - - Load 0% </p>																																																																						
	<p style="text-align: center;"> △ — Load 100% □ --- Load 50% ○ - - - Load 0% </p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <th colspan="2">Input Current [A]</th> </tr> <tr> <th>[V]</th> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.020</td><td>0.000</td><td>0.000</td></tr> <tr><td>12.0</td><td>0.016</td><td>0.016</td><td>0.015</td></tr> <tr><td>15.6</td><td>0.174</td><td>4.001</td><td>7.480</td></tr> <tr><td>16.0</td><td>0.172</td><td>3.864</td><td>7.700</td></tr> <tr><td>18.0</td><td>0.162</td><td>3.372</td><td>6.720</td></tr> <tr><td>20.0</td><td>0.149</td><td>3.022</td><td>6.030</td></tr> <tr><td>24.0</td><td>0.135</td><td>2.536</td><td>5.020</td></tr> <tr><td>28.0</td><td>0.125</td><td>2.186</td><td>4.304</td></tr> <tr><td>32.0</td><td>0.119</td><td>1.930</td><td>3.773</td></tr> <tr><td>36.0</td><td>0.114</td><td>1.724</td><td>3.365</td></tr> <tr><td>40.0</td><td>0.109</td><td>1.564</td><td>3.042</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> </table>	Input Current [A]		[V]	Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	4.0	0.000	0.000	0.000	8.0	0.020	0.000	0.000	12.0	0.016	0.016	0.015	15.6	0.174	4.001	7.480	16.0	0.172	3.864	7.700	18.0	0.162	3.372	6.720	20.0	0.149	3.022	6.030	24.0	0.135	2.536	5.020	28.0	0.125	2.186	4.304	32.0	0.119	1.930	3.773	36.0	0.114	1.724	3.365	40.0	0.109	1.564	3.042	---	—	—	—	---	—	—	—	---	—	—	—
Input Current [A]																																																																							
[V]	Load 0%	Load 50%	Load 100%																																																																				
0	0.000	0.000	0.000																																																																				
4.0	0.000	0.000	0.000																																																																				
8.0	0.020	0.000	0.000																																																																				
12.0	0.016	0.016	0.015																																																																				
15.6	0.174	4.001	7.480																																																																				
16.0	0.172	3.864	7.700																																																																				
18.0	0.162	3.372	6.720																																																																				
20.0	0.149	3.022	6.030																																																																				
24.0	0.135	2.536	5.020																																																																				
28.0	0.125	2.186	4.304																																																																				
32.0	0.119	1.930	3.773																																																																				
36.0	0.114	1.724	3.365																																																																				
40.0	0.109	1.564	3.042																																																																				
---	—	—	—																																																																				
---	—	—	—																																																																				
---	—	—	—																																																																				
	<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注) 斜線は定格入力電圧範囲を示す。</p>																																																																						

COSSEL

Model	CBS1002405
Item	Input Current (by Load Current) 入力電流（負荷特性）
Object	—



Note: Slanted line shows the range of the rated load current.


(注) 斜線は定格負荷電流範囲を示す。

Temperature 25°C
 Testing Circuitry Figure A

2. Values

Load Current [A]	Input Current [A]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
0	0.159	0.134	0.114
4	1.498	1.134	0.795
8	2.806	2.092	1.422
12	4.184	3.084	2.070
16	5.630	4.112	2.730
20	7.160	5.180	3.410
22	7.960	5.740	3.760
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—

CSEL

Model	CBS1002405																																																		
Item	Input Power (by Load Current) 入力電力 (負荷特性)	Temperature Testing Circuitry	25°C Figure A																																																
Object																																																			
1. Graph	<p>—△— Input Volt. 18V - - - □ - - Input Volt. 24V - - ○ - - Input Volt. 36V</p>  <p>The graph plots Input Power [W] on the Y-axis (0 to 200) against Load Current [A] on the X-axis (0 to 20). Three curves are shown for input voltages of 18V, 24V, and 36V. A slanted line indicates the rated load current range.</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>18V [W]</th> <th>24V [W]</th> <th>36V [W]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0</td><td>0</td><td>0</td></tr> <tr><td>2</td><td>~10</td><td>~12</td><td>~15</td></tr> <tr><td>4</td><td>~20</td><td>~25</td><td>~30</td></tr> <tr><td>6</td><td>~30</td><td>~40</td><td>~50</td></tr> <tr><td>8</td><td>~40</td><td>~55</td><td>~70</td></tr> <tr><td>10</td><td>~50</td><td>~70</td><td>~90</td></tr> <tr><td>12</td><td>~60</td><td>~90</td><td>~115</td></tr> <tr><td>14</td><td>~70</td><td>~110</td><td>~140</td></tr> <tr><td>16</td><td>~80</td><td>~130</td><td>~165</td></tr> <tr><td>18</td><td>~90</td><td>~150</td><td>~190</td></tr> <tr><td>20</td><td>~100</td><td>~170</td><td>~215</td></tr> </tbody> </table>			Load Current [A]	18V [W]	24V [W]	36V [W]	0	0	0	0	2	~10	~12	~15	4	~20	~25	~30	6	~30	~40	~50	8	~40	~55	~70	10	~50	~70	~90	12	~60	~90	~115	14	~70	~110	~140	16	~80	~130	~165	18	~90	~150	~190	20	~100	~170	~215
Load Current [A]	18V [W]	24V [W]	36V [W]																																																
0	0	0	0																																																
2	~10	~12	~15																																																
4	~20	~25	~30																																																
6	~30	~40	~50																																																
8	~40	~55	~70																																																
10	~50	~70	~90																																																
12	~60	~90	~115																																																
14	~70	~110	~140																																																
16	~80	~130	~165																																																
18	~90	~150	~190																																																
20	~100	~170	~215																																																
2. Values																																																			
Load Current [A]	Input Power [W]																																																		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																
0	2.8	3.2	4.1																																																
4	26.6	27.0	28.6																																																
8	49.4	49.7	51.0																																																
12	72.8	72.7	74.3																																																
16	97.0	96.4	97.6																																																
20	121.9	120.8	121.5																																																
22	134.8	133.4	133.7																																																
—	—	—	—																																																
—	—	—	—																																																
—	—	—	—																																																
—	—	—	—																																																

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

COSEL

Model	CBS1002405	Temperature	25°C																															
Item	Efficiency (by Input Voltage) 効率(入力電圧特性)	Testing Circuitry	Figure A																															
Object																																		
1. Graph																																		
			2. Values																															
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>16</td><td>80.9</td><td>81.6</td></tr> <tr> <td>18</td><td>82.7</td><td>82.8</td></tr> <tr> <td>20</td><td>82.8</td><td>83.1</td></tr> <tr> <td>24</td><td>82.3</td><td>83.2</td></tr> <tr> <td>30</td><td>81.4</td><td>83.1</td></tr> <tr> <td>36</td><td>80.5</td><td>82.7</td></tr> <tr> <td>40</td><td>79.8</td><td>82.4</td></tr> <tr> <td>--</td><td>--</td><td>--</td></tr> <tr> <td>--</td><td>--</td><td>--</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	16	80.9	81.6	18	82.7	82.8	20	82.8	83.1	24	82.3	83.2	30	81.4	83.1	36	80.5	82.7	40	79.8	82.4	--	--	--	--	--	--
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
16	80.9	81.6																																
18	82.7	82.8																																
20	82.8	83.1																																
24	82.3	83.2																																
30	81.4	83.1																																
36	80.5	82.7																																
40	79.8	82.4																																
--	--	--																																
--	--	--																																

Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。

CSEL

Model	CBS1002405	Temperature	25°C																																																				
Item	Efficiency (by Load Current) 効率（負荷特性）	Testing Circuitry	Figure A																																																				
Object	—	—	—																																																				
1. Graph		2. Values																																																					
<p>—▲— Input Volt. 18V ---□--- Input Volt. 24V ---○--- Input Volt. 36V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency 18V [%]</th> <th>Efficiency 24V [%]</th> <th>Efficiency 36V [%]</th> </tr> </thead> <tbody> <tr><td>0</td><td>75.4</td><td>74.3</td><td>70.3</td></tr> <tr><td>4</td><td>81.4</td><td>80.9</td><td>78.8</td></tr> <tr><td>8</td><td>82.9</td><td>83.0</td><td>81.2</td></tr> <tr><td>12</td><td>82.9</td><td>83.4</td><td>82.4</td></tr> <tr><td>16</td><td>82.5</td><td>83.2</td><td>82.7</td></tr> <tr><td>20</td><td>82.1</td><td>82.9</td><td>82.7</td></tr> </tbody> </table>	Load Current [A]	Efficiency 18V [%]	Efficiency 24V [%]	Efficiency 36V [%]	0	75.4	74.3	70.3	4	81.4	80.9	78.8	8	82.9	83.0	81.2	12	82.9	83.4	82.4	16	82.5	83.2	82.7	20	82.1	82.9	82.7																											
Load Current [A]	Efficiency 18V [%]	Efficiency 24V [%]	Efficiency 36V [%]																																																				
0	75.4	74.3	70.3																																																				
4	81.4	80.9	78.8																																																				
8	82.9	83.0	81.2																																																				
12	82.9	83.4	82.4																																																				
16	82.5	83.2	82.7																																																				
20	82.1	82.9	82.7																																																				
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>4</td><td>75.4</td><td>74.3</td><td>70.3</td></tr> <tr><td>8</td><td>81.4</td><td>80.9</td><td>78.8</td></tr> <tr><td>12</td><td>82.9</td><td>83.0</td><td>81.2</td></tr> <tr><td>16</td><td>82.9</td><td>83.4</td><td>82.4</td></tr> <tr><td>20</td><td>82.5</td><td>83.2</td><td>82.7</td></tr> <tr><td>22</td><td>82.1</td><td>82.9</td><td>82.7</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	—	—	—	4	75.4	74.3	70.3	8	81.4	80.9	78.8	12	82.9	83.0	81.2	16	82.9	83.4	82.4	20	82.5	83.2	82.7	22	82.1	82.9	82.7	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																						
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																				
0	—	—	—																																																				
4	75.4	74.3	70.3																																																				
8	81.4	80.9	78.8																																																				
12	82.9	83.0	81.2																																																				
16	82.9	83.4	82.4																																																				
20	82.5	83.2	82.7																																																				
22	82.1	82.9	82.7																																																				
—	—	—	—																																																				
—	—	—	—																																																				
—	—	—	—																																																				
—	—	—	—																																																				

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

COSEL


Model CBS1002405

Item Load Regulation
靜的負荷變動

Object +5V20A

1. Graph

—▲— Input Volt. 18V
 - - - □ - - - Input Volt. 24V
 - - ○ - - - Input Volt. 36V



Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

Temperature 25°C
Testing Circuitry Figure A

2. Values


Load Current [A]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
0	5.045	5.045	5.045
4	5.045	5.045	5.045
8	5.045	5.045	5.045
12	5.044	5.044	5.045
16	5.045	5.045	5.045
20	5.045	5.045	5.045
22	5.045	5.045	5.045
--	--	--	--
--	--	--	--
--	--	--	--

COSEL

Model	CBS1002405
Item	Ripple Voltage (by Load Current) リップル電圧 (負荷特性)
Object	+5V20A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップル電圧は、下図 p - p 値で示される。
(注) 斜線は定格負荷電流範囲を示す。

Ripple [mVp-p]




Fig. Complex Ripple Wave Form
図 リップル波形詳細図


2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0	5	5
4	5	10
8	5	10
12	5	10
16	5	10
20	5	10
24	5	10
—	—	—
—	—	—
—	—	—
—	—	—

COSEL


Model	CBS1002405																																							
Item	Ripple-Noise リップルノイズ	Temperature 25°C Testing Circuitry Figure A																																						
Object	+5V20A																																							
1. Graph																																								
2. Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>15</td><td>20</td></tr> <tr><td>4</td><td>15</td><td>25</td></tr> <tr><td>8</td><td>15</td><td>25</td></tr> <tr><td>12</td><td>20</td><td>25</td></tr> <tr><td>16</td><td>20</td><td>25</td></tr> <tr><td>20</td><td>20</td><td>25</td></tr> <tr><td>24</td><td>20</td><td>25</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0	15	20	4	15	25	8	15	25	12	20	25	16	20	25	20	20	25	24	20	25	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 18 [V]	Input Volt. 36 [V]																																						
0	15	20																																						
4	15	25																																						
8	15	25																																						
12	20	25																																						
16	20	25																																						
20	20	25																																						
24	20	25																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図 p - p 値で示される。 (注) 斜線は定格負荷電流範囲を示す。</p>																																								
<p>Fig. Complex Ripple Noise Wave Form 図 リップルノイズ波形</p>																																								

COSEL

Model	CBS1002405	Temperature Testing Circuitry 25°C Figure A																																																											
Item	Overcurrent Protection 過電流保護																																																												
Object	+5V20A																																																												
1. Graph	<p>— Input Volt. 18V - - - - Input Volt. 24V - - - - Input Volt. 36V</p> 	2. Values																																																											
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>5.00</td><td>20.21</td><td>20.56</td><td>20.56</td></tr> <tr><td>4.75</td><td>26.55</td><td>26.01</td><td>26.27</td></tr> <tr><td>4.50</td><td>26.54</td><td>26.11</td><td>26.45</td></tr> <tr><td>4.00</td><td>26.46</td><td>26.33</td><td>26.86</td></tr> <tr><td>3.50</td><td>26.54</td><td>26.52</td><td>27.21</td></tr> <tr><td>3.00</td><td>26.63</td><td>26.68</td><td>27.56</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	5.00	20.21	20.56	20.56	4.75	26.55	26.01	26.27	4.50	26.54	26.11	26.45	4.00	26.46	26.33	26.86	3.50	26.54	26.52	27.21	3.00	26.63	26.68	27.56	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Output Voltage [V]	Load Current [A]																																																												
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																										
5.00	20.21	20.56	20.56																																																										
4.75	26.55	26.01	26.27																																																										
4.50	26.54	26.11	26.45																																																										
4.00	26.46	26.33	26.86																																																										
3.50	26.54	26.52	27.21																																																										
3.00	26.63	26.68	27.56																																																										
—	—	—	—																																																										
—	—	—	—																																																										
—	—	—	—																																																										
—	—	—	—																																																										
—	—	—	—																																																										
—	—	—	—																																																										
—	—	—	—																																																										
<p>Note: Slanted line shows the range of the rated load current. (注) 斜線は定格負荷電流範囲を示す。</p> <p>Intermittent operation occurs when the output voltage is from 3V to 0V. 3V~0V間は、間欠モードとなる。</p>																																																													

COSEL

Model	CBS1002405
Item	Overvoltage Protection 過電圧保護
Object	+5V20A



Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Operating Point [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-50	6.51	6.51	6.51
-40	6.51	6.51	6.51
-20	6.51	6.51	6.51
0	6.51	6.51	6.51
25	6.50	6.50	6.50
40	6.50	6.50	6.50
60	6.50	6.50	6.50
85	6.49	6.49	6.49
100	6.49	6.49	6.49
105	6.48	6.48	6.48
--	--	--	--

Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。



COSEL

Model	CBS1002405	Temperature	25°C
Item	Dynamic Load Response 動的負荷變動	Testing Circuitry	Figure A
Object	+5V20A		



Input Volt. 24 V
Cycle 1000 ms





Min. Load (0A) ↔
Load 100% (20A)



Min. Load (0A) ↔
Load 50% (10A)



Load 10% (2A) ↔
Load 100% (20A)



COSSEL


Model CBS1002405

Item Rise and Fall Time
立上り、立下り時間

Object +5V20A


Temperature 25°C
Testing Circuitry Figure A

1. Graph




2. Values

Load	Time	T _d	T _r	T _s	T _h	T _f	[mS]
50 %		16.3	9.3	25.5	0.2	3.4	
100 %		16.3	9.3	25.5	0.2	1.8	



COSEL

Model	CBS1002405
Item	Ambient Temperature Drift 周囲温度変動
Object	+5V20A



Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-50	5.034	5.034	5.035
-40	5.037	5.037	5.038
-20	5.043	5.043	5.043
0	5.048	5.048	5.048
25	5.051	5.051	5.051
40	5.050	5.050	5.050
60	5.047	5.047	5.047
85	5.041	5.041	5.041
100	5.037	5.037	5.036
105	5.035	5.035	5.034
--	—	—	—

COSEL

Model	CBS1002405																																								
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧	Testing Circuitry Figure A																																							
Object	+5V20A																																								
1. Graph																																									
		2. Values																																							
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-50</td><td>14.5</td><td>15.1</td> </tr> <tr> <td>-40</td><td>14.5</td><td>15.2</td> </tr> <tr> <td>-20</td><td>14.5</td><td>15.2</td> </tr> <tr> <td>0</td><td>14.5</td><td>15.3</td> </tr> <tr> <td>25</td><td>14.5</td><td>15.3</td> </tr> <tr> <td>40</td><td>14.5</td><td>15.4</td> </tr> <tr> <td>60</td><td>14.5</td><td>15.4</td> </tr> <tr> <td>85</td><td>14.5</td><td>15.4</td> </tr> <tr> <td>100</td><td>14.5</td><td>15.4</td> </tr> <tr> <td>105</td><td>14.4</td><td>15.4</td> </tr> <tr> <td>--</td><td>—</td><td>—</td> </tr> </tbody> </table>				Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-50	14.5	15.1	-40	14.5	15.2	-20	14.5	15.2	0	14.5	15.3	25	14.5	15.3	40	14.5	15.4	60	14.5	15.4	85	14.5	15.4	100	14.5	15.4	105	14.4	15.4	--	—	—
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-50	14.5	15.1																																							
-40	14.5	15.2																																							
-20	14.5	15.2																																							
0	14.5	15.3																																							
25	14.5	15.3																																							
40	14.5	15.4																																							
60	14.5	15.4																																							
85	14.5	15.4																																							
100	14.5	15.4																																							
105	14.4	15.4																																							
--	—	—																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>(注) 斜線は定格周囲温度範囲を示す。</p>																																									


COSEL

Model CBS1002405

Item Ripple Voltage (by Ambient Temp.)
リップル電圧 (周囲温度特性)

Object +5V20A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-50	85	85
-40	60	60
-20	25	25
0	10	10
25	10	10
40	10	10
60	10	10
85	10	10
100	15	15
105	15	15
--	—	—

COSSEL

Model	CBS1002405	Temperature	25°C																						
Item	Time Lapse Drift 経時ドリフト	Testing Circuitry	Figure A																						
Object	+5V20A																								
1. Graph																									
<p>The graph plots Output Voltage [V] on the y-axis (ranging from 4.96 to 5.10) against Time [H] on the x-axis (ranging from 0 to 10). A single horizontal line is drawn at approximately 5.045V, representing the output voltage over an 8-hour period. The line starts at 0 hours and ends at 8 hours.</p> <p>Input Volt. 24V Load 100%</p>																									
2. Values																									
<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.046</td></tr> <tr><td>0.5</td><td>5.045</td></tr> <tr><td>1.0</td><td>5.045</td></tr> <tr><td>2.0</td><td>5.045</td></tr> <tr><td>3.0</td><td>5.045</td></tr> <tr><td>4.0</td><td>5.045</td></tr> <tr><td>5.0</td><td>5.045</td></tr> <tr><td>6.0</td><td>5.045</td></tr> <tr><td>7.0</td><td>5.045</td></tr> <tr><td>8.0</td><td>5.045</td></tr> </tbody> </table>				Time since start [H]	Output Voltage [V]	0.0	5.046	0.5	5.045	1.0	5.045	2.0	5.045	3.0	5.045	4.0	5.045	5.0	5.045	6.0	5.045	7.0	5.045	8.0	5.045
Time since start [H]	Output Voltage [V]																								
0.0	5.046																								
0.5	5.045																								
1.0	5.045																								
2.0	5.045																								
3.0	5.045																								
4.0	5.045																								
5.0	5.045																								
6.0	5.045																								
7.0	5.045																								
8.0	5.045																								



Model	CBS1002405	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	+5V20A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 ~ 100°C

Input Voltage : 18 ~ 36V

Load Current : 0 ~ 20A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 : -40 ~ 100°C

入力電圧 : 18 ~ 36V

負荷電流 : 0 ~ 20A

* 定電圧精度(変動値) = ±(出力電圧の最高値 - 出力電圧の最低値) / 2

$$* \text{定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	25	18	20	5.051		
Minimum Voltage	100	36	20	5.036	±8	±0.2



Model	CBS1002405	Testing Circuitry Figure A
Item	Condense 結露特性	
Object	+5V20A	

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	5.053	Input Volt.:24V, Load Current.:20A
Line Regulation [mV]	1	Input Volt.:18~36V, Load Current.:20A
Load Regulation [mV]	1	Input Volt.:24V, Load Current.:0~20A



Model	CBS1002405	Temperature Testing Circuitry	25°C Figure B
Item	Line Noise Tolerance 入力雑音耐量		
Object	+5V20A		

1. Conditions

- Input Voltage : 24 V
- Pulse Input Duration : 1 min. or more
- Pulse Voltage : 2000 V
- Load : 100 %
- Pulse Cycle : 16.7 mS

2. Results

Pulse Width [nS]	MODE	No protection failure should occur		DC-like Regulation of Output Voltage 出力電圧の直流的変動
		POLARITY	保護回路の誤動作がない	
50	COMMON	+	OK	no fluctuation
		-	OK	no fluctuation
	NORMAL	+	OK	no fluctuation
		-	OK	no fluctuation
1000	COMMON	+	OK	no fluctuation
		-	OK	no fluctuation
	NORMAL	+	OK	no fluctuation
		-	OK	no fluctuation

COSEL






Figure C