



TEST DATA OF CBS2004803

(48V INPUT)

Regulated DC Power Supply
Feb. 19, 2001

Approved by : Takayuki Fukuda
Takayuki Fukuda Design Manager

Prepared by : Atsushi Yoshiyama
Atsushi Yoshiyama Design Engineer

コーセル株式会社
COSEL CO.,LTD.



C O N T E N T S


1. Line Regulation	1
静的入力変動	
2. Input Current (by Input Voltage)	2
入力電流 (入力電圧特性)	
3. Input Current (by Load Current)	3
入力電流 (負荷特性)	
4. Input Power (by Load Current)	4
入力電力 (負荷特性)	
5. Efficiency (by Input Voltage)	5
効率 (入力電圧特性)	
6. Efficiency (by Load Current)	6
効率 (負荷特性)	
7. Load Regulation	7
静的負荷変動	
8. Ripple Voltage (by Load Current)	8
リップル電圧 (負荷特性)	
9. Ripple-Noise	9
リップルノイズ	
10. Overcurrent Protection	10
過電流保護	
11. Overvoltage Protection	11
過電圧保護	
12. Dynamic Load Response	12
動的負荷変動	
13. Rise and Fall Time	13
立上り、立下り時間	
14. Ambient Temperature Drift	14
周囲温度変動	
15. Minimum Input Voltage for Regulated Output Voltage	15
最低レギュレーション電圧	
16. Ripple Voltage (by Ambient Temperature)	16
リップル電圧 (周囲温度特性)	
17. Time Lapse Drift	17
経時ドリフト	
18. Output Voltage Accuracy	18
定電圧精度	
19. Condensation	19
結露特性	
20. Line Noise Tolerance	20
入力雑音耐量	
21. Figure of Testing Circuitry	21
測定回路図	

(Final Page 21)



Model	CBS2004803
Item	Line Regulation 静的の入力変動
Object	+3. 3V35A

1 . Graph



Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。

Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
33	3.308	3.308
36	3.308	3.308
40	3.308	3.308
48	3.308	3.308
55	3.308	3.308
60	3.308	3.308
70	3.308	3.308
76	3.308	3.308
80	3.308	3.308

COSEL

Model	CBS2004803	Temperature	25°C																																																																							
Item	Input Current (by Input Voltage) 入力電流 (入力電圧特性)	Testing Circuitry	Figure A																																																																							
Object																																																																										
1. Graph	<p style="text-align: center;">—△— Load 100% - - -□- - Load 50% - -○--- Load 0%</p> <p>Input Current [A]</p> <p>Input Voltage [V]</p>																																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>8.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>16.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>24.0</td><td>0.009</td><td>0.009</td><td>0.009</td></tr> <tr><td>30.6</td><td>0.090</td><td>2.214</td><td>4.094</td></tr> <tr><td>33.0</td><td>0.085</td><td>2.028</td><td>3.754</td></tr> <tr><td>36.0</td><td>0.080</td><td>1.840</td><td>3.408</td></tr> <tr><td>40.0</td><td>0.075</td><td>1.647</td><td>3.052</td></tr> <tr><td>48.0</td><td>0.059</td><td>1.371</td><td>2.540</td></tr> <tr><td>60.0</td><td>0.053</td><td>1.110</td><td>2.036</td></tr> <tr><td>70.0</td><td>0.048</td><td>0.962</td><td>1.748</td></tr> <tr><td>76.0</td><td>0.046</td><td>0.892</td><td>1.615</td></tr> <tr><td>80.0</td><td>0.044</td><td>0.851</td><td>1.538</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	8.0	0.000	0.000	0.000	16.0	0.000	0.000	0.000	24.0	0.009	0.009	0.009	30.6	0.090	2.214	4.094	33.0	0.085	2.028	3.754	36.0	0.080	1.840	3.408	40.0	0.075	1.647	3.052	48.0	0.059	1.371	2.540	60.0	0.053	1.110	2.036	70.0	0.048	0.962	1.748	76.0	0.046	0.892	1.615	80.0	0.044	0.851	1.538	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Input Voltage [V]	Input Current [A]																																																																									
	Load 0%	Load 50%	Load 100%																																																																							
8.0	0.000	0.000	0.000																																																																							
16.0	0.000	0.000	0.000																																																																							
24.0	0.009	0.009	0.009																																																																							
30.6	0.090	2.214	4.094																																																																							
33.0	0.085	2.028	3.754																																																																							
36.0	0.080	1.840	3.408																																																																							
40.0	0.075	1.647	3.052																																																																							
48.0	0.059	1.371	2.540																																																																							
60.0	0.053	1.110	2.036																																																																							
70.0	0.048	0.962	1.748																																																																							
76.0	0.046	0.892	1.615																																																																							
80.0	0.044	0.851	1.538																																																																							
--	--	--	--																																																																							
--	--	--	--																																																																							
--	--	--	--																																																																							
--	--	--	--																																																																							

Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。


COSEL

Model	CBS2004803	Temperature	25°C																																																			
Item	Input Current (by Load Current) 入力電流 (負荷特性)	Testing Circuitry	Figure A																																																			
Object																																																						
1. Graph	<p>—△— Input Volt. 36V - - -□- Input Volt. 48V - - ○- Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 36V [A]</th> <th>Input Volt. 48V [A]</th> <th>Input Volt. 76V [A]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.081</td><td>0.060</td><td>0.046</td></tr> <tr><td>6.0</td><td>0.758</td><td>0.565</td><td>0.382</td></tr> <tr><td>12.0</td><td>1.401</td><td>1.046</td><td>0.686</td></tr> <tr><td>18.0</td><td>2.072</td><td>1.542</td><td>0.999</td></tr> <tr><td>24.0</td><td>2.764</td><td>2.062</td><td>1.320</td></tr> <tr><td>30.0</td><td>3.484</td><td>2.596</td><td>1.652</td></tr> <tr><td>35.0</td><td>4.104</td><td>3.054</td><td>1.938</td></tr> <tr><td>38.5</td><td>4.560</td><td>3.385</td><td>2.142</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 36V [A]	Input Volt. 48V [A]	Input Volt. 76V [A]	0.0	0.081	0.060	0.046	6.0	0.758	0.565	0.382	12.0	1.401	1.046	0.686	18.0	2.072	1.542	0.999	24.0	2.764	2.062	1.320	30.0	3.484	2.596	1.652	35.0	4.104	3.054	1.938	38.5	4.560	3.385	2.142															
Load Current [A]	Input Volt. 36V [A]	Input Volt. 48V [A]	Input Volt. 76V [A]																																																			
0.0	0.081	0.060	0.046																																																			
6.0	0.758	0.565	0.382																																																			
12.0	1.401	1.046	0.686																																																			
18.0	2.072	1.542	0.999																																																			
24.0	2.764	2.062	1.320																																																			
30.0	3.484	2.596	1.652																																																			
35.0	4.104	3.054	1.938																																																			
38.5	4.560	3.385	2.142																																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.081</td><td>0.060</td><td>0.046</td></tr> <tr><td>6.0</td><td>0.758</td><td>0.565</td><td>0.382</td></tr> <tr><td>12.0</td><td>1.401</td><td>1.046</td><td>0.686</td></tr> <tr><td>18.0</td><td>2.072</td><td>1.542</td><td>0.999</td></tr> <tr><td>24.0</td><td>2.764</td><td>2.062</td><td>1.320</td></tr> <tr><td>30.0</td><td>3.484</td><td>2.596</td><td>1.652</td></tr> <tr><td>35.0</td><td>4.104</td><td>3.054</td><td>1.938</td></tr> <tr><td>38.5</td><td>4.560</td><td>3.385</td><td>2.142</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	0.081	0.060	0.046	6.0	0.758	0.565	0.382	12.0	1.401	1.046	0.686	18.0	2.072	1.542	0.999	24.0	2.764	2.062	1.320	30.0	3.484	2.596	1.652	35.0	4.104	3.054	1.938	38.5	4.560	3.385	2.142	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	0.081	0.060	0.046																																																			
6.0	0.758	0.565	0.382																																																			
12.0	1.401	1.046	0.686																																																			
18.0	2.072	1.542	0.999																																																			
24.0	2.764	2.062	1.320																																																			
30.0	3.484	2.596	1.652																																																			
35.0	4.104	3.054	1.938																																																			
38.5	4.560	3.385	2.142																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

COSSEL

Model	CBS2004803																																																					
Item	Input Power (by Load Current) 入力電力 (負荷特性)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	<hr/>																																																					
1. Graph	<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - - ○- - Input Volt. 76V</p>  <p>The graph plots Input Power [W] on the Y-axis (0 to 200) against Load Current [A] on the X-axis (0 to 40). Three curves are shown for input voltages of 36V, 48V, and 76V. A slanted line on the graph indicates the rated load current range.</p>																																																					
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>3.0</td><td>2.9</td><td>3.7</td></tr> <tr><td>6.0</td><td>27.2</td><td>27.1</td><td>29.1</td></tr> <tr><td>12.0</td><td>50.2</td><td>50.1</td><td>52.2</td></tr> <tr><td>18.0</td><td>74.2</td><td>73.7</td><td>76.1</td></tr> <tr><td>24.0</td><td>98.6</td><td>98.6</td><td>100.4</td></tr> <tr><td>30.0</td><td>124.0</td><td>123.8</td><td>125.4</td></tr> <tr><td>35.0</td><td>145.7</td><td>145.5</td><td>147.5</td></tr> <tr><td>38.5</td><td>161.8</td><td>161.0</td><td>162.9</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	3.0	2.9	3.7	6.0	27.2	27.1	29.1	12.0	50.2	50.1	52.2	18.0	74.2	73.7	76.1	24.0	98.6	98.6	100.4	30.0	124.0	123.8	125.4	35.0	145.7	145.5	147.5	38.5	161.8	161.0	162.9	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	3.0	2.9	3.7																																																			
6.0	27.2	27.1	29.1																																																			
12.0	50.2	50.1	52.2																																																			
18.0	74.2	73.7	76.1																																																			
24.0	98.6	98.6	100.4																																																			
30.0	124.0	123.8	125.4																																																			
35.0	145.7	145.5	147.5																																																			
38.5	161.8	161.0	162.9																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

COSSEL

Model	CBS2004803																																	
Item	Efficiency (by Input Voltage) 効率 (入力電圧特性)	Temperature Testing Circuitry 25°C Figure A																																
Object	—	—																																
1. Graph																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注) 斜線は定格入力電圧範囲を示す。</p>																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>33</td><td>80.2</td><td>79.3</td></tr> <tr> <td>36</td><td>80.7</td><td>79.7</td></tr> <tr> <td>40</td><td>80.9</td><td>80.1</td></tr> <tr> <td>48</td><td>80.9</td><td>80.0</td></tr> <tr> <td>55</td><td>80.5</td><td>79.6</td></tr> <tr> <td>60</td><td>80.0</td><td>79.6</td></tr> <tr> <td>70</td><td>79.1</td><td>79.3</td></tr> <tr> <td>76</td><td>78.6</td><td>79.1</td></tr> <tr> <td>80</td><td>78.3</td><td>78.9</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	33	80.2	79.3	36	80.7	79.7	40	80.9	80.1	48	80.9	80.0	55	80.5	79.6	60	80.0	79.6	70	79.1	79.3	76	78.6	79.1	80	78.3	78.9
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
33	80.2	79.3																																
36	80.7	79.7																																
40	80.9	80.1																																
48	80.9	80.0																																
55	80.5	79.6																																
60	80.0	79.6																																
70	79.1	79.3																																
76	78.6	79.1																																
80	78.3	78.9																																


COSSEL

Model	CBS2004803																																																					
Item	Efficiency (by Load Current) 効率(負荷特性)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object	<hr/>																																																					
1. Graph	<p>—▲— Input Volt. 36V - - - □ - - Input Volt. 48V - - ○ - - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [36V] (%)</th> <th>Efficiency [48V] (%)</th> <th>Efficiency [76V] (%)</th> </tr> </thead> <tbody> <tr><td>8</td><td>73.6</td><td>73.0</td><td>69.8</td></tr> <tr><td>12</td><td>79.0</td><td>79.1</td><td>76.5</td></tr> <tr><td>18</td><td>80.8</td><td>80.8</td><td>79.4</td></tr> <tr><td>24</td><td>80.8</td><td>80.6</td><td>79.5</td></tr> <tr><td>30</td><td>80.6</td><td>80.5</td><td>79.4</td></tr> <tr><td>35</td><td>80.2</td><td>80.0</td><td>79.1</td></tr> <tr><td>38.5</td><td>79.6</td><td>79.9</td><td>78.7</td></tr> </tbody> </table>			Load Current [A]	Efficiency [36V] (%)	Efficiency [48V] (%)	Efficiency [76V] (%)	8	73.6	73.0	69.8	12	79.0	79.1	76.5	18	80.8	80.8	79.4	24	80.8	80.6	79.5	30	80.6	80.5	79.4	35	80.2	80.0	79.1	38.5	79.6	79.9	78.7																			
Load Current [A]	Efficiency [36V] (%)	Efficiency [48V] (%)	Efficiency [76V] (%)																																																			
8	73.6	73.0	69.8																																																			
12	79.0	79.1	76.5																																																			
18	80.8	80.8	79.4																																																			
24	80.8	80.6	79.5																																																			
30	80.6	80.5	79.4																																																			
35	80.2	80.0	79.1																																																			
38.5	79.6	79.9	78.7																																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>6.0</td><td>73.6</td><td>73.0</td><td>69.8</td></tr> <tr><td>12.0</td><td>79.0</td><td>79.1</td><td>76.5</td></tr> <tr><td>18.0</td><td>80.8</td><td>80.8</td><td>79.4</td></tr> <tr><td>24.0</td><td>80.8</td><td>80.6</td><td>79.5</td></tr> <tr><td>30.0</td><td>80.6</td><td>80.5</td><td>79.4</td></tr> <tr><td>35.0</td><td>80.2</td><td>80.0</td><td>79.1</td></tr> <tr><td>38.5</td><td>79.6</td><td>79.9</td><td>78.7</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	-	-	-	6.0	73.6	73.0	69.8	12.0	79.0	79.1	76.5	18.0	80.8	80.8	79.4	24.0	80.8	80.6	79.5	30.0	80.6	80.5	79.4	35.0	80.2	80.0	79.1	38.5	79.6	79.9	78.7	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	-	-	-																																																			
6.0	73.6	73.0	69.8																																																			
12.0	79.0	79.1	76.5																																																			
18.0	80.8	80.8	79.4																																																			
24.0	80.8	80.6	79.5																																																			
30.0	80.6	80.5	79.4																																																			
35.0	80.2	80.0	79.1																																																			
38.5	79.6	79.9	78.7																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

COSEL

Model	CBS2004803	Temperature	25°C																																															
Item	Load Regulation 静的負荷変動	Testing Circuitry	Figure A																																															
Object	+3.3V35A																																																	
1. Graph		—△— Input Volt. 36V - - □ - - Input Volt. 48V - - ○ - - Input Volt. 76V																																																
			2. Values																																															
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>3.309</td> <td>3.308</td> <td>3.308</td> </tr> <tr> <td>6.0</td> <td>3.309</td> <td>3.308</td> <td>3.308</td> </tr> <tr> <td>12.0</td> <td>3.309</td> <td>3.308</td> <td>3.308</td> </tr> <tr> <td>18.0</td> <td>3.309</td> <td>3.308</td> <td>3.308</td> </tr> <tr> <td>24.0</td> <td>3.309</td> <td>3.308</td> <td>3.308</td> </tr> <tr> <td>30.0</td> <td>3.309</td> <td>3.308</td> <td>3.308</td> </tr> <tr> <td>35.0</td> <td>3.309</td> <td>3.308</td> <td>3.308</td> </tr> <tr> <td>38.5</td> <td>3.309</td> <td>3.308</td> <td>3.308</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	3.309	3.308	3.308	6.0	3.309	3.308	3.308	12.0	3.309	3.308	3.308	18.0	3.309	3.308	3.308	24.0	3.309	3.308	3.308	30.0	3.309	3.308	3.308	35.0	3.309	3.308	3.308	38.5	3.309	3.308	3.308	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																	
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																															
0.0	3.309	3.308	3.308																																															
6.0	3.309	3.308	3.308																																															
12.0	3.309	3.308	3.308																																															
18.0	3.309	3.308	3.308																																															
24.0	3.309	3.308	3.308																																															
30.0	3.309	3.308	3.308																																															
35.0	3.309	3.308	3.308																																															
38.5	3.309	3.308	3.308																																															
--	-	-	-																																															
--	-	-	-																																															
Note: Slanted line shows the range of the rated load current. (注) 斜線は定格負荷電流範囲を示す。																																																		

COSEL

Model	CBS2004803	Temperature Testing Circuitry 25°C Figure A																																			
Item	Ripple Voltage (by Load Current) リップル電圧 (負荷特性)																																				
Object	+3.3V35A																																				
1. Graph		2. Values																																			
<p>—▲— Input Volt. 36V ---○--- Input Volt. 76V</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Output Voltage [mV] (Input Volt. 36 [V])</th> <th>Ripple Output Voltage [mV] (Input Volt. 76 [V])</th> </tr> </thead> <tbody> <tr><td>0</td><td>5</td><td>5</td></tr> <tr><td>7</td><td>10</td><td>10</td></tr> <tr><td>14</td><td>10</td><td>10</td></tr> <tr><td>21</td><td>10</td><td>10</td></tr> <tr><td>28</td><td>10</td><td>10</td></tr> <tr><td>35</td><td>10</td><td>10</td></tr> <tr><td>42</td><td>10</td><td>10</td></tr> <tr><td>---</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Ripple Output Voltage [mV] (Input Volt. 36 [V])	Ripple Output Voltage [mV] (Input Volt. 76 [V])	0	5	5	7	10	10	14	10	10	21	10	10	28	10	10	35	10	10	42	10	10	---	—	—	---	—	—	---	—	—	---	—	—
Load Current [A]	Ripple Output Voltage [mV] (Input Volt. 36 [V])	Ripple Output Voltage [mV] (Input Volt. 76 [V])																																			
0	5	5																																			
7	10	10																																			
14	10	10																																			
21	10	10																																			
28	10	10																																			
35	10	10																																			
42	10	10																																			
---	—	—																																			
---	—	—																																			
---	—	—																																			
---	—	—																																			
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p - p 値で示される。 (注) 斜線は定格負荷電流範囲を示す。</p>																																					
<p>Ripple [mVp-p]</p>																																					
<p>Fig. Complex Ripple Wave Form 図 リップル波形図</p>																																					

COSSEL

Model	CBS2004803																																							
Item	Ripple-Noise リップルノイズ	Temperature 25°C Testing Circuitry Figure A																																						
Object	+3.3V35A																																							
1. Graph																																								
<p>—▲— Input Volt. 36V - - ○ - - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from Figure 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>Ripple-Noise [mV] (Input Volt. 36V)</th> <th>Ripple-Noise [mV] (Input Volt. 76V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>20</td><td>30</td></tr> <tr><td>7</td><td>25</td><td>30</td></tr> <tr><td>14</td><td>25</td><td>30</td></tr> <tr><td>21</td><td>30</td><td>30</td></tr> <tr><td>28</td><td>30</td><td>30</td></tr> <tr><td>35</td><td>35</td><td>40</td></tr> <tr><td>42</td><td>40</td><td>45</td></tr> </tbody> </table>		Load Current [A]	Ripple-Noise [mV] (Input Volt. 36V)	Ripple-Noise [mV] (Input Volt. 76V)	0	20	30	7	25	30	14	25	30	21	30	30	28	30	30	35	35	40	42	40	45															
Load Current [A]	Ripple-Noise [mV] (Input Volt. 36V)	Ripple-Noise [mV] (Input Volt. 76V)																																						
0	20	30																																						
7	25	30																																						
14	25	30																																						
21	30	30																																						
28	30	30																																						
35	35	40																																						
42	40	45																																						
2. Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 36 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>20</td><td>30</td></tr> <tr><td>7</td><td>25</td><td>30</td></tr> <tr><td>14</td><td>25</td><td>30</td></tr> <tr><td>21</td><td>30</td><td>30</td></tr> <tr><td>28</td><td>30</td><td>30</td></tr> <tr><td>35</td><td>35</td><td>40</td></tr> <tr><td>42</td><td>40</td><td>45</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0	20	30	7	25	30	14	25	30	21	30	30	28	30	30	35	35	40	42	40	45	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 36 [V]	Input Volt. 76 [V]																																						
0	20	30																																						
7	25	30																																						
14	25	30																																						
21	30	30																																						
28	30	30																																						
35	35	40																																						
42	40	45																																						
--	--	--																																						
--	--	--																																						
--	--	--																																						
--	--	--																																						
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図p-p値で示される。 (注) 斜線は定格負荷電流範囲を示す。</p> <p>Fig. Complex Ripple Noise Wave Form 図 リップルノイズ波形</p>																																								

COSEL

Model	CBS2004803	Temperature Testing Circuitry	25°C Figure A	
Item	Overcurrent Protection 過電流保護			
Object	+3.3V35A	2. Values		
1. Graph	<p>Input Volt. 36V Input Volt. 48V Input Volt. 76V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>	Output Voltage [V]	Load Current [A]	
		36[V]	48[V]	76[V]
	3.300	35.51	36.99	36.93
	3.135	44.88	44.73	46.51
	2.970	44.93	44.89	46.95
	2.640	45.04	45.14	47.59
	--	--	--	--
	--	--	--	--
	--	--	--	--
	--	--	--	--
	--	--	--	--
	--	--	--	--
	--	--	--	--
	--	--	--	--

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

Intermittent operation occurs when the output voltage is from 2.5V to 0V.


2.5V~0V間は、間欠モードとなる。




<p>Testing Circuitry Figure A</p>																	
<p>Model CBS2004803</p> <p>Item Overvoltage Protection 過電圧保護</p> <p>Object +3.3V35A</p> <p>1. Graph</p> <p>Operating Point [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 0%</p>																	
<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th><th colspan="3">Operating Point [V]</th></tr> <tr> <th>Input Volt. 36[V]</th><th>Input Volt. 48[V]</th><th>Input Volt. 76[V]</th></tr> </thead> <tbody> <tr> <td>-50</td><td>4.25</td><td>4.25</td><td>4.25</td></tr> <tr> <td>-40</td><td>4.25</td><td>4.25</td><td>4.25</td></tr> </tbody> </table>			Ambient Temperature [°C]	Operating Point [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	-50	4.25	4.25	4.25	-40	4.25	4.25	4.25
Ambient Temperature [°C]	Operating Point [V]																
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]														
-50	4.25	4.25	4.25														
-40	4.25	4.25	4.25														

Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

COSEL

COSEL



COSSEL

Model	CBS2004803																																																					
Item	Ambient Temperature Drift 周囲温度変動																																																					
Object	+3.3V35A																																																					
Testing Circuitry Figure A																																																						
1. Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 36V Input Volt. 48V Input Volt. 76V 																																																					
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>-50</td><td>3.309</td><td>3.309</td><td>3.309</td></tr> <tr> <td>-40</td><td>3.310</td><td>3.311</td><td>3.311</td></tr> <tr> <td>-20</td><td>3.312</td><td>3.313</td><td>3.313</td></tr> <tr> <td>0</td><td>3.314</td><td>3.314</td><td>3.314</td></tr> <tr> <td>25</td><td>3.314</td><td>3.314</td><td>3.314</td></tr> <tr> <td>40</td><td>3.311</td><td>3.311</td><td>3.311</td></tr> <tr> <td>60</td><td>3.307</td><td>3.307</td><td>3.306</td></tr> <tr> <td>85</td><td>3.300</td><td>3.300</td><td>3.300</td></tr> <tr> <td>100</td><td>3.296</td><td>3.295</td><td>3.295</td></tr> <tr> <td>105</td><td>3.293</td><td>3.293</td><td>3.293</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	-50	3.309	3.309	3.309	-40	3.310	3.311	3.311	-20	3.312	3.313	3.313	0	3.314	3.314	3.314	25	3.314	3.314	3.314	40	3.311	3.311	3.311	60	3.307	3.307	3.306	85	3.300	3.300	3.300	100	3.296	3.295	3.295	105	3.293	3.293	3.293	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
-50	3.309	3.309	3.309																																																			
-40	3.310	3.311	3.311																																																			
-20	3.312	3.313	3.313																																																			
0	3.314	3.314	3.314																																																			
25	3.314	3.314	3.314																																																			
40	3.311	3.311	3.311																																																			
60	3.307	3.307	3.306																																																			
85	3.300	3.300	3.300																																																			
100	3.296	3.295	3.295																																																			
105	3.293	3.293	3.293																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated ambient temperature.	<p>(注) 斜線は定格周囲温度範囲を示す。</p>																																																					


COSEL

<p>Model CBS2004803</p> <p>Item Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧</p> <p>Object +3.3V35A</p>	Testing Circuitry Figure A																																				
	1. Graph	2. Values																																			
	<p style="text-align: center;">---□--- Load 50% —△— Load 100%</p> <table border="1"> <caption>Data points from Figure A Graph</caption> <thead> <tr> <th>Ambient Temperature [°C]</th> <th>Load 50% [V]</th> <th>Load 100% [V]</th> </tr> </thead> <tbody> <tr><td>-50</td><td>28.3</td><td>28.4</td></tr> <tr><td>-40</td><td>28.3</td><td>28.4</td></tr> <tr><td>-20</td><td>28.3</td><td>28.4</td></tr> <tr><td>0</td><td>28.3</td><td>28.4</td></tr> <tr><td>25</td><td>28.3</td><td>28.4</td></tr> <tr><td>40</td><td>28.1</td><td>28.1</td></tr> <tr><td>60</td><td>28.1</td><td>27.9</td></tr> <tr><td>85</td><td>27.8</td><td>27.9</td></tr> <tr><td>100</td><td>27.7</td><td>27.7</td></tr> <tr><td>105</td><td>27.7</td><td>27.7</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Load 50% [V]	Load 100% [V]	-50	28.3	28.4	-40	28.3	28.4	-20	28.3	28.4	0	28.3	28.4	25	28.3	28.4	40	28.1	28.1	60	28.1	27.9	85	27.8	27.9	100	27.7	27.7	105	27.7	27.7	--	-	-
Ambient Temperature [°C]	Load 50% [V]	Load 100% [V]																																			
-50	28.3	28.4																																			
-40	28.3	28.4																																			
-20	28.3	28.4																																			
0	28.3	28.4																																			
25	28.3	28.4																																			
40	28.1	28.1																																			
60	28.1	27.9																																			
85	27.8	27.9																																			
100	27.7	27.7																																			
105	27.7	27.7																																			
--	-	-																																			
<p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>(注) 斜線は定格周囲温度範囲を示す。</p>																																					

COSEL

Model	CBS2004803
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)
Object	+3.3V35A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-50	100	100
-40	75	75
-20	30	30
0	15	15
25	10	10
40	10	10
60	10	10
85	10	10
100	15	15
105	15	15
--	—	—

COSEL

Model	CBS2004803	Temperature	25°C																						
Item	Time Lapse Drift 経時ドリフト	Testing Circuitry	Figure A																						
Object	+3.3V35A																								
1. Graph	<p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V Load 100%</p>																								
2. Values	<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>3.310</td></tr> <tr><td>0.5</td><td>3.308</td></tr> <tr><td>1.0</td><td>3.308</td></tr> <tr><td>2.0</td><td>3.308</td></tr> <tr><td>3.0</td><td>3.308</td></tr> <tr><td>4.0</td><td>3.308</td></tr> <tr><td>5.0</td><td>3.308</td></tr> <tr><td>6.0</td><td>3.308</td></tr> <tr><td>7.0</td><td>3.308</td></tr> <tr><td>8.0</td><td>3.308</td></tr> </tbody> </table>			Time since start [H]	Output Voltage [V]	0.0	3.310	0.5	3.308	1.0	3.308	2.0	3.308	3.0	3.308	4.0	3.308	5.0	3.308	6.0	3.308	7.0	3.308	8.0	3.308
Time since start [H]	Output Voltage [V]																								
0.0	3.310																								
0.5	3.308																								
1.0	3.308																								
2.0	3.308																								
3.0	3.308																								
4.0	3.308																								
5.0	3.308																								
6.0	3.308																								
7.0	3.308																								
8.0	3.308																								



Model	CBS2004803	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	+3.3V35A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 ~ 100°C

Input Voltage : 36 ~ 76V

Load Current : 0 ~ 35A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 : -40 ~ 100°C

入力電圧 : 36 ~ 76V

負荷電流 : 0 ~ 35A

* 定電圧精度(変動値) = ±(出力電圧の最高値 - 出力電圧の最低値) / 2

$$* \text{定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	25	76	0	3.313	±10	±0.3
Minimum Voltage	100	76	35	3.294		



Model	CBS2004803	Testing Circuitry Figure A
Item	Condense 結露特性	
Object	+3.3V35A	

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	3.311	Input Volt.:48V, Load Current.:35A
Line Regulation [mV]	1	Input Volt.:36~76V, Load Current.:35A
Load Regulation [mV]	2	Input Volt.:48V, Load Current.:0~35A



Model	CBS2004803	Temperature Testing Circuitry	25°C Figure B
Item	Line Noise Tolerance 入力雑音耐量		
Object	+3.3V35A		

1. Conditions

- Input Voltage : 48 V
- Pulse Input Duration : 1 min. or more
- Pulse Voltage : 2000 V
- Load : 100 %
- Pulse Cycle : 16.7 ms

2. Results

Pulse Width [ns]	MODE	No protection failure should occur		DC-like Regulation of Output Voltage 出力電圧の直流的変動
		POLARITY	保護回路の誤動作がない	
50	COMMON	+	OK	no fluctuation
		-	OK	no fluctuation
	NORMAL	+	OK	no fluctuation
		-	OK	no fluctuation
1000	COMMON	+	OK	no fluctuation
		-	OK	no fluctuation
	NORMAL	+	OK	no fluctuation
		-	OK	no fluctuation

COSEL






Figure C

C1 : 100V 33 μ F

C2 : 4700pF

C3 : 50V 0.1 μ F(-40°C \leq T_B \leq -20°C)

C4 : CBS2004803, 05	10V 2200 μ F \times 2
CBS2004812, 15	25V 1000 μ F \times 2
CBS2004824, 28	35V 470 μ F \times 2

(-20°C < T_B \leq 100°C)

C4 : CBS2004803, 05	10V 2200 μ F
CBS2004812, 15	25V 1000 μ F
CBS2004824, 28	35V 470 μ F

T_B:Base Plate Temp.