

TEST DATA OF CBS4504832

Regulated DC Power Supply
Aug 29, 2008

Approved by : Tatsuya Mano
Tatsuya Mano Design Manager

Prepared by : Takuya Mori
Takuya Mori Design Engineer

COSEL CO.,LTD.


CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Overvoltage Protection	18
19.Figure of Testing Circuitry	19

(Final Page 19)



Model	CBS4504832	Temperature	25°C
Item	Input Current (by Input Voltage)	Testing Circuitry	Figure A
Object	_____		



Note: Slanted line shows the range of the rated input voltage.

2.Values

Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0.0	0.000	0.000	0.000
8.0	0.002	0.002	0.002
16.0	0.000	0.000	0.002
24.0	0.006	0.006	0.006
27.4	0.006	0.006	0.006
30.6	0.079	6.660	12.500
32.2	0.078	6.870	13.120
33.0	0.077	6.660	13.420
36.0	0.074	6.060	12.210
40.0	0.072	5.450	10.930
48.0	0.060	4.580	9.140
60.0	0.047	3.704	7.330
70.0	0.041	3.206	6.320
76.0	0.040	2.968	5.840
80.0	0.038	2.830	5.560
-	-	-	-
-	-	-	-
-	-	-	-



Model		CBS4504832		Temperature 25°C																																																				
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		—△— Input Volt. 36V - - □ - - Input Volt. 48V - · ○ - · - Input Volt. 76V		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.074</td><td>0.060</td><td>0.040</td></tr> <tr><td>2.00</td><td>2.010</td><td>1.514</td><td>1.011</td></tr> <tr><td>4.00</td><td>3.888</td><td>2.956</td><td>1.940</td></tr> <tr><td>6.00</td><td>5.780</td><td>4.382</td><td>2.844</td></tr> <tr><td>8.00</td><td>7.720</td><td>5.820</td><td>3.754</td></tr> <tr><td>10.00</td><td>9.680</td><td>7.270</td><td>4.680</td></tr> <tr><td>12.00</td><td>11.680</td><td>8.760</td><td>5.610</td></tr> <tr><td>12.50</td><td>12.210</td><td>9.140</td><td>5.840</td></tr> <tr><td>13.75</td><td>13.510</td><td>10.080</td><td>6.440</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	0.074	0.060	0.040	2.00	2.010	1.514	1.011	4.00	3.888	2.956	1.940	6.00	5.780	4.382	2.844	8.00	7.720	5.820	3.754	10.00	9.680	7.270	4.680	12.00	11.680	8.760	5.610	12.50	12.210	9.140	5.840	13.75	13.510	10.080	6.440	-	-	-	-	-	-	-	-
Load Current [A]	Input Current [A]																																																							
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																					
0.00	0.074	0.060	0.040																																																					
2.00	2.010	1.514	1.011																																																					
4.00	3.888	2.956	1.940																																																					
6.00	5.780	4.382	2.844																																																					
8.00	7.720	5.820	3.754																																																					
10.00	9.680	7.270	4.680																																																					
12.00	11.680	8.760	5.610																																																					
12.50	12.210	9.140	5.840																																																					
13.75	13.510	10.080	6.440																																																					
-	-	-	-																																																					
-	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								



Model		CBS4504832		Temperature 25°C																																																				
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		—△— Input Volt. 36V ---□--- Input Volt. 48V -·-○-·- Input Volt. 76V		2.Values																																																				
				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>2.7</td><td>2.9</td><td>3.0</td></tr> <tr><td>2.00</td><td>72.2</td><td>72.7</td><td>76.8</td></tr> <tr><td>4.00</td><td>140.0</td><td>141.8</td><td>147.3</td></tr> <tr><td>6.00</td><td>208.6</td><td>210.2</td><td>215.7</td></tr> <tr><td>8.00</td><td>277.9</td><td>279.4</td><td>285.0</td></tr> <tr><td>10.00</td><td>349.0</td><td>349.3</td><td>355.0</td></tr> <tr><td>12.00</td><td>421.0</td><td>420.5</td><td>426.0</td></tr> <tr><td>12.50</td><td>439.0</td><td>439.0</td><td>444.0</td></tr> <tr><td>13.75</td><td>486.0</td><td>484.0</td><td>488.0</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	2.7	2.9	3.0	2.00	72.2	72.7	76.8	4.00	140.0	141.8	147.3	6.00	208.6	210.2	215.7	8.00	277.9	279.4	285.0	10.00	349.0	349.3	355.0	12.00	421.0	420.5	426.0	12.50	439.0	439.0	444.0	13.75	486.0	484.0	488.0	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																							
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																					
0.00	2.7	2.9	3.0																																																					
2.00	72.2	72.7	76.8																																																					
4.00	140.0	141.8	147.3																																																					
6.00	208.6	210.2	215.7																																																					
8.00	277.9	279.4	285.0																																																					
10.00	349.0	349.3	355.0																																																					
12.00	421.0	420.5	426.0																																																					
12.50	439.0	439.0	444.0																																																					
13.75	486.0	484.0	488.0																																																					
--	-	-	-																																																					
--	-	-	-																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>																																																								



Model		CBS4504832		Temperature 25°C Testing Circuitry Figure A																																
Item		Efficiency (by Input Voltage)																																		
Object		_____																																		
1.Graph			2.Values																																	
<p>---□--- Load 50% —△— Load 100%</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>33</td><td>91.2</td><td>90.1</td></tr> <tr><td>36</td><td>92.2</td><td>91.2</td></tr> <tr><td>40</td><td>92.2</td><td>91.4</td></tr> <tr><td>48</td><td>91.5</td><td>91.2</td></tr> <tr><td>55</td><td>91.0</td><td>91.1</td></tr> <tr><td>60</td><td>90.6</td><td>90.9</td></tr> <tr><td>70</td><td>89.7</td><td>90.6</td></tr> <tr><td>76</td><td>89.2</td><td>90.2</td></tr> <tr><td>80</td><td>88.8</td><td>89.9</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	33	91.2	90.1	36	92.2	91.2	40	92.2	91.4	48	91.5	91.2	55	91.0	91.1	60	90.6	90.9	70	89.7	90.6	76	89.2	90.2	80	88.8	89.9
Input Voltage [V]	Efficiency [%]																																			
	Load 50%	Load 100%																																		
33	91.2	90.1																																		
36	92.2	91.2																																		
40	92.2	91.4																																		
48	91.5	91.2																																		
55	91.0	91.1																																		
60	90.6	90.9																																		
70	89.7	90.6																																		
76	89.2	90.2																																		
80	88.8	89.9																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																				



Model		CBS4504832	Temperature		25°C																																																		
Item		Efficiency (by Load Current)	Testing Circuitry		Figure A																																																		
Object																																																							
1.Graph		—△— Input Volt. 36V - - □ - - Input Volt. 48V - · ○ - · Input Volt. 76V	2.Values																																																				
Efficiency [%] 	100	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.00</td><td>89.1</td><td>88.4</td><td>83.3</td></tr> <tr><td>4.00</td><td>91.6</td><td>90.4</td><td>86.8</td></tr> <tr><td>6.00</td><td>92.2</td><td>91.5</td><td>89.1</td></tr> <tr><td>8.00</td><td>92.2</td><td>91.8</td><td>89.9</td></tr> <tr><td>10.00</td><td>91.7</td><td>91.7</td><td>90.2</td></tr> <tr><td>12.00</td><td>91.3</td><td>91.4</td><td>90.2</td></tr> <tr><td>12.50</td><td>91.2</td><td>91.2</td><td>90.2</td></tr> <tr><td>13.75</td><td>90.6</td><td>90.9</td><td>90.2</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	-	-	-	2.00	89.1	88.4	83.3	4.00	91.6	90.4	86.8	6.00	92.2	91.5	89.1	8.00	92.2	91.8	89.9	10.00	91.7	91.7	90.2	12.00	91.3	91.4	90.2	12.50	91.2	91.2	90.2	13.75	90.6	90.9	90.2	--	-	-	-	--	-	-	-
	Load Current [A]	Efficiency [%]																																																					
		Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
	0.00	-	-	-																																																			
	2.00	89.1	88.4	83.3																																																			
	4.00	91.6	90.4	86.8																																																			
	6.00	92.2	91.5	89.1																																																			
	8.00	92.2	91.8	89.9																																																			
	10.00	91.7	91.7	90.2																																																			
	12.00	91.3	91.4	90.2																																																			
	12.50	91.2	91.2	90.2																																																			
	13.75	90.6	90.9	90.2																																																			
	--	-	-	-																																																			
	--	-	-	-																																																			
92																																																							
84																																																							
76																																																							
68																																																							
60																																																							
52																																																							
44																																																							
0	4	8	12																																																				
		Load Current [A]																																																					
Note: Slanted line shows the range of the rated load current.																																																							



Model		CBS4504832	Temperature 25°C Testing Circuitry Figure A																																
Item		Line Regulation																																	
Object		+32V12.5A																																	
1.Graph			2.Values																																
<p>---□--- Load 50% —△— Load 100%</p>																																			
<p>Note: Slanted line shows the range of the rated input voltage.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>33</td><td>32.137</td><td>-</td></tr> <tr><td>36</td><td>32.137</td><td>32.137</td></tr> <tr><td>40</td><td>32.137</td><td>32.137</td></tr> <tr><td>48</td><td>32.137</td><td>32.137</td></tr> <tr><td>55</td><td>32.137</td><td>32.137</td></tr> <tr><td>60</td><td>32.137</td><td>32.137</td></tr> <tr><td>70</td><td>32.137</td><td>32.137</td></tr> <tr><td>76</td><td>32.137</td><td>32.137</td></tr> <tr><td>80</td><td>32.137</td><td>32.137</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	33	32.137	-	36	32.137	32.137	40	32.137	32.137	48	32.137	32.137	55	32.137	32.137	60	32.137	32.137	70	32.137	32.137	76	32.137	32.137	80	32.137	32.137
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
33	32.137	-																																	
36	32.137	32.137																																	
40	32.137	32.137																																	
48	32.137	32.137																																	
55	32.137	32.137																																	
60	32.137	32.137																																	
70	32.137	32.137																																	
76	32.137	32.137																																	
80	32.137	32.137																																	



<p>Model CBS4504832</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
<p>Item Load Regulation</p>																																																					
<p>Object +32V12.5A</p>																																																					
<p>1.Graph</p> <p> —△— Input Volt. 36V ---□--- Input Volt. 48V -·-○-·- Input Volt. 76V </p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>32.135</td><td>32.136</td><td>32.136</td></tr> <tr><td>2.00</td><td>32.135</td><td>32.136</td><td>32.136</td></tr> <tr><td>4.00</td><td>32.136</td><td>32.136</td><td>32.136</td></tr> <tr><td>6.00</td><td>32.136</td><td>32.136</td><td>32.136</td></tr> <tr><td>8.00</td><td>32.136</td><td>32.136</td><td>32.136</td></tr> <tr><td>10.00</td><td>32.137</td><td>32.137</td><td>32.136</td></tr> <tr><td>12.00</td><td>32.137</td><td>32.137</td><td>32.137</td></tr> <tr><td>12.50</td><td>32.137</td><td>32.137</td><td>32.137</td></tr> <tr><td>13.75</td><td>32.137</td><td>32.137</td><td>32.137</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	32.135	32.136	32.136	2.00	32.135	32.136	32.136	4.00	32.136	32.136	32.136	6.00	32.136	32.136	32.136	8.00	32.136	32.136	32.136	10.00	32.137	32.137	32.136	12.00	32.137	32.137	32.137	12.50	32.137	32.137	32.137	13.75	32.137	32.137	32.137	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																				
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																		
0.00	32.135	32.136	32.136																																																		
2.00	32.135	32.136	32.136																																																		
4.00	32.136	32.136	32.136																																																		
6.00	32.136	32.136	32.136																																																		
8.00	32.136	32.136	32.136																																																		
10.00	32.137	32.137	32.136																																																		
12.00	32.137	32.137	32.137																																																		
12.50	32.137	32.137	32.137																																																		
13.75	32.137	32.137	32.137																																																		
--	-	-	-																																																		
--	-	-	-																																																		
<p>Note: Slanted line shows the range of the rated load current.</p>																																																					



Model	CBS4504832
Item	Dynamic Load Response
Object	+32V12.5A


Temperature 25°C
Testing Circuitry Figure A

Input Volt. 48 V
Cycle 1000 mS




Min. Load (0A) ←→
Load 100% (12.5A)

1 V/div




500µs/div




5ms/div

Min. Load (0A) ←→
Load 50% (6.25A)

1 V/div




500µs/div




5ms/div

Load 10% (1.25A) ←→
Load 100% (12.5A)

1 V/div



500µs/div



5ms/div



<p>Model CBS4504832</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
<p>Item Ripple Voltage (by Load Current)</p>																																								
<p>Object +32V12.5A</p>																																								
<p>1.Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 36V -·-○-·- Input Volt. 76V</p> </div> <p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 36 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>15</td></tr> <tr><td>2.00</td><td>25</td><td>45</td></tr> <tr><td>4.00</td><td>30</td><td>55</td></tr> <tr><td>6.00</td><td>30</td><td>55</td></tr> <tr><td>8.00</td><td>30</td><td>55</td></tr> <tr><td>10.00</td><td>30</td><td>55</td></tr> <tr><td>12.00</td><td>30</td><td>55</td></tr> <tr><td>12.50</td><td>30</td><td>60</td></tr> <tr><td>13.75</td><td>30</td><td>60</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.00	10	15	2.00	25	45	4.00	30	55	6.00	30	55	8.00	30	55	10.00	30	55	12.00	30	55	12.50	30	60	13.75	30	60	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 36 [V]	Input Volt. 76 [V]																																						
0.00	10	15																																						
2.00	25	45																																						
4.00	30	55																																						
6.00	30	55																																						
8.00	30	55																																						
10.00	30	55																																						
12.00	30	55																																						
12.50	30	60																																						
13.75	30	60																																						
--	-	-																																						
--	-	-																																						
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								




<p>Model CBS4504832</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
<p>Item Ripple-Noise</p>																																								
<p>Object +32V12.5A</p>																																								
<p>1.Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 36V - -○- - Input Volt. 76V</p> </div> <p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 36 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>20</td><td>40</td></tr> <tr><td>2.00</td><td>30</td><td>55</td></tr> <tr><td>4.00</td><td>35</td><td>60</td></tr> <tr><td>6.00</td><td>35</td><td>60</td></tr> <tr><td>8.00</td><td>40</td><td>65</td></tr> <tr><td>10.00</td><td>50</td><td>70</td></tr> <tr><td>12.00</td><td>55</td><td>75</td></tr> <tr><td>12.50</td><td>60</td><td>80</td></tr> <tr><td>13.75</td><td>60</td><td>80</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.00	20	40	2.00	30	55	4.00	35	60	6.00	35	60	8.00	40	65	10.00	50	70	12.00	55	75	12.50	60	80	13.75	60	80	-	-	-	-	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 36 [V]	Input Volt. 76 [V]																																						
0.00	20	40																																						
2.00	30	55																																						
4.00	35	60																																						
6.00	35	60																																						
8.00	40	65																																						
10.00	50	70																																						
12.00	55	75																																						
12.50	60	80																																						
13.75	60	80																																						
-	-	-																																						
-	-	-																																						
<p>Fig.Complex Ripple Noise Wave Form</p>																																								



Model	CBS4504832
Item	Ripple Voltage (by Ambient Temp.)
Object	+32V12.5A

Testing Circuitry Figure B

1.Graph



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-50	70	70
-40	70	70
-20	60	60
0	50	50
25	40	40
40	40	40
60	40	40
85	40	40
100	35	35
105	35	35
-	-	-

Measured by 100 MHz Oscilloscope.
 Note: Slanted line shows the range of the rated ambient temperature.




Fig.Complex Ripple Wave Form




Model	CBS4504832
Item	Ambient Temperature Drift
Object	+32V12.5A

Testing Circuitry Figure A

1.Graph

- △— Input Volt. 36V
- Input Volt. 48V
- Input Volt. 76V



Load 100%

Note: Slanted line shows the range of the rated ambient temperature.

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-50	32.017	32.020	32.025
-40	32.045	32.048	32.051
-20	32.098	32.100	32.102
0	32.124	32.124	32.125
25	32.132	32.131	32.130
40	32.125	32.124	32.123
60	32.105	32.103	32.101
85	32.066	32.062	32.059
100	32.032	32.029	32.024
-	-	-	-
-	-	-	-



COSEL		
Model	CBS4504832	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+32V12.5A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 100°C

Input Voltage : 36 - 76V

Load Current : 0 - 12.5A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	25	36	12.5	32.132	±54	±0.2
Minimum Voltage	100	76	12.5	32.024		




Model CBS4504832		Temperature 25°C Testing Circuitry Figure A																						
Item	Time Lapse Drift																							
Object	+32V12.5A																							
1.Graph  <p style="text-align: center;">Time [H]</p> <p>Input Volt. 48V Load 100%</p>		2.Values <table border="1" data-bbox="909 481 1284 1025"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>32.138</td></tr> <tr><td>0.5</td><td>32.137</td></tr> <tr><td>1.0</td><td>32.136</td></tr> <tr><td>2.0</td><td>32.136</td></tr> <tr><td>3.0</td><td>32.136</td></tr> <tr><td>4.0</td><td>32.136</td></tr> <tr><td>5.0</td><td>32.136</td></tr> <tr><td>6.0</td><td>32.136</td></tr> <tr><td>7.0</td><td>32.136</td></tr> <tr><td>8.0</td><td>32.136</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	32.138	0.5	32.137	1.0	32.136	2.0	32.136	3.0	32.136	4.0	32.136	5.0	32.136	6.0	32.136	7.0	32.136	8.0	32.136
Time since start [H]	Output Voltage [V]																							
0.0	32.138																							
0.5	32.137																							
1.0	32.136																							
2.0	32.136																							
3.0	32.136																							
4.0	32.136																							
5.0	32.136																							
6.0	32.136																							
7.0	32.136																							
8.0	32.136																							



Model		CBS4504832	Temperature 25°C Testing Circuitry Figure A
Item		Rise and Fall Time	
Object		+32V12.5A	

1. Graph


Input Volt. 48 V



2. Values

[mS]

Load \ Time	Td	Tr	Ts	Th	Tf
50 %	22.3	4.8	27.1	0.5	8.4
100 %	22.3	4.8	27.1	0.3	4.3





<p>Model CBS4504832</p> <p>Item Minimum Input Voltage for Regulated Output Voltage</p> <p>Object +32V12.5A</p>		<p>Testing Circuitry Figure A</p>																																						
<p>1.Graph</p> <div style="text-align: right;"> <p>---□--- Load 50%</p> <p>—△— Load 100%</p> </div> <p style="text-align: center;">Ambient Temperature [°C]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-50</td><td>30.2</td><td>31.1</td></tr> <tr><td>-40</td><td>30.2</td><td>31.1</td></tr> <tr><td>-20</td><td>30.7</td><td>31.5</td></tr> <tr><td>0</td><td>30.9</td><td>31.8</td></tr> <tr><td>25</td><td>30.9</td><td>32.0</td></tr> <tr><td>40</td><td>31.0</td><td>32.1</td></tr> <tr><td>60</td><td>31.0</td><td>32.1</td></tr> <tr><td>85</td><td>31.0</td><td>32.3</td></tr> <tr><td>100</td><td>31.0</td><td>32.3</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-50	30.2	31.1	-40	30.2	31.1	-20	30.7	31.5	0	30.9	31.8	25	30.9	32.0	40	31.0	32.1	60	31.0	32.1	85	31.0	32.3	100	31.0	32.3	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-50	30.2	31.1																																						
-40	30.2	31.1																																						
-20	30.7	31.5																																						
0	30.9	31.8																																						
25	30.9	32.0																																						
40	31.0	32.1																																						
60	31.0	32.1																																						
85	31.0	32.3																																						
100	31.0	32.3																																						
--	-	-																																						
--	-	-																																						
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																								



<p>Model CBS4504832</p> <p>Item Overcurrent Protection</p> <p>Object +32V12.5A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure A</p>																																																							
<p>1.Graph</p> <p> Input Volt. 36V Input Volt. 48V Input Volt. 76V </p> <p style="text-align: center;">Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when the output voltage is from 19.2V to 0V.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>32.0</td> <td>12.60</td> <td>12.61</td> <td>12.61</td> </tr> <tr> <td>30.4</td> <td>15.78</td> <td>15.58</td> <td>16.06</td> </tr> <tr> <td>28.8</td> <td>15.74</td> <td>15.66</td> <td>16.22</td> </tr> <tr> <td>25.6</td> <td>15.79</td> <td>15.86</td> <td>16.59</td> </tr> <tr> <td>22.4</td> <td>15.91</td> <td>16.05</td> <td>16.91</td> </tr> <tr> <td>19.2</td> <td>16.03</td> <td>16.22</td> <td>17.43</td> </tr> <tr> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	32.0	12.60	12.61	12.61	30.4	15.78	15.58	16.06	28.8	15.74	15.66	16.22	25.6	15.79	15.86	16.59	22.4	15.91	16.05	16.91	19.2	16.03	16.22	17.43	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																						
32.0	12.60	12.61	12.61																																																						
30.4	15.78	15.58	16.06																																																						
28.8	15.74	15.66	16.22																																																						
25.6	15.79	15.86	16.59																																																						
22.4	15.91	16.05	16.91																																																						
19.2	16.03	16.22	17.43																																																						
-	-	-	-																																																						
-	-	-	-																																																						
-	-	-	-																																																						
-	-	-	-																																																						
-	-	-	-																																																						
-	-	-	-																																																						



Model		CBS4504832	Testing Circuitry Figure A																																																					
Item		Overvoltage Protection																																																						
Object		+32V12.5A																																																						
1.Graph		<p> —△— Input Volt. 36V ---□--- Input Volt. 48V -·-○-·- Input Volt. 76V </p> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: right;">Load 0%</p>	2.Values																																																					
			<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>-50</td><td>41.55</td><td>41.55</td><td>41.55</td></tr> <tr><td>-40</td><td>41.55</td><td>41.55</td><td>41.55</td></tr> <tr><td>-20</td><td>41.67</td><td>41.67</td><td>41.67</td></tr> <tr><td>0</td><td>41.67</td><td>41.67</td><td>41.67</td></tr> <tr><td>25</td><td>41.55</td><td>41.55</td><td>41.55</td></tr> <tr><td>40</td><td>41.55</td><td>41.55</td><td>41.55</td></tr> <tr><td>60</td><td>41.55</td><td>41.55</td><td>41.55</td></tr> <tr><td>85</td><td>41.49</td><td>41.49</td><td>41.49</td></tr> <tr><td>100</td><td>41.37</td><td>41.37</td><td>41.37</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Ambient Temperature [°C]	Operating Point [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	-50	41.55	41.55	41.55	-40	41.55	41.55	41.55	-20	41.67	41.67	41.67	0	41.67	41.67	41.67	25	41.55	41.55	41.55	40	41.55	41.55	41.55	60	41.55	41.55	41.55	85	41.49	41.49	41.49	100	41.37	41.37	41.37	-	-	-	-	-	-	-	-
Ambient Temperature [°C]	Operating Point [V]																																																							
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																					
-50	41.55	41.55	41.55																																																					
-40	41.55	41.55	41.55																																																					
-20	41.67	41.67	41.67																																																					
0	41.67	41.67	41.67																																																					
25	41.55	41.55	41.55																																																					
40	41.55	41.55	41.55																																																					
60	41.55	41.55	41.55																																																					
85	41.49	41.49	41.49																																																					
100	41.37	41.37	41.37																																																					
-	-	-	-																																																					
-	-	-	-																																																					
Note: Slanted line shows the range of the rated ambient temperature.																																																								




Figure A




Figure B