

TEST DATA OF CBS502415

(24V INPUT)

Regulated DC Power Supply

Jun. 22, 2002

Approved by : Isao Yasuda
Isao Yasuda Design Manager

Prepared by : Kouichi Kinoshita
Kouichi Kinoshita Design Engineer

コーワセル株式会社
COSEL CO.,LTD.

C O N T E N T S

1. Line Regulation	1
静的入力変動	
2. Input Current (by Input Voltage)	2
入力電流 (入力電圧特性)	
3. Input Current (by Load Current)	3
入力電流 (負荷特性)	
4. Input Power (by Load Current)	4
入力電力 (負荷特性)	
5. Efficiency (by Input Voltage)	5
効率 (入力電圧特性)	
6. Efficiency (by Load Current)	6
効率 (負荷特性)	
7. Load Regulation	7
静的負荷変動	
8. Ripple Voltage (by Load Current)	8
リップル電圧 (負荷特性)	
9. Ripple-Noise	9
リップルノイズ	
10. Overcurrent Protection	10
過電流保護	
11. Overvoltage Protection	11
過電圧保護	
12. Dynamic Load Response	12
動的負荷変動	
13. Rise and Fall Time	13
立上り、立下り時間	
14. Ambient Temperature Drift	14
周囲温度変動	
15. Minimum Input Voltage for Regulated Output Voltage	15
最低レギュレーション電圧	
16. Ripple Voltage (by Ambient Temperature)	16
リップル電圧 (周囲温度特性)	
17. Time Lapse Drift	17
経時ドリフト	
18. Output Voltage Accuracy	18
定電圧精度	
19. Condensation	19
結露特性	
20. Line Noise Tolerance	20
入力雑音耐量	
21. Figure of Testing Circuitry	21
測定回路図	

(Final Page 21)

COSEL

Model	CBS502415	Temperature	25°C																																
Item	Line Regulation 静的の入力変動	Testing Circuitry	Figure A																																
Object	+15V3.4A																																		
1. Graph			2. Values																																
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line), Load 100% (solid line)</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>16</td><td>15.104</td><td>15.104</td></tr> <tr><td>18</td><td>15.104</td><td>15.104</td></tr> <tr><td>20</td><td>15.104</td><td>15.104</td></tr> <tr><td>24</td><td>15.104</td><td>15.104</td></tr> <tr><td>30</td><td>15.104</td><td>15.104</td></tr> <tr><td>36</td><td>15.104</td><td>15.104</td></tr> <tr><td>40</td><td>15.104</td><td>15.104</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	16	15.104	15.104	18	15.104	15.104	20	15.104	15.104	24	15.104	15.104	30	15.104	15.104	36	15.104	15.104	40	15.104	15.104	--	--	--	--	--	--
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
16	15.104	15.104																																	
18	15.104	15.104																																	
20	15.104	15.104																																	
24	15.104	15.104																																	
30	15.104	15.104																																	
36	15.104	15.104																																	
40	15.104	15.104																																	
--	--	--																																	
--	--	--																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注) 斜線は定格入力電圧範囲を示す。</p>																																			


COSEL

Model	CBS502415	Temperature	25°C																																																																							
Item	Input Current (by Input Voltage) 入力電流 (入力電圧特性)	Testing Circuitry	Figure A																																																																							
Object																																																																										
1. Graph	<p>—△— Load 100%</p> <p>- - □ - - Load 50%</p> <p>- - ○ - - Load 0%</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 0% [A]</th> <th>Load 50% [A]</th> <th>Load 100% [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>12.0</td><td>0.015</td><td>0.015</td><td>0.015</td></tr> <tr><td>15.6</td><td>0.109</td><td>1.930</td><td>3.829</td></tr> <tr><td>16.0</td><td>0.108</td><td>1.876</td><td>3.698</td></tr> <tr><td>18.0</td><td>0.100</td><td>1.656</td><td>3.279</td></tr> <tr><td>20.0</td><td>0.095</td><td>1.493</td><td>2.950</td></tr> <tr><td>24.0</td><td>0.083</td><td>1.258</td><td>2.458</td></tr> <tr><td>28.0</td><td>0.074</td><td>1.089</td><td>2.120</td></tr> <tr><td>32.0</td><td>0.066</td><td>0.962</td><td>1.860</td></tr> <tr><td>36.0</td><td>0.060</td><td>0.864</td><td>1.658</td></tr> <tr><td>40.0</td><td>0.054</td><td>0.788</td><td>1.505</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>			Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]	0	0.000	0.000	0.000	4.0	0.000	0.000	0.000	8.0	0.000	0.000	0.000	12.0	0.015	0.015	0.015	15.6	0.109	1.930	3.829	16.0	0.108	1.876	3.698	18.0	0.100	1.656	3.279	20.0	0.095	1.493	2.950	24.0	0.083	1.258	2.458	28.0	0.074	1.089	2.120	32.0	0.066	0.962	1.860	36.0	0.060	0.864	1.658	40.0	0.054	0.788	1.505	--	--	--	--	--	--	--	--	--	--	--	--			
Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]																																																																							
0	0.000	0.000	0.000																																																																							
4.0	0.000	0.000	0.000																																																																							
8.0	0.000	0.000	0.000																																																																							
12.0	0.015	0.015	0.015																																																																							
15.6	0.109	1.930	3.829																																																																							
16.0	0.108	1.876	3.698																																																																							
18.0	0.100	1.656	3.279																																																																							
20.0	0.095	1.493	2.950																																																																							
24.0	0.083	1.258	2.458																																																																							
28.0	0.074	1.089	2.120																																																																							
32.0	0.066	0.962	1.860																																																																							
36.0	0.060	0.864	1.658																																																																							
40.0	0.054	0.788	1.505																																																																							
--	--	--	--																																																																							
--	--	--	--																																																																							
--	--	--	--																																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>12.0</td><td>0.015</td><td>0.015</td><td>0.015</td></tr> <tr><td>15.6</td><td>0.109</td><td>1.930</td><td>3.829</td></tr> <tr><td>16.0</td><td>0.108</td><td>1.876</td><td>3.698</td></tr> <tr><td>18.0</td><td>0.100</td><td>1.656</td><td>3.279</td></tr> <tr><td>20.0</td><td>0.095</td><td>1.493</td><td>2.950</td></tr> <tr><td>24.0</td><td>0.083</td><td>1.258</td><td>2.458</td></tr> <tr><td>28.0</td><td>0.074</td><td>1.089</td><td>2.120</td></tr> <tr><td>32.0</td><td>0.066</td><td>0.962</td><td>1.860</td></tr> <tr><td>36.0</td><td>0.060</td><td>0.864</td><td>1.658</td></tr> <tr><td>40.0</td><td>0.054</td><td>0.788</td><td>1.505</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	4.0	0.000	0.000	0.000	8.0	0.000	0.000	0.000	12.0	0.015	0.015	0.015	15.6	0.109	1.930	3.829	16.0	0.108	1.876	3.698	18.0	0.100	1.656	3.279	20.0	0.095	1.493	2.950	24.0	0.083	1.258	2.458	28.0	0.074	1.089	2.120	32.0	0.066	0.962	1.860	36.0	0.060	0.864	1.658	40.0	0.054	0.788	1.505	--	--	--	--	--	--	--	--	--	--	--	--
Input Voltage [V]	Input Current [A]																																																																									
	Load 0%	Load 50%	Load 100%																																																																							
0	0.000	0.000	0.000																																																																							
4.0	0.000	0.000	0.000																																																																							
8.0	0.000	0.000	0.000																																																																							
12.0	0.015	0.015	0.015																																																																							
15.6	0.109	1.930	3.829																																																																							
16.0	0.108	1.876	3.698																																																																							
18.0	0.100	1.656	3.279																																																																							
20.0	0.095	1.493	2.950																																																																							
24.0	0.083	1.258	2.458																																																																							
28.0	0.074	1.089	2.120																																																																							
32.0	0.066	0.962	1.860																																																																							
36.0	0.060	0.864	1.658																																																																							
40.0	0.054	0.788	1.505																																																																							
--	--	--	--																																																																							
--	--	--	--																																																																							
--	--	--	--																																																																							

Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。

COSEL

Model	CBS502415																																																					
Item	Input Current (by Load Current) 入力電流 (負荷特性)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	<hr/>																																																					
1. Graph	<p>—△— Input Volt. 18V - - -□- - Input Volt. 24V - - ○- - Input Volt. 36V</p> 																																																					
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.100</td><td>0.084</td><td>0.059</td></tr> <tr><td>0.60</td><td>0.669</td><td>0.513</td><td>0.357</td></tr> <tr><td>1.20</td><td>1.218</td><td>0.926</td><td>0.644</td></tr> <tr><td>1.80</td><td>1.782</td><td>1.338</td><td>0.914</td></tr> <tr><td>2.40</td><td>2.370</td><td>1.766</td><td>1.193</td></tr> <tr><td>3.00</td><td>2.972</td><td>2.204</td><td>1.477</td></tr> <tr><td>3.40</td><td>3.384</td><td>2.500</td><td>1.669</td></tr> <tr><td>3.74</td><td>3.740</td><td>2.753</td><td>1.834</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	0.100	0.084	0.059	0.60	0.669	0.513	0.357	1.20	1.218	0.926	0.644	1.80	1.782	1.338	0.914	2.40	2.370	1.766	1.193	3.00	2.972	2.204	1.477	3.40	3.384	2.500	1.669	3.74	3.740	2.753	1.834	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Input Current [A]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.00	0.100	0.084	0.059																																																			
0.60	0.669	0.513	0.357																																																			
1.20	1.218	0.926	0.644																																																			
1.80	1.782	1.338	0.914																																																			
2.40	2.370	1.766	1.193																																																			
3.00	2.972	2.204	1.477																																																			
3.40	3.384	2.500	1.669																																																			
3.74	3.740	2.753	1.834																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
Note:	Slanted line shows the range of the rated load current.																																																					
(注)	斜線は定格負荷電流範囲を示す。																																																					

COSEL

Model	CBS502415	Temperature	25°C																																																			
Item	Input Power (by Load Current) 入力電力 (負荷特性)	Testing Circuitry	Figure A																																																			
Object																																																						
1. Graph	<p>—▲— Input Volt. 18V ---□--- Input Volt. 24V -○--- Input Volt. 36V</p> <table border="1"> <caption>Data points from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>18[V] [W]</th> <th>24[V] [W]</th> <th>36[V] [W]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.00</td><td>0.00</td><td>0.00</td></tr> <tr><td>0.60</td><td>11.94</td><td>12.25</td><td>12.83</td></tr> <tr><td>1.20</td><td>21.62</td><td>22.03</td><td>23.15</td></tr> <tr><td>1.80</td><td>31.40</td><td>31.74</td><td>32.80</td></tr> <tr><td>2.40</td><td>41.60</td><td>41.81</td><td>42.70</td></tr> <tr><td>3.00</td><td>51.90</td><td>52.10</td><td>52.90</td></tr> <tr><td>3.40</td><td>58.80</td><td>58.90</td><td>59.70</td></tr> <tr><td>3.74</td><td>64.80</td><td>64.70</td><td>65.70</td></tr> </tbody> </table>			Load Current [A]	18[V] [W]	24[V] [W]	36[V] [W]	0.00	0.00	0.00	0.00	0.60	11.94	12.25	12.83	1.20	21.62	22.03	23.15	1.80	31.40	31.74	32.80	2.40	41.60	41.81	42.70	3.00	51.90	52.10	52.90	3.40	58.80	58.90	59.70	3.74	64.80	64.70	65.70															
Load Current [A]	18[V] [W]	24[V] [W]	36[V] [W]																																																			
0.00	0.00	0.00	0.00																																																			
0.60	11.94	12.25	12.83																																																			
1.20	21.62	22.03	23.15																																																			
1.80	31.40	31.74	32.80																																																			
2.40	41.60	41.81	42.70																																																			
3.00	51.90	52.10	52.90																																																			
3.40	58.80	58.90	59.70																																																			
3.74	64.80	64.70	65.70																																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>1.81</td><td>2.04</td><td>2.13</td></tr> <tr><td>0.60</td><td>11.94</td><td>12.25</td><td>12.83</td></tr> <tr><td>1.20</td><td>21.62</td><td>22.03</td><td>23.15</td></tr> <tr><td>1.80</td><td>31.40</td><td>31.74</td><td>32.80</td></tr> <tr><td>2.40</td><td>41.60</td><td>41.81</td><td>42.70</td></tr> <tr><td>3.00</td><td>51.90</td><td>52.10</td><td>52.90</td></tr> <tr><td>3.40</td><td>58.80</td><td>58.90</td><td>59.70</td></tr> <tr><td>3.74</td><td>64.80</td><td>64.70</td><td>65.70</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			18[V]	24[V]	36[V]	0.00	1.81	2.04	2.13	0.60	11.94	12.25	12.83	1.20	21.62	22.03	23.15	1.80	31.40	31.74	32.80	2.40	41.60	41.81	42.70	3.00	51.90	52.10	52.90	3.40	58.80	58.90	59.70	3.74	64.80	64.70	65.70	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Input Power [W]																																																					
	18[V]	24[V]	36[V]																																																			
0.00	1.81	2.04	2.13																																																			
0.60	11.94	12.25	12.83																																																			
1.20	21.62	22.03	23.15																																																			
1.80	31.40	31.74	32.80																																																			
2.40	41.60	41.81	42.70																																																			
3.00	51.90	52.10	52.90																																																			
3.40	58.80	58.90	59.70																																																			
3.74	64.80	64.70	65.70																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
Note: Slanted line shows the range of the rated load current.																																																						
(注) 斜線は定格負荷電流範囲を示す。																																																						

COSEL

Model	CBS502415	Temperature	25°C																															
Item	Efficiency (by Input Voltage) 効率(入力電圧特性)	Testing Circuitry	Figure A																															
Object	<hr/>																																	
1. Graph																																		
			2. Values																															
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>16</td><td>85.6</td><td>86.8</td></tr> <tr> <td>18</td><td>86.2</td><td>87.3</td></tr> <tr> <td>20</td><td>86.0</td><td>87.3</td></tr> <tr> <td>24</td><td>85.1</td><td>87.1</td></tr> <tr> <td>30</td><td>83.7</td><td>86.5</td></tr> <tr> <td>36</td><td>82.3</td><td>85.9</td></tr> <tr> <td>40</td><td>81.2</td><td>85.4</td></tr> <tr> <td>---</td><td>—</td><td>—</td></tr> <tr> <td>---</td><td>—</td><td>—</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	16	85.6	86.8	18	86.2	87.3	20	86.0	87.3	24	85.1	87.1	30	83.7	86.5	36	82.3	85.9	40	81.2	85.4	---	—	—	---	—	—
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
16	85.6	86.8																																
18	86.2	87.3																																
20	86.0	87.3																																
24	85.1	87.1																																
30	83.7	86.5																																
36	82.3	85.9																																
40	81.2	85.4																																
---	—	—																																
---	—	—																																

Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。

COSEL

Model	CBS502415																																																					
Item	Efficiency (by Load Current) 効率(負荷特性)																																																					
Object																																																						
1. Graph		Temperature 25°C Testing Circuitry Figure A																																																				
<p>The graph shows efficiency increasing with load current for all input voltages. The 18V curve is the highest, followed by 24V, and then 36V. A slanted line from the top-left to the bottom-right of the graph area indicates the rated load current range.</p>		<p>2. Values</p> <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>0.60</td><td>76.3</td><td>74.5</td><td>71.0</td></tr> <tr><td>1.20</td><td>84.0</td><td>82.5</td><td>78.4</td></tr> <tr><td>1.80</td><td>86.5</td><td>85.6</td><td>82.8</td></tr> <tr><td>2.40</td><td>87.1</td><td>86.7</td><td>84.9</td></tr> <tr><td>3.00</td><td>87.3</td><td>86.9</td><td>85.6</td></tr> <tr><td>3.40</td><td>87.3</td><td>87.1</td><td>85.9</td></tr> <tr><td>3.74</td><td>87.1</td><td>87.2</td><td>85.9</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	—	—	—	0.60	76.3	74.5	71.0	1.20	84.0	82.5	78.4	1.80	86.5	85.6	82.8	2.40	87.1	86.7	84.9	3.00	87.3	86.9	85.6	3.40	87.3	87.1	85.9	3.74	87.1	87.2	85.9	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.00	—	—	—																																																			
0.60	76.3	74.5	71.0																																																			
1.20	84.0	82.5	78.4																																																			
1.80	86.5	85.6	82.8																																																			
2.40	87.1	86.7	84.9																																																			
3.00	87.3	86.9	85.6																																																			
3.40	87.3	87.1	85.9																																																			
3.74	87.1	87.2	85.9																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			

COSEL

Model	CBS502415	Temperature	25°C																																															
Item	Load Regulation 静的負荷変動	Testing Circuitry	Figure A																																															
Object	+15V3.4A																																																	
1. Graph	<p>—△— Input Volt. 18V ---□--- Input Volt. 24V -○--- Input Volt. 36V</p>																																																	
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>15.104</td> <td>15.104</td> <td>15.104</td> </tr> <tr> <td>0.60</td> <td>15.104</td> <td>15.104</td> <td>15.104</td> </tr> <tr> <td>1.20</td> <td>15.104</td> <td>15.104</td> <td>15.104</td> </tr> <tr> <td>1.80</td> <td>15.104</td> <td>15.104</td> <td>15.104</td> </tr> <tr> <td>2.40</td> <td>15.104</td> <td>15.104</td> <td>15.104</td> </tr> <tr> <td>3.00</td> <td>15.104</td> <td>15.104</td> <td>15.104</td> </tr> <tr> <td>3.40</td> <td>15.104</td> <td>15.104</td> <td>15.104</td> </tr> <tr> <td>3.74</td> <td>15.104</td> <td>15.104</td> <td>15.104</td> </tr> <tr> <td>--</td> <td>--</td> <td>--</td> <td>--</td> </tr> <tr> <td>--</td> <td>--</td> <td>--</td> <td>--</td> </tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	15.104	15.104	15.104	0.60	15.104	15.104	15.104	1.20	15.104	15.104	15.104	1.80	15.104	15.104	15.104	2.40	15.104	15.104	15.104	3.00	15.104	15.104	15.104	3.40	15.104	15.104	15.104	3.74	15.104	15.104	15.104	--	--	--	--	--	--	--	--
Load Current [A]	Output Voltage [V]																																																	
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																															
0.00	15.104	15.104	15.104																																															
0.60	15.104	15.104	15.104																																															
1.20	15.104	15.104	15.104																																															
1.80	15.104	15.104	15.104																																															
2.40	15.104	15.104	15.104																																															
3.00	15.104	15.104	15.104																																															
3.40	15.104	15.104	15.104																																															
3.74	15.104	15.104	15.104																																															
--	--	--	--																																															
--	--	--	--																																															
Note:	Slanted line shows the range of the rated load current.																																																	
(注)	(注) 斜線は定格負荷電流範囲を示す。																																																	

COSEL

Model	CBS502415	Temperature	25°C																																						
Item	Ripple Voltage (by Load Current) リップル電圧 (負荷特性)	Testing Circuitry	Figure A																																						
Object	+15V3.4A																																								
1. Graph	<p>—△— Input Volt. 18V -○- Input Volt. 36V</p>																																								
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>5</td> <td>10</td> </tr> <tr> <td>0.7</td> <td>10</td> <td>10</td> </tr> <tr> <td>1.4</td> <td>10</td> <td>10</td> </tr> <tr> <td>2.0</td> <td>10</td> <td>10</td> </tr> <tr> <td>2.7</td> <td>10</td> <td>10</td> </tr> <tr> <td>3.4</td> <td>10</td> <td>10</td> </tr> <tr> <td>4.1</td> <td>10</td> <td>10</td> </tr> <tr> <td>---</td> <td>—</td> <td>—</td> </tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0.0	5	10	0.7	10	10	1.4	10	10	2.0	10	10	2.7	10	10	3.4	10	10	4.1	10	10	---	—	—	---	—	—	---	—	—	---	—	—
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 18 [V]	Input Volt. 36 [V]																																							
0.0	5	10																																							
0.7	10	10																																							
1.4	10	10																																							
2.0	10	10																																							
2.7	10	10																																							
3.4	10	10																																							
4.1	10	10																																							
---	—	—																																							
---	—	—																																							
---	—	—																																							
---	—	—																																							
<p>Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p-p 値で示される。 (注) 斜線は定格負荷電流範囲を示す。</p>																																									
<p>Ripple [mVp-p]</p>																																									
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																									

COSEL

Model	CBS502415	Temperature	25°C																																						
Item	Ripple-Noise リップルノイズ	Testing Circuitry	Figure A																																						
Object	+15V3.4A																																								
1. Graph			2. Values																																						
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15</td><td>25</td></tr> <tr><td>0.7</td><td>20</td><td>25</td></tr> <tr><td>1.4</td><td>20</td><td>25</td></tr> <tr><td>2.0</td><td>15</td><td>25</td></tr> <tr><td>2.7</td><td>15</td><td>25</td></tr> <tr><td>3.4</td><td>15</td><td>20</td></tr> <tr><td>4.1</td><td>15</td><td>20</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0.0	15	25	0.7	20	25	1.4	20	25	2.0	15	25	2.7	15	25	3.4	15	20	4.1	15	20	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 18 [V]	Input Volt. 36 [V]																																							
0.0	15	25																																							
0.7	20	25																																							
1.4	20	25																																							
2.0	15	25																																							
2.7	15	25																																							
3.4	15	20																																							
4.1	15	20																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図 p - p 値で示される。 (注) 斜線は定格負荷電流範囲を示す。</p>																																									
<p>Fig. Complex Ripple Noise Wave Form 図 リップルノイズ波形</p>																																									

COSEL

Model	CBS502415	Temperature	25°C	
Item	Overcurrent Protection 過電流保護	Testing Circuitry	Figure A	
Object	+15V3.4A	2. Values		
1. Graph	<p>— Input Volt. 18V - - - Input Volt. 24V - - - - Input Volt. 36V</p>			
		Output Voltage [V]	Load Current [A]	
		Input Volt.	18[V] 24[V] 36[V]	
		15.00	3.41 3.48 3.48	
		14.25	4.42 4.43 4.48	
		13.50	4.44 4.44 4.51	
		12.00	4.47 4.48 4.56	
		10.50	4.52 4.52 4.62	
		---	— — —	
		---	— — —	
		---	— — —	
		---	— — —	
		---	— — —	
		---	— — —	
		---	— — —	
		---	— — —	


Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

Intermittent operation occurs when the output voltage is from 10.5V to 0V.
10.5V～0V間は、間欠モードとなる。

COSEL


Model	CBS502415	Testing Circuitry Figure A																																																					
Item	Overvoltage Protection 過電圧保護																																																						
Object	+15V3.4A																																																						
1. Graph	<p>—△— Input Volt. 18V - - -□- Input Volt. 24V - - ○- Input Volt. 36V</p>																																																						
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>-50</td><td>19.67</td><td>19.67</td><td>19.67</td></tr> <tr> <td>-40</td><td>19.67</td><td>19.67</td><td>19.67</td></tr> <tr> <td>-20</td><td>19.73</td><td>19.73</td><td>19.72</td></tr> <tr> <td>0</td><td>19.72</td><td>19.72</td><td>19.72</td></tr> <tr> <td>25</td><td>19.72</td><td>19.72</td><td>19.72</td></tr> <tr> <td>40</td><td>19.72</td><td>19.72</td><td>19.72</td></tr> <tr> <td>60</td><td>19.72</td><td>19.72</td><td>19.72</td></tr> <tr> <td>85</td><td>19.66</td><td>19.66</td><td>19.66</td></tr> <tr> <td>100</td><td>19.66</td><td>19.66</td><td>19.66</td></tr> <tr> <td>105</td><td>19.66</td><td>19.66</td><td>19.66</td></tr> <tr> <td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>				Ambient Temperature [°C]	Operating Point [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	-50	19.67	19.67	19.67	-40	19.67	19.67	19.67	-20	19.73	19.73	19.72	0	19.72	19.72	19.72	25	19.72	19.72	19.72	40	19.72	19.72	19.72	60	19.72	19.72	19.72	85	19.66	19.66	19.66	100	19.66	19.66	19.66	105	19.66	19.66	19.66	--	--	--	--
Ambient Temperature [°C]	Operating Point [V]																																																						
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																				
-50	19.67	19.67	19.67																																																				
-40	19.67	19.67	19.67																																																				
-20	19.73	19.73	19.72																																																				
0	19.72	19.72	19.72																																																				
25	19.72	19.72	19.72																																																				
40	19.72	19.72	19.72																																																				
60	19.72	19.72	19.72																																																				
85	19.66	19.66	19.66																																																				
100	19.66	19.66	19.66																																																				
105	19.66	19.66	19.66																																																				
--	--	--	--																																																				
Note:	Slanted line shows the range of the rated ambient temperature.																																																						
(注)	斜線は定格周囲温度範囲を示す。																																																						

COSEL

COSSEL

Model	CBS502415	Temperature	25°C																					
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A																					
Object	+15V3.4A																							
1. Graph																								
			Input Volt. 18 V																					
2. Values [mS]																								
<table border="1"> <thead> <tr> <th>Load</th> <th>Time</th> <th>T_d</th> <th>T_r</th> <th>T_s</th> <th>T_h</th> <th>T_f</th> </tr> </thead> <tbody> <tr> <td>50 %</td> <td></td> <td>16.0</td> <td>3.5</td> <td>19.5</td> <td>0.5</td> <td>11.6</td> </tr> <tr> <td>100 %</td> <td></td> <td>16.0</td> <td>3.3</td> <td>19.3</td> <td>0.3</td> <td>5.9</td> </tr> </tbody> </table>				Load	Time	T _d	T _r	T _s	T _h	T _f	50 %		16.0	3.5	19.5	0.5	11.6	100 %		16.0	3.3	19.3	0.3	5.9
Load	Time	T _d	T _r	T _s	T _h	T _f																		
50 %		16.0	3.5	19.5	0.5	11.6																		
100 %		16.0	3.3	19.3	0.3	5.9																		

COSEL

Model	CBS502415	Testing Circuitry Figure A																																																					
Item	Ambient Temperature Drift 周囲温度変動																																																						
Object	+15V3.4A																																																						
1. Graph																																																							
		—▲— Input Volt. 18V - - -□- - Input Volt. 24V - - ○- - Input Volt. 36V																																																					
																																																							
2. Values																																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>-50</td><td>15.095</td><td>15.095</td><td>15.095</td></tr> <tr> <td>-40</td><td>15.101</td><td>15.101</td><td>15.101</td></tr> <tr> <td>-20</td><td>15.108</td><td>15.108</td><td>15.109</td></tr> <tr> <td>0</td><td>15.114</td><td>15.115</td><td>15.115</td></tr> <tr> <td>25</td><td>15.113</td><td>15.113</td><td>15.113</td></tr> <tr> <td>40</td><td>15.104</td><td>15.104</td><td>15.104</td></tr> <tr> <td>60</td><td>15.086</td><td>15.086</td><td>15.086</td></tr> <tr> <td>85</td><td>15.057</td><td>15.057</td><td>15.057</td></tr> <tr> <td>100</td><td>15.036</td><td>15.035</td><td>15.035</td></tr> <tr> <td>105</td><td>15.028</td><td>15.027</td><td>15.027</td></tr> <tr> <td>--</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	-50	15.095	15.095	15.095	-40	15.101	15.101	15.101	-20	15.108	15.108	15.109	0	15.114	15.115	15.115	25	15.113	15.113	15.113	40	15.104	15.104	15.104	60	15.086	15.086	15.086	85	15.057	15.057	15.057	100	15.036	15.035	15.035	105	15.028	15.027	15.027	--	—	—	—
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																				
-50	15.095	15.095	15.095																																																				
-40	15.101	15.101	15.101																																																				
-20	15.108	15.108	15.109																																																				
0	15.114	15.115	15.115																																																				
25	15.113	15.113	15.113																																																				
40	15.104	15.104	15.104																																																				
60	15.086	15.086	15.086																																																				
85	15.057	15.057	15.057																																																				
100	15.036	15.035	15.035																																																				
105	15.028	15.027	15.027																																																				
--	—	—	—																																																				
Note: Slanted line shows the range of the rated ambient temperature.																																																							
(注) 斜線は定格周囲温度範囲を示す。																																																							

COSEL

Model	CBS502415																																								
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧	Testing Circuitry Figure A																																							
Object	+15V3.4A																																								
1. Graph																																									
		2. Values																																							
<p>---□--- Load 50%</p> <p>—△— Load 100%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-50</td><td>12.9</td><td>13.3</td> </tr> <tr> <td>-40</td><td>12.8</td><td>13.3</td> </tr> <tr> <td>-20</td><td>12.9</td><td>13.4</td> </tr> <tr> <td>0</td><td>13.0</td><td>13.5</td> </tr> <tr> <td>25</td><td>13.0</td><td>13.7</td> </tr> <tr> <td>40</td><td>13.1</td><td>13.6</td> </tr> <tr> <td>60</td><td>13.1</td><td>13.7</td> </tr> <tr> <td>85</td><td>13.1</td><td>13.7</td> </tr> <tr> <td>100</td><td>13.1</td><td>13.8</td> </tr> <tr> <td>105</td><td>13.1</td><td>13.8</td> </tr> <tr> <td>--</td><td>—</td><td>—</td> </tr> </tbody> </table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-50	12.9	13.3	-40	12.8	13.3	-20	12.9	13.4	0	13.0	13.5	25	13.0	13.7	40	13.1	13.6	60	13.1	13.7	85	13.1	13.7	100	13.1	13.8	105	13.1	13.8	--	—	—
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-50	12.9	13.3																																							
-40	12.8	13.3																																							
-20	12.9	13.4																																							
0	13.0	13.5																																							
25	13.0	13.7																																							
40	13.1	13.6																																							
60	13.1	13.7																																							
85	13.1	13.7																																							
100	13.1	13.8																																							
105	13.1	13.8																																							
--	—	—																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>(注) 斜線は定格周囲温度範囲を示す。</p>																																									


COSEL

<p>Model CBS502415</p> <p>Item Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)</p> <p>Object +15V3.4A</p>	Testing Circuitry Figure A																																						
	1. Graph	2. Values																																					
	<p>---□--- Load 50%</p> <p>—△— Load 100%</p> <p>Ripple Voltage [mV]</p> <p>Ambient Temperature [°C]</p> <p>Input Volt. 24V</p>	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-50</td><td>45</td><td>45</td></tr> <tr><td>-40</td><td>35</td><td>35</td></tr> <tr><td>-20</td><td>20</td><td>20</td></tr> <tr><td>0</td><td>15</td><td>15</td></tr> <tr><td>25</td><td>10</td><td>10</td></tr> <tr><td>40</td><td>10</td><td>10</td></tr> <tr><td>60</td><td>10</td><td>10</td></tr> <tr><td>85</td><td>10</td><td>10</td></tr> <tr><td>100</td><td>10</td><td>10</td></tr> <tr><td>105</td><td>10</td><td>10</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-50	45	45	-40	35	35	-20	20	20	0	15	15	25	10	10	40	10	10	60	10	10	85	10	10	100	10	10	105	10	10	—	—
Ambient Temperature [°C]	Ripple Voltage [mV]																																						
	Load 50%	Load 100%																																					
-50	45	45																																					
-40	35	35																																					
-20	20	20																																					
0	15	15																																					
25	10	10																																					
40	10	10																																					
60	10	10																																					
85	10	10																																					
100	10	10																																					
105	10	10																																					
—	—	—																																					

Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

COSEL

Model	CBS502415	Temperature	25°C																						
Item	Time Lapse Drift 経時ドリフト	Testing Circuitry	Figure A																						
Object	+15V3.4A																								
1. Graph			2. Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 24V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.107</td></tr> <tr><td>0.5</td><td>15.103</td></tr> <tr><td>1.0</td><td>15.104</td></tr> <tr><td>2.0</td><td>15.104</td></tr> <tr><td>3.0</td><td>15.104</td></tr> <tr><td>4.0</td><td>15.104</td></tr> <tr><td>5.0</td><td>15.104</td></tr> <tr><td>6.0</td><td>15.104</td></tr> <tr><td>7.0</td><td>15.104</td></tr> <tr><td>8.0</td><td>15.104</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	15.107	0.5	15.103	1.0	15.104	2.0	15.104	3.0	15.104	4.0	15.104	5.0	15.104	6.0	15.104	7.0	15.104	8.0	15.104
Time since start [H]	Output Voltage [V]																								
0.0	15.107																								
0.5	15.103																								
1.0	15.104																								
2.0	15.104																								
3.0	15.104																								
4.0	15.104																								
5.0	15.104																								
6.0	15.104																								
7.0	15.104																								
8.0	15.104																								



Model	CBS502415	
Item	Output Voltage Accuracy 定電圧精度	Testing Circuitry Figure A
Object	+15V3.4A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 ~ 100°C

Input Voltage : 18 ~ 36V

Load Current : 0 ~ 3.4A

* Output Voltage Accuracy = $\pm (\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$* \text{ Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage}}{\text{Rated Output Voltage}} \times 100$$

1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 : -40 ~ 100°C

入力電圧 : 18 ~ 36V

負荷電流 : 0 ~ 3.4A

* 定電圧精度(変動値) = $\pm (\text{出力電圧の最高値} - \text{出力電圧の最低値}) / 2$

$$* \text{ 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage [V]	Output		Output Voltage Accuracy	
			Current [A]	Voltage [V]	Value [mV]	Ration [%]
Maximum Voltage	25	18	3.4	15.113	± 40	± 0.3
Minimum Voltage	100	18	0	15.034		



Model	CBS502415	Testing Circuitry Figure A
Item	Condense 結露特性	
Object	+15V3.4A	

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	15.120	Input Volt.:24V, Load Current.:3.4A
Line Regulation [mV]	1	Input Volt.:18~36V, Load Current.:3.4A
Load Regulation [mV]	1	Input Volt.:24V, Load Current.:0~3.4A



Model	CBS502415	Temperature Testing Circuitry	25°C Figure B
Item	Line Noise Tolerance 入力雑音耐量		
Object	+15V3.4A		

1. Conditions

- Input Voltage : 24 V
- Pulse Input Duration : 1 min. or more
- Pulse Voltage : 2000 V
- Load : 100 %
- Pulse Cycle : 16.7 mS

2. Results

Pulse Width [nS]	MODE		No protection failure should occur	DC-like Regulation of Output Voltage
	POLARITY		保護回路の誤動作がない	出力電圧の直流的変動
50	COMMON	+	OK	no fluctuation
		-	OK	no fluctuation
	NORMAL	+	OK	no fluctuation
		-	OK	no fluctuation
1000	COMMON	+	OK	no fluctuation
		-	OK	no fluctuation
	NORMAL	+	OK	no fluctuation
		-	OK	no fluctuation

COSEL






Figure B

C1 : 50V 68 μ F

C2 : 4700pF

C3 : 50V 0.1 μ FC4 : 25V 470 μ F × 2 (-40°C ≤ T_B ≤ -20°C)25V 470 μ F (-20°C < T_B ≤ 100°C)T_B : Base Plate Temp.

Figure C