



TEST DATA OF CBS504815

(48V INPUT)

Regulated DC Power Supply
Mar. 3, 2001

Approved by : Takayuki Fukuda _____
Takayuki Fukuda Design Manager

Prepared by : Atsushi Yoshiyama _____
Atsushi Yoshiyama Design Engineer

コーセル株式会社
COSEL CO.,LTD.



C O N T E N T S

1. Line Regulation	1
静的入力変動	
2. Input Current (by Input Voltage)	2
入力電流 (入力電圧特性)	
3. Input Current (by Load Current)	3
入力電流 (負荷特性)	
4. Input Power (by Load Current)	4
入力電力 (負荷特性)	
5. Efficiency (by Input Voltage)	5
効率 (入力電圧特性)	
6. Efficiency (by Load Current)	6
効率 (負荷特性)	
7. Load Regulation	7
静的負荷変動	
8. Ripple Voltage (by Load Current)	8
リップル電圧 (負荷特性)	
9. Ripple-Noise	9
リップルノイズ	
10. Overcurrent Protection	10
過電流保護	
11. Overvoltage Protection	11
過電圧保護	
12. Dynamic Load Response	12
動的負荷変動	
13. Rise and Fall Time	13
立上り、立下り時間	
14. Ambient Temperature Drift	14
周囲温度変動	
15. Minimum Input Voltage for Regulated Output Voltage	15
最低レギュレーション電圧	
16. Ripple Voltage (by Ambient Temperature)	16
リップル電圧 (周囲温度特性)	
17. Time Lapse Drift	17
経時ドリフト	
18. Output Voltage Accuracy	18
定電圧精度	
19. Condensation	19
結露特性	
20. Conducted Emission	20
雑音端子電圧	
21. Figure of Testing Circuitry	21
測定回路図	

(Final Page 21)

COSEL

Model	CBS504815	Temperature Testing Circuitry	25°C Figure A																																
Item	Line Regulation 静的入力変動																																		
Object	+15V3.4A																																		
1. Graph			2. Values																																
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Load 50%</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>33</td><td>15.138</td><td>15.138</td></tr> <tr><td>36</td><td>15.138</td><td>15.138</td></tr> <tr><td>40</td><td>15.138</td><td>15.138</td></tr> <tr><td>48</td><td>15.138</td><td>15.138</td></tr> <tr><td>55</td><td>15.138</td><td>15.138</td></tr> <tr><td>60</td><td>15.138</td><td>15.138</td></tr> <tr><td>70</td><td>15.138</td><td>15.138</td></tr> <tr><td>76</td><td>15.138</td><td>15.138</td></tr> <tr><td>80</td><td>15.138</td><td>15.138</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	33	15.138	15.138	36	15.138	15.138	40	15.138	15.138	48	15.138	15.138	55	15.138	15.138	60	15.138	15.138	70	15.138	15.138	76	15.138	15.138	80	15.138	15.138
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
33	15.138	15.138																																	
36	15.138	15.138																																	
40	15.138	15.138																																	
48	15.138	15.138																																	
55	15.138	15.138																																	
60	15.138	15.138																																	
70	15.138	15.138																																	
76	15.138	15.138																																	
80	15.138	15.138																																	

Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。

COSEL

Model	CBS504815	Temperature	25°C																																																																							
Item	Input Current (by Input Voltage) 入力電流 (入力電圧特性)	Testing Circuitry	Figure A																																																																							
Object	<hr/>																																																																									
1. Graph	<p style="text-align: center;"> —△— Load 100% ---□--- Load 50% ---○--- Load 0% </p> <p>Input Current [A]</p> <p>Input Voltage [V]</p>																																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>8.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>16.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>24.0</td><td>0.008</td><td>0.008</td><td>0.008</td></tr> <tr><td>30.6</td><td>0.058</td><td>0.986</td><td>1.926</td></tr> <tr><td>33.0</td><td>0.056</td><td>0.904</td><td>1.784</td></tr> <tr><td>36.0</td><td>0.053</td><td>0.824</td><td>1.625</td></tr> <tr><td>40.0</td><td>0.050</td><td>0.744</td><td>1.462</td></tr> <tr><td>48.0</td><td>0.040</td><td>0.626</td><td>1.222</td></tr> <tr><td>60.0</td><td>0.034</td><td>0.509</td><td>0.984</td></tr> <tr><td>70.0</td><td>0.028</td><td>0.442</td><td>0.850</td></tr> <tr><td>76.0</td><td>0.027</td><td>0.411</td><td>0.786</td></tr> <tr><td>80.0</td><td>0.026</td><td>0.393</td><td>0.750</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	8.0	0.000	0.000	0.000	16.0	0.000	0.000	0.000	24.0	0.008	0.008	0.008	30.6	0.058	0.986	1.926	33.0	0.056	0.904	1.784	36.0	0.053	0.824	1.625	40.0	0.050	0.744	1.462	48.0	0.040	0.626	1.222	60.0	0.034	0.509	0.984	70.0	0.028	0.442	0.850	76.0	0.027	0.411	0.786	80.0	0.026	0.393	0.750	---	—	—	—	---	—	—	—	---	—	—	—	---	—	—	—
Input Voltage [V]	Input Current [A]																																																																									
	Load 0%	Load 50%	Load 100%																																																																							
8.0	0.000	0.000	0.000																																																																							
16.0	0.000	0.000	0.000																																																																							
24.0	0.008	0.008	0.008																																																																							
30.6	0.058	0.986	1.926																																																																							
33.0	0.056	0.904	1.784																																																																							
36.0	0.053	0.824	1.625																																																																							
40.0	0.050	0.744	1.462																																																																							
48.0	0.040	0.626	1.222																																																																							
60.0	0.034	0.509	0.984																																																																							
70.0	0.028	0.442	0.850																																																																							
76.0	0.027	0.411	0.786																																																																							
80.0	0.026	0.393	0.750																																																																							
---	—	—	—																																																																							
---	—	—	—																																																																							
---	—	—	—																																																																							
---	—	—	—																																																																							

Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。

COSSEL

Model	CBS504815																																																					
Item	Input Current (by Load Current) 入力電流（負荷特性）	Temperature 25°C	Testing Circuitry Figure A																																																			
Object																																																						
1. Graph	<p>—▲— Input Volt. 36V - - - □ - - Input Volt. 48V - - ○ - - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 36V [A]</th> <th>Input Volt. 48V [A]</th> <th>Input Volt. 76V [A]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.053</td><td>0.039</td><td>0.027</td></tr> <tr><td>0.6</td><td>0.325</td><td>0.252</td><td>0.169</td></tr> <tr><td>1.2</td><td>0.592</td><td>0.453</td><td>0.302</td></tr> <tr><td>1.8</td><td>0.864</td><td>0.655</td><td>0.429</td></tr> <tr><td>2.4</td><td>1.141</td><td>0.862</td><td>0.560</td></tr> <tr><td>3.0</td><td>1.422</td><td>1.070</td><td>0.691</td></tr> <tr><td>3.4</td><td>1.612</td><td>1.211</td><td>0.780</td></tr> <tr><td>3.8</td><td>1.802</td><td>1.352</td><td>0.868</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 36V [A]	Input Volt. 48V [A]	Input Volt. 76V [A]	0.0	0.053	0.039	0.027	0.6	0.325	0.252	0.169	1.2	0.592	0.453	0.302	1.8	0.864	0.655	0.429	2.4	1.141	0.862	0.560	3.0	1.422	1.070	0.691	3.4	1.612	1.211	0.780	3.8	1.802	1.352	0.868															
Load Current [A]	Input Volt. 36V [A]	Input Volt. 48V [A]	Input Volt. 76V [A]																																																			
0.0	0.053	0.039	0.027																																																			
0.6	0.325	0.252	0.169																																																			
1.2	0.592	0.453	0.302																																																			
1.8	0.864	0.655	0.429																																																			
2.4	1.141	0.862	0.560																																																			
3.0	1.422	1.070	0.691																																																			
3.4	1.612	1.211	0.780																																																			
3.8	1.802	1.352	0.868																																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.053</td><td>0.039</td><td>0.027</td></tr> <tr><td>0.6</td><td>0.325</td><td>0.252</td><td>0.169</td></tr> <tr><td>1.2</td><td>0.592</td><td>0.453</td><td>0.302</td></tr> <tr><td>1.8</td><td>0.864</td><td>0.655</td><td>0.429</td></tr> <tr><td>2.4</td><td>1.141</td><td>0.862</td><td>0.560</td></tr> <tr><td>3.0</td><td>1.422</td><td>1.070</td><td>0.691</td></tr> <tr><td>3.4</td><td>1.612</td><td>1.211</td><td>0.780</td></tr> <tr><td>3.8</td><td>1.802</td><td>1.352</td><td>0.868</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	0.053	0.039	0.027	0.6	0.325	0.252	0.169	1.2	0.592	0.453	0.302	1.8	0.864	0.655	0.429	2.4	1.141	0.862	0.560	3.0	1.422	1.070	0.691	3.4	1.612	1.211	0.780	3.8	1.802	1.352	0.868	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	0.053	0.039	0.027																																																			
0.6	0.325	0.252	0.169																																																			
1.2	0.592	0.453	0.302																																																			
1.8	0.864	0.655	0.429																																																			
2.4	1.141	0.862	0.560																																																			
3.0	1.422	1.070	0.691																																																			
3.4	1.612	1.211	0.780																																																			
3.8	1.802	1.352	0.868																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

COSEL

Model	CBS504815	Temperature	25°C																																																			
Item	Input Power (by Load Current) 入力電力(負荷特性)	Testing Circuitry	Figure A																																																			
Object																																																						
1. Graph	<p>—△— Input Volt. 36V - - - □ - - Input Volt. 48V - - ○ - - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Power [W] (36V)</th> <th>Input Power [W] (48V)</th> <th>Input Power [W] (76V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0</td><td>0</td><td>0</td></tr> <tr><td>0.6</td><td>11.68</td><td>12.09</td><td>12.92</td></tr> <tr><td>1.2</td><td>21.31</td><td>21.77</td><td>22.91</td></tr> <tr><td>1.8</td><td>31.03</td><td>31.45</td><td>32.55</td></tr> <tr><td>2.4</td><td>41.00</td><td>41.25</td><td>42.60</td></tr> <tr><td>3.0</td><td>50.90</td><td>51.30</td><td>52.70</td></tr> <tr><td>3.4</td><td>57.80</td><td>58.00</td><td>59.40</td></tr> <tr><td>3.8</td><td>64.50</td><td>64.80</td><td>66.00</td></tr> </tbody> </table>			Load Current [A]	Input Power [W] (36V)	Input Power [W] (48V)	Input Power [W] (76V)	0.0	0	0	0	0.6	11.68	12.09	12.92	1.2	21.31	21.77	22.91	1.8	31.03	31.45	32.55	2.4	41.00	41.25	42.60	3.0	50.90	51.30	52.70	3.4	57.80	58.00	59.40	3.8	64.50	64.80	66.00															
Load Current [A]	Input Power [W] (36V)	Input Power [W] (48V)	Input Power [W] (76V)																																																			
0.0	0	0	0																																																			
0.6	11.68	12.09	12.92																																																			
1.2	21.31	21.77	22.91																																																			
1.8	31.03	31.45	32.55																																																			
2.4	41.00	41.25	42.60																																																			
3.0	50.90	51.30	52.70																																																			
3.4	57.80	58.00	59.40																																																			
3.8	64.50	64.80	66.00																																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>1.93</td><td>1.92</td><td>2.17</td></tr> <tr><td>0.6</td><td>11.68</td><td>12.09</td><td>12.92</td></tr> <tr><td>1.2</td><td>21.31</td><td>21.77</td><td>22.91</td></tr> <tr><td>1.8</td><td>31.03</td><td>31.45</td><td>32.55</td></tr> <tr><td>2.4</td><td>41.00</td><td>41.25</td><td>42.60</td></tr> <tr><td>3.0</td><td>50.90</td><td>51.30</td><td>52.70</td></tr> <tr><td>3.4</td><td>57.80</td><td>58.00</td><td>59.40</td></tr> <tr><td>3.8</td><td>64.50</td><td>64.80</td><td>66.00</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	1.93	1.92	2.17	0.6	11.68	12.09	12.92	1.2	21.31	21.77	22.91	1.8	31.03	31.45	32.55	2.4	41.00	41.25	42.60	3.0	50.90	51.30	52.70	3.4	57.80	58.00	59.40	3.8	64.50	64.80	66.00	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	1.93	1.92	2.17																																																			
0.6	11.68	12.09	12.92																																																			
1.2	21.31	21.77	22.91																																																			
1.8	31.03	31.45	32.55																																																			
2.4	41.00	41.25	42.60																																																			
3.0	50.90	51.30	52.70																																																			
3.4	57.80	58.00	59.40																																																			
3.8	64.50	64.80	66.00																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

COSEL

Model	CBS504815	Temperature	25°C																																
Item	Efficiency (by Input Voltage) 効率(入力電圧特性)	Testing Circuitry	Figure A																																
Object	—	—	—																																
1. Graph		2. Values																																	
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>33</td> <td>87.0</td> <td>88.7</td> </tr> <tr> <td>36</td> <td>87.2</td> <td>89.0</td> </tr> <tr> <td>40</td> <td>87.0</td> <td>89.0</td> </tr> <tr> <td>48</td> <td>86.2</td> <td>88.6</td> </tr> <tr> <td>55</td> <td>85.3</td> <td>88.1</td> </tr> <tr> <td>60</td> <td>84.6</td> <td>87.8</td> </tr> <tr> <td>70</td> <td>83.4</td> <td>87.1</td> </tr> <tr> <td>76</td> <td>82.6</td> <td>86.6</td> </tr> <tr> <td>80</td> <td>82.4</td> <td>86.3</td> </tr> </tbody> </table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	33	87.0	88.7	36	87.2	89.0	40	87.0	89.0	48	86.2	88.6	55	85.3	88.1	60	84.6	87.8	70	83.4	87.1	76	82.6	86.6	80	82.4	86.3
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
33	87.0	88.7																																	
36	87.2	89.0																																	
40	87.0	89.0																																	
48	86.2	88.6																																	
55	85.3	88.1																																	
60	84.6	87.8																																	
70	83.4	87.1																																	
76	82.6	86.6																																	
80	82.4	86.3																																	

Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。

COSEL

Model	CBS504815	Temperature	25°C																																																			
Item	Efficiency (by Load Current) 効率(負荷特性)	Testing Circuitry	Figure A																																																			
Object																																																						
1. Graph	<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - - ○- - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [36V] [%]</th> <th>Efficiency [48V] [%]</th> <th>Efficiency [76V] [%]</th> </tr> </thead> <tbody> <tr><td>0.6</td><td>77.7</td><td>74.9</td><td>70.0</td></tr> <tr><td>1.2</td><td>85.0</td><td>83.3</td><td>79.2</td></tr> <tr><td>1.8</td><td>87.5</td><td>86.4</td><td>83.5</td></tr> <tr><td>2.4</td><td>88.4</td><td>87.9</td><td>85.1</td></tr> <tr><td>3.0</td><td>89.0</td><td>88.3</td><td>86.0</td></tr> <tr><td>3.4</td><td>88.9</td><td>88.6</td><td>86.5</td></tr> <tr><td>3.8</td><td>88.9</td><td>88.5</td><td>86.9</td></tr> </tbody> </table>			Load Current [A]	Efficiency [36V] [%]	Efficiency [48V] [%]	Efficiency [76V] [%]	0.6	77.7	74.9	70.0	1.2	85.0	83.3	79.2	1.8	87.5	86.4	83.5	2.4	88.4	87.9	85.1	3.0	89.0	88.3	86.0	3.4	88.9	88.6	86.5	3.8	88.9	88.5	86.9																			
Load Current [A]	Efficiency [36V] [%]	Efficiency [48V] [%]	Efficiency [76V] [%]																																																			
0.6	77.7	74.9	70.0																																																			
1.2	85.0	83.3	79.2																																																			
1.8	87.5	86.4	83.5																																																			
2.4	88.4	87.9	85.1																																																			
3.0	89.0	88.3	86.0																																																			
3.4	88.9	88.6	86.5																																																			
3.8	88.9	88.5	86.9																																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.6</td><td>77.7</td><td>74.9</td><td>70.0</td></tr> <tr><td>1.2</td><td>85.0</td><td>83.3</td><td>79.2</td></tr> <tr><td>1.8</td><td>87.5</td><td>86.4</td><td>83.5</td></tr> <tr><td>2.4</td><td>88.4</td><td>87.9</td><td>85.1</td></tr> <tr><td>3.0</td><td>89.0</td><td>88.3</td><td>86.0</td></tr> <tr><td>3.4</td><td>88.9</td><td>88.6</td><td>86.5</td></tr> <tr><td>3.8</td><td>88.9</td><td>88.5</td><td>86.9</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	-	-	-	0.6	77.7	74.9	70.0	1.2	85.0	83.3	79.2	1.8	87.5	86.4	83.5	2.4	88.4	87.9	85.1	3.0	89.0	88.3	86.0	3.4	88.9	88.6	86.5	3.8	88.9	88.5	86.9	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	-	-	-																																																			
0.6	77.7	74.9	70.0																																																			
1.2	85.0	83.3	79.2																																																			
1.8	87.5	86.4	83.5																																																			
2.4	88.4	87.9	85.1																																																			
3.0	89.0	88.3	86.0																																																			
3.4	88.9	88.6	86.5																																																			
3.8	88.9	88.5	86.9																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						
(注) 斜線は定格負荷電流範囲を示す。																																																						

COSEL

Model	CBS504815	Temperature	25°C																																															
Item	Load Regulation 静的負荷変動	Testing Circuitry	Figure A																																															
Object	+15V3.4A	2. Values																																																
1. Graph	<p>—▲— Input Volt. 36V - - - □ - - Input Volt. 48V - - ○ - - Input Volt. 76V</p>																																																	
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>15.138</td> <td>15.138</td> <td>15.138</td> </tr> <tr> <td>0.6</td> <td>15.138</td> <td>15.138</td> <td>15.138</td> </tr> <tr> <td>1.2</td> <td>15.138</td> <td>15.138</td> <td>15.138</td> </tr> <tr> <td>1.8</td> <td>15.138</td> <td>15.138</td> <td>15.139</td> </tr> <tr> <td>2.4</td> <td>15.138</td> <td>15.139</td> <td>15.139</td> </tr> <tr> <td>3.0</td> <td>15.138</td> <td>15.138</td> <td>15.139</td> </tr> <tr> <td>3.4</td> <td>15.139</td> <td>15.139</td> <td>15.139</td> </tr> <tr> <td>3.8</td> <td>15.139</td> <td>15.138</td> <td>15.139</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	15.138	15.138	15.138	0.6	15.138	15.138	15.138	1.2	15.138	15.138	15.138	1.8	15.138	15.138	15.139	2.4	15.138	15.139	15.139	3.0	15.138	15.138	15.139	3.4	15.139	15.139	15.139	3.8	15.139	15.138	15.139	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																	
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																															
0.0	15.138	15.138	15.138																																															
0.6	15.138	15.138	15.138																																															
1.2	15.138	15.138	15.138																																															
1.8	15.138	15.138	15.139																																															
2.4	15.138	15.139	15.139																																															
3.0	15.138	15.138	15.139																																															
3.4	15.139	15.139	15.139																																															
3.8	15.139	15.138	15.139																																															
--	-	-	-																																															
--	-	-	-																																															

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

COSEL

Model	CBS504815	Temperature	25°C																																						
Item	Ripple Voltage (by Load Current) リップル電圧 (負荷特性)	Testing Circuitry	Figure A																																						
Object	+15V3.4A																																								
1. Graph	<p style="text-align: center;"> Input Volt. 36V Input Volt. 76V </p>																																								
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Output Voltage [mV]</th> </tr> <tr> <th>Input Volt. 36 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5</td><td>5</td></tr> <tr><td>0.7</td><td>10</td><td>10</td></tr> <tr><td>1.4</td><td>10</td><td>10</td></tr> <tr><td>2.0</td><td>10</td><td>10</td></tr> <tr><td>2.7</td><td>10</td><td>10</td></tr> <tr><td>3.4</td><td>10</td><td>10</td></tr> <tr><td>4.1</td><td>10</td><td>10</td></tr> <tr><td>---</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td></tr> <tr><td>---</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Ripple Output Voltage [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.0	5	5	0.7	10	10	1.4	10	10	2.0	10	10	2.7	10	10	3.4	10	10	4.1	10	10	---	—	—	---	—	—	---	—	—	---	—	—
Load Current [A]	Ripple Output Voltage [mV]																																								
	Input Volt. 36 [V]	Input Volt. 76 [V]																																							
0.0	5	5																																							
0.7	10	10																																							
1.4	10	10																																							
2.0	10	10																																							
2.7	10	10																																							
3.4	10	10																																							
4.1	10	10																																							
---	—	—																																							
---	—	—																																							
---	—	—																																							
---	—	—																																							
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p – p 値で示される。 (注) 斜線は定格負荷電流範囲を示す。</p>																																									
<p>Ripple [mVp-p]</p>																																									
<p>Fig. Complex Ripple Wave Form 図 リップル波形図</p>																																									

COSEL

Model	CBS504815	Temperature	25°C																
Item	Ripple-Noise リップルノイズ	Testing Circuitry	Figure A																
Object	+15V3.4A																		
1. Graph			2. Values																
<p>—△— Input Volt. 36V - - ○ - - Input Volt. 76V</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple-Noise [mV] (Input Volt. 36V)</th> <th>Ripple-Noise [mV] (Input Volt. 76V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>~15</td><td>~30</td></tr> <tr><td>1.0</td><td>~20</td><td>~30</td></tr> <tr><td>2.0</td><td>~25</td><td>~30</td></tr> <tr><td>3.0</td><td>~30</td><td>~35</td></tr> <tr><td>4.0</td><td>~35</td><td>~40</td></tr> </tbody> </table>		Load Current [A]	Ripple-Noise [mV] (Input Volt. 36V)	Ripple-Noise [mV] (Input Volt. 76V)	0.0	~15	~30	1.0	~20	~30	2.0	~25	~30	3.0	~30	~35	4.0	~35	~40
Load Current [A]	Ripple-Noise [mV] (Input Volt. 36V)	Ripple-Noise [mV] (Input Volt. 76V)																	
0.0	~15	~30																	
1.0	~20	~30																	
2.0	~25	~30																	
3.0	~30	~35																	
4.0	~35	~40																	
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図 p-p 値で示される。 (注) 斜線は定格負荷電流範囲を示す。</p> <p>Ripple Noise [mVp-p]</p>																			
<p>Fig. Complex Ripple Noise Wave Form 図 リップルノイズ波形</p>																			

COSEL

Model	CBS504815	Temperature	25°C
Item	Overcurrent Protection 過電流保護	Testing Circuitry	Figure A
Object	+15V3.4A		
1. Graph	<p>The graph plots Output Voltage [V] on the Y-axis (0 to 20) against Load Current [A] on the X-axis (0 to 6). Three curves represent different input voltages: 36V (solid line), 48V (dashed line), and 76V (dotted line). A diagonal hatched band between approximately 3.4A and 4.8A on the X-axis represents the rated load current range.</p>	2. Values	
2. Values			
Output Voltage [V]	Load Current [A]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
15.00	3.49	3.42	3.42
14.25	4.82	4.66	4.68
13.50	4.80	4.67	4.71
12.00	4.78	4.70	4.75
10.50	4.73	4.71	4.80
9.00	4.71	4.71	4.82
--	--	--	--
--	--	--	--
--	--	--	--
--	--	--	--
--	--	--	--
--	--	--	--
--	--	--	--


Note: Slanted line shows the range of the rated load current.


(注) 斜線は定格負荷電流範囲を示す。

Intermittent operation occurs when the output voltage is from 9V to 0V.
9V～0V間は、間欠モードとなる。



		Testing Circuitry Figure A																																																							
Model	CBS504815																																																								
Item	Overvoltage Protection 過電圧保護																																																								
Object	+15V3.4A																																																								
1. Graph	<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - - ○- - Input Volt. 76V</p> <p>Operating Point [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 0%</p>																																																								
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Operating Point [V]</th> </tr> <tr> <th>Input Volt.</th> <th>Input Volt.</th> <th>Input Volt.</th> </tr> </thead> <tbody> <tr> <td>36[V]</td> <td>48[V]</td> <td>76[V]</td> </tr> <tr> <td>-50</td> <td>19.65</td> <td>19.65</td> <td>19.65</td> </tr> <tr> <td>-40</td> <td>19.65</td> <td>19.65</td> <td>19.65</td> </tr> <tr> <td>-20</td> <td>19.72</td> <td>19.72</td> <td>19.72</td> </tr> <tr> <td>0</td> <td>19.72</td> <td>19.72</td> <td>19.72</td> </tr> <tr> <td>25</td> <td>19.72</td> <td>19.72</td> <td>19.72</td> </tr> <tr> <td>40</td> <td>19.72</td> <td>19.72</td> <td>19.72</td> </tr> <tr> <td>60</td> <td>19.72</td> <td>19.72</td> <td>19.72</td> </tr> <tr> <td>85</td> <td>19.65</td> <td>19.64</td> <td>19.64</td> </tr> <tr> <td>100</td> <td>19.64</td> <td>19.64</td> <td>19.64</td> </tr> <tr> <td>105</td> <td>19.64</td> <td>19.64</td> <td>19.64</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Ambient Temperature [°C]	Operating Point [V]			Input Volt.	Input Volt.	Input Volt.	36[V]	48[V]	76[V]	-50	19.65	19.65	19.65	-40	19.65	19.65	19.65	-20	19.72	19.72	19.72	0	19.72	19.72	19.72	25	19.72	19.72	19.72	40	19.72	19.72	19.72	60	19.72	19.72	19.72	85	19.65	19.64	19.64	100	19.64	19.64	19.64	105	19.64	19.64	19.64	--	-	-	-
Ambient Temperature [°C]	Operating Point [V]																																																								
	Input Volt.	Input Volt.	Input Volt.																																																						
36[V]	48[V]	76[V]																																																							
-50	19.65	19.65	19.65																																																						
-40	19.65	19.65	19.65																																																						
-20	19.72	19.72	19.72																																																						
0	19.72	19.72	19.72																																																						
25	19.72	19.72	19.72																																																						
40	19.72	19.72	19.72																																																						
60	19.72	19.72	19.72																																																						
85	19.65	19.64	19.64																																																						
100	19.64	19.64	19.64																																																						
105	19.64	19.64	19.64																																																						
--	-	-	-																																																						
<p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>(注) 斜線は定格周囲温度範囲を示す。</p>																																																									

COSEL

COSEL



<p>Model CBS504815</p> <p>Item Ambient Temperature Drift 周囲温度変動</p> <p>Object +15V3.4A</p>	Testing Circuitry Figure A																																																				
	2. Values																																																				
	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>-50</td><td>15.116</td><td>15.116</td><td>15.117</td></tr> <tr> <td>-40</td><td>15.123</td><td>15.123</td><td>15.124</td></tr> <tr> <td>-20</td><td>15.134</td><td>15.135</td><td>15.135</td></tr> <tr> <td>0</td><td>15.147</td><td>15.148</td><td>15.148</td></tr> <tr> <td>25</td><td>15.160</td><td>15.160</td><td>15.160</td></tr> <tr> <td>40</td><td>15.157</td><td>15.157</td><td>15.158</td></tr> <tr> <td>60</td><td>15.148</td><td>15.148</td><td>15.148</td></tr> <tr> <td>85</td><td>15.130</td><td>15.130</td><td>15.130</td></tr> <tr> <td>100</td><td>15.115</td><td>15.115</td><td>15.116</td></tr> <tr> <td>105</td><td>15.106</td><td>15.107</td><td>15.107</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	-50	15.116	15.116	15.117	-40	15.123	15.123	15.124	-20	15.134	15.135	15.135	0	15.147	15.148	15.148	25	15.160	15.160	15.160	40	15.157	15.157	15.158	60	15.148	15.148	15.148	85	15.130	15.130	15.130	100	15.115	15.115	15.116	105	15.106	15.107	15.107	--	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																				
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																		
-50	15.116	15.116	15.117																																																		
-40	15.123	15.123	15.124																																																		
-20	15.134	15.135	15.135																																																		
0	15.147	15.148	15.148																																																		
25	15.160	15.160	15.160																																																		
40	15.157	15.157	15.158																																																		
60	15.148	15.148	15.148																																																		
85	15.130	15.130	15.130																																																		
100	15.115	15.115	15.116																																																		
105	15.106	15.107	15.107																																																		
--	-	-	-																																																		
<p>1. Graph</p> <p>—△— Input Volt. 36V ---□--- Input Volt. 48V -·○-- Input Volt. 76V</p> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>																																																					

Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

COSEL


Model	CBS504815																																								
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧	Testing Circuitry Figure A																																							
Object	+15V3.4A																																								
1. Graph																																									
		2. Values																																							
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-50</td><td>28.1</td><td>28.8</td> </tr> <tr> <td>-40</td><td>28.0</td><td>28.8</td> </tr> <tr> <td>-20</td><td>28.2</td><td>28.8</td> </tr> <tr> <td>0</td><td>28.3</td><td>29.0</td> </tr> <tr> <td>25</td><td>28.4</td><td>29.2</td> </tr> <tr> <td>40</td><td>28.4</td><td>29.2</td> </tr> <tr> <td>60</td><td>28.4</td><td>29.2</td> </tr> <tr> <td>85</td><td>28.4</td><td>29.2</td> </tr> <tr> <td>100</td><td>28.3</td><td>29.2</td> </tr> <tr> <td>105</td><td>28.3</td><td>29.0</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>				Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-50	28.1	28.8	-40	28.0	28.8	-20	28.2	28.8	0	28.3	29.0	25	28.4	29.2	40	28.4	29.2	60	28.4	29.2	85	28.4	29.2	100	28.3	29.2	105	28.3	29.0	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-50	28.1	28.8																																							
-40	28.0	28.8																																							
-20	28.2	28.8																																							
0	28.3	29.0																																							
25	28.4	29.2																																							
40	28.4	29.2																																							
60	28.4	29.2																																							
85	28.4	29.2																																							
100	28.3	29.2																																							
105	28.3	29.0																																							
--	-	-																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>(注) 斜線は定格周囲温度範囲を示す。</p>																																									

COSEL

Model	CBS504815
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)
Object	+15V3.4A

Testing Circuitry Figure A

1. Graph




Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-50	35	35
-40	30	30
-20	20	20
0	10	10
25	10	10
40	10	10
60	10	10
85	10	10
100	10	10
105	10	10
--	—	—

COSEL

Model	CBS504815	Temperature	25°C																						
Item	Time Lapse Drift 経時ドリフト	Testing Circuitry	Figure A																						
Object	+15V3.4A																								
1. Graph	 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V Load 100%</p>																								
2. Values	<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.145</td></tr> <tr><td>0.5</td><td>15.140</td></tr> <tr><td>1.0</td><td>15.141</td></tr> <tr><td>2.0</td><td>15.141</td></tr> <tr><td>3.0</td><td>15.142</td></tr> <tr><td>4.0</td><td>15.142</td></tr> <tr><td>5.0</td><td>15.142</td></tr> <tr><td>6.0</td><td>15.142</td></tr> <tr><td>7.0</td><td>15.142</td></tr> <tr><td>8.0</td><td>15.143</td></tr> </tbody> </table>			Time since start [H]	Output Voltage [V]	0.0	15.145	0.5	15.140	1.0	15.141	2.0	15.141	3.0	15.142	4.0	15.142	5.0	15.142	6.0	15.142	7.0	15.142	8.0	15.143
Time since start [H]	Output Voltage [V]																								
0.0	15.145																								
0.5	15.140																								
1.0	15.141																								
2.0	15.141																								
3.0	15.142																								
4.0	15.142																								
5.0	15.142																								
6.0	15.142																								
7.0	15.142																								
8.0	15.143																								



Model	CBS504815	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	+15V3.4A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 ~ 100°C

Input Voltage : 36 ~ 76V

Load Current : 0 ~ 3.4A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 : -40 ~ 100°C

入力電圧 : 36 ~ 76V

負荷電流 : 0 ~ 3.4A

* 定電圧精度(変動値) = ±(出力電圧の最高値 - 出力電圧の最低値) / 2

$$* \text{定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	25	48	3.4	15.159	±25	±0.2
Minimum Voltage	100	76	0	15.109		



Model	CBS504815	
Item	Condense 結露特性	Testing Circuitry Figure A
Object	+15V3.4A	

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い異常がないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	15.157	Input Volt.:48V, Load Current.:3.4A
Line Regulation [mV]	1	Input Volt.:36~76V, Load Current.:3.4A
Load Regulation [mV]	1	Input Volt.:48V, Load Current.:0~3.4A



Model	CBS504815	Temperature	25°C
Item	Line Noise Tolerance 输入雜音耐量	Testing Circuitry	Figure B
Object	+15V3.4A		




1. Conditions

- Input Voltage : 48 V
- Pulse Input Duration : 1 min. or more
- Pulse Voltage : 2000 V
- Load : 100 %
- Pulse Cycle : 16.7 ms

2. Results

Pulse Width [ns]	MODE	No protection failure should occur		DC-like Regulation of Output Voltage 出力電圧の直流的変動
		POLARITY	保護回路の誤動作がない	
50	COMMON	+	OK	no fluctuation
		-	OK	no fluctuation
	NORMAL	+	OK	no fluctuation
		-	OK	no fluctuation
1000	COMMON	+	OK	no fluctuation
		-	OK	no fluctuation
	NORMAL	+	OK	no fluctuation
		-	OK	no fluctuation

coSEL

C1 : 100V 33 μ F

C2 : 4700pF

C3 : 50V 0.1 μ F $(-40^{\circ}\text{C} \leq T_B \leq -20^{\circ}\text{C})$

C4 : CBS504803, 05	10V 2200 μ F	$\times 2$
CBS504812, 15	35V 470 μ F	$\times 2$
CBS504824, 28	35V 220 μ F	$\times 2$

 $(-20^{\circ}\text{C} < T_B \leq 100^{\circ}\text{C})$

C4 : CBS504803, 05	10V 2200 μ F	
CBS504812, 15	35V 470 μ F	
CBS504824, 28	35V 220 μ F	

 T_B :Base Plate Temp.