



# TEST DATA OF CDS6002412

(24V INPUT)

Regulated DC Power Supply

Sep. 7, 2001

Approved by : Kazuyoshi Shimano  
Design Manager

Prepared by : Katsumi Mizui  
Design Engineer


**コーセル株式会社**  
**COSEL CO., LTD.**

## CONTENTS

1. Line Regulation . . . . .	1
静的入力変動	
2. Input Current (by Input Voltage) . . . . .	2
入力電流 (入力電圧特性)	
3. Input Current (by Load Current) . . . . .	3
入力電流 (負荷特性)	
4. Input Power (by Load Current) . . . . .	4
入力電力 (負荷特性)	
5. Efficiency (by Input Voltage) . . . . .	5
効率 (入力電圧特性)	
6. Efficiency (by Load Current) . . . . .	6
効率 (負荷特性)	
7. Load Regulation . . . . .	7
静的負荷変動	
8. Ripple Voltage (by Load Current) . . . . .	8
リップル電圧 (負荷特性)	
9. Ripple-Noise . . . . .	9
リップルノイズ	
10. Overcurrent Protection . . . . .	10
過電流保護	
11. Overvoltage Protection . . . . .	11
過電圧保護	
12. Dynamic Load Responce . . . . .	12
動的負荷変動	
13. Rise and Fall Time . . . . .	13
立上り、立下り時間	
14. Ambient Temperature Drift . . . . .	14
周囲温度変動	
15. Minimum Input Voltage for Regulated Output Voltage . . . . .	15
最低レギュレーション電圧	
16. Ripple Voltage (by Ambient Temperature) . . . . .	16
リップル電圧 (周囲温度特性)	
17. Time Lapse Drift . . . . .	17
経時ドリフト	
18. Output Voltage Accuracy . . . . .	18
定電圧精度	
19. Condensation . . . . .	19
結露特性	
20. Line Noise Tolerance . . . . .	20
入力雑音耐量	
21. Figure of Testing Circuitry . . . . .	21
測定回路図	

(Final Page 21 )


**COSEL**

Model CDS6002412		Temperature 25°C Testing Circuitry Figure A																																
Item	Line Regulation 静の入力変動																																	
Object	+12.5V48A																																	
<p>1. Graph</p> <p>□ Load 50% △ Load 100%</p>  <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注) 斜線は定格入力電圧範囲を示す。</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th><th colspan="2">Output Voltage [V]</th></tr> <tr> <th>Load 50%</th><th>Load 100%</th></tr> </thead> <tbody> <tr><td>16</td><td>12.536</td><td>12.535</td></tr> <tr><td>18</td><td>12.536</td><td>12.535</td></tr> <tr><td>21</td><td>12.536</td><td>12.534</td></tr> <tr><td>24</td><td>12.535</td><td>12.534</td></tr> <tr><td>27</td><td>12.534</td><td>12.534</td></tr> <tr><td>30</td><td>12.533</td><td>12.534</td></tr> <tr><td>33</td><td>12.531</td><td>12.535</td></tr> <tr><td>36</td><td>12.531</td><td>12.535</td></tr> <tr><td>40</td><td>12.531</td><td>12.535</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	16	12.536	12.535	18	12.536	12.535	21	12.536	12.534	24	12.535	12.534	27	12.534	12.534	30	12.533	12.534	33	12.531	12.535	36	12.531	12.535	40	12.531	12.535
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
16	12.536	12.535																																
18	12.536	12.535																																
21	12.536	12.534																																
24	12.535	12.534																																
27	12.534	12.534																																
30	12.533	12.534																																
33	12.531	12.535																																
36	12.531	12.535																																
40	12.531	12.535																																

**COSEL**

Model		CDS6002412		Temperature		25℃																																																																								
Item		Input Current (by Input Voltage) 入力電流 (入力電圧特性)		Testing Circuitry		Figure A																																																																								
Object																																																																														
1. Graph				2. Values																																																																										
<div><div>—△— Load 100%</div><div>—□— Load 50%</div><div>—○— Load 0%</div></div> <div><div>[A]</div><div>50.00</div><div>40.00</div><div>30.00</div><div>20.00</div><div>10.00</div><div>0.00</div><div>0</div><div>10</div><div>20</div><div>30</div><div>40</div><div>50</div><div>Input Voltage [V]</div></div> <div>Note: Slanted line shows the range of the rated input voltage.</div> <div>(注) 斜線は定格入力電圧範囲を示す。</div>				<table><tr><th rowspan="2">Input Voltage [V]</th><th colspan="3">Input Current [A]</th></tr><tr><th>Load 0%</th><th>Load 50%</th><th>Load 100%</th></tr><tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr><tr><td>3.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr><tr><td>6.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr><tr><td>9.0</td><td>0.055</td><td>0.057</td><td>0.064</td></tr><tr><td>12.0</td><td>0.045</td><td>0.046</td><td>0.049</td></tr><tr><td>12.3</td><td>0.179</td><td>19.524</td><td>34.344</td></tr><tr><td>14.4</td><td>0.158</td><td>22.790</td><td>40.363</td></tr><tr><td>15.0</td><td>0.156</td><td>21.773</td><td>41.976</td></tr><tr><td>15.9</td><td>0.151</td><td>20.592</td><td>43.881</td></tr><tr><td>18.0</td><td>0.128</td><td>18.177</td><td>38.260</td></tr><tr><td>21.0</td><td>0.121</td><td>15.630</td><td>32.704</td></tr><tr><td>24.0</td><td>0.115</td><td>13.690</td><td>28.577</td></tr><tr><td>30.0</td><td>0.105</td><td>11.037</td><td>22.846</td></tr><tr><td>36.0</td><td>0.095</td><td>9.289</td><td>19.163</td></tr><tr><td>39.0</td><td>0.083</td><td>8.616</td><td>17.751</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr></table>				Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	3.0	0.000	0.000	0.000	6.0	0.000	0.000	0.000	9.0	0.055	0.057	0.064	12.0	0.045	0.046	0.049	12.3	0.179	19.524	34.344	14.4	0.158	22.790	40.363	15.0	0.156	21.773	41.976	15.9	0.151	20.592	43.881	18.0	0.128	18.177	38.260	21.0	0.121	15.630	32.704	24.0	0.115	13.690	28.577	30.0	0.105	11.037	22.846	36.0	0.095	9.289	19.163	39.0	0.083	8.616	17.751	—	—	—	—
Input Voltage [V]	Input Current [A]																																																																													
	Load 0%	Load 50%	Load 100%																																																																											
0.0	0.000	0.000	0.000																																																																											
3.0	0.000	0.000	0.000																																																																											
6.0	0.000	0.000	0.000																																																																											
9.0	0.055	0.057	0.064																																																																											
12.0	0.045	0.046	0.049																																																																											
12.3	0.179	19.524	34.344																																																																											
14.4	0.158	22.790	40.363																																																																											
15.0	0.156	21.773	41.976																																																																											
15.9	0.151	20.592	43.881																																																																											
18.0	0.128	18.177	38.260																																																																											
21.0	0.121	15.630	32.704																																																																											
24.0	0.115	13.690	28.577																																																																											
30.0	0.105	11.037	22.846																																																																											
36.0	0.095	9.289	19.163																																																																											
39.0	0.083	8.616	17.751																																																																											
—	—	—	—																																																																											

**COSEL**

Model		CDS6002412		Temperature		25℃																																																								
Item		Input Current (by Load Current) 入力電流 (負荷特性)		Testing Circuitry		Figure A																																																								
Object																																																														
1. Graph				2. Values																																																										
<div><div>△</div>Input Volt. 18V</div> <div><div>□</div>Input Volt. 24V</div> <div><div>○</div>Input Volt. 36V</div>  <p>Note: Slanted line shows the range of the rated load current.</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>				<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Input Current [A]</th></tr><tr><th>Input Volt. 18[V]</th><th>Input Volt. 24[V]</th><th>Input Volt. 36[V]</th></tr><tr><td>0.00</td><td>0.132</td><td>0.120</td><td>0.094</td></tr><tr><td>8.00</td><td>6.491</td><td>4.957</td><td>3.440</td></tr><tr><td>16.00</td><td>12.484</td><td>9.433</td><td>6.496</td></tr><tr><td>24.00</td><td>19.077</td><td>14.295</td><td>9.761</td></tr><tr><td>32.00</td><td>25.642</td><td>19.489</td><td>13.100</td></tr><tr><td>40.00</td><td>32.544</td><td>24.597</td><td>16.673</td></tr><tr><td>48.00</td><td>39.949</td><td>29.986</td><td>20.276</td></tr><tr><td>52.80</td><td>44.965</td><td>33.538</td><td>22.599</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr></table>				Load Current [A]	Input Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	0.132	0.120	0.094	8.00	6.491	4.957	3.440	16.00	12.484	9.433	6.496	24.00	19.077	14.295	9.761	32.00	25.642	19.489	13.100	40.00	32.544	24.597	16.673	48.00	39.949	29.986	20.276	52.80	44.965	33.538	22.599	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Current [A]																																																													
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																											
0.00	0.132	0.120	0.094																																																											
8.00	6.491	4.957	3.440																																																											
16.00	12.484	9.433	6.496																																																											
24.00	19.077	14.295	9.761																																																											
32.00	25.642	19.489	13.100																																																											
40.00	32.544	24.597	16.673																																																											
48.00	39.949	29.986	20.276																																																											
52.80	44.965	33.538	22.599																																																											
—	—	—	—																																																											
—	—	—	—																																																											
—	—	—	—																																																											
—	—	—	—																																																											

**COSEL**

CDS6002412			
Model	CDS6002412		
Item	Input Power (by Load Current) 入力電力 (負荷特性)		
Object			

1. Graph

—△— Input Volt. 18V

—□— Input Volt. 24V

—○— Input Volt. 36V

Input Power [W]

1000

800

600

400

200

0

0

20

40

60

Load Current [A]

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

Load Current [A]	Input Power [W]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
0.00	2.37	2.88	3.38
8.00	115.59	118.55	123.79
16.00	224.78	227.61	233.05
24.00	339.57	342.63	349.26
32.00	460.58	463.83	471.21
40.00	587.26	590.10	597.78
48.00	718.69	720.95	729.96
52.80	801.60	802.27	811.96
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—

2. Values

# COSEL

Model		CDS6002412	
Item		Efficiency (by Input Voltage) 効率 (入力電圧特性)	
Object			

1. Graph

□

Load 50%

△

Load 100%

Efficiency [%]

98

94

90

86

82

78

74

70

10

20

30

40

50

Input Voltage [V]

Input Voltage [V]	Load 50% Efficiency [%]	Load 100% Efficiency [%]
16	87.9	83.1
18	87.7	83.1
21	87.3	82.9
24	86.8	82.7
27	86.5	82.5
30	86.0	82.2
33	85.6	81.9
36	85.1	81.5
40	84.4	81.0

Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。

2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
16	87.9	83.1
18	87.7	83.1
21	87.3	82.9
24	86.8	82.7
27	86.5	82.5
30	86.0	82.2
33	85.6	81.9
36	85.1	81.5
40	84.4	81.0

# COSEL

Model	CDS6002412	Temperature	25°C
Item	Efficiency (by Load Current) 効率 (負荷特性)	Testing Circuitry	Figure A
Object			

1. Graph

—△— Input Volt. 18V

—□— Input Volt. 24V

—○— Input Volt. 36V

Efficiency [%]

Load Current [A]

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

2. Values

Load Current [A]	Efficiency [%]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
8.00	84.7	82.7	78.9
16.00	87.9	86.8	84.7
24.00	87.7	86.8	85.0
32.00	86.3	85.7	84.2
40.00	84.7	84.3	83.0
48.00	83.0	82.7	81.6
52.80	81.9	81.7	80.7
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—



**COSEL**

Model		CDS6002412		Temperature		25℃																																																
Item		Load Regulation 静的負荷変動		Testing Circuitry		Figure A																																																
Object		+12.5V48A																																																				
1. Graph				2. Values																																																		
<div><div><div>△</div><div>□</div><div>○</div></div><div><div>Input Volt. 18 V</div><div>Input Volt. 24 V</div><div>Input Volt. 36 V</div></div></div> <div><div><div>Output Voltage [V]</div><div><div><div>12.800</div><div>12.700</div><div>12.600</div><div>12.500</div><div>12.400</div><div>12.300</div><div>12.200</div><div>12.100</div></div><div><div>0</div><div>20</div><div>40</div><div>60</div></div><div>Load Current [A]</div></div></div></div>				<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 18[V]</th><th>Input Volt. 24[V]</th><th>Input Volt. 36[V]</th></tr><tr><td>0.00</td><td>12.503</td><td>12.506</td><td>12.507</td></tr><tr><td>8.00</td><td>12.512</td><td>12.514</td><td>12.514</td></tr><tr><td>16.00</td><td>12.521</td><td>12.523</td><td>12.524</td></tr><tr><td>24.00</td><td>12.531</td><td>12.535</td><td>12.532</td></tr><tr><td>32.00</td><td>12.531</td><td>12.535</td><td>12.537</td></tr><tr><td>40.00</td><td>12.531</td><td>12.535</td><td>12.538</td></tr><tr><td>48.00</td><td>12.535</td><td>12.537</td><td>12.539</td></tr><tr><td>52.80</td><td>12.536</td><td>12.538</td><td>12.539</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr></table>				Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	12.503	12.506	12.507	8.00	12.512	12.514	12.514	16.00	12.521	12.523	12.524	24.00	12.531	12.535	12.532	32.00	12.531	12.535	12.537	40.00	12.531	12.535	12.538	48.00	12.535	12.537	12.539	52.80	12.536	12.538	12.539	—	—	—	—	—	—	—	—
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.00	12.503	12.506	12.507																																																			
8.00	12.512	12.514	12.514																																																			
16.00	12.521	12.523	12.524																																																			
24.00	12.531	12.535	12.532																																																			
32.00	12.531	12.535	12.537																																																			
40.00	12.531	12.535	12.538																																																			
48.00	12.535	12.537	12.539																																																			
52.80	12.536	12.538	12.539																																																			
—	—	—	—																																																			
—	—	—	—																																																			
<div>Note: Slanted line shows the range of the rated load current.</div> <div>(注)斜線は定格負荷電流範囲を示す。</div>																																																						

**COSEL**


Model		CDS6002412	
Item	Ripple Voltage (by Load Current) リップル電圧 (負荷特性)		Temperature 25°C Testing Circuitry Figure A
Object	+12.5V 48A		

1. Graph

—△— Input Volt. 18V

- - -□- - - Input Volt. 36V

Ripple Voltage [mV]



Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップル電圧は、下図 p-p 値で示される。  
(注) 斜線は定格負荷電流範囲を示す。




図 リップル波形図

2. Values

Load Current [A]	Ripple Output Volt. [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.0	20	20
8.0	20	20
16.0	20	20
24.0	20	20
32.0	20	30
40.0	30	30
48.0	30	30
52.8	30	30
—	—	—
—	—	—
—	—	—

**COSEL**


Model CDS6002412		Temperature 25°C Testing Circuitry Figure A																																						
Item	Ripple-Noise リップルノイズ																																							
Object	+12.5V48A																																							
<p>1. Graph</p> <p> <span style="display: inline-block; width: 20px; border-bottom: 1px solid black; margin-right: 5px;"></span> <math>\triangle</math> Input Volt. 18V  <span style="display: inline-block; width: 20px; border-bottom: 1px dashed black; margin-right: 5px;"></span> <math>\square</math> Input Volt. 36V </p> <p>[mV]</p> <p>Ripple-Noise</p> <p>Load Current [A]</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load current [A]</th><th colspan="2">Ripple-Noise [mV]</th></tr> <tr> <th>Input Volt. 18 [V]</th><th>Input Volt. 36 [V]</th></tr> </thead> <tbody> <tr><td>0.0</td><td>30</td><td>40</td></tr> <tr><td>8.0</td><td>50</td><td>60</td></tr> <tr><td>16.0</td><td>70</td><td>70</td></tr> <tr><td>24.0</td><td>70</td><td>70</td></tr> <tr><td>32.0</td><td>70</td><td>70</td></tr> <tr><td>40.0</td><td>70</td><td>70</td></tr> <tr><td>48.0</td><td>70</td><td>70</td></tr> <tr><td>52.8</td><td>70</td><td>70</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load current [A]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0.0	30	40	8.0	50	60	16.0	70	70	24.0	70	70	32.0	70	70	40.0	70	70	48.0	70	70	52.8	70	70	—	—	—	—	—	—	—	—	—
Load current [A]	Ripple-Noise [mV]																																							
	Input Volt. 18 [V]	Input Volt. 36 [V]																																						
0.0	30	40																																						
8.0	50	60																																						
16.0	70	70																																						
24.0	70	70																																						
32.0	70	70																																						
40.0	70	70																																						
48.0	70	70																																						
52.8	70	70																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						
<p>Ripple-Noise is shown as p-p in the figure below.  Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図 p-p 値で示される。  (注) 斜線は定格負荷電流範囲を示す。</p> <p>図 リップルノイズ波形図</p>																																								

**COSEL**

Model		CDS6002412		Temperature		25℃																																																								
Item		Overcurrent Protection 過電流保護		Testing Circuitry		Figure A																																																								
Object		+12.5V48A																																																												
1. Graph				2. Values																																																										
<div><div>[V]</div><div><div><div></div></div><div><div></div></div><div><div></div></div></div><div><div>Input Volt. 18 V</div><div>Input Volt. 24 V</div><div>Input Volt. 36 V</div></div></div> <div><div><div>Output Voltage</div><div>[V]</div></div><div><div>20.0</div><div>15.0</div><div>10.0</div><div>5.0</div><div>0.0</div></div><div><div>0</div><div>20</div><div>40</div><div>60</div><div>80</div></div><div><div>Load Current</div><div>[A]</div></div></div>				<table><tr><th rowspan="2">Output Voltage [V]</th><th colspan="3">Load Current [A]</th></tr><tr><th>Input Volt. 18[V]</th><th>Input Volt. 24[V]</th><th>Input Volt. 36[V]</th></tr><tr><td>12.50</td><td>54.83</td><td>56.94</td><td>48.50</td></tr><tr><td>11.88</td><td>54.97</td><td>57.42</td><td>61.57</td></tr><tr><td>11.25</td><td>55.46</td><td>57.90</td><td>62.14</td></tr><tr><td>10.00</td><td>56.05</td><td>58.72</td><td>63.37</td></tr><tr><td>8.75</td><td>56.92</td><td>59.58</td><td>64.18</td></tr><tr><td>7.50</td><td>57.34</td><td>60.06</td><td>64.93</td></tr><tr><td>6.25</td><td>—</td><td>—</td><td>—</td></tr><tr><td>5.00</td><td>—</td><td>—</td><td>—</td></tr><tr><td>3.75</td><td>—</td><td>—</td><td>—</td></tr><tr><td>2.50</td><td>—</td><td>—</td><td>—</td></tr><tr><td>1.25</td><td>—</td><td>—</td><td>—</td></tr><tr><td>0.00</td><td>—</td><td>—</td><td>—</td></tr></table>				Output Voltage [V]	Load Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	12.50	54.83	56.94	48.50	11.88	54.97	57.42	61.57	11.25	55.46	57.90	62.14	10.00	56.05	58.72	63.37	8.75	56.92	59.58	64.18	7.50	57.34	60.06	64.93	6.25	—	—	—	5.00	—	—	—	3.75	—	—	—	2.50	—	—	—	1.25	—	—	—	0.00	—	—	—
Output Voltage [V]	Load Current [A]																																																													
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																											
12.50	54.83	56.94	48.50																																																											
11.88	54.97	57.42	61.57																																																											
11.25	55.46	57.90	62.14																																																											
10.00	56.05	58.72	63.37																																																											
8.75	56.92	59.58	64.18																																																											
7.50	57.34	60.06	64.93																																																											
6.25	—	—	—																																																											
5.00	—	—	—																																																											
3.75	—	—	—																																																											
2.50	—	—	—																																																											
1.25	—	—	—																																																											
0.00	—	—	—																																																											
<div><div>Note: Slanted line shows the range of the rated load current.</div><div>Intermittent operation occurs when the output voltage is from 6.5V to 0V.</div><div>(注)斜線は定格負荷電流範囲を示す。</div><div>6.5V～0V間は、間欠モードとなる。</div></div>																																																														

# COSEL

Model	CDS6002412
Item	Overvoltage Protection 過電圧保護
Object	+12.5V48A



Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Operating Point [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-35	16.00	15.88	15.88
-20	16.06	16.06	16.06
0	16.29	16.18	16.18
15	16.35	16.35	16.35
25	16.47	16.35	16.35
40	16.59	16.47	16.47
55	16.65	16.65	16.65
70	16.76	16.76	16.76
85	16.88	16.88	16.88
90	16.87	16.87	16.87
100	17.04	16.98	16.99

# COSEL

Model	CDS6002412	Temperature	25°C
Item	Dynamic Load Response 動的負荷変動	Testing Circuitry	Figure A
Object	+12.5V48A		

Input Volt. 24 V


Cycle 1000 ms

Load Current


Min. Load (0A) ←→

Load 100% (48A)

500 mV/div



500 μs/div




100 ms/div


Min. Load (0A) ←→

Load 50% (24A)

500 mV/div



500 μs/div




100 ms/div


Load 10% (4.8A) ←→

Load 100% (48A)

500 mV/div



500 μs/div




100 ms/div

**COSEL**

Model	CDS6002412	Temperature	25°C
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	+12.5V48A		

## 1. Graph


Input Volt. 18 V



## 2. Values

[mS]

Load \ Time	T d	T r	T s	T h	T f
50 %	40.00	7.00	47.00	0.50	2.00
100 %	40.00	6.50	46.50	0.50	1.00



**COSEL**

Model		CDS6002412	
Item		Ambient Temperature Drift 周囲温度変動	
Object		+12.5V48A	

1. Graph

△

Input Volt. 18V

□

Input Volt. 24V

○

Input Volt. 36V

Output Voltage [V]

</



**COSEL**

Model CDS6002412		Testing Circuitry Figure A																																						
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧																																							
Object	+12.5V48A																																							
1. Graph <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">□ ..... Load 50%</div> <div style="text-align: center;">△ ..... Load 100%</div> </div> <p style="text-align: center;">Ambient Temperature [°C]</p>		2. Values <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th><th colspan="2">Input Voltage [V]</th></tr> <tr> <th>Load 50%</th><th>Load 100%</th></tr> </thead> <tbody> <tr><td>-35</td><td>13.5</td><td>14.7</td></tr> <tr><td>-20</td><td>13.6</td><td>14.7</td></tr> <tr><td>0</td><td>13.6</td><td>14.8</td></tr> <tr><td>15</td><td>13.7</td><td>14.9</td></tr> <tr><td>25</td><td>13.7</td><td>14.9</td></tr> <tr><td>40</td><td>13.7</td><td>15.0</td></tr> <tr><td>55</td><td>13.7</td><td>14.9</td></tr> <tr><td>70</td><td>13.7</td><td>14.9</td></tr> <tr><td>85</td><td>13.7</td><td>14.9</td></tr> <tr><td>90</td><td>13.7</td><td>15.0</td></tr> <tr><td>100</td><td>13.7</td><td>14.9</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-35	13.5	14.7	-20	13.6	14.7	0	13.6	14.8	15	13.7	14.9	25	13.7	14.9	40	13.7	15.0	55	13.7	14.9	70	13.7	14.9	85	13.7	14.9	90	13.7	15.0	100	13.7	14.9
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-35	13.5	14.7																																						
-20	13.6	14.7																																						
0	13.6	14.8																																						
15	13.7	14.9																																						
25	13.7	14.9																																						
40	13.7	15.0																																						
55	13.7	14.9																																						
70	13.7	14.9																																						
85	13.7	14.9																																						
90	13.7	15.0																																						
100	13.7	14.9																																						
Note: Slanted line shows the range of the rated ambient temperature.  (注) 斜線は定格周囲温度範囲を示す。																																								

# COSEL

Model		CDS6002412	
Item		Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)	
Object		+12.5V48A	

1. Graph

-----□-----

Load 50%

-----△-----

Load 100%

[mV]

140

120

100

80

60

40

20

0

Ripple Voltage

-50

-10

30

70

110

Ambient Temperature

[°C]

Input Volt. 24 V


Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

2. Values

Ambient Temp. [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-35	30	30
-20	30	30
0	30	30
15	30	30
25	20	30
40	20	30
55	20	20
70	20	20
85	20	20
90	20	20
100	20	20

**COSEL**

COSEL																									
Model	CDS6002412																								
Item	Time Lapse Drift 経時ドリフト	Temperature	25℃																						
		Testing Circuitry	Figure A																						
Object	+12.5V48A																								
1. Graph		2.Values																							
<div>[V]</div> <div></div> <div>Output Voltage [V]</div> <div>Time [H]</div> <div>Input Volt. 24V</div> <div>Load 100%</div>		<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>12.553</td></tr><tr><td>0.5</td><td>12.535</td></tr><tr><td>1.0</td><td>12.535</td></tr><tr><td>2.0</td><td>12.536</td></tr><tr><td>3.0</td><td>12.536</td></tr><tr><td>4.0</td><td>12.536</td></tr><tr><td>5.0</td><td>12.536</td></tr><tr><td>6.0</td><td>12.536</td></tr><tr><td>7.0</td><td>12.536</td></tr><tr><td>8.0</td><td>12.536</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	12.553	0.5	12.535	1.0	12.535	2.0	12.536	3.0	12.536	4.0	12.536	5.0	12.536	6.0	12.536	7.0	12.536	8.0	12.536
Time since start [H]	Output Voltage [V]																								
0.0	12.553																								
0.5	12.535																								
1.0	12.535																								
2.0	12.536																								
3.0	12.536																								
4.0	12.536																								
5.0	12.536																								
6.0	12.536																								
7.0	12.536																								
8.0	12.536																								

**COSEL**

Model	CDS6002412	Testing Circuitry    Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	+12.5V48A	

## 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20~85 °C

Input Voltage : 18~ 36 V

Load Current : 0~48 A

\* Output Voltage Accuracy =  $\pm (\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

\* Output Voltage Accuracy (Ration) =  $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

## 1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度            -20~85 °C

入力電圧            18~ 36 V

負荷電流            0~48 A

\* 定電圧精度(変動値) =  $\pm (\text{出力電圧の最高値} - \text{出力電圧の最低値}) / 2$

\* 定電圧精度(変動率) =  $\frac{\text{変動値}}{\text{定格出力電圧}} \times 100$

## 2. Values

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-20	36	48	12.574	±55	±0.5
Minimum Voltage	85	36	0	12.464		



**COSEL**

Model	CDS6002412	Temperature 25°C Testing Circuitry Figure B	
Item	Line Noise Tolerance 入力雑音耐量		
Object	+12.5 V 48 A		

## 1. Results

Pulse Width [n S]	MODE	No protection failure should occur 保護回路の誤動作がない	DC-like Regulation of Output Voltage 出力電圧の直流的変動
50	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation
1000	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation

## Conditions

Input Voltage : 24 V  
 Pulse Voltage :  $\pm 2000$  V  
 Pulse Cycle : 10 mS  
 Pulse Input Duration: 1 min. or more  
 Load : 100 %

# COSEL




Figure A




Figure B




Figure C (General Electric Characteristic)  
一般電気特性