

TEST DATA OF CES24120-6

Regulated DC Power Supply
Aug 10, 2007

Approved by : *Tatsuya Mano*
Tatsuya Maño Design Manager

Prepared by : *Masahiro Miyake*
Masahiro Miyake Design Engineer

COSEL CO.,LTD.



CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	9
10. Ripple-Noise	10
11. Ripple Voltage (by Ambient Temperature)	11
12. Ambient Temperature Drift	12
13. Output Voltage Accuracy	13
14. Time Lapse Drift	14
15. Rise and Fall Time	15
16. Minimum Input Voltage for Regulated Output Voltage	16
17. Overcurrent Protection	17
18. Overvoltage Protection	18
19. Figure of Testing Circuitry	19

(Final Page 19)



Model		CES24120-6		Temperature	25°C																																																																																
Item		Input Current (by Input Voltage)		Testing Circuitry	Figure A																																																																																
Object		_____																																																																																			
1. Graph			—△— Load 100% - - - □ - - Load 50% - · - ○ - · - Load 0%	2. Values																																																																																	
Input Current [A]				<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>12.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>16.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>16.4</td><td>0.142</td><td>2.388</td><td>4.900</td></tr> <tr><td>18.0</td><td>0.130</td><td>2.189</td><td>4.360</td></tr> <tr><td>20.0</td><td>0.120</td><td>1.960</td><td>3.918</td></tr> <tr><td>24.0</td><td>0.114</td><td>1.650</td><td>3.259</td></tr> <tr><td>28.0</td><td>0.112</td><td>1.423</td><td>2.812</td></tr> <tr><td>32.0</td><td>0.111</td><td>1.257</td><td>2.466</td></tr> <tr><td>36.0</td><td>0.111</td><td>1.130</td><td>2.207</td></tr> <tr><td>40.0</td><td>0.112</td><td>1.030</td><td>1.996</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	4.0	0.000	0.000	0.000	8.0	0.000	0.000	0.000	12.0	0.000	0.000	0.000	16.0	0.000	0.000	0.000	16.4	0.142	2.388	4.900	18.0	0.130	2.189	4.360	20.0	0.120	1.960	3.918	24.0	0.114	1.650	3.259	28.0	0.112	1.423	2.812	32.0	0.111	1.257	2.466	36.0	0.111	1.130	2.207	40.0	0.112	1.030	1.996	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Input Voltage [V]	Input Current [A]																																																																																			
		Load 0%	Load 50%	Load 100%																																																																																	
	0.0	0.000	0.000	0.000																																																																																	
	4.0	0.000	0.000	0.000																																																																																	
	8.0	0.000	0.000	0.000																																																																																	
	12.0	0.000	0.000	0.000																																																																																	
	16.0	0.000	0.000	0.000																																																																																	
	16.4	0.142	2.388	4.900																																																																																	
	18.0	0.130	2.189	4.360																																																																																	
	20.0	0.120	1.960	3.918																																																																																	
	24.0	0.114	1.650	3.259																																																																																	
28.0	0.112	1.423	2.812																																																																																		
32.0	0.111	1.257	2.466																																																																																		
36.0	0.111	1.130	2.207																																																																																		
40.0	0.112	1.030	1.996																																																																																		
-	-	-	-																																																																																		
-	-	-	-																																																																																		
-	-	-	-																																																																																		
-	-	-	-																																																																																		
-	-	-	-																																																																																		
Note: Slanted line shows the range of the rated input voltage.																																																																																					



Model		CES24120-6		Temperature	25°C																																																			
Item		Input Current (by Load Current)		Testing Circuitry	Figure A																																																			
Object		_____																																																						
1.Graph		—△— Input Volt. 18V - - -□- - Input Volt. 24V - · -○- · - Input Volt. 36V		2.Values																																																				
<p>The graph plots Input Current [A] on the y-axis (0 to 10) against Load Current [A] on the x-axis (0 to 6). Three data series are shown: 18V (solid line with triangles), 24V (dashed line with squares), and 36V (dash-dot line with circles). A vertical slanted line is drawn at approximately 6.6A on the x-axis, indicating the rated load current range.</p>				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.130</td><td>0.114</td><td>0.111</td></tr> <tr><td>1.0</td><td>0.806</td><td>0.621</td><td>0.447</td></tr> <tr><td>2.0</td><td>1.491</td><td>1.133</td><td>0.789</td></tr> <tr><td>3.0</td><td>2.189</td><td>1.650</td><td>1.130</td></tr> <tr><td>4.0</td><td>2.894</td><td>2.202</td><td>1.489</td></tr> <tr><td>5.0</td><td>3.630</td><td>2.727</td><td>1.850</td></tr> <tr><td>6.0</td><td>4.360</td><td>3.259</td><td>2.207</td></tr> <tr><td>6.6</td><td>4.800</td><td>3.612</td><td>2.430</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.0	0.130	0.114	0.111	1.0	0.806	0.621	0.447	2.0	1.491	1.133	0.789	3.0	2.189	1.650	1.130	4.0	2.894	2.202	1.489	5.0	3.630	2.727	1.850	6.0	4.360	3.259	2.207	6.6	4.800	3.612	2.430	-	-	-	-	-	-	-	-	-	-	-	-
Load Current [A]	Input Current [A]																																																							
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																					
0.0	0.130	0.114	0.111																																																					
1.0	0.806	0.621	0.447																																																					
2.0	1.491	1.133	0.789																																																					
3.0	2.189	1.650	1.130																																																					
4.0	2.894	2.202	1.489																																																					
5.0	3.630	2.727	1.850																																																					
6.0	4.360	3.259	2.207																																																					
6.6	4.800	3.612	2.430																																																					
-	-	-	-																																																					
-	-	-	-																																																					
-	-	-	-																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>																																																								




Model		CES24120-6		Temperature 25°C																																																				
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1. Graph			2. Values																																																					
<p> —△— Input Volt. 18V ---□--- Input Volt. 24V -·-○-·- Input Volt. 36V </p> <p>Input Power [W]</p> <p>Load Current [A]</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>2.35</td><td>2.75</td><td>3.98</td></tr> <tr><td>1.0</td><td>14.49</td><td>14.91</td><td>16.14</td></tr> <tr><td>2.0</td><td>26.86</td><td>27.24</td><td>28.46</td></tr> <tr><td>3.0</td><td>39.52</td><td>39.75</td><td>40.90</td></tr> <tr><td>4.0</td><td>52.30</td><td>52.70</td><td>53.70</td></tr> <tr><td>5.0</td><td>65.40</td><td>65.60</td><td>66.80</td></tr> <tr><td>6.0</td><td>78.80</td><td>78.85</td><td>79.79</td></tr> <tr><td>6.6</td><td>87.10</td><td>87.20</td><td>87.90</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.0	2.35	2.75	3.98	1.0	14.49	14.91	16.14	2.0	26.86	27.24	28.46	3.0	39.52	39.75	40.90	4.0	52.30	52.70	53.70	5.0	65.40	65.60	66.80	6.0	78.80	78.85	79.79	6.6	87.10	87.20	87.90	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																							
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																					
0.0	2.35	2.75	3.98																																																					
1.0	14.49	14.91	16.14																																																					
2.0	26.86	27.24	28.46																																																					
3.0	39.52	39.75	40.90																																																					
4.0	52.30	52.70	53.70																																																					
5.0	65.40	65.60	66.80																																																					
6.0	78.80	78.85	79.79																																																					
6.6	87.10	87.20	87.90																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>																																																								



Model	CES24120-6
Item	Efficiency (by Input Voltage)
Object	

Temperature 25°C
Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated input voltage.

2. Values


Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
17	91.1	90.9
18	91.1	91.1
20	91.1	91.2
24	90.6	91.1
30	89.2	90.7
36	88.0	89.9
40	86.9	89.3
--	-	-
--	-	-



Model	CES24120-6
Item	Efficiency (by Load Current)
Object	_____

Temperature 25°C
Testing Circuitry Figure A

1.Graph
 —△— Input Volt. 18V
 - - □ - - Input Volt. 24V
 - - ○ - - Input Volt. 36V



Note: Slanted line shows the range of the rated load current.

2.Values

Load Current [A]	Efficiency [%]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
0.0	-	-	-
1.0	83.7	81.4	75.2
2.0	89.5	88.3	84.5
3.0	91.1	90.6	88.0
4.0	91.6	90.9	89.2
5.0	91.5	91.2	89.5
6.0	91.1	91.1	89.9
6.6	90.6	90.5	89.8
-	-	-	-
-	-	-	-
--	-	-	-



COSEL																																			
Model	CES24120-6	Temperature	25°C																																
Item	Line Regulation	Testing Circuitry	Figure A																																
Object	+12V6A																																		
<p>1. Graph</p> <div style="text-align: right;"> <p>---□--- Load 50%</p> <p>—△— Load 100%</p> </div> <p style="text-align: center;">Input Voltage [V]</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>17</td><td>12.011</td><td>12.011</td></tr> <tr><td>18</td><td>12.012</td><td>12.010</td></tr> <tr><td>20</td><td>12.013</td><td>12.010</td></tr> <tr><td>24</td><td>12.013</td><td>12.010</td></tr> <tr><td>30</td><td>12.013</td><td>12.010</td></tr> <tr><td>36</td><td>12.013</td><td>12.010</td></tr> <tr><td>40</td><td>12.013</td><td>12.009</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	17	12.011	12.011	18	12.012	12.010	20	12.013	12.010	24	12.013	12.010	30	12.013	12.010	36	12.013	12.010	40	12.013	12.009	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
17	12.011	12.011																																	
18	12.012	12.010																																	
20	12.013	12.010																																	
24	12.013	12.010																																	
30	12.013	12.010																																	
36	12.013	12.010																																	
40	12.013	12.009																																	
--	-	-																																	
--	-	-																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			





Model CES24120-6		Temperature 25°C Testing Circuitry Figure A																																																			
Item	Load Regulation																																																				
Object	+12V6A																																																				
<p>1. Graph</p> <p>—△— Input Volt. 18V ---□--- Input Volt. 24V -·-○-·- Input Volt. 36V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.010</td><td>12.011</td><td>12.011</td></tr> <tr><td>1.0</td><td>12.010</td><td>12.011</td><td>12.011</td></tr> <tr><td>2.0</td><td>12.011</td><td>12.011</td><td>12.011</td></tr> <tr><td>3.0</td><td>12.012</td><td>12.012</td><td>12.011</td></tr> <tr><td>4.0</td><td>12.012</td><td>12.012</td><td>12.011</td></tr> <tr><td>5.0</td><td>12.012</td><td>12.012</td><td>12.011</td></tr> <tr><td>6.0</td><td>12.011</td><td>12.011</td><td>12.011</td></tr> <tr><td>6.6</td><td>12.010</td><td>12.010</td><td>12.011</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.0	12.010	12.011	12.011	1.0	12.010	12.011	12.011	2.0	12.011	12.011	12.011	3.0	12.012	12.012	12.011	4.0	12.012	12.012	12.011	5.0	12.012	12.012	12.011	6.0	12.011	12.011	12.011	6.6	12.010	12.010	12.011	-	-	-	-	-	-	-	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																		
0.0	12.010	12.011	12.011																																																		
1.0	12.010	12.011	12.011																																																		
2.0	12.011	12.011	12.011																																																		
3.0	12.012	12.012	12.011																																																		
4.0	12.012	12.012	12.011																																																		
5.0	12.012	12.012	12.011																																																		
6.0	12.011	12.011	12.011																																																		
6.6	12.010	12.010	12.011																																																		
-	-	-	-																																																		
-	-	-	-																																																		
-	-	-	-																																																		
<p>Note: Slanted line shows the range of the rated load current.</p>																																																					

Model		CES24120-6	Temperature		25°C
Item		Dynamic Load Response	Testing Circuitry		Figure A
Object		+12V6A			



Input Volt. 24 V
Cycle 5 mS





Min. Load (0A) ←→
Load 100% (6A)



Min. Load (0A) ←→
Load 50% (3A)



Load 50% (3A) ←→
Load 100% (6A)





Model CES24120-6		Temperature 25°C Testing Circuitry Figure B																																						
Item	Ripple Voltage (by Load Current)																																							
Object	+12V6A																																							
1. Graph <div style="text-align: right;"> —△— Input Volt. 18V - - ○ - - Input Volt. 36V </div>		2. Values <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5</td><td>5</td></tr> <tr><td>1.0</td><td>5</td><td>5</td></tr> <tr><td>2.0</td><td>5</td><td>5</td></tr> <tr><td>3.0</td><td>5</td><td>5</td></tr> <tr><td>4.0</td><td>5</td><td>5</td></tr> <tr><td>5.0</td><td>5</td><td>5</td></tr> <tr><td>6.0</td><td>5</td><td>5</td></tr> <tr><td>6.6</td><td>5</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0.0	5	5	1.0	5	5	2.0	5	5	3.0	5	5	4.0	5	5	5.0	5	5	6.0	5	5	6.6	5	5	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 18 [V]	Input Volt. 36 [V]																																						
0.0	5	5																																						
1.0	5	5																																						
2.0	5	5																																						
3.0	5	5																																						
4.0	5	5																																						
5.0	5	5																																						
6.0	5	5																																						
6.6	5	5																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p> <p>Fig. Complex Ripple Wave Form</p>																																								



Model CES24120-6		Temperature 25°C Testing Circuitry Figure B																																						
Item	Ripple-Noise																																							
Object	+12V6A																																							
<p>1. Graph</p> <div style="display: flex; justify-content: space-around; align-items: flex-start;"> <div style="text-align: center;"> <p>—△— Input Volt. 18V</p> <p>- -○- - Input Volt. 36V</p> </div> </div> <p style="text-align: center;">Load Current [A]</p> <p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <div style="text-align: center;"> <p>Ripple Noise[mVp-p]</p> </div> <p style="text-align: center;">Fig.Complex Ripple Noise Wave Form</p>		<p>2.Values</p> <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10</td><td>15</td></tr> <tr><td>1.0</td><td>10</td><td>15</td></tr> <tr><td>2.0</td><td>10</td><td>15</td></tr> <tr><td>3.0</td><td>10</td><td>15</td></tr> <tr><td>4.0</td><td>10</td><td>15</td></tr> <tr><td>5.0</td><td>10</td><td>20</td></tr> <tr><td>6.0</td><td>15</td><td>20</td></tr> <tr><td>6.6</td><td>15</td><td>20</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0.0	10	15	1.0	10	15	2.0	10	15	3.0	10	15	4.0	10	15	5.0	10	20	6.0	15	20	6.6	15	20	-	-	-	-	-	-	-	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 18 [V]	Input Volt. 36 [V]																																						
0.0	10	15																																						
1.0	10	15																																						
2.0	10	15																																						
3.0	10	15																																						
4.0	10	15																																						
5.0	10	20																																						
6.0	15	20																																						
6.6	15	20																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						



Model CES24120-6		Testing Circuitry Figure B																																						
Item	Ripple Voltage (by Ambient Temp.)																																							
Object	+12V6A																																							
<p>1. Graph</p> <p style="text-align: center;">Input Volt. 24V</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-40</td><td>5</td><td>5</td></tr> <tr><td>-20</td><td>5</td><td>5</td></tr> <tr><td>0</td><td>5</td><td>5</td></tr> <tr><td>25</td><td>5</td><td>5</td></tr> <tr><td>40</td><td>5</td><td>5</td></tr> <tr><td>60</td><td>5</td><td>5</td></tr> <tr><td>85</td><td>5</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-40	5	5	-20	5	5	0	5	5	25	5	5	40	5	5	60	5	5	85	5	5	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																							
	Load 50%	Load 100%																																						
-40	5	5																																						
-20	5	5																																						
0	5	5																																						
25	5	5																																						
40	5	5																																						
60	5	5																																						
85	5	5																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Note: Slanted line shows the range of the rated ambient temperature.</p>																																								




Model	CES24120-6
Item	Ambient Temperature Drift
Object	+12V6A

Testing Circuitry Figure A

1. Graph

—△— Input Volt. 18V
 ---□--- Input Volt. 24V
 -·-○-·- Input Volt. 36V



2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-40	12.046	12.045	12.046
-20	12.037	12.036	12.036
0	12.027	12.026	12.026
25	12.012	12.011	12.010
40	12.000	11.999	11.998
60	11.983	11.982	11.981
85	11.958	11.956	11.955
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



COSEL		
Model	CES24120-6	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+12V6A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 85°C

Input Voltage : 18 - 36V

Load Current : 0 - 6A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ratio) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	-40	36	0	12.046	±46	±0.4
Minimum Voltage	85	36	6	11.955		




COSEL																								
Model	CES24120-6																							
Item	Time Lapse Drift	Temperature 25°C Testing Circuitry Figure A																						
Object	+12V6A																							
<p>1. Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt. 24V Load 100%</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.016</td></tr> <tr><td>0.5</td><td>12.009</td></tr> <tr><td>1.0</td><td>12.009</td></tr> <tr><td>2.0</td><td>12.009</td></tr> <tr><td>3.0</td><td>12.008</td></tr> <tr><td>4.0</td><td>12.009</td></tr> <tr><td>5.0</td><td>12.009</td></tr> <tr><td>6.0</td><td>12.008</td></tr> <tr><td>7.0</td><td>12.008</td></tr> <tr><td>8.0</td><td>12.008</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	12.016	0.5	12.009	1.0	12.009	2.0	12.009	3.0	12.008	4.0	12.009	5.0	12.009	6.0	12.008	7.0	12.008	8.0	12.008
Time since start [H]	Output Voltage [V]																							
0.0	12.016																							
0.5	12.009																							
1.0	12.009																							
2.0	12.009																							
3.0	12.008																							
4.0	12.009																							
5.0	12.009																							
6.0	12.008																							
7.0	12.008																							
8.0	12.008																							




Model	CES24120-6	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+12V6A		

1. Graph



2. Values

		[mS]				
Load \ Time	Time	Td	Tr	Ts	Th	Tf
50 %		14.7	5.4	20.1	0.2	1.5
100 %		14.7	5.6	20.3	0.2	0.8






Model	CES24120-6
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V6A

Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	15.7	15.6
-20	15.7	15.7
0	15.7	15.7
25	15.8	15.6
40	15.6	15.6
60	15.6	15.6
85	15.5	15.6
-	-	-
-	-	-
-	-	-
-	-	-



Model CES24120-6		Temperature 25°C Testing Circuitry Figure A.																																																							
Item	Overcurrent Protection																																																								
Object	+12V6A																																																								
<p>1.Graph</p> <p> Input Volt. 18V Input Volt. 24V Input Volt. 36V </p> <p style="text-align: center;">Output Voltage [V]</p> <p style="text-align: center;">Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>When the output voltage fell lower than 9.6V, the unit shuts off output by operating low voltage protection.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>7.47</td><td>7.54</td><td>7.76</td></tr> <tr><td>11.4</td><td>7.40</td><td>7.50</td><td>7.73</td></tr> <tr><td>10.8</td><td>7.34</td><td>7.46</td><td>7.70</td></tr> <tr><td>9.6</td><td>7.25</td><td>7.41</td><td>7.67</td></tr> <tr><td>8.4</td><td>7.21</td><td>7.38</td><td>7.66</td></tr> <tr><td>7.2</td><td>7.21</td><td>7.38</td><td>7.66</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	12.0	7.47	7.54	7.76	11.4	7.40	7.50	7.73	10.8	7.34	7.46	7.70	9.6	7.25	7.41	7.67	8.4	7.21	7.38	7.66	7.2	7.21	7.38	7.66	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																						
12.0	7.47	7.54	7.76																																																						
11.4	7.40	7.50	7.73																																																						
10.8	7.34	7.46	7.70																																																						
9.6	7.25	7.41	7.67																																																						
8.4	7.21	7.38	7.66																																																						
7.2	7.21	7.38	7.66																																																						
-	-	-	-																																																						
-	-	-	-																																																						
-	-	-	-																																																						
-	-	-	-																																																						
-	-	-	-																																																						
-	-	-	-																																																						



Model	CES24120-6
Item	Overvoltage Protection
Object	+12V6A

1. Graph

—△— Input Volt. 18V

---□--- Input Volt. 24V

-·-○-·- Input Volt. 36V

Ambient Temperature [°C]

Load 0%

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Operating Point [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-40	14.81	14.81	14.81
-20	14.78	14.78	14.78
0	14.74	14.74	14.74
25	14.68	14.69	14.69
40	14.65	14.65	14.65
60	14.60	14.60	14.60
85	14.54	14.54	14.54
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-




Figure A




Figure B