



M T B F

(E I A J R C R - 9 1 0 2)

| | |
|-------|------------|
| Model | CHS1204824 |
|-------|------------|

| No. | P a r t s | | Q'ty of Device | Failure rate [10 ⁻⁶ /H] | R e f e r e n c e |
|--|------------------------|---------------------|----------------|------------------------------------|-------------------|
| 1 | I C | M o n o l i t h i c | 7 | 0.2360 | |
| 2 | | H y b r i d | 0 | 0.0000 | |
| 3 | T r a n s i s t o r s | | 9 | 0.4994 | |
| 4 | D i o d e s | | 13 | 0.2355 | |
| 5 | LED・Optocouplers | | 1 | 0.0700 | |
| 6 | R e s i s t o r s | | 77 | 0.3375 | |
| 7 | C a p a c i t o r s | | 45 | 0.3330 | |
| 8 | Transformer・Choke Coil | | 1 | 0.0230 | |
| 9 | C o n n e c t o r s | | 406 | 0.0559 | |
| 10 | O t h e r s | | 1 | 0.1100 | |
| Total Failure Rate [10 ⁻⁶ /H] | | | | 1.9003 | |

| | | |
|---------------------|------|---------|
| M T B F | [H] | 526,000 |
| Ambient Temperature | [°C] | — |
| Load Factor | [%] | — |