

# TEST DATA OF CHS3002415

Regulated DC Power Supply  
June 24, 2015

Approved by : Yoshimichi Hirokawa  
Yoshimichi Hirokawa Design Manager

Prepared by : Tomomi Akai  
Tomomi Akai Design Engineer

**COSEL CO.,LTD.**

## CONTENTS

1.Input Current (by Input Voltage) . . . . .	1
2.Input Current (by Load Current) . . . . .	2
3.Input Power (by Load Current) . . . . .	3
4.Efficiency (by Input Voltage) . . . . .	4
5.Efficiency (by Load Current) . . . . .	5
6.Line Regulation . . . . .	6
7.Load Regulation . . . . .	7
8.Dynamic Load Response . . . . .	8
9.Ripple Voltage (by Load Current) . . . . .	9
10.Ripple-Noise . . . . .	10
11.Ripple Voltage (by Ambient Temperature) . . . . .	11
12.Ambient Temperature Drift . . . . .	12
13.Output Voltage Accuracy . . . . .	13
14.Time Lapse Drift . . . . .	14
15.Rise and Fall Time . . . . .	15
16.Minimum Input Voltage for Regulated Output Voltage . . . . .	16
17.Overcurrent Protection . . . . .	17
18.Overvoltage Protection . . . . .	18
19.Figure of Testing Circuitry . . . . .	19

(Final Page 19)



Model		CHS3002415		Temperature	25°C																																																																															
Item		Input Current (by Input Voltage)		Testing Circuitry	Figure A																																																																															
Object		_____																																																																																		
1.Graph			2.Values																																																																																	
<p>Legend:                  —△— Load 100%                  - - - □ - - - Load 50%                  - - - ○ - - - Load 0%</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.005</td><td>0.005</td><td>0.005</td></tr> <tr><td>12.0</td><td>0.005</td><td>0.005</td><td>0.005</td></tr> <tr><td>16.0</td><td>0.019</td><td>0.019</td><td>0.019</td></tr> <tr><td>17.5</td><td>0.152</td><td>6.090</td><td>12.340</td></tr> <tr><td>18.0</td><td>0.154</td><td>5.920</td><td>12.000</td></tr> <tr><td>19.0</td><td>0.159</td><td>5.610</td><td>11.350</td></tr> <tr><td>20.0</td><td>0.166</td><td>5.340</td><td>10.870</td></tr> <tr><td>24.0</td><td>0.189</td><td>4.511</td><td>9.100</td></tr> <tr><td>28.0</td><td>0.203</td><td>3.889</td><td>7.790</td></tr> <tr><td>32.0</td><td>0.210</td><td>3.446</td><td>6.870</td></tr> <tr><td>36.0</td><td>0.212</td><td>3.084</td><td>6.130</td></tr> <tr><td>40.0</td><td>0.211</td><td>2.794</td><td>5.530</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	4.0	0.000	0.000	0.000	8.0	0.005	0.005	0.005	12.0	0.005	0.005	0.005	16.0	0.019	0.019	0.019	17.5	0.152	6.090	12.340	18.0	0.154	5.920	12.000	19.0	0.159	5.610	11.350	20.0	0.166	5.340	10.870	24.0	0.189	4.511	9.100	28.0	0.203	3.889	7.790	32.0	0.210	3.446	6.870	36.0	0.212	3.084	6.130	40.0	0.211	2.794	5.530	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																			
	Load 0%	Load 50%	Load 100%																																																																																	
0.0	0.000	0.000	0.000																																																																																	
4.0	0.000	0.000	0.000																																																																																	
8.0	0.005	0.005	0.005																																																																																	
12.0	0.005	0.005	0.005																																																																																	
16.0	0.019	0.019	0.019																																																																																	
17.5	0.152	6.090	12.340																																																																																	
18.0	0.154	5.920	12.000																																																																																	
19.0	0.159	5.610	11.350																																																																																	
20.0	0.166	5.340	10.870																																																																																	
24.0	0.189	4.511	9.100																																																																																	
28.0	0.203	3.889	7.790																																																																																	
32.0	0.210	3.446	6.870																																																																																	
36.0	0.212	3.084	6.130																																																																																	
40.0	0.211	2.794	5.530																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																																				



Model		CHS3002415		Temperature 25°C																																																				
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph			2.Values																																																					
<p>                 —△— Input Volt. 18V                  - - - □ - - - Input Volt. 24V                  - - - ○ - - - Input Volt. 36V             </p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.154</td><td>0.189</td><td>0.212</td></tr> <tr><td>2.0</td><td>2.035</td><td>1.450</td><td>1.053</td></tr> <tr><td>4.0</td><td>3.550</td><td>2.740</td><td>1.908</td></tr> <tr><td>6.0</td><td>5.267</td><td>4.040</td><td>2.776</td></tr> <tr><td>8.0</td><td>7.042</td><td>5.370</td><td>3.654</td></tr> <tr><td>10.0</td><td>8.816</td><td>6.710</td><td>4.550</td></tr> <tr><td>12.0</td><td>10.575</td><td>8.050</td><td>5.460</td></tr> <tr><td>13.5</td><td>12.000</td><td>9.100</td><td>6.130</td></tr> <tr><td>14.9</td><td>13.213</td><td>10.040</td><td>6.760</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.0	0.154	0.189	0.212	2.0	2.035	1.450	1.053	4.0	3.550	2.740	1.908	6.0	5.267	4.040	2.776	8.0	7.042	5.370	3.654	10.0	8.816	6.710	4.550	12.0	10.575	8.050	5.460	13.5	12.000	9.100	6.130	14.9	13.213	10.040	6.760	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																							
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																					
0.0	0.154	0.189	0.212																																																					
2.0	2.035	1.450	1.053																																																					
4.0	3.550	2.740	1.908																																																					
6.0	5.267	4.040	2.776																																																					
8.0	7.042	5.370	3.654																																																					
10.0	8.816	6.710	4.550																																																					
12.0	10.575	8.050	5.460																																																					
13.5	12.000	9.100	6.130																																																					
14.9	13.213	10.040	6.760																																																					
--	-	-	-																																																					
--	-	-	-																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>																																																								



<p>Model CHS3002415</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
Item	Input Power (by Load Current)																																																				
Object	_____																																																				
<p>1.Graph</p> <p>                     —△— Input Volt. 18V                      - - - □ - - - Input Volt. 24V                      · · · ○ · · · Input Volt. 36V                 </p> <p>Input Power [W]</p> <p>Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>2.9</td><td>4.4</td><td>7.5</td></tr> <tr><td>2.0</td><td>33.3</td><td>34.7</td><td>37.7</td></tr> <tr><td>4.0</td><td>64.2</td><td>65.4</td><td>68.4</td></tr> <tr><td>6.0</td><td>95.3</td><td>96.6</td><td>99.5</td></tr> <tr><td>8.0</td><td>126.7</td><td>128.3</td><td>131.3</td></tr> <tr><td>10.0</td><td>158.5</td><td>160.1</td><td>163.7</td></tr> <tr><td>12.0</td><td>191.0</td><td>192.4</td><td>196.0</td></tr> <tr><td>13.5</td><td>216.0</td><td>217.2</td><td>220.6</td></tr> <tr><td>14.9</td><td>238.6</td><td>239.8</td><td>242.9</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Power [W]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.0	2.9	4.4	7.5	2.0	33.3	34.7	37.7	4.0	64.2	65.4	68.4	6.0	95.3	96.6	99.5	8.0	126.7	128.3	131.3	10.0	158.5	160.1	163.7	12.0	191.0	192.4	196.0	13.5	216.0	217.2	220.6	14.9	238.6	239.8	242.9	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																		
0.0	2.9	4.4	7.5																																																		
2.0	33.3	34.7	37.7																																																		
4.0	64.2	65.4	68.4																																																		
6.0	95.3	96.6	99.5																																																		
8.0	126.7	128.3	131.3																																																		
10.0	158.5	160.1	163.7																																																		
12.0	191.0	192.4	196.0																																																		
13.5	216.0	217.2	220.6																																																		
14.9	238.6	239.8	242.9																																																		
--	-	-	-																																																		
--	-	-	-																																																		
<p>Note: Slanted line shows the range of the rated load current.</p>																																																					



Model		CHS3002415																																	
Item		Efficiency (by Input Voltage)																																	
Object																																			
1.Graph		Temperature 25°C Testing Circuitry Figure A																																	
<p>1.Graph</p> <p style="text-align: right;">---□--- Load 50% —△— Load 100%</p> <p style="text-align: center;">Input Voltage [V]</p>		2.Values																																	
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>17</td><td>95.2</td><td>93.9</td></tr> <tr><td>18</td><td>95.0</td><td>93.9</td></tr> <tr><td>19</td><td>94.8</td><td>93.9</td></tr> <tr><td>20</td><td>94.5</td><td>93.8</td></tr> <tr><td>24</td><td>93.5</td><td>93.4</td></tr> <tr><td>30</td><td>92.3</td><td>92.7</td></tr> <tr><td>36</td><td>91.1</td><td>92.0</td></tr> <tr><td>40</td><td>90.4</td><td>91.6</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	17	95.2	93.9	18	95.0	93.9	19	94.8	93.9	20	94.5	93.8	24	93.5	93.4	30	92.3	92.7	36	91.1	92.0	40	90.4	91.6	--	-	-
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
17	95.2	93.9																																	
18	95.0	93.9																																	
19	94.8	93.9																																	
20	94.5	93.8																																	
24	93.5	93.4																																	
30	92.3	92.7																																	
36	91.1	92.0																																	
40	90.4	91.6																																	
--	-	-																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			



<p>Model CHS3002415</p>		<p>Temperature 25°C</p>																																																				
<p>Item Efficiency (by Load Current)</p>		<p>Testing Circuitry Figure A</p>																																																				
<p>Object _____</p>																																																						
<p>1.Graph</p> <p>                     —△— Input Volt. 18V                      - - - □ - - - Input Volt. 24V                      · · · ○ · · · Input Volt. 36V                 </p> <p>                     Efficiency [%]                      Load Current [A]                 </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.0</td><td>90.4</td><td>86.9</td><td>80.0</td></tr> <tr><td>4.0</td><td>93.7</td><td>92.0</td><td>88.0</td></tr> <tr><td>6.0</td><td>94.6</td><td>93.3</td><td>90.6</td></tr> <tr><td>8.0</td><td>94.9</td><td>93.7</td><td>91.6</td></tr> <tr><td>10.0</td><td>94.8</td><td>93.8</td><td>91.8</td></tr> <tr><td>12.0</td><td>94.4</td><td>93.7</td><td>92.0</td></tr> <tr><td>13.5</td><td>93.9</td><td>93.4</td><td>92.0</td></tr> <tr><td>14.9</td><td>93.5</td><td>93.1</td><td>91.9</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.0	-	-	-	2.0	90.4	86.9	80.0	4.0	93.7	92.0	88.0	6.0	94.6	93.3	90.6	8.0	94.9	93.7	91.6	10.0	94.8	93.8	91.8	12.0	94.4	93.7	92.0	13.5	93.9	93.4	92.0	14.9	93.5	93.1	91.9	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.0	-	-	-																																																			
2.0	90.4	86.9	80.0																																																			
4.0	93.7	92.0	88.0																																																			
6.0	94.6	93.3	90.6																																																			
8.0	94.9	93.7	91.6																																																			
10.0	94.8	93.8	91.8																																																			
12.0	94.4	93.7	92.0																																																			
13.5	93.9	93.4	92.0																																																			
14.9	93.5	93.1	91.9																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						



<b>COSEL</b>																																			
Model	CHS3002415	Temperature	25°C																																
Item	Line Regulation	Testing Circuitry	Figure A																																
Object	+15V13.5A																																		
<p>1.Graph</p> <div style="text-align: right;"> <p>---□--- Load 50%</p> <p>—△— Load 100%</p> </div> <p style="text-align: center;">Note: Slanted line shows the range of the rated input voltage.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>17</td><td>15.009</td><td>15.010</td></tr> <tr><td>18</td><td>15.009</td><td>15.010</td></tr> <tr><td>19</td><td>15.009</td><td>15.010</td></tr> <tr><td>20</td><td>15.010</td><td>15.011</td></tr> <tr><td>24</td><td>15.010</td><td>15.011</td></tr> <tr><td>30</td><td>15.010</td><td>15.011</td></tr> <tr><td>36</td><td>15.010</td><td>15.011</td></tr> <tr><td>40</td><td>15.010</td><td>15.011</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	17	15.009	15.010	18	15.009	15.010	19	15.009	15.010	20	15.010	15.011	24	15.010	15.011	30	15.010	15.011	36	15.010	15.011	40	15.010	15.011	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
17	15.009	15.010																																	
18	15.009	15.010																																	
19	15.009	15.010																																	
20	15.010	15.011																																	
24	15.010	15.011																																	
30	15.010	15.011																																	
36	15.010	15.011																																	
40	15.010	15.011																																	
--	-	-																																	




<p>Model CHS3002415</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
<p>Item Load Regulation</p>																																																					
<p>Object +15V13.5A</p>																																																					
<p>1.Graph</p> <p>                     —△— Input Volt. 18V                      - - - □ - - - Input Volt. 24V                      · · · ○ · · · Input Volt. 36V                 </p> <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.012</td><td>15.013</td><td>15.013</td></tr> <tr><td>2.0</td><td>15.012</td><td>15.013</td><td>15.012</td></tr> <tr><td>4.0</td><td>15.011</td><td>15.012</td><td>15.012</td></tr> <tr><td>6.0</td><td>15.010</td><td>15.011</td><td>15.011</td></tr> <tr><td>8.0</td><td>15.009</td><td>15.011</td><td>15.011</td></tr> <tr><td>10.0</td><td>15.009</td><td>15.010</td><td>15.011</td></tr> <tr><td>12.0</td><td>15.009</td><td>15.010</td><td>15.011</td></tr> <tr><td>13.5</td><td>15.009</td><td>15.010</td><td>15.011</td></tr> <tr><td>14.9</td><td>15.009</td><td>15.010</td><td>15.011</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.0	15.012	15.013	15.013	2.0	15.012	15.013	15.012	4.0	15.011	15.012	15.012	6.0	15.010	15.011	15.011	8.0	15.009	15.011	15.011	10.0	15.009	15.010	15.011	12.0	15.009	15.010	15.011	13.5	15.009	15.010	15.011	14.9	15.009	15.010	15.011	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																		
0.0	15.012	15.013	15.013																																																		
2.0	15.012	15.013	15.012																																																		
4.0	15.011	15.012	15.012																																																		
6.0	15.010	15.011	15.011																																																		
8.0	15.009	15.011	15.011																																																		
10.0	15.009	15.010	15.011																																																		
12.0	15.009	15.010	15.011																																																		
13.5	15.009	15.010	15.011																																																		
14.9	15.009	15.010	15.011																																																		
--	-	-	-																																																		
--	-	-	-																																																		



Model	CHS3002415	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+15V13.5A		

Input Volt. 24 V  
Cycle 5 ms

t1,t2=50µS





<p>Model CHS3002415</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
Item	Ripple Voltage (by Load Current)																																							
Object	+15V13.5A																																							
<p>1.Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 18V - - ○ - - Input Volt. 36V</p> </div> <p>Ripple Voltage [mV]</p> <p>Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>2.0</td><td>25</td><td>85</td></tr> <tr><td>4.0</td><td>25</td><td>85</td></tr> <tr><td>6.0</td><td>25</td><td>85</td></tr> <tr><td>8.0</td><td>25</td><td>85</td></tr> <tr><td>10.0</td><td>25</td><td>85</td></tr> <tr><td>12.0</td><td>25</td><td>85</td></tr> <tr><td>13.5</td><td>25</td><td>85</td></tr> <tr><td>14.9</td><td>30</td><td>85</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	2.0	25	85	4.0	25	85	6.0	25	85	8.0	25	85	10.0	25	85	12.0	25	85	13.5	25	85	14.9	30	85	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 18 [V]	Input Volt. 36 [V]																																						
2.0	25	85																																						
4.0	25	85																																						
6.0	25	85																																						
8.0	25	85																																						
10.0	25	85																																						
12.0	25	85																																						
13.5	25	85																																						
14.9	30	85																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								

<p>Model CHS3002415</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
<p>Item Ripple-Noise</p>																																								
<p>Object +15V13.5A</p>																																								
<p>1.Graph</p> <div style="display: flex; align-items: center;"> <div style="margin-right: 20px;"> <p>—△— Input Volt. 18V</p> <p>- - -○- - - Input Volt. 36V</p> </div> </div>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>2.0</td><td>25</td><td>85</td></tr> <tr><td>4.0</td><td>25</td><td>85</td></tr> <tr><td>6.0</td><td>25</td><td>85</td></tr> <tr><td>8.0</td><td>25</td><td>90</td></tr> <tr><td>10.0</td><td>30</td><td>95</td></tr> <tr><td>12.0</td><td>30</td><td>100</td></tr> <tr><td>13.5</td><td>30</td><td>105</td></tr> <tr><td>14.9</td><td>30</td><td>115</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	2.0	25	85	4.0	25	85	6.0	25	85	8.0	25	90	10.0	30	95	12.0	30	100	13.5	30	105	14.9	30	115	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 18 [V]	Input Volt. 36 [V]																																						
2.0	25	85																																						
4.0	25	85																																						
6.0	25	85																																						
8.0	25	90																																						
10.0	30	95																																						
12.0	30	100																																						
13.5	30	105																																						
14.9	30	115																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Fig.Complex Ripple Noise Wave Form</p>																																								



Model		CHS3002415	Testing Circuitry Figure B																																						
Item		Ripple Voltage (by Ambient Temp.)																																							
Object		+15V13.5A																																							
1.Graph		<div style="text-align: right;">                     --- □ --- Load 50%                      — △ — Load 100%                 </div> <p style="text-align: center;">Ambient Temperature [°C] Input Volt. 24 V</p>	2.Values																																						
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-50</td><td>115</td><td>115</td></tr> <tr><td>-40</td><td>100</td><td>100</td></tr> <tr><td>-20</td><td>80</td><td>80</td></tr> <tr><td>0</td><td>65</td><td>60</td></tr> <tr><td>25</td><td>60</td><td>60</td></tr> <tr><td>40</td><td>60</td><td>60</td></tr> <tr><td>60</td><td>60</td><td>60</td></tr> <tr><td>85</td><td>55</td><td>55</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-50	115	115	-40	100	100	-20	80	80	0	65	60	25	60	60	40	60	60	60	60	60	85	55	55	--	-	-	--	-	-	--	-	-	
Ambient Temperature [°C]	Ripple Voltage [mV]																																								
	Load 50%	Load 100%																																							
-50	115	115																																							
-40	100	100																																							
-20	80	80																																							
0	65	60																																							
25	60	60																																							
40	60	60																																							
60	60	60																																							
85	55	55																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Measured by 100 MHz Oscilloscope.                      Note: Slanted line shows the range of the rated ambient temperature.</p>																																									
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																									



<b>COSEL</b>																																																					
Model	CHS3002415																																																				
Item	Ambient Temperature Drift	Testing Circuitry Figure A																																																			
Object	+15V13.5A																																																				
1.Graph	<p>                     —△— Input Volt. 18V                      - - - □ - - - Input Volt. 24V                      - · - ○ - · - - Input Volt. 36V                 </p> <p style="text-align: center;">Ambient Temperature [°C] Load 100%</p>	2.Values																																																			
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>-40</td><td>15.014</td><td>15.012</td><td>15.011</td></tr> <tr><td>-20</td><td>15.004</td><td>15.002</td><td>15.002</td></tr> <tr><td>0</td><td>15.007</td><td>15.009</td><td>15.009</td></tr> <tr><td>25</td><td>15.015</td><td>15.015</td><td>15.015</td></tr> <tr><td>40</td><td>15.016</td><td>15.018</td><td>15.019</td></tr> <tr><td>55</td><td>15.020</td><td>15.022</td><td>15.023</td></tr> <tr><td>60</td><td>15.021</td><td>15.022</td><td>15.023</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	-40	15.014	15.012	15.011	-20	15.004	15.002	15.002	0	15.007	15.009	15.009	25	15.015	15.015	15.015	40	15.016	15.018	15.019	55	15.020	15.022	15.023	60	15.021	15.022	15.023	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																		
-40	15.014	15.012	15.011																																																		
-20	15.004	15.002	15.002																																																		
0	15.007	15.009	15.009																																																		
25	15.015	15.015	15.015																																																		
40	15.016	15.018	15.019																																																		
55	15.020	15.022	15.023																																																		
60	15.021	15.022	15.023																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																					



<b>COSEL</b>		
Model	CHS3002415	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+15V13.5A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 18 - 36V

Load Current : 0 - 13.5A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

\* Output Voltage Accuracy (Ration) = 
$$\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	36	13.5	15.023	±11	±0.1
Minimum Voltage	-20	36	13.5	15.002		




<b>COSEL</b>																								
Model	CHS3002415																							
Item	Time Lapse Drift	Temperature 25°C Testing Circuitry Figure A																						
Object	+15V13.5A																							
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt. 24V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.009</td></tr> <tr><td>0.5</td><td>15.010</td></tr> <tr><td>1.0</td><td>15.010</td></tr> <tr><td>2.0</td><td>15.010</td></tr> <tr><td>3.0</td><td>15.010</td></tr> <tr><td>4.0</td><td>15.010</td></tr> <tr><td>5.0</td><td>15.010</td></tr> <tr><td>6.0</td><td>15.010</td></tr> <tr><td>7.0</td><td>15.010</td></tr> <tr><td>8.0</td><td>15.010</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	15.009	0.5	15.010	1.0	15.010	2.0	15.010	3.0	15.010	4.0	15.010	5.0	15.010	6.0	15.010	7.0	15.010	8.0	15.010
Time since start [H]	Output Voltage [V]																							
0.0	15.009																							
0.5	15.010																							
1.0	15.010																							
2.0	15.010																							
3.0	15.010																							
4.0	15.010																							
5.0	15.010																							
6.0	15.010																							
7.0	15.010																							
8.0	15.010																							



Model		CHS3002415	Temperature	25°C
Item		Rise and Fall Time	Testing Circuitry	Figure A
Object		+15V13.5A		

1. Graph


Input Volt. 24 V



2. Values

[ms]

Load \ Time	Td	Tr	Ts	Th	Tf
50 %	7.9	5.0	12.9	4.0	0.6
100 %	7.9	5.5	13.4	1.9	0.5





<b>COSEL</b>																																								
Model	CHS3002415																																							
Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A																																						
Object	+15V13.5A																																							
<p>1.Graph</p> <p style="text-align: center;"> <span style="margin-right: 20px;">---□--- Load 50%</span>  <span>—△— Load 100%</span> </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-40</td><td>16.1</td><td>16.1</td></tr> <tr><td>-20</td><td>16.0</td><td>16.1</td></tr> <tr><td>0</td><td>15.9</td><td>16.0</td></tr> <tr><td>25</td><td>15.8</td><td>15.9</td></tr> <tr><td>40</td><td>15.8</td><td>15.9</td></tr> <tr><td>55</td><td>15.8</td><td>15.9</td></tr> <tr><td>60</td><td>15.8</td><td>15.9</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-40	16.1	16.1	-20	16.0	16.1	0	15.9	16.0	25	15.8	15.9	40	15.8	15.9	55	15.8	15.9	60	15.8	15.9	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-40	16.1	16.1																																						
-20	16.0	16.1																																						
0	15.9	16.0																																						
25	15.8	15.9																																						
40	15.8	15.9																																						
55	15.8	15.9																																						
60	15.8	15.9																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																								



<p>Model CHS3002415</p> <p>Item Overcurrent Protection</p> <p>Object +15V13.5A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure A</p>																																																							
<p>1.Graph</p> <p> <span style="color: black;">—</span> Input Volt. 18V  <span style="color: blue;">—</span> Input Volt. 24V  <span style="color: orange;">—</span> Input Volt. 36V                 </p> <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>14.3</td> <td>18.50</td> <td>18.29</td> <td>17.67</td> </tr> <tr> <td>13.5</td> <td>18.47</td> <td>18.17</td> <td>17.62</td> </tr> <tr> <td>12.0</td> <td>18.32</td> <td>18.21</td> <td>17.60</td> </tr> <tr> <td>10.5</td> <td>18.34</td> <td>18.11</td> <td>17.63</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	14.3	18.50	18.29	17.67	13.5	18.47	18.17	17.62	12.0	18.32	18.21	17.60	10.5	18.34	18.11	17.63	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																						
14.3	18.50	18.29	17.67																																																						
13.5	18.47	18.17	17.62																																																						
12.0	18.32	18.21	17.60																																																						
10.5	18.34	18.11	17.63																																																						
--	-	-	-																																																						
--	-	-	-																																																						
--	-	-	-																																																						
--	-	-	-																																																						
--	-	-	-																																																						
--	-	-	-																																																						
--	-	-	-																																																						
--	-	-	-																																																						



<b>COSEL</b>																																								
Model	CHS3002415																																							
Item	Overvoltage Protection	Testing Circuitry Figure A																																						
Object	+15V13.5A																																							
<p>1.Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 24V</p> <p>---□--- Input Volt. 36V</p> </div> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: right;">Load 0%</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>-40</td><td>17.03</td><td>17.03</td></tr> <tr><td>-20</td><td>17.08</td><td>17.09</td></tr> <tr><td>0</td><td>17.13</td><td>17.15</td></tr> <tr><td>25</td><td>17.18</td><td>17.18</td></tr> <tr><td>40</td><td>17.21</td><td>17.23</td></tr> <tr><td>55</td><td>17.23</td><td>17.24</td></tr> <tr><td>85</td><td>17.27</td><td>17.26</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Operating Point [V]		Input Volt. 24[V]	Input Volt. 36[V]	-40	17.03	17.03	-20	17.08	17.09	0	17.13	17.15	25	17.18	17.18	40	17.21	17.23	55	17.23	17.24	85	17.27	17.26	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Operating Point [V]																																							
	Input Volt. 24[V]	Input Volt. 36[V]																																						
-40	17.03	17.03																																						
-20	17.08	17.09																																						
0	17.13	17.15																																						
25	17.18	17.18																																						
40	17.21	17.23																																						
55	17.23	17.24																																						
85	17.27	17.26																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						




Figure A

Data Acquisition/Control Unit




Figure B