

# TEST DATA OF CHS3804812H

Regulated DC Power Supply  
March 30, 2017

Approved by : Junichi Hatagishi  
Junichi Hatagishi Design Manager

Prepared by : Hiroyuki Shoji  
Hiroyuki Syoji Design Engineer

**COSEL CO.,LTD.**

## CONTENTS

1.Input Current (by Input Voltage) . . . . .	1
2.Input Current (by Load Current) . . . . .	2
3.Input Power (by Load Current) . . . . .	3
4.Efficiency (by Input Voltage) . . . . .	4
5.Efficiency (by Load Current) . . . . .	5
6.Line Regulation . . . . .	6
7.Load Regulation . . . . .	7
8.Dynamic Load Response . . . . .	8
9.Ripple Voltage (by Load Current) . . . . .	9
10.Ripple-Noise . . . . .	10
11.Ripple Voltage (by Ambient Temperature) . . . . .	11
12.Ambient Temperature Drift . . . . .	12
13.Output Voltage Accuracy . . . . .	13
14.Time Lapse Drift . . . . .	14
15.Rise and Fall Time . . . . .	15
16.Minimum Input Voltage for Regulated Output Voltage . . . . .	16
17.Overcurrent Protection . . . . .	17
18.Overvoltage Protection . . . . .	18
19.Figure of Testing Circuitry . . . . .	19

(Final Page 19)



Model		CHS3804812H		Temperature 25°C																																																																																
Item		Input Current (by Input Voltage)		Testing Circuitry Figure A																																																																																
Object		_____																																																																																		
1.Graph			2.Values																																																																																	
<p>                 —△— Load 100%                  - - □ - - Load 50%                  - · ○ - · Load 0%             </p> <p>Note: Slanted line shows the range of the rated input voltage.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.009</td><td>0.009</td><td>0.009</td></tr> <tr><td>16.0</td><td>0.009</td><td>0.009</td><td>0.009</td></tr> <tr><td>24.0</td><td>0.010</td><td>0.010</td><td>0.010</td></tr> <tr><td>33.0</td><td>0.010</td><td>0.010</td><td>0.010</td></tr> <tr><td>35.2</td><td>0.067</td><td>5.210</td><td>10.309</td></tr> <tr><td>36.0</td><td>0.070</td><td>5.218</td><td>10.314</td></tr> <tr><td>38.4</td><td>0.077</td><td>5.213</td><td>10.322</td></tr> <tr><td>40.0</td><td>0.075</td><td>4.995</td><td>10.117</td></tr> <tr><td>48.0</td><td>0.076</td><td>4.193</td><td>8.421</td></tr> <tr><td>60.0</td><td>0.084</td><td>3.376</td><td>6.748</td></tr> <tr><td>70.0</td><td>0.088</td><td>2.912</td><td>5.802</td></tr> <tr><td>76.0</td><td>0.089</td><td>2.696</td><td>5.351</td></tr> <tr><td>80.0</td><td>0.089</td><td>2.567</td><td>5.090</td></tr> <tr><td>84.0</td><td>0.090</td><td>2.451</td><td>4.852</td></tr> <tr><td>88.0</td><td>0.090</td><td>2.346</td><td>4.641</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	8.0	0.009	0.009	0.009	16.0	0.009	0.009	0.009	24.0	0.010	0.010	0.010	33.0	0.010	0.010	0.010	35.2	0.067	5.210	10.309	36.0	0.070	5.218	10.314	38.4	0.077	5.213	10.322	40.0	0.075	4.995	10.117	48.0	0.076	4.193	8.421	60.0	0.084	3.376	6.748	70.0	0.088	2.912	5.802	76.0	0.089	2.696	5.351	80.0	0.089	2.567	5.090	84.0	0.090	2.451	4.852	88.0	0.090	2.346	4.641	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																			
	Load 0%	Load 50%	Load 100%																																																																																	
0.0	0.000	0.000	0.000																																																																																	
8.0	0.009	0.009	0.009																																																																																	
16.0	0.009	0.009	0.009																																																																																	
24.0	0.010	0.010	0.010																																																																																	
33.0	0.010	0.010	0.010																																																																																	
35.2	0.067	5.210	10.309																																																																																	
36.0	0.070	5.218	10.314																																																																																	
38.4	0.077	5.213	10.322																																																																																	
40.0	0.075	4.995	10.117																																																																																	
48.0	0.076	4.193	8.421																																																																																	
60.0	0.084	3.376	6.748																																																																																	
70.0	0.088	2.912	5.802																																																																																	
76.0	0.089	2.696	5.351																																																																																	
80.0	0.089	2.567	5.090																																																																																	
84.0	0.090	2.451	4.852																																																																																	
88.0	0.090	2.346	4.641																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	



Model		CHS3804812H		Temperature 25°C																																																				
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph			2.Values																																																					
<p>                 —△— Input Volt. 40V                  - - □ - - Input Volt. 48V                  - · - ○ - · - Input Volt. 76V             </p> <p>Note: Slanted line shows the range of the rated load current.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 40[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.075</td><td>0.076</td><td>0.089</td></tr> <tr><td>4.0</td><td>1.300</td><td>1.099</td><td>0.733</td></tr> <tr><td>8.0</td><td>2.519</td><td>2.123</td><td>1.377</td></tr> <tr><td>12.0</td><td>3.752</td><td>3.143</td><td>2.030</td></tr> <tr><td>16.0</td><td>4.995</td><td>4.193</td><td>2.696</td></tr> <tr><td>20.0</td><td>6.272</td><td>5.234</td><td>3.350</td></tr> <tr><td>25.0</td><td>7.859</td><td>6.549</td><td>4.178</td></tr> <tr><td>30.0</td><td>9.474</td><td>7.880</td><td>5.012</td></tr> <tr><td>32.0</td><td>10.117</td><td>8.421</td><td>5.351</td></tr> <tr><td>35.2</td><td>11.176</td><td>9.293</td><td>5.903</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 40[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	0.075	0.076	0.089	4.0	1.300	1.099	0.733	8.0	2.519	2.123	1.377	12.0	3.752	3.143	2.030	16.0	4.995	4.193	2.696	20.0	6.272	5.234	3.350	25.0	7.859	6.549	4.178	30.0	9.474	7.880	5.012	32.0	10.117	8.421	5.351	35.2	11.176	9.293	5.903	--	-	-	-
Load Current [A]	Input Current [A]																																																							
	Input Volt. 40[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																					
0.0	0.075	0.076	0.089																																																					
4.0	1.300	1.099	0.733																																																					
8.0	2.519	2.123	1.377																																																					
12.0	3.752	3.143	2.030																																																					
16.0	4.995	4.193	2.696																																																					
20.0	6.272	5.234	3.350																																																					
25.0	7.859	6.549	4.178																																																					
30.0	9.474	7.880	5.012																																																					
32.0	10.117	8.421	5.351																																																					
35.2	11.176	9.293	5.903																																																					
--	-	-	-																																																					



Model		CHS3804812H		Temperature 25°C																																																				
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		—△— Input Volt. 40V - - - □ - - - Input Volt. 48V - - - ○ - - - Input Volt. 76V		2.Values																																																				
				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 40[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>3.0</td><td>3.7</td><td>6.7</td></tr> <tr><td>4.0</td><td>52.1</td><td>52.7</td><td>55.7</td></tr> <tr><td>8.0</td><td>101.0</td><td>101.9</td><td>104.7</td></tr> <tr><td>12.0</td><td>150.1</td><td>151.0</td><td>154.3</td></tr> <tr><td>16.0</td><td>199.8</td><td>201.1</td><td>204.8</td></tr> <tr><td>20.0</td><td>251.1</td><td>251.3</td><td>254.7</td></tr> <tr><td>25.0</td><td>314.9</td><td>314.6</td><td>317.5</td></tr> <tr><td>30.0</td><td>379.5</td><td>378.7</td><td>381.1</td></tr> <tr><td>32.0</td><td>404.7</td><td>404.4</td><td>406.8</td></tr> <tr><td>35.2</td><td>447.5</td><td>446.7</td><td>448.5</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Power [W]			Input Volt. 40[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	3.0	3.7	6.7	4.0	52.1	52.7	55.7	8.0	101.0	101.9	104.7	12.0	150.1	151.0	154.3	16.0	199.8	201.1	204.8	20.0	251.1	251.3	254.7	25.0	314.9	314.6	317.5	30.0	379.5	378.7	381.1	32.0	404.7	404.4	406.8	35.2	447.5	446.7	448.5	--	-	-	-
Load Current [A]	Input Power [W]																																																							
	Input Volt. 40[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																					
0.0	3.0	3.7	6.7																																																					
4.0	52.1	52.7	55.7																																																					
8.0	101.0	101.9	104.7																																																					
12.0	150.1	151.0	154.3																																																					
16.0	199.8	201.1	204.8																																																					
20.0	251.1	251.3	254.7																																																					
25.0	314.9	314.6	317.5																																																					
30.0	379.5	378.7	381.1																																																					
32.0	404.7	404.4	406.8																																																					
35.2	447.5	446.7	448.5																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								



Model		CHS3804812H	Temperature 25°C Testing Circuitry Figure A																																
Item		Efficiency (by Input Voltage)																																	
Object																																			
1.Graph		<p>---□--- Load 50% —△— Load 100%</p>	2.Values																																
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>40</td><td>96.3</td><td>95.1</td></tr> <tr><td>42</td><td>96.2</td><td>95.1</td></tr> <tr><td>46</td><td>96.0</td><td>95.2</td></tr> <tr><td>48</td><td>95.9</td><td>95.2</td></tr> <tr><td>55</td><td>95.5</td><td>95.1</td></tr> <tr><td>60</td><td>95.2</td><td>95.0</td></tr> <tr><td>70</td><td>94.6</td><td>94.8</td></tr> <tr><td>76</td><td>94.2</td><td>94.6</td></tr> <tr><td>80</td><td>93.9</td><td>94.5</td></tr> </tbody> </table>	Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	40	96.3	95.1	42	96.2	95.1	46	96.0	95.2	48	95.9	95.2	55	95.5	95.1	60	95.2	95.0	70	94.6	94.8	76	94.2	94.6	80	93.9	94.5	
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
40	96.3	95.1																																	
42	96.2	95.1																																	
46	96.0	95.2																																	
48	95.9	95.2																																	
55	95.5	95.1																																	
60	95.2	95.0																																	
70	94.6	94.8																																	
76	94.2	94.6																																	
80	93.9	94.5																																	
Note: Slanted line shows the range of the rated input voltage.																																			



Model		CHS3804812H		Temperature 25°C																																																				
Item		Efficiency (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		—△— Input Volt. 40V ---□--- Input Volt. 48V -·-○-·- Input Volt. 76V		2.Values																																																				
				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 40[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.0</td><td>93.0</td><td>91.9</td><td>87.1</td></tr> <tr><td>8.0</td><td>95.5</td><td>94.7</td><td>92.1</td></tr> <tr><td>12.0</td><td>96.2</td><td>95.7</td><td>93.6</td></tr> <tr><td>16.0</td><td>96.3</td><td>95.9</td><td>94.2</td></tr> <tr><td>20.0</td><td>96.1</td><td>95.8</td><td>94.6</td></tr> <tr><td>25.0</td><td>95.7</td><td>95.6</td><td>94.8</td></tr> <tr><td>30.0</td><td>95.2</td><td>95.3</td><td>94.7</td></tr> <tr><td>32.0</td><td>95.1</td><td>95.2</td><td>94.6</td></tr> <tr><td>35.2</td><td>94.7</td><td>94.9</td><td>94.5</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 40[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	-	-	-	4.0	93.0	91.9	87.1	8.0	95.5	94.7	92.1	12.0	96.2	95.7	93.6	16.0	96.3	95.9	94.2	20.0	96.1	95.8	94.6	25.0	95.7	95.6	94.8	30.0	95.2	95.3	94.7	32.0	95.1	95.2	94.6	35.2	94.7	94.9	94.5	--	-	-	-
Load Current [A]	Efficiency [%]																																																							
	Input Volt. 40[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																					
0.0	-	-	-																																																					
4.0	93.0	91.9	87.1																																																					
8.0	95.5	94.7	92.1																																																					
12.0	96.2	95.7	93.6																																																					
16.0	96.3	95.9	94.2																																																					
20.0	96.1	95.8	94.6																																																					
25.0	95.7	95.6	94.8																																																					
30.0	95.2	95.3	94.7																																																					
32.0	95.1	95.2	94.6																																																					
35.2	94.7	94.9	94.5																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								



<p>Model CHS3804812H</p> <p>Item Line Regulation</p> <p>Object +12V32A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure A</p>																																											
<p>1.Graph</p> <p>—△— Load 100%</p> <p>---□--- Load 50%</p> <p>---○--- Load 0%</p> <p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>36</td> <td>11.689</td> <td>11.274</td> <td>11.001</td> </tr> <tr> <td>38</td> <td>12.017</td> <td>11.923</td> <td>11.635</td> </tr> <tr> <td>39</td> <td>12.021</td> <td>12.021</td> <td>11.952</td> </tr> <tr> <td>40</td> <td>12.023</td> <td>12.021</td> <td>12.021</td> </tr> <tr> <td>48</td> <td>12.024</td> <td>12.024</td> <td>12.024</td> </tr> <tr> <td>55</td> <td>12.024</td> <td>12.025</td> <td>12.024</td> </tr> <tr> <td>60</td> <td>12.024</td> <td>12.025</td> <td>12.024</td> </tr> <tr> <td>70</td> <td>12.024</td> <td>12.025</td> <td>12.024</td> </tr> <tr> <td>76</td> <td>12.024</td> <td>12.024</td> <td>12.024</td> </tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]			Load 0%	Load 50%	Load 100%	36	11.689	11.274	11.001	38	12.017	11.923	11.635	39	12.021	12.021	11.952	40	12.023	12.021	12.021	48	12.024	12.024	12.024	55	12.024	12.025	12.024	60	12.024	12.025	12.024	70	12.024	12.025	12.024	76	12.024	12.024	12.024
Input Voltage [V]	Output Voltage [V]																																												
	Load 0%	Load 50%	Load 100%																																										
36	11.689	11.274	11.001																																										
38	12.017	11.923	11.635																																										
39	12.021	12.021	11.952																																										
40	12.023	12.021	12.021																																										
48	12.024	12.024	12.024																																										
55	12.024	12.025	12.024																																										
60	12.024	12.025	12.024																																										
70	12.024	12.025	12.024																																										
76	12.024	12.024	12.024																																										




Model		CHS3804812H		Temperature 25°C																																																				
Item		Load Regulation		Testing Circuitry Figure A																																																				
Object		+12V32A																																																						
1.Graph		—△— Input Volt. 40V - - - □ - - Input Volt. 48V - · - ○ - · - Input Volt. 76V		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 40[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.023</td><td>12.024</td><td>12.024</td></tr> <tr><td>4.0</td><td>12.023</td><td>12.024</td><td>12.024</td></tr> <tr><td>8.0</td><td>12.023</td><td>12.024</td><td>12.024</td></tr> <tr><td>12.0</td><td>12.022</td><td>12.024</td><td>12.024</td></tr> <tr><td>16.0</td><td>12.021</td><td>12.024</td><td>12.024</td></tr> <tr><td>20.0</td><td>12.021</td><td>12.024</td><td>12.024</td></tr> <tr><td>25.0</td><td>12.021</td><td>12.024</td><td>12.024</td></tr> <tr><td>30.0</td><td>12.021</td><td>12.024</td><td>12.024</td></tr> <tr><td>32.0</td><td>12.021</td><td>12.024</td><td>12.024</td></tr> <tr><td>35.2</td><td>12.021</td><td>12.024</td><td>12.024</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Output Voltage [V]			Input Volt. 40[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	12.023	12.024	12.024	4.0	12.023	12.024	12.024	8.0	12.023	12.024	12.024	12.0	12.022	12.024	12.024	16.0	12.021	12.024	12.024	20.0	12.021	12.024	12.024	25.0	12.021	12.024	12.024	30.0	12.021	12.024	12.024	32.0	12.021	12.024	12.024	35.2	12.021	12.024	12.024	--	-	-	-
Load Current [A]	Output Voltage [V]																																																							
	Input Volt. 40[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																					
0.0	12.023	12.024	12.024																																																					
4.0	12.023	12.024	12.024																																																					
8.0	12.023	12.024	12.024																																																					
12.0	12.022	12.024	12.024																																																					
16.0	12.021	12.024	12.024																																																					
20.0	12.021	12.024	12.024																																																					
25.0	12.021	12.024	12.024																																																					
30.0	12.021	12.024	12.024																																																					
32.0	12.021	12.024	12.024																																																					
35.2	12.021	12.024	12.024																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								



Model	CHS3804812H	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+12V32A		

Input Volt. 48 V  
Cycle 5 ms

t1,t2=50 μs





<p>Model CHS3804812H</p> <p>Item Ripple Voltage (by Load Current)</p> <p>Object +12V32A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure B</p>																																						
<p>1.Graph</p> <div style="text-align: center;"> <p>—△— Input Volt. 40V</p> <p>- - -○- - - Input Volt. 76V</p> </div> <p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 40 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>35</td><td>115</td></tr> <tr><td>4.0</td><td>35</td><td>115</td></tr> <tr><td>8.0</td><td>35</td><td>115</td></tr> <tr><td>12.0</td><td>35</td><td>115</td></tr> <tr><td>16.0</td><td>35</td><td>115</td></tr> <tr><td>20.0</td><td>35</td><td>115</td></tr> <tr><td>25.0</td><td>35</td><td>115</td></tr> <tr><td>30.0</td><td>35</td><td>115</td></tr> <tr><td>32.0</td><td>35</td><td>115</td></tr> <tr><td>35.2</td><td>35</td><td>115</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 40 [V]	Input Volt. 76 [V]	0.0	35	115	4.0	35	115	8.0	35	115	12.0	35	115	16.0	35	115	20.0	35	115	25.0	35	115	30.0	35	115	32.0	35	115	35.2	35	115	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 40 [V]	Input Volt. 76 [V]																																						
0.0	35	115																																						
4.0	35	115																																						
8.0	35	115																																						
12.0	35	115																																						
16.0	35	115																																						
20.0	35	115																																						
25.0	35	115																																						
30.0	35	115																																						
32.0	35	115																																						
35.2	35	115																																						
--	-	-																																						
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								




<p>Model CHS3804812H</p> <p>Item Ripple-Noise</p> <p>Object +12V32A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure B</p>																																						
<p>1.Graph</p> <p>             —△— Input Volt. 40V              - - -○- - - Input Volt. 76V         </p> <p>Measured by 100 MHz Oscilloscope.              Ripple-Noise is shown as p-p in the figure below.              Note: Slanted line shows the range of the rated load current.</p> <p>Fig.Complex Ripple Noise Wave Form</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 40 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>50</td><td>130</td></tr> <tr><td>4.0</td><td>50</td><td>130</td></tr> <tr><td>8.0</td><td>50</td><td>130</td></tr> <tr><td>12.0</td><td>55</td><td>130</td></tr> <tr><td>16.0</td><td>60</td><td>130</td></tr> <tr><td>20.0</td><td>60</td><td>130</td></tr> <tr><td>25.0</td><td>60</td><td>130</td></tr> <tr><td>30.0</td><td>60</td><td>130</td></tr> <tr><td>32.0</td><td>60</td><td>130</td></tr> <tr><td>35.2</td><td>60</td><td>135</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 40 [V]	Input Volt. 76 [V]	0.0	50	130	4.0	50	130	8.0	50	130	12.0	55	130	16.0	60	130	20.0	60	130	25.0	60	130	30.0	60	130	32.0	60	130	35.2	60	135	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 40 [V]	Input Volt. 76 [V]																																						
0.0	50	130																																						
4.0	50	130																																						
8.0	50	130																																						
12.0	55	130																																						
16.0	60	130																																						
20.0	60	130																																						
25.0	60	130																																						
30.0	60	130																																						
32.0	60	130																																						
35.2	60	135																																						
--	-	-																																						



Model	CHS3804812H
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V32A

Testing Circuitry Figure B

1.Graph



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	60	60
-20	50	50
0	45	45
25	50	50
40	55	55
55	60	60
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.




Fig.Complex Ripple Noise Wave Form



Model		CHS3804812H		Testing Circuitry Figure A																																																				
Item		Ambient Temperature Drift																																																						
Object		+12V32A																																																						
1.Graph		—△— Input Volt. 40V - - - □ - - - Input Volt. 48V - · - ○ - · - - Input Volt. 76V		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 40[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>-40</td> <td>12.073</td> <td>12.076</td> <td>12.074</td> </tr> <tr> <td>-20</td> <td>12.053</td> <td>12.056</td> <td>12.055</td> </tr> <tr> <td>0</td> <td>12.038</td> <td>12.041</td> <td>12.041</td> </tr> <tr> <td>25</td> <td>12.021</td> <td>12.024</td> <td>12.024</td> </tr> <tr> <td>40</td> <td>12.013</td> <td>12.016</td> <td>12.016</td> </tr> <tr> <td>55</td> <td>12.007</td> <td>12.010</td> <td>12.011</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 40[V]	Input Volt. 48[V]	Input Volt. 76[V]	-40	12.073	12.076	12.074	-20	12.053	12.056	12.055	0	12.038	12.041	12.041	25	12.021	12.024	12.024	40	12.013	12.016	12.016	55	12.007	12.010	12.011	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																							
	Input Volt. 40[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																					
-40	12.073	12.076	12.074																																																					
-20	12.053	12.056	12.055																																																					
0	12.038	12.041	12.041																																																					
25	12.021	12.024	12.024																																																					
40	12.013	12.016	12.016																																																					
55	12.007	12.010	12.011																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated ambient temperature.																																																								



<b>COSEL</b>		
Model	CHS3804812H	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+12V32A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 36 - 76V

Load Current : 0 - 32A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

\* Output Voltage Accuracy (Ration) = 
$$\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-40	48	32	12.076	±35	±0.3
Minimum Voltage	55	40	32	12.007		




<b>COSEL</b>																									
Model	CHS3804812H	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V32A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt.      48V Load                100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.024</td></tr> <tr><td>0.5</td><td>12.024</td></tr> <tr><td>1.0</td><td>12.024</td></tr> <tr><td>2.0</td><td>12.024</td></tr> <tr><td>3.0</td><td>12.024</td></tr> <tr><td>4.0</td><td>12.024</td></tr> <tr><td>5.0</td><td>12.024</td></tr> <tr><td>6.0</td><td>12.024</td></tr> <tr><td>7.0</td><td>12.024</td></tr> <tr><td>8.0</td><td>12.024</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	12.024	0.5	12.024	1.0	12.024	2.0	12.024	3.0	12.024	4.0	12.024	5.0	12.024	6.0	12.024	7.0	12.024	8.0	12.024
Time since start [H]	Output Voltage [V]																								
0.0	12.024																								
0.5	12.024																								
1.0	12.024																								
2.0	12.024																								
3.0	12.024																								
4.0	12.024																								
5.0	12.024																								
6.0	12.024																								
7.0	12.024																								
8.0	12.024																								



Model		CHS3804812H	Temperature	25°C
Item		Rise and Fall Time	Testing Circuitry	Figure A
Object		+12V32A		


1. Graph

Input Volt. 48 V



2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		9.8	13.5	23.3	0.6	0.4
100 %		10.0	15.8	25.8	0.3	0.2





<b>COSEL</b>																																								
Model	CHS3804812H																																							
Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A																																						
Object	+12V32A																																							
<p>1.Graph</p> <p style="text-align: center;"> <span style="margin-right: 20px;">---□---</span> Load 50%  <span>—△—</span> Load 100%         </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-40</td><td>36.3</td><td>37.0</td></tr> <tr><td>-20</td><td>36.3</td><td>37.1</td></tr> <tr><td>0</td><td>36.4</td><td>37.2</td></tr> <tr><td>25</td><td>36.5</td><td>37.4</td></tr> <tr><td>40</td><td>36.5</td><td>37.5</td></tr> <tr><td>55</td><td>36.6</td><td>37.6</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-40	36.3	37.0	-20	36.3	37.1	0	36.4	37.2	25	36.5	37.4	40	36.5	37.5	55	36.6	37.6	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-40	36.3	37.0																																						
-20	36.3	37.1																																						
0	36.4	37.2																																						
25	36.5	37.4																																						
40	36.5	37.5																																						
55	36.6	37.6																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																								



<p>Model CHS3804812H</p> <p>Item Overcurrent Protection</p> <p>Object +12V32A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure A</p>																																																							
<p>1.Graph</p> <p>                     _____ Input Volt. 36V                      _____ Input Volt. 48V                      _____ Input Volt. 76V                 </p> <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>11.4</td> <td>41.92</td> <td>41.98</td> <td>42.10</td> </tr> <tr> <td>10.8</td> <td>42.08</td> <td>41.93</td> <td>42.21</td> </tr> <tr> <td>9.6</td> <td>42.15</td> <td>41.84</td> <td>42.55</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	11.4	41.92	41.98	42.10	10.8	42.08	41.93	42.21	9.6	42.15	41.84	42.55	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																						
11.4	41.92	41.98	42.10																																																						
10.8	42.08	41.93	42.21																																																						
9.6	42.15	41.84	42.55																																																						
--	-	-	-																																																						
--	-	-	-																																																						
--	-	-	-																																																						
--	-	-	-																																																						
--	-	-	-																																																						
--	-	-	-																																																						
--	-	-	-																																																						
--	-	-	-																																																						
--	-	-	-																																																						



<p>Model CHS3804812H</p>		<p>Testing Circuitry Figure A</p>																																						
<p>Item</p>	<p>Overvoltage Protection</p>																																							
<p>Object</p>	<p>+12V32A</p>																																							
<p>1. Graph</p> <div style="text-align: center;"> <p>—△— Input Volt. 48V</p> <p>---□--- Input Volt. 76V</p> </div> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: right;">Load 0%</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>-40</td><td>15.14</td><td>15.26</td></tr> <tr><td>-20</td><td>15.14</td><td>15.24</td></tr> <tr><td>0</td><td>15.16</td><td>15.24</td></tr> <tr><td>25</td><td>15.16</td><td>15.28</td></tr> <tr><td>40</td><td>15.20</td><td>15.26</td></tr> <tr><td>55</td><td>15.18</td><td>15.24</td></tr> <tr><td>60</td><td>15.18</td><td>15.24</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Operating Point [V]		Input Volt. 48[V]	Input Volt. 76[V]	-40	15.14	15.26	-20	15.14	15.24	0	15.16	15.24	25	15.16	15.28	40	15.20	15.26	55	15.18	15.24	60	15.18	15.24	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Operating Point [V]																																							
	Input Volt. 48[V]	Input Volt. 76[V]																																						
-40	15.14	15.26																																						
-20	15.14	15.24																																						
0	15.16	15.24																																						
25	15.16	15.28																																						
40	15.20	15.26																																						
55	15.18	15.24																																						
60	15.18	15.24																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																								




Figure A

Data Acquisition/Control Unit




Figure B