



TEST DATA OF CHS4004815

Regulated DC Power Supply
January 25, 2019

Approved by : Takayuki Fukuda Design Manager
Takayuki Fukuda

Prepared by : Tatsuya Nakagawa Design Engineer
Tatsuya Nakagawa

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Overvoltage Protection	18
19.Figure of Testing Circuitry	19

(Final Page 19)


COSEL

Model	CHS4004815	Temperature	25°C																																																																															
Item	Input Current (by Input Voltage)	Testing Circuitry	Figure A																																																																															
Object	_____																																																																																	
1.Graph		2.Values																																																																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>16.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>24.0</td><td>0.005</td><td>0.005</td><td>0.005</td></tr> <tr><td>33.0</td><td>0.014</td><td>0.014</td><td>0.014</td></tr> <tr><td>34.4</td><td>0.073</td><td>5.961</td><td>12.124</td></tr> <tr><td>36.0</td><td>0.073</td><td>5.742</td><td>11.727</td></tr> <tr><td>40.0</td><td>0.074</td><td>5.187</td><td>10.504</td></tr> <tr><td>48.0</td><td>0.078</td><td>4.339</td><td>8.760</td></tr> <tr><td>60.0</td><td>0.081</td><td>3.498</td><td>7.000</td></tr> <tr><td>70.0</td><td>0.081</td><td>3.011</td><td>6.019</td></tr> <tr><td>76.0</td><td>0.081</td><td>2.783</td><td>5.566</td></tr> <tr><td>80.0</td><td>0.081</td><td>2.647</td><td>5.276</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	8.0	0.000	0.000	0.000	16.0	0.000	0.000	0.000	24.0	0.005	0.005	0.005	33.0	0.014	0.014	0.014	34.4	0.073	5.961	12.124	36.0	0.073	5.742	11.727	40.0	0.074	5.187	10.504	48.0	0.078	4.339	8.760	60.0	0.081	3.498	7.000	70.0	0.081	3.011	6.019	76.0	0.081	2.783	5.566	80.0	0.081	2.647	5.276	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
8.0	0.000	0.000	0.000																																																																															
16.0	0.000	0.000	0.000																																																																															
24.0	0.005	0.005	0.005																																																																															
33.0	0.014	0.014	0.014																																																																															
34.4	0.073	5.961	12.124																																																																															
36.0	0.073	5.742	11.727																																																																															
40.0	0.074	5.187	10.504																																																																															
48.0	0.078	4.339	8.760																																																																															
60.0	0.081	3.498	7.000																																																																															
70.0	0.081	3.011	6.019																																																																															
76.0	0.081	2.783	5.566																																																																															
80.0	0.081	2.647	5.276																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															

COSEL

Model	CHS4004815																																																					
Item	Input Current (by Load Current)																																																					
Object	<u> </u>																																																					
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> — ▲ — Input Volt. 36V - - ■ - - Input Volt. 48V - · ○ - · Input Volt. 76V <p>Approximate data points from graph:</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>36V [A]</th> <th>48V [A]</th> <th>76V [A]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.073</td><td>0.078</td><td>0.081</td></tr> <tr><td>4.00</td><td>1.768</td><td>1.352</td><td>0.880</td></tr> <tr><td>8.00</td><td>3.482</td><td>2.637</td><td>1.708</td></tr> <tr><td>12.00</td><td>5.212</td><td>3.936</td><td>2.531</td></tr> <tr><td>16.00</td><td>6.976</td><td>5.246</td><td>3.351</td></tr> <tr><td>20.00</td><td>8.748</td><td>6.570</td><td>4.194</td></tr> <tr><td>24.00</td><td>10.560</td><td>7.900</td><td>5.032</td></tr> <tr><td>26.50</td><td>11.727</td><td>8.760</td><td>5.566</td></tr> <tr><td>29.15</td><td>12.952</td><td>9.687</td><td>6.141</td></tr> </tbody> </table>			Load Current [A]	36V [A]	48V [A]	76V [A]	0.00	0.073	0.078	0.081	4.00	1.768	1.352	0.880	8.00	3.482	2.637	1.708	12.00	5.212	3.936	2.531	16.00	6.976	5.246	3.351	20.00	8.748	6.570	4.194	24.00	10.560	7.900	5.032	26.50	11.727	8.760	5.566	29.15	12.952	9.687	6.141											
Load Current [A]	36V [A]	48V [A]	76V [A]																																																			
0.00	0.073	0.078	0.081																																																			
4.00	1.768	1.352	0.880																																																			
8.00	3.482	2.637	1.708																																																			
12.00	5.212	3.936	2.531																																																			
16.00	6.976	5.246	3.351																																																			
20.00	8.748	6.570	4.194																																																			
24.00	10.560	7.900	5.032																																																			
26.50	11.727	8.760	5.566																																																			
29.15	12.952	9.687	6.141																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.073</td><td>0.078</td><td>0.081</td></tr> <tr><td>4.00</td><td>1.768</td><td>1.352</td><td>0.880</td></tr> <tr><td>8.00</td><td>3.482</td><td>2.637</td><td>1.708</td></tr> <tr><td>12.00</td><td>5.212</td><td>3.936</td><td>2.531</td></tr> <tr><td>16.00</td><td>6.976</td><td>5.246</td><td>3.351</td></tr> <tr><td>20.00</td><td>8.748</td><td>6.570</td><td>4.194</td></tr> <tr><td>24.00</td><td>10.560</td><td>7.900</td><td>5.032</td></tr> <tr><td>26.50</td><td>11.727</td><td>8.760</td><td>5.566</td></tr> <tr><td>29.15</td><td>12.952</td><td>9.687</td><td>6.141</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	0.073	0.078	0.081	4.00	1.768	1.352	0.880	8.00	3.482	2.637	1.708	12.00	5.212	3.936	2.531	16.00	6.976	5.246	3.351	20.00	8.748	6.570	4.194	24.00	10.560	7.900	5.032	26.50	11.727	8.760	5.566	29.15	12.952	9.687	6.141	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.00	0.073	0.078	0.081																																																			
4.00	1.768	1.352	0.880																																																			
8.00	3.482	2.637	1.708																																																			
12.00	5.212	3.936	2.531																																																			
16.00	6.976	5.246	3.351																																																			
20.00	8.748	6.570	4.194																																																			
24.00	10.560	7.900	5.032																																																			
26.50	11.727	8.760	5.566																																																			
29.15	12.952	9.687	6.141																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL


Model	CHS4004815																																																					
Item	Input Power (by Load Current)																																																					
Object	<hr/>																																																					
1.Graph	<p style="text-align: center;"> Input Volt. 36V Input Volt. 48V Input Volt. 76V </p>  <p style="text-align: center;">Input Power [W]</p> <p style="text-align: center;">Load Current [A]</p>																																																					
2.Values	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>2.3</td><td>3.2</td><td>5.6</td></tr> <tr> <td>4.00</td><td>63.6</td><td>64.8</td><td>66.9</td></tr> <tr> <td>8.00</td><td>125.3</td><td>126.5</td><td>129.7</td></tr> <tr> <td>12.00</td><td>187.5</td><td>188.5</td><td>192.2</td></tr> <tr> <td>16.00</td><td>250.4</td><td>251.4</td><td>254.6</td></tr> <tr> <td>20.00</td><td>314.4</td><td>315.0</td><td>318.3</td></tr> <tr> <td>24.00</td><td>379.7</td><td>379.2</td><td>382.3</td></tr> <tr> <td>26.50</td><td>421.0</td><td>420.2</td><td>422.7</td></tr> <tr> <td>29.15</td><td>465.8</td><td>464.3</td><td>466.2</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	2.3	3.2	5.6	4.00	63.6	64.8	66.9	8.00	125.3	126.5	129.7	12.00	187.5	188.5	192.2	16.00	250.4	251.4	254.6	20.00	314.4	315.0	318.3	24.00	379.7	379.2	382.3	26.50	421.0	420.2	422.7	29.15	465.8	464.3	466.2	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.00	2.3	3.2	5.6																																																			
4.00	63.6	64.8	66.9																																																			
8.00	125.3	126.5	129.7																																																			
12.00	187.5	188.5	192.2																																																			
16.00	250.4	251.4	254.6																																																			
20.00	314.4	315.0	318.3																																																			
24.00	379.7	379.2	382.3																																																			
26.50	421.0	420.2	422.7																																																			
29.15	465.8	464.3	466.2																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	CHS4004815
Item	Efficiency (by Input Voltage)
Object	_____

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
34	95.9	94.4
36	95.9	94.5
40	95.9	94.6
48	95.5	94.7
55	95.0	94.6
60	94.7	94.4
70	94.1	94.2
76	93.9	94.1
80	93.8	93.9

Note: Slanted line shows the range of the rated input voltage.

COSEL


Model	CHS4004815																																																		
Item	Efficiency (by Load Current)																																																		
Object	<u> </u>																																																		
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 36V Input Volt. 48V Input Volt. 76V <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>36[V] %</th> <th>48[V] %</th> <th>76[V] %</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.00</td><td>94.5</td><td>92.8</td><td>90.0</td></tr> <tr><td>8.00</td><td>95.8</td><td>94.9</td><td>92.5</td></tr> <tr><td>12.00</td><td>96.0</td><td>95.4</td><td>93.6</td></tr> <tr><td>16.00</td><td>95.8</td><td>95.4</td><td>94.2</td></tr> <tr><td>20.00</td><td>95.5</td><td>95.2</td><td>94.3</td></tr> <tr><td>24.00</td><td>94.9</td><td>95.0</td><td>94.2</td></tr> <tr><td>26.50</td><td>94.5</td><td>94.7</td><td>94.1</td></tr> <tr><td>29.15</td><td>93.9</td><td>94.2</td><td>93.8</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	36[V] %	48[V] %	76[V] %	0.00	-	-	-	4.00	94.5	92.8	90.0	8.00	95.8	94.9	92.5	12.00	96.0	95.4	93.6	16.00	95.8	95.4	94.2	20.00	95.5	95.2	94.3	24.00	94.9	95.0	94.2	26.50	94.5	94.7	94.1	29.15	93.9	94.2	93.8	--	-	-	-	--	-	-	-
Load Current [A]	36[V] %	48[V] %	76[V] %																																																
0.00	-	-	-																																																
4.00	94.5	92.8	90.0																																																
8.00	95.8	94.9	92.5																																																
12.00	96.0	95.4	93.6																																																
16.00	95.8	95.4	94.2																																																
20.00	95.5	95.2	94.3																																																
24.00	94.9	95.0	94.2																																																
26.50	94.5	94.7	94.1																																																
29.15	93.9	94.2	93.8																																																
--	-	-	-																																																
--	-	-	-																																																
2.Values																																																			
Note: Slanted line shows the range of the rated load current.																																																			

COSEL

Model	CHS4004815
Item	Line Regulation
Object	+15V26.5A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values


Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
34	14.995	14.994
36	14.995	14.994
40	14.995	14.994
48	14.995	14.994
55	14.995	14.994
60	14.995	14.994
70	14.996	14.995
76	14.996	14.995
80	14.996	14.995

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	CHS4004815																																																					
Item	Load Regulation																																																					
Object	+15V26.5A																																																					
1.Graph	—△— Input Volt. 36V ---□--- Input Volt. 48V —·○— Input Volt. 76V	Temperature 25°C Testing Circuitry Figure A	2.Values																																																			
	<p>Output Voltage [V]</p> <p>Load Current [A]</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>14.995</td><td>14.995</td><td>14.996</td></tr> <tr><td>4.00</td><td>14.995</td><td>14.995</td><td>14.996</td></tr> <tr><td>8.00</td><td>14.995</td><td>14.995</td><td>14.996</td></tr> <tr><td>12.00</td><td>14.995</td><td>14.995</td><td>14.996</td></tr> <tr><td>16.00</td><td>14.995</td><td>14.995</td><td>14.996</td></tr> <tr><td>20.00</td><td>14.994</td><td>14.994</td><td>14.995</td></tr> <tr><td>24.00</td><td>14.994</td><td>14.994</td><td>14.995</td></tr> <tr><td>26.50</td><td>14.994</td><td>14.994</td><td>14.995</td></tr> <tr><td>29.15</td><td>14.994</td><td>14.994</td><td>14.995</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	14.995	14.995	14.996	4.00	14.995	14.995	14.996	8.00	14.995	14.995	14.996	12.00	14.995	14.995	14.996	16.00	14.995	14.995	14.996	20.00	14.994	14.994	14.995	24.00	14.994	14.994	14.995	26.50	14.994	14.994	14.995	29.15	14.994	14.994	14.995	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.00	14.995	14.995	14.996																																																			
4.00	14.995	14.995	14.996																																																			
8.00	14.995	14.995	14.996																																																			
12.00	14.995	14.995	14.996																																																			
16.00	14.995	14.995	14.996																																																			
20.00	14.994	14.994	14.995																																																			
24.00	14.994	14.994	14.995																																																			
26.50	14.994	14.994	14.995																																																			
29.15	14.994	14.994	14.995																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.


COSEL

COSEL

Model	CHS4004815
Item	Ripple Voltage (by Load Current)
Object	+15V26.5A

Temperature 25°C
Testing Circuitry Figure B

1.Graph



2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.00	25	90
4.00	25	90
8.00	25	90
12.00	25	90
16.00	25	90
20.00	25	90
24.00	25	90
26.50	25	90
29.15	25	90
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

COSEL

Model	CHS4004815
Item	Ripple-Noise
Object	+15V26.5A

 Temperature 25°C
 Testing Circuitry Figure B

1.Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.00	45	110
4.00	45	110
8.00	45	115
12.00	45	115
16.00	45	115
20.00	45	115
24.00	45	120
26.50	45	130
29.15	50	145
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

COSEL

Model	CHS4004815
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V26.5A

1. Graph



Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure B

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-50	100	100
-40	90	90
-20	70	70
0	60	60
25	55	55
40	55	55
55	55	55
60	55	55
--	-	-
--	-	-
--	-	-

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

COSEL

Model	CHS4004815
Item	Ambient Temperature Drift
Object	+15V26.5A



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-40	15.026	15.024	15.023
-20	15.010	15.008	15.008
0	14.996	14.997	14.998
25	14.994	14.994	14.995
40	14.991	14.991	14.992
55	14.993	14.994	14.996
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	CHS4004815	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+15V26.5A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 36 - 76V

Load Current : 0 - 26.5A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	-40	36	0	15.027	± 18	± 0.1
Minimum Voltage	40	36	26.5	14.991		


COSEL

Model	CHS4004815	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+15V26.5A																								
1. Graph			2. Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>14.994</td></tr> <tr><td>0.5</td><td>14.994</td></tr> <tr><td>1.0</td><td>14.994</td></tr> <tr><td>2.0</td><td>14.994</td></tr> <tr><td>3.0</td><td>14.994</td></tr> <tr><td>4.0</td><td>14.994</td></tr> <tr><td>5.0</td><td>14.994</td></tr> <tr><td>6.0</td><td>14.994</td></tr> <tr><td>7.0</td><td>14.994</td></tr> <tr><td>8.0</td><td>14.994</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	14.994	0.5	14.994	1.0	14.994	2.0	14.994	3.0	14.994	4.0	14.994	5.0	14.994	6.0	14.994	7.0	14.994	8.0	14.994
Time since start [H]	Output Voltage [V]																								
0.0	14.994																								
0.5	14.994																								
1.0	14.994																								
2.0	14.994																								
3.0	14.994																								
4.0	14.994																								
5.0	14.994																								
6.0	14.994																								
7.0	14.994																								
8.0	14.994																								

COSEL


Model	CHS4004815	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+15V26.5A		

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		9.0	6.3	15.3	0.2	0.4	
100 %		9.0	12.2	21.2	0.2	0.2	




COSEL

Model	CHS4004815
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V26.5A

Testing Circuitry Figure A

1. Graph




2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	32.5	32.3
-20	32.3	32.3
0	32.1	32.5
25	31.9	32.6
40	31.8	32.8
55	31.7	32.8
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	CHS4004815
Item	Overcurrent Protection
Object	+15V26.5A



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2.Values


Output Voltage [V]	Load Current [A]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
14.3	31.02	30.78	29.89
13.5	31.68	31.30	30.31
12.0	32.49	32.21	31.20
10.5	33.20	33.24	32.21
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	CHS4004815
Item	Overvoltage Protection
Object	+15V26.5A

Testing Circuitry Figure A

1. Graph



2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 48[V]	Input Volt. 76[V]
-40	17.94	17.95
-20	17.95	17.96
0	17.99	18.00
25	18.01	18.02
40	18.02	18.03
55	18.04	18.05
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

COSEL




Figure A

Data Acquisition/Control Unit




Figure B