

TEST DATA OF CHS7004812H

Regulated DC Power Supply

March 27, 2018

Approved by : Junichi Hatagishi
Junichi Hatagishi

Design Manager

Prepared by : Sho Saito
Sho Saito

Design Engineer

COSEL CO.,LTD.



CONTENTS


1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Overvoltage Protection	18
19.Figure of Testing Circuitry	19

(Final Page 19)

COSEL

Model	CHS7004812H
Item	Input Current (by Input Voltage)
Object	_____

1.Graph




Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0.0	0.000	0.000	0.000
8.0	0.007	0.008	0.007
16.0	0.009	0.008	0.009
24.0	0.009	0.009	0.012
33.0	0.007	0.008	0.009
35.2	0.112	9.524	18.883
36.0	0.115	9.376	18.875
38.0	0.128	9.374	18.888
40.0	0.125	8.908	18.329
48.0	0.128	7.459	15.252
55.0	0.133	6.529	13.333
60.0	0.138	6.015	12.242
70.0	0.145	5.200	10.514
76.0	0.149	4.807	9.709
80.0	0.151	4.574	9.218
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	CHS7004812H																																																					
Item	Input Current (by Load Current)																																																					
Object	<u> </u>																																																					
1.Graph	—△— Input Volt. 40V - - -□- - Input Volt. 48V - - ○- - Input Volt. 76V																																																					
																																																						
Note: Slanted line shows the range of the rated load current.																																																						
Temperature	25°C																																																					
Testing Circuitry	Figure A																																																					
2.Values																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 40[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>0.125</td> <td>0.128</td> <td>0.149</td> </tr> <tr> <td>8.0</td> <td>2.534</td> <td>2.144</td> <td>1.426</td> </tr> <tr> <td>16.0</td> <td>4.967</td> <td>4.175</td> <td>2.721</td> </tr> <tr> <td>24.0</td> <td>7.431</td> <td>6.224</td> <td>4.019</td> </tr> <tr> <td>32.0</td> <td>9.914</td> <td>8.283</td> <td>5.321</td> </tr> <tr> <td>40.0</td> <td>12.417</td> <td>10.378</td> <td>6.636</td> </tr> <tr> <td>48.0</td> <td>14.971</td> <td>12.482</td> <td>7.961</td> </tr> <tr> <td>56.0</td> <td>17.559</td> <td>14.632</td> <td>9.306</td> </tr> <tr> <td>58.5</td> <td>18.329</td> <td>15.252</td> <td>9.709</td> </tr> <tr> <td>64.3</td> <td>20.310</td> <td>16.911</td> <td>10.735</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Load Current [A]	Input Current [A]			Input Volt. 40[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	0.125	0.128	0.149	8.0	2.534	2.144	1.426	16.0	4.967	4.175	2.721	24.0	7.431	6.224	4.019	32.0	9.914	8.283	5.321	40.0	12.417	10.378	6.636	48.0	14.971	12.482	7.961	56.0	17.559	14.632	9.306	58.5	18.329	15.252	9.709	64.3	20.310	16.911	10.735	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 40[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	0.125	0.128	0.149																																																			
8.0	2.534	2.144	1.426																																																			
16.0	4.967	4.175	2.721																																																			
24.0	7.431	6.224	4.019																																																			
32.0	9.914	8.283	5.321																																																			
40.0	12.417	10.378	6.636																																																			
48.0	14.971	12.482	7.961																																																			
56.0	17.559	14.632	9.306																																																			
58.5	18.329	15.252	9.709																																																			
64.3	20.310	16.911	10.735																																																			
--	-	-	-																																																			

COSEL


Model	CHS7004812H																																																					
Item	Input Power (by Load Current)																																																					
Object	<hr/>																																																					
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 40V Input Volt. 48V Input Volt. 76V <p>Input Power [W]</p> <p>Load Current [A]</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 40[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>5.0</td><td>6.1</td><td>11.3</td></tr> <tr> <td>8.0</td><td>101.3</td><td>102.9</td><td>108.4</td></tr> <tr> <td>16.0</td><td>198.7</td><td>200.4</td><td>206.8</td></tr> <tr> <td>24.0</td><td>297.2</td><td>298.7</td><td>305.4</td></tr> <tr> <td>32.0</td><td>396.5</td><td>397.6</td><td>404.4</td></tr> <tr> <td>40.0</td><td>496.7</td><td>497.5</td><td>503.8</td></tr> <tr> <td>48.0</td><td>598.2</td><td>598.5</td><td>603.7</td></tr> <tr> <td>56.0</td><td>700.1</td><td>699.5</td><td>704.8</td></tr> <tr> <td>58.5</td><td>732.6</td><td>732.1</td><td>737.1</td></tr> <tr> <td>64.3</td><td>808.9</td><td>808.1</td><td>812.3</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 40[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	5.0	6.1	11.3	8.0	101.3	102.9	108.4	16.0	198.7	200.4	206.8	24.0	297.2	298.7	305.4	32.0	396.5	397.6	404.4	40.0	496.7	497.5	503.8	48.0	598.2	598.5	603.7	56.0	700.1	699.5	704.8	58.5	732.6	732.1	737.1	64.3	808.9	808.1	812.3	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 40[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	5.0	6.1	11.3																																																			
8.0	101.3	102.9	108.4																																																			
16.0	198.7	200.4	206.8																																																			
24.0	297.2	298.7	305.4																																																			
32.0	396.5	397.6	404.4																																																			
40.0	496.7	497.5	503.8																																																			
48.0	598.2	598.5	603.7																																																			
56.0	700.1	699.5	704.8																																																			
58.5	732.6	732.1	737.1																																																			
64.3	808.9	808.1	812.3																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	CHS7004812H
Item	Efficiency (by Input Voltage)
Object	_____

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
34	-	-
36	97.0	95.6
40	96.9	95.8
48	96.6	95.9
55	96.2	95.8
60	95.8	95.7
70	95.2	95.4
76	94.8	95.3
80	94.5	95.0

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	CHS7004812H																																																					
Item	Efficiency (by Load Current)																																																					
Object	<hr/>																																																					
1.Graph																																																						
<p style="text-align: center;"> —△— Input Volt. 40V - - □ - - Input Volt. 48V - - ○ - - Input Volt. 76V </p> <p>Efficiency [%]</p> <p>Load Current [A]</p>																																																						
Note: Slanted line shows the range of the rated load current.																																																						
Temperature 25°C Testing Circuitry Figure A																																																						
2.Values																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 40[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>8.0</td> <td>94.7</td> <td>93.3</td> <td>88.6</td> </tr> <tr> <td>16.0</td> <td>96.6</td> <td>95.8</td> <td>92.8</td> </tr> <tr> <td>24.0</td> <td>96.9</td> <td>96.4</td> <td>94.3</td> </tr> <tr> <td>32.0</td> <td>96.8</td> <td>96.6</td> <td>95.0</td> </tr> <tr> <td>40.0</td> <td>96.7</td> <td>96.5</td> <td>95.3</td> </tr> <tr> <td>48.0</td> <td>96.3</td> <td>96.3</td> <td>95.4</td> </tr> <tr> <td>56.0</td> <td>96.0</td> <td>96.1</td> <td>95.3</td> </tr> <tr> <td>58.5</td> <td>95.8</td> <td>95.9</td> <td>95.3</td> </tr> <tr> <td>64.3</td> <td>95.4</td> <td>95.5</td> <td>95.0</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Load Current [A]	Efficiency [%]			Input Volt. 40[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	-	-	-	8.0	94.7	93.3	88.6	16.0	96.6	95.8	92.8	24.0	96.9	96.4	94.3	32.0	96.8	96.6	95.0	40.0	96.7	96.5	95.3	48.0	96.3	96.3	95.4	56.0	96.0	96.1	95.3	58.5	95.8	95.9	95.3	64.3	95.4	95.5	95.0	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 40[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	-	-	-																																																			
8.0	94.7	93.3	88.6																																																			
16.0	96.6	95.8	92.8																																																			
24.0	96.9	96.4	94.3																																																			
32.0	96.8	96.6	95.0																																																			
40.0	96.7	96.5	95.3																																																			
48.0	96.3	96.3	95.4																																																			
56.0	96.0	96.1	95.3																																																			
58.5	95.8	95.9	95.3																																																			
64.3	95.4	95.5	95.0																																																			
--	-	-	-																																																			

COSEL


Model	CHS7004812H	Temperature	25°C																																
Item	Line Regulation	Testing Circuitry	Figure A																																
Object	+12V58.5A																																		
1.Graph		2.Values																																	
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: ---□--- Load 50% —△— Load 100%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>36</td><td>11.371</td><td>11.104</td></tr> <tr><td>38</td><td>12.003</td><td>11.749</td></tr> <tr><td>40</td><td>12.003</td><td>12.002</td></tr> <tr><td>48</td><td>12.003</td><td>12.002</td></tr> <tr><td>55</td><td>12.003</td><td>12.002</td></tr> <tr><td>60</td><td>12.002</td><td>12.002</td></tr> <tr><td>70</td><td>12.002</td><td>12.002</td></tr> <tr><td>76</td><td>12.002</td><td>12.002</td></tr> <tr><td>80</td><td>12.002</td><td>12.002</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	36	11.371	11.104	38	12.003	11.749	40	12.003	12.002	48	12.003	12.002	55	12.003	12.002	60	12.002	12.002	70	12.002	12.002	76	12.002	12.002	80	12.002	12.002
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
36	11.371	11.104																																	
38	12.003	11.749																																	
40	12.003	12.002																																	
48	12.003	12.002																																	
55	12.003	12.002																																	
60	12.002	12.002																																	
70	12.002	12.002																																	
76	12.002	12.002																																	
80	12.002	12.002																																	

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	CHS7004812H																																																					
Item	Load Regulation																																																					
Object	+12V58.5A																																																					
1.Graph	—△— Input Volt. 40V ---□--- Input Volt. 48V —○— Input Volt. 76V	2.Values																																																				
	<p>Output Voltage [V]</p> <p>Load Current [A]</p>	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 40[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.003</td><td>12.003</td><td>12.002</td></tr> <tr><td>8.0</td><td>12.003</td><td>12.003</td><td>12.002</td></tr> <tr><td>16.0</td><td>12.003</td><td>12.003</td><td>12.002</td></tr> <tr><td>24.0</td><td>12.003</td><td>12.003</td><td>12.002</td></tr> <tr><td>32.0</td><td>12.003</td><td>12.003</td><td>12.002</td></tr> <tr><td>40.0</td><td>12.003</td><td>12.003</td><td>12.002</td></tr> <tr><td>48.0</td><td>12.003</td><td>12.002</td><td>12.002</td></tr> <tr><td>56.0</td><td>12.003</td><td>12.002</td><td>12.002</td></tr> <tr><td>58.5</td><td>12.002</td><td>12.002</td><td>12.002</td></tr> <tr><td>64.3</td><td>12.002</td><td>12.002</td><td>12.002</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 40[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	12.003	12.003	12.002	8.0	12.003	12.003	12.002	16.0	12.003	12.003	12.002	24.0	12.003	12.003	12.002	32.0	12.003	12.003	12.002	40.0	12.003	12.003	12.002	48.0	12.003	12.002	12.002	56.0	12.003	12.002	12.002	58.5	12.002	12.002	12.002	64.3	12.002	12.002	12.002	--	-	-	-	
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 40[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	12.003	12.003	12.002																																																			
8.0	12.003	12.003	12.002																																																			
16.0	12.003	12.003	12.002																																																			
24.0	12.003	12.003	12.002																																																			
32.0	12.003	12.003	12.002																																																			
40.0	12.003	12.003	12.002																																																			
48.0	12.003	12.002	12.002																																																			
56.0	12.003	12.002	12.002																																																			
58.5	12.002	12.002	12.002																																																			
64.3	12.002	12.002	12.002																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.


COSEL

COSEL

Model	CHS7004812H
Item	Ripple Voltage (by Load Current)
Object	+12V58.5A

Temperature 25°C
Testing Circuitry Figure B

1.Graph



2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 40 [V]	Input Volt. 76 [V]
0.0	30	110
8.0	30	110
16.0	30	110
24.0	30	110
32.0	30	110
40.0	30	110
48.0	30	110
56.0	30	110
58.5	30	115
64.3	30	115
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

COSEL

Model	CHS7004812H	Temperature	25°C
Item	Ripple-Noise	Testing Circuitry	Figure B
Object	+12V58.5A		

1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 40 [V]	Input Volt. 76 [V]
0.0	40	130
8.0	40	130
16.0	40	130
24.0	40	130
32.0	40	130
40.0	40	130
48.0	40	130
56.0	40	130
58.5	40	135
64.3	40	135
--	-	-





Fig.Complex Ripple Noise Wave Form

COSEL

Model	CHS7004812H
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V58.5A

Testing Circuitry Figure B

1.Graph



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-50	80	80
-40	70	70
-20	60	60
0	60	60
25	60	60
40	60	60
55	70	70
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

COSEL

Model	CHS7004812H
Item	Ambient Temperature Drift
Object	+12V58.5A



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 40[V]	Input Volt. 48[V]	Input Volt. 76[V]
-40	12.018	12.016	12.015
-20	12.008	12.007	12.006
0	12.004	12.003	12.003
25	12.002	12.002	12.002
40	12.002	12.002	12.002
55	12.005	12.006	12.006
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	CHS7004812H	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+12V58.5A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 40 - 76V

Load Current : 0 - 58.5A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	-40	40	0	12.020	± 9	± 0.1
Minimum Voltage	25	76	58.5	12.002		


COSEL

Model	CHS7004812H	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V58.5A																								
1. Graph			2. Values																						
<p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.002</td></tr> <tr><td>0.5</td><td>12.002</td></tr> <tr><td>1.0</td><td>12.002</td></tr> <tr><td>2.0</td><td>12.002</td></tr> <tr><td>3.0</td><td>12.002</td></tr> <tr><td>4.0</td><td>12.002</td></tr> <tr><td>5.0</td><td>12.002</td></tr> <tr><td>6.0</td><td>12.002</td></tr> <tr><td>7.0</td><td>12.002</td></tr> <tr><td>8.0</td><td>12.002</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	12.002	0.5	12.002	1.0	12.002	2.0	12.002	3.0	12.002	4.0	12.002	5.0	12.002	6.0	12.002	7.0	12.002	8.0	12.002
Time since start [H]	Output Voltage [V]																								
0.0	12.002																								
0.5	12.002																								
1.0	12.002																								
2.0	12.002																								
3.0	12.002																								
4.0	12.002																								
5.0	12.002																								
6.0	12.002																								
7.0	12.002																								
8.0	12.002																								

COSEL


Model	CHS7004812H	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+12V58.5A		

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		10.4	11.9	22.3	0.1	0.1	
100 %		10.8	13.5	24.3	0.1	0.1	




COSEL

Model	CHS7004812H
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V58.5A

Testing Circuitry Figure A

1. Graph




2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	35.20	36.50
-20	35.20	36.50
0	35.30	36.70
25	35.30	36.80
40	35.30	37.00
55	35.40	37.10
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	CHS7004812H
Item	Overcurrent Protection
Object	+12V58.5A



Note: Slanted line shows the range of the rated load current.

Intermittent operation occurs when the output voltage is from 12V to 0V.

Temperature 25°C
Testing Circuitry Figure A

2. Values


Output Voltage [V]	Load Current [A]		
	Input Volt. 40[V]	Input Volt. 48[V]	Input Volt. 76[V]
12.0	66.40	66.98	67.06
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	CHS7004812H
Item	Overvoltage Protection
Object	+12V58.5A

Testing Circuitry Figure A

1.Graph




2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 48[V]	Input Volt. 76[V]
-40	14.71	14.79
-20	14.75	14.83
0	14.80	14.89
25	14.89	14.96
40	14.87	14.95
55	14.87	14.93
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

COSEL



Data Acquisition/Control Unit

Figure A




Figure B