

TEST DATA OF CQHS3004832

Regulated DC Power Supply
October 28, 2010

Approved by : Toshiyuki Tsuri
Toshiyuki Tsuri Design Manager

Prepared by : Yutaka Tamura
Yutaka Tamura Design Engineer

COSEL CO.,LTD.



CONTENTS


1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	9
10. Ripple-Noise	10
11. Ripple Voltage (by Ambient Temperature)	11
12. Ambient Temperature Drift	12
13. Output Voltage Accuracy	13
14. Time Lapse Drift	14
15. Rise and Fall Time	15
16. Minimum Input Voltage for Regulated Output Voltage	16
17. Overcurrent Protection	17
18. Overvoltage Protection	18
19. Figure of Testing Circuitry	19

(Final Page 19)

COSEL

Model	CQHS3004832	Temperature 25°C Testing Circuitry Figure A																																																																																	
Item	Input Current (by Input Voltage)																																																																																		
Object	_____	2. Values																																																																																	
1. Graph	Load 100% Load 50% Load 0%																																																																																		
	<p>Input Current [A]</p> <p>Input Voltage [V]</p>																																																																																		
Note:	Slanted line shows the range of the rated input voltage.																																																																																		
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>25.0</td><td>0.010</td><td>0.010</td><td>0.010</td></tr> <tr><td>30.0</td><td>0.006</td><td>0.006</td><td>0.006</td></tr> <tr><td>33.0</td><td>0.007</td><td>0.007</td><td>0.007</td></tr> <tr><td>35.5</td><td>0.149</td><td>4.439</td><td>8.970</td></tr> <tr><td>36.0</td><td>0.146</td><td>4.374</td><td>8.870</td></tr> <tr><td>40.0</td><td>0.109</td><td>3.955</td><td>7.940</td></tr> <tr><td>48.0</td><td>0.109</td><td>3.318</td><td>6.630</td></tr> <tr><td>54.0</td><td>0.109</td><td>2.971</td><td>5.910</td></tr> <tr><td>60.0</td><td>0.108</td><td>2.682</td><td>5.310</td></tr> <tr><td>68.0</td><td>0.106</td><td>2.390</td><td>4.720</td></tr> <tr><td>76.0</td><td>0.104</td><td>2.162</td><td>4.240</td></tr> <tr><td>80.0</td><td>0.103</td><td>2.062</td><td>4.038</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	25.0	0.010	0.010	0.010	30.0	0.006	0.006	0.006	33.0	0.007	0.007	0.007	35.5	0.149	4.439	8.970	36.0	0.146	4.374	8.870	40.0	0.109	3.955	7.940	48.0	0.109	3.318	6.630	54.0	0.109	2.971	5.910	60.0	0.108	2.682	5.310	68.0	0.106	2.390	4.720	76.0	0.104	2.162	4.240	80.0	0.103	2.062	4.038	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																		
	Load 0%	Load 50%	Load 100%																																																																																
0.0	0.000	0.000	0.000																																																																																
25.0	0.010	0.010	0.010																																																																																
30.0	0.006	0.006	0.006																																																																																
33.0	0.007	0.007	0.007																																																																																
35.5	0.149	4.439	8.970																																																																																
36.0	0.146	4.374	8.870																																																																																
40.0	0.109	3.955	7.940																																																																																
48.0	0.109	3.318	6.630																																																																																
54.0	0.109	2.971	5.910																																																																																
60.0	0.108	2.682	5.310																																																																																
68.0	0.106	2.390	4.720																																																																																
76.0	0.104	2.162	4.240																																																																																
80.0	0.103	2.062	4.038																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																

COSEL

Model	CQHS3004832																																																					
Item	Input Current (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object	<hr/>																																																					
1.Graph																																																						
—△— Input Volt. 36V - -□--- Input Volt. 48V - -○--- Input Volt. 76V			2.Values																																																			
																																																						
Note: Slanted line shows the range of the rated load current.																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>0.146</td> <td>0.109</td> <td>0.104</td> </tr> <tr> <td>1.50</td> <td>1.447</td> <td>1.078</td> <td>0.718</td> </tr> <tr> <td>3.00</td> <td>2.800</td> <td>2.120</td> <td>1.366</td> </tr> <tr> <td>4.50</td> <td>4.164</td> <td>3.154</td> <td>2.054</td> </tr> <tr> <td>6.00</td> <td>5.570</td> <td>4.188</td> <td>2.701</td> </tr> <tr> <td>7.50</td> <td>6.960</td> <td>5.250</td> <td>3.363</td> </tr> <tr> <td>9.00</td> <td>8.410</td> <td>6.310</td> <td>4.032</td> </tr> <tr> <td>9.40</td> <td>8.870</td> <td>6.630</td> <td>4.240</td> </tr> <tr> <td>10.34</td> <td>9.720</td> <td>7.270</td> <td>4.640</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Load Current [A]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	0.146	0.109	0.104	1.50	1.447	1.078	0.718	3.00	2.800	2.120	1.366	4.50	4.164	3.154	2.054	6.00	5.570	4.188	2.701	7.50	6.960	5.250	3.363	9.00	8.410	6.310	4.032	9.40	8.870	6.630	4.240	10.34	9.720	7.270	4.640	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.00	0.146	0.109	0.104																																																			
1.50	1.447	1.078	0.718																																																			
3.00	2.800	2.120	1.366																																																			
4.50	4.164	3.154	2.054																																																			
6.00	5.570	4.188	2.701																																																			
7.50	6.960	5.250	3.363																																																			
9.00	8.410	6.310	4.032																																																			
9.40	8.870	6.630	4.240																																																			
10.34	9.720	7.270	4.640																																																			
--	-	-	-																																																			
--	-	-	-																																																			

COSEL

Model	CQHS3004832																																																
Item	Input Power (by Load Current)																																																
Object	<p>1.Graph</p> <p>The graph plots Input Power [W] on the Y-axis (0 to 500) against Load Current [A] on the X-axis (0 to 12). Three data series are shown for different input voltages:</p> <ul style="list-style-type: none"> Input Volt. 36V: Represented by a solid line with open triangle markers. Input Volt. 48V: Represented by a dashed line with open square markers. Input Volt. 76V: Represented by a dash-dot line with open circle markers. <p>A slanted line is drawn through the origin, representing the rated load current range. The data points for each voltage fall exactly on this line.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Power [W] (36V)</th> <th>Input Power [W] (48V)</th> <th>Input Power [W] (76V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5.2</td><td>5.2</td><td>7.9</td></tr> <tr><td>1.50</td><td>51.9</td><td>51.6</td><td>54.4</td></tr> <tr><td>3.00</td><td>100.4</td><td>101.5</td><td>103.6</td></tr> <tr><td>4.50</td><td>149.6</td><td>151.0</td><td>155.6</td></tr> <tr><td>6.00</td><td>199.4</td><td>200.5</td><td>204.9</td></tr> <tr><td>7.50</td><td>250.1</td><td>251.0</td><td>254.7</td></tr> <tr><td>9.00</td><td>301.7</td><td>301.9</td><td>305.5</td></tr> <tr><td>9.40</td><td>315.6</td><td>315.7</td><td>319.2</td></tr> <tr><td>10.34</td><td>349.0</td><td>348.2</td><td>352.0</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Power [W] (36V)	Input Power [W] (48V)	Input Power [W] (76V)	0.00	5.2	5.2	7.9	1.50	51.9	51.6	54.4	3.00	100.4	101.5	103.6	4.50	149.6	151.0	155.6	6.00	199.4	200.5	204.9	7.50	250.1	251.0	254.7	9.00	301.7	301.9	305.5	9.40	315.6	315.7	319.2	10.34	349.0	348.2	352.0	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W] (36V)	Input Power [W] (48V)	Input Power [W] (76V)																																														
0.00	5.2	5.2	7.9																																														
1.50	51.9	51.6	54.4																																														
3.00	100.4	101.5	103.6																																														
4.50	149.6	151.0	155.6																																														
6.00	199.4	200.5	204.9																																														
7.50	250.1	251.0	254.7																																														
9.00	301.7	301.9	305.5																																														
9.40	315.6	315.7	319.2																																														
10.34	349.0	348.2	352.0																																														
--	-	-	-																																														
--	-	-	-																																														

Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Input Power [W]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
0.00	5.2	5.2	7.9
1.50	51.9	51.6	54.4
3.00	100.4	101.5	103.6
4.50	149.6	151.0	155.6
6.00	199.4	200.5	204.9
7.50	250.1	251.0	254.7
9.00	301.7	301.9	305.5
9.40	315.6	315.7	319.2
10.34	349.0	348.2	352.0
--	-	-	-
--	-	-	-


Note: Slanted line shows the range of the rated load current.

COSEL

Model	CQHS3004832
Item	Efficiency (by Input Voltage)
Object	_____

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
35.5	95.1	94.4
36.0	95.1	94.5
40.0	94.9	94.5
48.0	94.2	94.5
55.0	93.8	94.3
60.0	93.3	94.2
70.0	92.3	93.8
76.0	91.5	93.4
80.0	91.2	93.3

Note: Slanted line shows the range of the rated input voltage.

COSEL


Model	CQHS3004832	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Efficiency (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 36V Input Volt. 48V Input Volt. 76V 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>1.50</td><td>89.8</td><td>90.4</td><td>85.8</td></tr> <tr> <td>3.00</td><td>94.0</td><td>93.0</td><td>91.2</td></tr> <tr> <td>4.50</td><td>95.0</td><td>94.1</td><td>91.4</td></tr> <tr> <td>6.00</td><td>95.2</td><td>94.7</td><td>92.7</td></tr> <tr> <td>7.50</td><td>95.0</td><td>94.7</td><td>93.3</td></tr> <tr> <td>9.00</td><td>94.6</td><td>94.6</td><td>93.5</td></tr> <tr> <td>9.40</td><td>94.5</td><td>94.5</td><td>93.4</td></tr> <tr> <td>10.34</td><td>94.0</td><td>94.3</td><td>93.3</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	-	-	-	1.50	89.8	90.4	85.8	3.00	94.0	93.0	91.2	4.50	95.0	94.1	91.4	6.00	95.2	94.7	92.7	7.50	95.0	94.7	93.3	9.00	94.6	94.6	93.5	9.40	94.5	94.5	93.4	10.34	94.0	94.3	93.3	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.00	-	-	-																																																			
1.50	89.8	90.4	85.8																																																			
3.00	94.0	93.0	91.2																																																			
4.50	95.0	94.1	91.4																																																			
6.00	95.2	94.7	92.7																																																			
7.50	95.0	94.7	93.3																																																			
9.00	94.6	94.6	93.5																																																			
9.40	94.5	94.5	93.4																																																			
10.34	94.0	94.3	93.3																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	CQHS3004832
Item	Line Regulation
Object	+32V9.4A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
35.5	31.950	31.949
36.0	31.947	31.951
40.0	31.947	31.953
48.0	31.948	31.954
55.0	31.949	31.955
60.0	31.950	31.957
70.0	31.952	31.959
76.0	31.953	31.960
80.0	31.954	31.961

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	CQHS3004832
Item	Load Regulation
Object	+32V9.4A

1. Graph

Load Current [A]	Input Volt. 36V	Input Volt. 48V	Input Volt. 76V
------------------	-----------------	-----------------	-----------------


Load Current [A]	Output Voltage [V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
0.00	31.959	31.954	31.957	
1.50	31.956	31.951	31.956	
3.00	31.953	31.950	31.956	
4.50	31.951	31.950	31.956	
6.00	31.950	31.950	31.956	
7.50	31.950	31.951	31.958	
9.00	31.951	31.953	31.959	
9.40	31.951	31.954	31.960	
10.34	31.954	31.956	31.961	
--	-	-	-	
--	-	-	-	

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
0.00	31.959	31.954	31.957
1.50	31.956	31.951	31.956
3.00	31.953	31.950	31.956
4.50	31.951	31.950	31.956
6.00	31.950	31.950	31.956
7.50	31.950	31.951	31.958
9.00	31.951	31.953	31.959
9.40	31.951	31.954	31.960
10.34	31.954	31.956	31.961
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

COSEL

COSEL

Model	CQHS3004832																																						
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																					
Object	+32V9.4A																																						
1. Graph																																							
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 600 mV, and the X-axis ranges from 0 to 12 A. Two sets of data points are plotted: solid triangles for 36V and dashed circles for 76V. A slanted line indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input Volt. 36V)</th> <th>Ripple Voltage [mV] (Input Volt. 76V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>52</td><td>148</td></tr> <tr><td>1.50</td><td>55</td><td>142</td></tr> <tr><td>3.00</td><td>62</td><td>138</td></tr> <tr><td>4.50</td><td>67</td><td>135</td></tr> <tr><td>6.00</td><td>73</td><td>135</td></tr> <tr><td>7.50</td><td>79</td><td>142</td></tr> <tr><td>9.40</td><td>93</td><td>149</td></tr> <tr><td>10.34</td><td>94</td><td>159</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV] (Input Volt. 36V)	Ripple Voltage [mV] (Input Volt. 76V)	0.00	52	148	1.50	55	142	3.00	62	138	4.50	67	135	6.00	73	135	7.50	79	142	9.40	93	149	10.34	94	159	--	-	-	--	-	-	--	-	-		
Load Current [A]	Ripple Voltage [mV] (Input Volt. 36V)	Ripple Voltage [mV] (Input Volt. 76V)																																					
0.00	52	148																																					
1.50	55	142																																					
3.00	62	138																																					
4.50	67	135																																					
6.00	73	135																																					
7.50	79	142																																					
9.40	93	149																																					
10.34	94	159																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
2. Values																																							
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 36 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>52</td><td>148</td></tr> <tr><td>1.50</td><td>55</td><td>142</td></tr> <tr><td>3.00</td><td>62</td><td>138</td></tr> <tr><td>4.50</td><td>67</td><td>135</td></tr> <tr><td>6.00</td><td>73</td><td>135</td></tr> <tr><td>7.50</td><td>79</td><td>142</td></tr> <tr><td>9.40</td><td>93</td><td>149</td></tr> <tr><td>10.34</td><td>94</td><td>159</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.00	52	148	1.50	55	142	3.00	62	138	4.50	67	135	6.00	73	135	7.50	79	142	9.40	93	149	10.34	94	159	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																						
	Input Volt. 36 [V]	Input Volt. 76 [V]																																					
0.00	52	148																																					
1.50	55	142																																					
3.00	62	138																																					
4.50	67	135																																					
6.00	73	135																																					
7.50	79	142																																					
9.40	93	149																																					
10.34	94	159																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple [mVp-p]</p> <p>Fig. Complex Ripple Wave Form</p>																																							

COSEL

Model	CQHS3004832																																							
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure B																																						
Object	+32V9.4A																																							
1. Graph																																								
		2. Values																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 36 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>62</td><td>148</td></tr> <tr> <td>1.50</td><td>64</td><td>142</td></tr> <tr> <td>3.00</td><td>74</td><td>138</td></tr> <tr> <td>4.50</td><td>84</td><td>148</td></tr> <tr> <td>6.00</td><td>96</td><td>148</td></tr> <tr> <td>7.50</td><td>114</td><td>162</td></tr> <tr> <td>9.40</td><td>148</td><td>180</td></tr> <tr> <td>10.34</td><td>160</td><td>194</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.00	62	148	1.50	64	142	3.00	74	138	4.50	84	148	6.00	96	148	7.50	114	162	9.40	148	180	10.34	160	194	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 36 [V]	Input Volt. 76 [V]																																						
0.00	62	148																																						
1.50	64	142																																						
3.00	74	138																																						
4.50	84	148																																						
6.00	96	148																																						
7.50	114	162																																						
9.40	148	180																																						
10.34	160	194																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Fig.Complex Ripple Noise Wave Form</p>																																								


COSEL

Model CQHS3004832

Item Ripple Voltage (by Ambient Temp.)

Object +32V9.4A

1. Graph



Testing Circuitry Figure B

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-50	172	246
-40	156	222
-20	128	178
0	118	158
25	114	150
40	108	140
60	100	121
85	86	116
100	86	113
105	82	111
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	CQHS3004832	Testing Circuitry Figure A																																																					
Item	Ambient Temperature Drift																																																						
Object	+32V9.4A																																																						
1.Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <ul style="list-style-type: none"> — △ — Input Volt. 36V - - □ - - Input Volt. 48V - - ○ - - Input Volt. 76V 																																																						
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>-50</td><td>31.629</td><td>31.633</td><td>31.641</td></tr> <tr> <td>-40</td><td>31.684</td><td>31.690</td><td>31.697</td></tr> <tr> <td>-20</td><td>31.791</td><td>31.795</td><td>31.801</td></tr> <tr> <td>0</td><td>31.878</td><td>31.881</td><td>31.885</td></tr> <tr> <td>25</td><td>31.951</td><td>31.954</td><td>31.960</td></tr> <tr> <td>40</td><td>31.981</td><td>31.983</td><td>31.986</td></tr> <tr> <td>60</td><td>32.013</td><td>32.015</td><td>32.017</td></tr> <tr> <td>85</td><td>32.041</td><td>32.043</td><td>32.044</td></tr> <tr> <td>100</td><td>32.050</td><td>32.051</td><td>32.053</td></tr> <tr> <td>105</td><td>32.052</td><td>32.053</td><td>32.056</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	-50	31.629	31.633	31.641	-40	31.684	31.690	31.697	-20	31.791	31.795	31.801	0	31.878	31.881	31.885	25	31.951	31.954	31.960	40	31.981	31.983	31.986	60	32.013	32.015	32.017	85	32.041	32.043	32.044	100	32.050	32.051	32.053	105	32.052	32.053	32.056	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																				
-50	31.629	31.633	31.641																																																				
-40	31.684	31.690	31.697																																																				
-20	31.791	31.795	31.801																																																				
0	31.878	31.881	31.885																																																				
25	31.951	31.954	31.960																																																				
40	31.981	31.983	31.986																																																				
60	32.013	32.015	32.017																																																				
85	32.041	32.043	32.044																																																				
100	32.050	32.051	32.053																																																				
105	32.052	32.053	32.056																																																				
--	-	-	-																																																				
Note:	Slanted line shows the range of the rated ambient temperature.																																																						



Model	CQHS3004832	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+32V9.4A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 100°C

Input Voltage : 36 - 76V

Load Current : 0 - 9.4A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	100	76	9.4	32.053	±186	±0.6
Minimum Voltage	-40	48	0	31.682		

COSEL

Model	CQHS3004832	Temperature Testing Circuitry 25°C Figure A																						
Item	Time Lapse Drift																							
Object	+32V9.4A																							
1.Graph		2.Values																						
<p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V</p> <p>Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>31.934</td></tr> <tr><td>0.5</td><td>31.957</td></tr> <tr><td>1.0</td><td>31.957</td></tr> <tr><td>2.0</td><td>31.957</td></tr> <tr><td>3.0</td><td>31.957</td></tr> <tr><td>4.0</td><td>31.957</td></tr> <tr><td>5.0</td><td>31.957</td></tr> <tr><td>6.0</td><td>31.957</td></tr> <tr><td>7.0</td><td>31.957</td></tr> <tr><td>8.0</td><td>31.957</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	31.934	0.5	31.957	1.0	31.957	2.0	31.957	3.0	31.957	4.0	31.957	5.0	31.957	6.0	31.957	7.0	31.957	8.0	31.957
Time since start [H]	Output Voltage [V]																							
0.0	31.934																							
0.5	31.957																							
1.0	31.957																							
2.0	31.957																							
3.0	31.957																							
4.0	31.957																							
5.0	31.957																							
6.0	31.957																							
7.0	31.957																							
8.0	31.957																							

COSEL


Model CQHS3004832

Item Rise and Fall Time

Object +32V9.4A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		113.5	6.3	119.8	0.8	15.5	
100 %		113.5	6.8	120.3	0.4	7.7	



COSEL


Model CQHS3004832

Item Minimum Input Voltage
for Regulated Output Voltage

Object +32V9.4A

1. Graph

---□--- Load 50%
—△— Load 100%



Note: Slanted line shows the range of the rated ambient temperature.


Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-50	32.7	33.3
-40	32.8	33.3
-20	32.7	33.3
0	32.7	33.5
25	32.9	33.6
40	32.8	33.7
60	32.9	33.9
85	33.0	33.9
100	33.0	34.1
105	33.0	33.9
--	-	-

COSEL

Model	CQHS3004832
Item	Overcurrent Protection
Object	+32V9.4A



Note: Slanted line shows the range of the rated load current.

When the output voltage fell to less than 27.2V ,the unit shuts off the output by operating low voltage protection .

Temperature 25°C
Testing Circuitry Figure A


2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
30.4	10.65	10.64	10.79
28.8	10.50	10.67	10.95
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	CQHS3004832
Item	Oversupply Protection
Object	+32V9.4A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 48[V]	Input Volt. 76[V]
-50	38.04	37.98
-40	38.20	38.06
-20	38.50	38.22
0	38.72	38.58
25	38.72	38.50
40	38.84	38.19
60	38.69	38.47
85	38.52	38.30
100	38.64	38.50
105	38.77	38.49
--	-	-

COSEL




Figure A


**Ci** : 100V 68 μ F ×2**Cy** : 4700pF**C1** : 100V 0.1 μ F**Co** : 50V 470 μ F**Cout** : 50V 470 μ F ×2 ($-40^{\circ}\text{C} \leq T_B \leq 0^{\circ}\text{C}$): 50V 470 μ F ($0^{\circ}\text{C} < T_B \leq 100^{\circ}\text{C}$)**T_B** : Base Plate Temp.**R=50Ω****C=0.01 μ F**

Figure B (Ripple and Ripple noise Characteristic)