

TEST DATA OF CQHS3504832

Regulated DC Power Supply
August 6, 2013

Approved by: Yoshimichi Hirokawa
Yoshimichi Hirokawa Design Manager

Prepared by: Masahiro Kondo
Masahiro Kondo Design Engineer

COSEL CO.,LTD.




CONTENTS


1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Overvoltage Protection	18
19.Figure of Testing Circuitry	19

(Final Page 19)

COSEL

Model	CQHS3504832																																																																																	
Item	Input Current (by Input Voltage)	Temperature 25°C	Testing Circuitry Figure A																																																																															
Object	_____																																																																																	
1.Graph		—△— Load 100% - -□--- Load 50% - -○--- Load 0%																																																																																
			2.Values																																																																															
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>25.0</td><td>0.012</td><td>0.012</td><td>0.012</td></tr> <tr><td>30.0</td><td>0.009</td><td>0.009</td><td>0.008</td></tr> <tr><td>33.0</td><td>0.009</td><td>0.009</td><td>0.009</td></tr> <tr><td>35.5</td><td>0.235</td><td>5.230</td><td>10.540</td></tr> <tr><td>36.0</td><td>0.233</td><td>5.160</td><td>10.410</td></tr> <tr><td>40.0</td><td>0.142</td><td>4.620</td><td>9.340</td></tr> <tr><td>48.0</td><td>0.135</td><td>3.878</td><td>7.780</td></tr> <tr><td>54.0</td><td>0.133</td><td>3.462</td><td>6.920</td></tr> <tr><td>60.0</td><td>0.131</td><td>3.130</td><td>6.240</td></tr> <tr><td>65.0</td><td>0.130</td><td>2.905</td><td>5.770</td></tr> <tr><td>68.0</td><td>0.129</td><td>2.792</td><td>5.530</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	25.0	0.012	0.012	0.012	30.0	0.009	0.009	0.008	33.0	0.009	0.009	0.009	35.5	0.235	5.230	10.540	36.0	0.233	5.160	10.410	40.0	0.142	4.620	9.340	48.0	0.135	3.878	7.780	54.0	0.133	3.462	6.920	60.0	0.131	3.130	6.240	65.0	0.130	2.905	5.770	68.0	0.129	2.792	5.530	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
25.0	0.012	0.012	0.012																																																																															
30.0	0.009	0.009	0.008																																																																															
33.0	0.009	0.009	0.009																																																																															
35.5	0.235	5.230	10.540																																																																															
36.0	0.233	5.160	10.410																																																																															
40.0	0.142	4.620	9.340																																																																															
48.0	0.135	3.878	7.780																																																																															
54.0	0.133	3.462	6.920																																																																															
60.0	0.131	3.130	6.240																																																																															
65.0	0.130	2.905	5.770																																																																															
68.0	0.129	2.792	5.530																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
Note: Slanted line shows the range of the rated input voltage.																																																																																		

COSEL

Model	CQHS3504832																																																					
Item	Input Current (by Load Current)																																																					
Object	_____																																																					
1.Graph	—△— Input Volt. 36V - - □- - Input Volt. 48V - - ○- - Input Volt. 65V																																																					
																																																						
Note: Slanted line shows the range of the rated load current.																																																						
Temperature 25°C Testing Circuitry Figure A																																																						
2.Values																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 65[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>0.232</td> <td>0.135</td> <td>0.129</td> </tr> <tr> <td>2.0</td> <td>2.008</td> <td>1.470</td> <td>1.106</td> </tr> <tr> <td>4.0</td> <td>3.806</td> <td>2.863</td> <td>2.152</td> </tr> <tr> <td>6.0</td> <td>5.660</td> <td>4.236</td> <td>3.172</td> </tr> <tr> <td>8.0</td> <td>7.520</td> <td>5.640</td> <td>4.196</td> </tr> <tr> <td>10.0</td> <td>9.460</td> <td>7.060</td> <td>5.240</td> </tr> <tr> <td>11.0</td> <td>10.440</td> <td>7.790</td> <td>5.780</td> </tr> <tr> <td>11.9</td> <td>11.330</td> <td>8.450</td> <td>6.260</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Load Current [A]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 65[V]	0.0	0.232	0.135	0.129	2.0	2.008	1.470	1.106	4.0	3.806	2.863	2.152	6.0	5.660	4.236	3.172	8.0	7.520	5.640	4.196	10.0	9.460	7.060	5.240	11.0	10.440	7.790	5.780	11.9	11.330	8.450	6.260	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 65[V]																																																			
0.0	0.232	0.135	0.129																																																			
2.0	2.008	1.470	1.106																																																			
4.0	3.806	2.863	2.152																																																			
6.0	5.660	4.236	3.172																																																			
8.0	7.520	5.640	4.196																																																			
10.0	9.460	7.060	5.240																																																			
11.0	10.440	7.790	5.780																																																			
11.9	11.330	8.450	6.260																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			


COSEL

Model	CQHS3504832																																																					
Item	Input Power (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 36V Input Volt. 48V Input Volt. 65V <p>Approximate data points from graph:</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Power [W] (36V)</th> <th>Input Power [W] (48V)</th> <th>Input Power [W] (65V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>8.3</td><td>6.5</td><td>8.4</td></tr> <tr><td>2.0</td><td>72.0</td><td>70.3</td><td>71.8</td></tr> <tr><td>4.0</td><td>136.7</td><td>137.0</td><td>139.7</td></tr> <tr><td>6.0</td><td>202.8</td><td>203.2</td><td>205.9</td></tr> <tr><td>8.0</td><td>270.0</td><td>270.2</td><td>272.5</td></tr> <tr><td>10.0</td><td>339.0</td><td>338.6</td><td>340.6</td></tr> <tr><td>11.0</td><td>374.0</td><td>373.2</td><td>375.1</td></tr> <tr><td>11.9</td><td>407.0</td><td>404.9</td><td>406.3</td></tr> </tbody> </table>			Load Current [A]	Input Power [W] (36V)	Input Power [W] (48V)	Input Power [W] (65V)	0.0	8.3	6.5	8.4	2.0	72.0	70.3	71.8	4.0	136.7	137.0	139.7	6.0	202.8	203.2	205.9	8.0	270.0	270.2	272.5	10.0	339.0	338.6	340.6	11.0	374.0	373.2	375.1	11.9	407.0	404.9	406.3															
Load Current [A]	Input Power [W] (36V)	Input Power [W] (48V)	Input Power [W] (65V)																																																			
0.0	8.3	6.5	8.4																																																			
2.0	72.0	70.3	71.8																																																			
4.0	136.7	137.0	139.7																																																			
6.0	202.8	203.2	205.9																																																			
8.0	270.0	270.2	272.5																																																			
10.0	339.0	338.6	340.6																																																			
11.0	374.0	373.2	375.1																																																			
11.9	407.0	404.9	406.3																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 65[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>8.3</td><td>6.5</td><td>8.4</td></tr> <tr><td>2.0</td><td>72.0</td><td>70.3</td><td>71.8</td></tr> <tr><td>4.0</td><td>136.7</td><td>137.0</td><td>139.7</td></tr> <tr><td>6.0</td><td>202.8</td><td>203.2</td><td>205.9</td></tr> <tr><td>8.0</td><td>270.0</td><td>270.2</td><td>272.5</td></tr> <tr><td>10.0</td><td>339.0</td><td>338.6</td><td>340.6</td></tr> <tr><td>11.0</td><td>374.0</td><td>373.2</td><td>375.1</td></tr> <tr><td>11.9</td><td>407.0</td><td>404.9</td><td>406.3</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 65[V]	0.0	8.3	6.5	8.4	2.0	72.0	70.3	71.8	4.0	136.7	137.0	139.7	6.0	202.8	203.2	205.9	8.0	270.0	270.2	272.5	10.0	339.0	338.6	340.6	11.0	374.0	373.2	375.1	11.9	407.0	404.9	406.3	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 65[V]																																																			
0.0	8.3	6.5	8.4																																																			
2.0	72.0	70.3	71.8																																																			
4.0	136.7	137.0	139.7																																																			
6.0	202.8	203.2	205.9																																																			
8.0	270.0	270.2	272.5																																																			
10.0	339.0	338.6	340.6																																																			
11.0	374.0	373.2	375.1																																																			
11.9	407.0	404.9	406.3																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	CQHS3504832	Temperature	25°C																																
Item	Efficiency (by Input Voltage)	Testing Circuitry	Figure A																																
Object	_____																																		
1.Graph		2.Values																																	
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend:</p> <ul style="list-style-type: none"> --□-- Load 50% —△— Load 100% 		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>35.5</td> <td>94.7</td> <td>93.8</td> </tr> <tr> <td>36.0</td> <td>94.7</td> <td>94.0</td> </tr> <tr> <td>42.0</td> <td>95.0</td> <td>94.2</td> </tr> <tr> <td>48.0</td> <td>94.5</td> <td>94.2</td> </tr> <tr> <td>54.0</td> <td>94.1</td> <td>94.1</td> </tr> <tr> <td>60.0</td> <td>93.6</td> <td>93.9</td> </tr> <tr> <td>65.0</td> <td>93.1</td> <td>93.8</td> </tr> <tr> <td>68.0</td> <td>92.8</td> <td>93.6</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	35.5	94.7	93.8	36.0	94.7	94.0	42.0	95.0	94.2	48.0	94.5	94.2	54.0	94.1	94.1	60.0	93.6	93.9	65.0	93.1	93.8	68.0	92.8	93.6	--	-	-
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
35.5	94.7	93.8																																	
36.0	94.7	94.0																																	
42.0	95.0	94.2																																	
48.0	94.5	94.2																																	
54.0	94.1	94.1																																	
60.0	93.6	93.9																																	
65.0	93.1	93.8																																	
68.0	92.8	93.6																																	
--	-	-																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			

COSEL

Model	CQHS3504832	Temperature	25°C																																																		
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																		
Object	<hr/>																																																				
1.Graph	—△— Input Volt. 36V - - □--- Input Volt. 48V - - ○--- Input Volt. 65V																																																				
			2.Values																																																		
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 65[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>2.0</td> <td>89.4</td> <td>91.7</td> <td>89.8</td> </tr> <tr> <td>4.0</td> <td>93.8</td> <td>93.6</td> <td>91.9</td> </tr> <tr> <td>6.0</td> <td>94.8</td> <td>94.6</td> <td>93.3</td> </tr> <tr> <td>8.0</td> <td>94.8</td> <td>94.7</td> <td>93.9</td> </tr> <tr> <td>10.0</td> <td>94.3</td> <td>94.5</td> <td>93.9</td> </tr> <tr> <td>11.0</td> <td>94.0</td> <td>94.2</td> <td>93.8</td> </tr> <tr> <td>11.9</td> <td>93.5</td> <td>94.0</td> <td>93.6</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 65[V]	0.0	-	-	-	2.0	89.4	91.7	89.8	4.0	93.8	93.6	91.9	6.0	94.8	94.6	93.3	8.0	94.8	94.7	93.9	10.0	94.3	94.5	93.9	11.0	94.0	94.2	93.8	11.9	93.5	94.0	93.6	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																				
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 65[V]																																																		
0.0	-	-	-																																																		
2.0	89.4	91.7	89.8																																																		
4.0	93.8	93.6	91.9																																																		
6.0	94.8	94.6	93.3																																																		
8.0	94.8	94.7	93.9																																																		
10.0	94.3	94.5	93.9																																																		
11.0	94.0	94.2	93.8																																																		
11.9	93.5	94.0	93.6																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
Note: Slanted line shows the range of the rated load current.																																																					

COSEL


Model	CQHS3504832	Temperature	25°C																																
Item	Line Regulation	Testing Circuitry	Figure A																																
Object	+32V11A																																		
1.Graph			2.Values																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>35.5</td><td>32.008</td><td>32.015</td></tr> <tr><td>36.0</td><td>32.008</td><td>32.015</td></tr> <tr><td>42.0</td><td>32.008</td><td>32.015</td></tr> <tr><td>48.0</td><td>32.008</td><td>32.016</td></tr> <tr><td>54.0</td><td>32.009</td><td>32.016</td></tr> <tr><td>60.0</td><td>32.009</td><td>32.017</td></tr> <tr><td>65.0</td><td>32.010</td><td>32.017</td></tr> <tr><td>68.0</td><td>32.011</td><td>32.017</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	35.5	32.008	32.015	36.0	32.008	32.015	42.0	32.008	32.015	48.0	32.008	32.016	54.0	32.009	32.016	60.0	32.009	32.017	65.0	32.010	32.017	68.0	32.011	32.017	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
35.5	32.008	32.015																																	
36.0	32.008	32.015																																	
42.0	32.008	32.015																																	
48.0	32.008	32.016																																	
54.0	32.009	32.016																																	
60.0	32.009	32.017																																	
65.0	32.010	32.017																																	
68.0	32.011	32.017																																	
--	-	-																																	

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	CQHS3504832	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+32V11A																																																					
1.Graph		2.Values																																																				
<p>The graph plots Output Voltage [V] on the Y-axis (31.60 to 32.30) against Load Current [A] on the X-axis (0 to 12). Three horizontal lines represent Input Voltages: 36V (solid line with open triangle), 48V (dashed line with open square), and 65V (dash-dot line with open circle). All three lines show a constant output voltage of 32.0V until a load current of about 10.5A, after which the output voltage drops sharply. A slanted line on the right side of the graph indicates the rated load current range.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 65[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>32.017</td><td>32.016</td><td>32.017</td></tr> <tr> <td>2.0</td><td>32.016</td><td>32.016</td><td>32.016</td></tr> <tr> <td>4.0</td><td>32.016</td><td>32.015</td><td>32.015</td></tr> <tr> <td>6.0</td><td>32.015</td><td>32.014</td><td>32.016</td></tr> <tr> <td>8.0</td><td>32.014</td><td>32.014</td><td>32.015</td></tr> <tr> <td>10.0</td><td>32.014</td><td>32.014</td><td>32.015</td></tr> <tr> <td>11.0</td><td>32.015</td><td>32.016</td><td>32.016</td></tr> <tr> <td>11.9</td><td>32.015</td><td>32.016</td><td>32.016</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 65[V]	0.0	32.017	32.016	32.017	2.0	32.016	32.016	32.016	4.0	32.016	32.015	32.015	6.0	32.015	32.014	32.016	8.0	32.014	32.014	32.015	10.0	32.014	32.014	32.015	11.0	32.015	32.016	32.016	11.9	32.015	32.016	32.016	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 65[V]																																																			
0.0	32.017	32.016	32.017																																																			
2.0	32.016	32.016	32.016																																																			
4.0	32.016	32.015	32.015																																																			
6.0	32.015	32.014	32.016																																																			
8.0	32.014	32.014	32.015																																																			
10.0	32.014	32.014	32.015																																																			
11.0	32.015	32.016	32.016																																																			
11.9	32.015	32.016	32.016																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL




COSEL

Model	CQHS3504832
Item	Ripple Voltage (by Load Current)
Object	+32V11A

Temperature 25°C
Testing Circuitry Figure B

1.Graph



2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 36 [V]	Input Volt. 65 [V]
0.0	72	128
2.0	72	128
4.0	74	128
6.0	92	130
8.0	110	140
10.0	112	152
11.0	142	154
11.9	132	160
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

COSEL

Model	CQHS3504832
Item	Ripple-Noise
Object	+32V11A

Temperature 25°C
Testing Circuitry Figure B

1.Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.
load current.

2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 65 [V]
0.0	88	128
2.0	88	128
4.0	92	128
6.0	108	140
8.0	124	164
10.0	152	180
11.0	188	200
11.9	204	208
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

COSEL

Model	CQHS3504832
Item	Ripple Voltage (by Ambient Temp.)
Object	+32V11A

Testing Circuitry Figure B

1. Graph



2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-50	176	272
-40	180	244
-20	152	212
0	120	168
25	112	140
40	104	124
60	100	142
85	104	148
100	100	142
105	100	142
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.





Fig.Complex Ripple Noise Wave Form

COSEL

Model	CQHS3504832
Item	Ambient Temperature Drift
Object	+32V11A



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 65[V]
-50	31.816	31.824	31.831
-40	31.861	31.868	31.875
-20	31.933	31.937	31.943
0	31.982	31.985	31.989
25	32.017	32.018	32.020
40	32.025	32.026	32.026
60	32.025	32.024	32.024
85	32.010	32.008	32.008
100	31.994	31.993	31.994
105	31.990	31.989	31.990
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	CQHS3504832	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+32V11A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 100°C

Input Voltage : 36 - 65V

Load Current : 0 - 11A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	60	65	0	32.027	±85	±0.3
Minimum Voltage	-40	65	0	31.858		

COSEL


Model	CQHS3504832	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+32V11A																								
1. Graph			2. Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>32.000</td></tr> <tr><td>0.5</td><td>32.017</td></tr> <tr><td>1.0</td><td>32.017</td></tr> <tr><td>2.0</td><td>32.017</td></tr> <tr><td>3.0</td><td>32.017</td></tr> <tr><td>4.0</td><td>32.017</td></tr> <tr><td>5.0</td><td>32.017</td></tr> <tr><td>6.0</td><td>32.017</td></tr> <tr><td>7.0</td><td>32.017</td></tr> <tr><td>8.0</td><td>32.017</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	32.000	0.5	32.017	1.0	32.017	2.0	32.017	3.0	32.017	4.0	32.017	5.0	32.017	6.0	32.017	7.0	32.017	8.0	32.017
Time since start [H]	Output Voltage [V]																								
0.0	32.000																								
0.5	32.017																								
1.0	32.017																								
2.0	32.017																								
3.0	32.017																								
4.0	32.017																								
5.0	32.017																								
6.0	32.017																								
7.0	32.017																								
8.0	32.017																								

COSEL

Model	CQHS3504832
Item	Rise and Fall Time
Object	+32V11A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		113.8	6.8	120.6	1.3	19.9	
100 %		113.8	7.5	121.3	0.7	9.9	



COSEL

Model	CQHS3504832	Testing Circuitry Figure A																																							
Item	Minimum Input Voltage for Regulated Output Voltage																																								
Object	+32V11A																																								
1. Graph			2. Values																																						
			<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-50</td><td>32.7</td><td>33.2</td></tr> <tr><td>-40</td><td>32.7</td><td>33.3</td></tr> <tr><td>-20</td><td>32.9</td><td>33.5</td></tr> <tr><td>0</td><td>32.8</td><td>33.5</td></tr> <tr><td>25</td><td>33.0</td><td>33.6</td></tr> <tr><td>40</td><td>33.1</td><td>33.8</td></tr> <tr><td>60</td><td>33.0</td><td>33.8</td></tr> <tr><td>85</td><td>32.8</td><td>34.0</td></tr> <tr><td>100</td><td>32.8</td><td>34.2</td></tr> <tr><td>105</td><td>32.9</td><td>34.2</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-50	32.7	33.2	-40	32.7	33.3	-20	32.9	33.5	0	32.8	33.5	25	33.0	33.6	40	33.1	33.8	60	33.0	33.8	85	32.8	34.0	100	32.8	34.2	105	32.9	34.2	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-50	32.7	33.2																																							
-40	32.7	33.3																																							
-20	32.9	33.5																																							
0	32.8	33.5																																							
25	33.0	33.6																																							
40	33.1	33.8																																							
60	33.0	33.8																																							
85	32.8	34.0																																							
100	32.8	34.2																																							
105	32.9	34.2																																							
--	-	-																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																									




Model	CQHS3504832	Temperature	25°C																																																																			
Item	Overcurrent Protection	Testing Circuitry	Figure A																																																																			
Object	+32V11A																																																																					
1.Graph	<p>— Input Volt. 36V — Input Volt. 48V — Input Volt. 65V</p>																																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 65[V]</th> </tr> </thead> <tbody> <tr><td>30.4</td><td>12.94</td><td>12.60</td><td>12.67</td></tr> <tr><td>27.2</td><td>13.12</td><td>13.00</td><td>13.11</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 65[V]	30.4	12.94	12.60	12.67	27.2	13.12	13.00	13.11	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Output Voltage [V]	Load Current [A]																																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 65[V]																																																																			
30.4	12.94	12.60	12.67																																																																			
27.2	13.12	13.00	13.11																																																																			
--	-	-	-																																																																			
--	-	-	-																																																																			
--	-	-	-																																																																			
--	-	-	-																																																																			
--	-	-	-																																																																			
--	-	-	-																																																																			
--	-	-	-																																																																			
--	-	-	-																																																																			
--	-	-	-																																																																			
--	-	-	-																																																																			
--	-	-	-																																																																			
--	-	-	-																																																																			
--	-	-	-																																																																			
Note:	Slanted line shows the range of the rated load current.																																																																					
When the output voltage fell to less than 26.88V ,the unit shuts off the output by operating low voltage protection.																																																																						

COSEL

Model	CQHS3504832
Item	Overvoltage Protection
Object	+32V11A

Testing Circuitry Figure A

1.Graph



2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 48[V]	Input Volt. 65[V]
-50	37.52	37.40
-40	37.70	37.52
-20	37.81	37.78
0	37.80	37.76
25	38.01	37.92
40	37.82	37.69
60	38.00	37.83
85	37.83	37.68
100	37.85	37.71
105	37.94	37.76
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

COSEL




Figure A


 $C_i : 100V\ 68\mu F \times 2$ $C_y : 4700pF$ $C_1 : 100V\ 0.1\mu F$ $C_o : 50V\ 470\mu F$ $C_{out} : 50V\ 470\mu F \times 2 (-40^\circ C \leq T_B \leq 0^\circ C)$ $: 50V\ 470\mu F (0^\circ C < T_B \leq 100^\circ C)$ $T_B : \text{Base Plate Temp.}$

Figure B (Ripple and Ripple noise Characteristic)