

**COSEL**

# TEST DATA OF DBS400B05

(280V INPUT)

Regulated DC Power Supply

Date : July 9. 1999

Approved by : I. Yasuda  
Design Manager

Prepared by : C. Fukuda  
Design Engineer

コーワセル株式会社  
**COSEL CO., LTD.**



## CONTENTS


1. Line Regulation . . . . .	1
静的入力変動	
2. Input Current (by Input Voltage) . . . . .	2
入力電流 (入力電圧特性)	
3. Input Current (by Load Current) . . . . .	3
入力電流 (負荷特性)	
4. Input Power (by Load Current) . . . . .	4
入力電力 (負荷特性)	
5. Efficiency (by Input Voltage) . . . . .	5
効率 (入力電圧特性)	
6. Efficiency (by Load Current) . . . . .	6
効率 (負荷特性)	
7. Load Regulation . . . . .	7
静的負荷変動	
8. Ripple Voltage (by Load Current) . . . . .	8
リップル電圧 (負荷特性)	
9. Ripple-Noise . . . . .	9
リップルノイズ	
10. Overcurrent Protection . . . . .	10
過電流保護	
11. Overvoltage Protection . . . . .	11
過電圧保護	
12. Dynamic Load Response . . . . .	12
動的負荷変動	
13. Rise and Fall Time . . . . .	13
立ち上り、立下り時間	
14. Ambient Temperature Drift . . . . .	14
周囲温度変動	
15. Minimum Input Voltage for Regulated Output Voltage . . . . .	15
最低レギュレーション電圧	
16. Ripple Voltage (by Ambient Temperature) . . . . .	16
リップル電圧 (周囲温度特性)	
17. Time Lapse Drift . . . . .	17
経時ドリフト	
18. Output Voltage Accuracy . . . . .	18
定電圧精度	
19. Condensation . . . . .	19
結露特性	
20. Line Noise Tolerance . . . . .	20
入力雑音耐量	
21. Figure of Testing Circuitry . . . . .	21
測定回路図	

(Final Page 22 )

**COSEL**

Model	DBS400B05
Item	Line Regulation 静的入力変動
Object	+5.0V 80A

Temperature 25°C  
Testing Circuitry Figure A



Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。

## 2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
180	5.043	5.042
200	5.043	5.042
220	5.043	5.041
250	5.043	5.041
300	5.043	5.041
350	5.043	5.041
400	5.043	5.041
420	5.044	5.040
-	-	-

COSEL

Model	DBS400B05	Temperature Testing Circuitry	25°C Figure A																																																						
Item	Input Current (by Input Voltage) 入力電流 (入力電圧特性)																																																								
Object	—	2. Values																																																							
1. Graph	<p style="text-align: center;"> <span style="color: black;">△</span> Load 100%  <span style="color: gray;">□</span> Load 50%  <span style="color: gray;">○</span> Load 0%         </p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 0% [A]</th> <th>Load 50% [A]</th> <th>Load 100% [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>50</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>100</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>150</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>165</td><td>0.022</td><td>1.481</td><td>2.725</td></tr> <tr><td>170</td><td>0.022</td><td>1.425</td><td>2.807</td></tr> <tr><td>180</td><td>0.021</td><td>1.331</td><td>2.691</td></tr> <tr><td>200</td><td>0.020</td><td>1.183</td><td>2.414</td></tr> <tr><td>250</td><td>0.018</td><td>0.952</td><td>1.922</td></tr> <tr><td>300</td><td>0.017</td><td>0.800</td><td>1.602</td></tr> <tr><td>350</td><td>0.017</td><td>0.693</td><td>1.378</td></tr> <tr><td>400</td><td>0.017</td><td>0.613</td><td>1.210</td></tr> <tr><td>420</td><td>0.016</td><td>0.588</td><td>1.156</td></tr> </tbody> </table>	Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]	0	0.000	0.000	0.000	50	0.000	0.000	0.000	100	0.002	0.002	0.002	150	0.003	0.003	0.003	165	0.022	1.481	2.725	170	0.022	1.425	2.807	180	0.021	1.331	2.691	200	0.020	1.183	2.414	250	0.018	0.952	1.922	300	0.017	0.800	1.602	350	0.017	0.693	1.378	400	0.017	0.613	1.210	420	0.016	0.588	1.156
Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]																																																						
0	0.000	0.000	0.000																																																						
50	0.000	0.000	0.000																																																						
100	0.002	0.002	0.002																																																						
150	0.003	0.003	0.003																																																						
165	0.022	1.481	2.725																																																						
170	0.022	1.425	2.807																																																						
180	0.021	1.331	2.691																																																						
200	0.020	1.183	2.414																																																						
250	0.018	0.952	1.922																																																						
300	0.017	0.800	1.602																																																						
350	0.017	0.693	1.378																																																						
400	0.017	0.613	1.210																																																						
420	0.016	0.588	1.156																																																						

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

Input Volt. [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0	0.000	0.000	0.000
50	0.000	0.000	0.000
100	0.002	0.002	0.002
150	0.003	0.003	0.003
165	0.022	1.481	2.725
170	0.022	1.425	2.807
180	0.021	1.331	2.691
200	0.020	1.183	2.414
250	0.018	0.952	1.922
300	0.017	0.800	1.602
350	0.017	0.693	1.378
400	0.017	0.613	1.210
420	0.016	0.588	1.156
—	—	—	—
—	—	—	—
—	—	—	—

**COSEL**


Model	DBS400B05																																																									
Item	Input Current (by Load Current) 入力電流 (負荷特性)	Temperature Testing Circuitry	25°C Figure A																																																							
Object	—																																																									
1. Graph	<p>—△— Input Volt. 200V        -□- Input Volt. 280V        -○- Input Volt. 400V</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.02</td><td>0.02</td><td>0.02</td></tr> <tr><td>15</td><td>0.46</td><td>0.33</td><td>0.25</td></tr> <tr><td>30</td><td>0.88</td><td>0.63</td><td>0.46</td></tr> <tr><td>45</td><td>1.31</td><td>0.94</td><td>0.68</td></tr> <tr><td>60</td><td>1.76</td><td>1.26</td><td>0.90</td></tr> <tr><td>75</td><td>2.23</td><td>1.59</td><td>1.12</td></tr> <tr><td>80</td><td>2.39</td><td>1.70</td><td>1.20</td></tr> <tr><td>88</td><td>2.65</td><td>1.88</td><td>1.32</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0	0.02	0.02	0.02	15	0.46	0.33	0.25	30	0.88	0.63	0.46	45	1.31	0.94	0.68	60	1.76	1.26	0.90	75	2.23	1.59	1.12	80	2.39	1.70	1.20	88	2.65	1.88	1.32	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Current [A]																																																									
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																							
0	0.02	0.02	0.02																																																							
15	0.46	0.33	0.25																																																							
30	0.88	0.63	0.46																																																							
45	1.31	0.94	0.68																																																							
60	1.76	1.26	0.90																																																							
75	2.23	1.59	1.12																																																							
80	2.39	1.70	1.20																																																							
88	2.65	1.88	1.32																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current

(注) 斜線は定格負荷電流範囲を示す。

**COSEL**

Model	DBS400B05
Item	Input Power (by Load Current) 入力電力 (負荷特性)
Object	_____



Note: Slanted line shows the range of the rated load current


(注) 斜線は定格負荷電流範囲を示す。

Temperature 25°C  
Humidity 40%RH  
Testing Circuitry Figure A

## 2. Values

Load Current [A]	Input Power [W]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
0	4	5	7
15	92	94	100
30	176	178	184
45	262	264	270
60	352	353	358
75	446	444	448
80	477	476	479
88	529	526	528
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—

**COSEL**


Model	DBS400B05																																	
Item	Efficiency (by Input Voltage) 効率(入力電圧特性)	Temperature 25°C Testing Circuitry Figure A																																
Object																																		
1. Graph																																		
[%] 		Load 50% Load 100%																																
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>180</td><td>85.7</td><td>84.1</td> </tr> <tr> <td>200</td><td>86.8</td><td>84.4</td> </tr> <tr> <td>220</td><td>86.4</td><td>84.6</td> </tr> <tr> <td>250</td><td>86.1</td><td>84.7</td> </tr> <tr> <td>300</td><td>85.3</td><td>84.7</td> </tr> <tr> <td>350</td><td>84.6</td><td>84.7</td> </tr> <tr> <td>400</td><td>83.6</td><td>84.4</td> </tr> <tr> <td>420</td><td>83.2</td><td>84.0</td> </tr> <tr> <td>-</td><td>-</td><td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	180	85.7	84.1	200	86.8	84.4	220	86.4	84.6	250	86.1	84.7	300	85.3	84.7	350	84.6	84.7	400	83.6	84.4	420	83.2	84.0	-	-	-
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
180	85.7	84.1																																
200	86.8	84.4																																
220	86.4	84.6																																
250	86.1	84.7																																
300	85.3	84.7																																
350	84.6	84.7																																
400	83.6	84.4																																
420	83.2	84.0																																
-	-	-																																

Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。

**COSEL**

Model	DBS400B05
Item	Efficiency (by Load Current) 効率(負荷特性)
Object	—



Note: Slanted line shows the range of the rated load current


(注) 斜線は定格負荷電流範囲を示す。

Temperature 25°C  
Testing Circuitry Figure A

2. Values

Load Current [A]	Efficiency [%]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
15	81.9	80.6	75.9
30	86.0	85.0	82.0
45	86.5	85.7	83.9
60	85.8	85.6	84.3
75	84.7	85.0	84.3
80	84.5	84.7	84.1
88	83.8	84.2	83.9
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—

**COSEL**

Model	DBS400B05	Temperature	25°C																																															
Item	Load Regulation 静的負荷変動	Testing Circuitry	Figure A																																															
Object	+5.0V 80A																																																	
1. Graph																																																		
△ Input Volt. 200V □ Input Volt. 280V ○ Input Volt. 400V																																																		
																																																		
Note: Slanted line shows the range of the rated load current.																																																		
(注) 斜線は定格負荷電流範囲を示す。																																																		
2. Values																																																		
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>5.048</td><td>5.047</td><td>5.046</td></tr> <tr> <td>15</td><td>5.046</td><td>5.046</td><td>5.045</td></tr> <tr> <td>30</td><td>5.045</td><td>5.045</td><td>5.044</td></tr> <tr> <td>45</td><td>5.045</td><td>5.044</td><td>5.044</td></tr> <tr> <td>60</td><td>5.044</td><td>5.044</td><td>5.043</td></tr> <tr> <td>75</td><td>5.044</td><td>5.043</td><td>5.043</td></tr> <tr> <td>80</td><td>5.043</td><td>5.043</td><td>5.042</td></tr> <tr> <td>88</td><td>5.043</td><td>5.042</td><td>5.042</td></tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Output Voltage [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0	5.048	5.047	5.046	15	5.046	5.046	5.045	30	5.045	5.045	5.044	45	5.045	5.044	5.044	60	5.044	5.044	5.043	75	5.044	5.043	5.043	80	5.043	5.043	5.042	88	5.043	5.042	5.042	—	—	—	—	—	—	—	—
Load Current [A]	Output Voltage [V]																																																	
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																															
0	5.048	5.047	5.046																																															
15	5.046	5.046	5.045																																															
30	5.045	5.045	5.044																																															
45	5.045	5.044	5.044																																															
60	5.044	5.044	5.043																																															
75	5.044	5.043	5.043																																															
80	5.043	5.043	5.042																																															
88	5.043	5.042	5.042																																															
—	—	—	—																																															
—	—	—	—																																															

**COSEL**


Model	DBS400B05	Temperature	25°C																																						
Item	Ripple Voltage (by Load Current) リップル電圧(負荷特性)	Testing Circuitry	Figure A																																						
Object	+5.0V 80A																																								
1. Graph																																									
<p style="text-align: center;">△ Input Volt. 200V [mV]</p>																																									
2. Values																																									
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Output Volt. [mV]</th> </tr> <tr> <th>Input Volt. 200 [V]</th> <th>Input Volt. 400 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>5</td><td>5</td></tr> <tr><td>10</td><td>10</td><td>15</td></tr> <tr><td>20</td><td>10</td><td>15</td></tr> <tr><td>40</td><td>10</td><td>15</td></tr> <tr><td>60</td><td>10</td><td>15</td></tr> <tr><td>80</td><td>10</td><td>15</td></tr> <tr><td>90</td><td>10</td><td>15</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Ripple Output Volt. [mV]		Input Volt. 200 [V]	Input Volt. 400 [V]	0	5	5	10	10	15	20	10	15	40	10	15	60	10	15	80	10	15	90	10	15	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Ripple Output Volt. [mV]																																								
	Input Volt. 200 [V]	Input Volt. 400 [V]																																							
0	5	5																																							
10	10	15																																							
20	10	15																																							
40	10	15																																							
60	10	15																																							
80	10	15																																							
90	10	15																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p>																																									

**COSEL**

Model DBS400B05

Item Ripple-Noise リップルノイズ

Object +5.0V80A



Ripple-Noise is shown as p-p in the figure below.  
Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図 p-p 値で示される。  
(注)斜線は定格負荷電流範囲を示す。




図 リップルノイズ波形図

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Load current [A]	Ripple-Noise [mV]	
	Input Volt. 200 [V]	Input Volt. 400 [V]
0	10	10
10	20	20
20	20	20
40	20	20
60	20	20
80	25	25
90	25	25
-	-	-
-	-	-
-	-	-
-	-	-

**COSEL**

Model	DBS400B05
Item	Overcurrent Protection 過電流保護
Object	+5.0V80A

1. Graph

Input Volt. 200 V  
Input Volt. 280 V  
Input Volt. 400 V

Output Voltage [V]	Load Current [A] (200[V])	Load Current [A] (280[V])	Load Current [A] (400[V])
5.00	94.65	95.46	97.32
4.75	94.87	95.68	97.64
4.50	95.10	95.91	97.86
4.00	95.73	96.15	98.32
3.50	95.93	96.35	98.91
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

Output Voltage [V]

Load Current [A]

Input Volt. 200[V]    Input Volt. 280[V]    Input Volt. 400[V]

2. Values

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
5.00	94.65	95.46	97.32
4.75	94.87	95.68	97.64
4.50	95.10	95.91	97.86
4.00	95.73	96.15	98.32
3.50	95.93	96.35	98.91
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

COSEL


Model DBS400B05

Item Overvoltage Protection  
過電圧保護

Object +5.0V80A

## 1. Graph

—△— Input Volt. 200 V  
 —□— Input Volt. 280 V  
 —○— Input Volt. 400 V



Load 0%

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

## 2. Values

Ambient Temp. [°C]	Operating Point [V]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
-35	6.72	6.72	6.72
-20	6.72	6.72	6.72
0	6.64	6.64	6.64
15	6.57	6.57	6.57
25	6.57	6.57	6.57
40	6.50	6.50	6.50
55	6.50	6.50	6.50
70	6.43	6.43	6.43
85	6.42	6.42	6.42
90	6.35	6.35	6.35
—	—	—	—

COSEL

Model	DBS400B05
Item	Dynamic Load Response 動的負荷變動
Object	+5V 80A

Temperature 25°C  
Testing Circuitry Figure A

Input Volt. 280 V



Cycle 1000 mS

Load Current

Min. Load (0.0A) ↔

Load 100% (80.0A)

500 mV/div





2 ms/div

Min. Load (0.0A) ↔

Load 50% (40.0A)

500 mV/div





2 ms/div

Load 10% (8.0A) ↔

Load 100% (80.0A)

500 mV/div



2 ms/div

COSEL


Model DBS400B05

Item Rise and Fall Time 立上り、立下り時間

Object +5.0V80A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Load	Time	T <sub>d</sub>	T <sub>r</sub>	T <sub>s</sub>	T <sub>h</sub>	T <sub>f</sub>
50 %		14.00	4.25	18.25	0.1	1.60
100 %		14.50	4.00	18.50	0.1	0.70




**COSEL**

Model DBS400B05

Item Ambient Temperature Drift  
周囲温度変動

Object +5.0V 80A

1. Graph
- |     |                  |
|-----|------------------|
| —△— | Input Volt. 200V |
| —□— | Input Volt. 280V |
| —○— | Input Volt. 400V |



Note: Slanted line shows the range of the rated ambient temperature.


(注)斜線は定格周囲温度範囲を示す。

## Testing Circuitry Figure A

## 2. Values

Temperature [°C]	Output Voltage [V]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
-35	5.056	5.056	5.056
-20	5.053	5.053	5.053
0	5.048	5.048	5.048
15	5.045	5.045	5.045
25	5.042	5.042	5.042
40	5.036	5.036	5.036
55	5.030	5.029	5.029
70	5.020	5.020	5.019
85	5.010	5.009	5.009
90	5.005	5.005	5.005
—	—	—	—

COSEL



Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

**COSEL**

Model DBS400B05

Item Ripple Voltage (by Ambient Temp.)  
リップル電圧 (周囲温度特性)


Object +5.0V 80A

## 1. Graph

Load 50%

Load 100%

[mV]



Input Volt. 280 V

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A


## 2. Values

Ambient Temp. [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	25	25
-20	20	20
0	10	10
25	10	10
45	10	10
65	15	15
85	15	15
100	15	15
—	—	—
—	—	—
—	—	—

**COSEL**

Model	DBS400B05
Item	Time Lapse Drift 経時ドリフト
Object	+5.0V80A

### 1. Graph



Temperature 25 °C  
Testing Circuitry Figure A

### 2. Values

Time since start [H]	Output Voltage [V]
0.0	5.045
0.5	5.031
1.0	5.031
2.0	5.031
3.0	5.032
4.0	5.032
5.0	5.032
6.0	5.031
7.0	5.031
8.0	5.031



Model	DBS400B05	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	+5.0V 80A	

#### Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20~85 °C

Input Voltage : 200~400 V

Load Current : 0.00~80.00 A

\* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{ Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

#### 定電圧精度

周囲温度、入力電圧、負荷を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -20~85 °C

入力電圧 200~400 V

負荷電流 0.00~80.00 A

\* 定電圧精度(変動値) = ±(出力電圧の最高値-出力電圧の最低値) / 2

$$* \text{ 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-20	400	0.00	5.057	±25	±0.5
Minimum Voltage	85	400	80.00	5.007		



Model	DBS400B05	Testing Circuitry Figure A
Item	Condensation 結露特性	
Object	+5.0V 80A	

### 1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

### 1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

### 2. Values

Item	Data	Testing Conditions
Output Voltage [V]	5.048	Input Volt.: 280V, Load Current:80A
Line Regulation [mV]	1	Input Volt.: 200~400V, Load Current:80A
Load Regulation [mV]	5	Input Volt.: 280V, Load Current:0~80A

**COSEL**

Model	DBS400B05	Temperature Testing Circuitry	25°C Figure C
Item	Line Noise Tolerance 入力雑音耐量		
Object	+5.0V 80A		

## 1. Results

Pulse Width [nS]	MODE	No protection failure should occur 保護回路の誤動作がない	DC-like Regulation of Output Voltage 出力電圧の直流的変動
50	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation
1000	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation

## Conditions

Input Voltage	: 200 V
Pulse Voltage	: ±2000 V
Pulse Cycle	: 10 mS
Pulse Input Duration	: 1 min. or more
Load	: 100 %

COSEL





Figure A

Figure B (General Electric Characteristic)  
一般電気特性

COSEL





Figure C

Figure D (Line Noise Tolerance)  
入力雑音耐量