

COSEL

TEST DATA OF DBS400B28
(280V INPUT)

Regulated DC Power Supply

Apr. 12, 2000

Approved by : Makoto Takashima
Design Manager

Prepared by : Kouichi Kinoshita
Design Engineer

コーセル株式会社
COSEL CO., LTD.



C O N T E N T S

1. Line Regulation	1
静的入力変動	
2. Input Current (by Input Voltage)	2
入力電流(入力電圧特性)	
3. Input Current (by Load Current)	3
入力電流(負荷特性)	
4. Input Power (by Load Current)	4
入力電力(負荷特性)	
5. Efficiency (by Input Voltage)	5
効率(入力電圧特性)	
6. Efficiency (by Load Current)	6
効率(負荷特性)	
7. Load Regulation	7
静的負荷変動	
8. Ripple Voltage (by Load Current)	8
リップル電圧(負荷特性)	
9. Ripple-Noise	9
リップルノイズ	
10. Overcurrent Protection	10
過電流保護	
11. Overvoltage Protection	11
過電圧保護	
12. Dynamic Load Response	12
動的負荷変動	
13. Rise and Fall Time	13
立ち上り、立下り時間	
14. Ambient Temperature Drift	14
周囲温度変動	
15. Minimum Input Voltage for Regulated Output Voltage	15
最低レギュレーション電圧	
16. Ripple Voltage (by Ambient Temperature)	16
リップル電圧(周囲温度特性)	
17. Time Lapse Drift	17
経時ドリフト	
18. Output Voltage Accuracy	18
定電圧精度	
19. Condensation	19
結露特性	
20. Line Noise Tolerance	20
入力雑音耐量	
21. Figure of Testing Circuitry	21
測定回路図	

(Final Page 22)

COSEL

Model	DBS400B28	Temperature Testing Circuitry	25°C Figure A																																
Item	Line Regulation 静的入力変動																																		
Object	+28.0V 14.5A																																		
1. Graph	<p>Output Voltage [V]</p> <p>Input Voltage [V]</p>	2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>170</td><td>27.892</td><td>27.856</td></tr> <tr><td>180</td><td>27.891</td><td>27.859</td></tr> <tr><td>200</td><td>27.891</td><td>27.861</td></tr> <tr><td>220</td><td>27.891</td><td>27.862</td></tr> <tr><td>250</td><td>27.892</td><td>27.863</td></tr> <tr><td>300</td><td>27.892</td><td>27.865</td></tr> <tr><td>350</td><td>27.891</td><td>27.867</td></tr> <tr><td>400</td><td>27.891</td><td>27.868</td></tr> <tr><td>420</td><td>27.891</td><td>27.869</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	170	27.892	27.856	180	27.891	27.859	200	27.891	27.861	220	27.891	27.862	250	27.892	27.863	300	27.892	27.865	350	27.891	27.867	400	27.891	27.868	420	27.891	27.869
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
170	27.892	27.856																																	
180	27.891	27.859																																	
200	27.891	27.861																																	
220	27.891	27.862																																	
250	27.892	27.863																																	
300	27.892	27.865																																	
350	27.891	27.867																																	
400	27.891	27.868																																	
420	27.891	27.869																																	


Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	DBS400B28																																																																										
Item	Input Current (by Input Voltage) 入力電流 (入力電圧特性)	Temperature Testing Circuitry	25°C	Figure A																																																																							
Object																																																																											
1. Graph	<p>Input Current [A]</p> <p>Input Voltage [V]</p> <p>Legend: Load 100% (△), Load 50% (□), Load 0% (○)</p>																																																																										
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>50</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>100</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>150</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>165</td><td>0.021</td><td>1.421</td><td>2.777</td></tr> <tr><td>170</td><td>0.021</td><td>1.363</td><td>2.699</td></tr> <tr><td>180</td><td>0.020</td><td>1.270</td><td>2.519</td></tr> <tr><td>200</td><td>0.019</td><td>1.125</td><td>2.241</td></tr> <tr><td>250</td><td>0.018</td><td>0.898</td><td>1.786</td></tr> <tr><td>300</td><td>0.018</td><td>0.760</td><td>1.498</td></tr> <tr><td>350</td><td>0.018</td><td>0.662</td><td>1.296</td></tr> <tr><td>400</td><td>0.018</td><td>0.589</td><td>1.145</td></tr> <tr><td>420</td><td>0.018</td><td>0.565</td><td>1.095</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	50	0.000	0.000	0.000	100	0.002	0.002	0.002	150	0.003	0.003	0.003	165	0.021	1.421	2.777	170	0.021	1.363	2.699	180	0.020	1.270	2.519	200	0.019	1.125	2.241	250	0.018	0.898	1.786	300	0.018	0.760	1.498	350	0.018	0.662	1.296	400	0.018	0.589	1.145	420	0.018	0.565	1.095	—	—	—	—	—	—	—	—	—	—	—	—
Input Voltage [V]	Input Current [A]																																																																										
	Load 0%	Load 50%	Load 100%																																																																								
0	0.000	0.000	0.000																																																																								
50	0.000	0.000	0.000																																																																								
100	0.002	0.002	0.002																																																																								
150	0.003	0.003	0.003																																																																								
165	0.021	1.421	2.777																																																																								
170	0.021	1.363	2.699																																																																								
180	0.020	1.270	2.519																																																																								
200	0.019	1.125	2.241																																																																								
250	0.018	0.898	1.786																																																																								
300	0.018	0.760	1.498																																																																								
350	0.018	0.662	1.296																																																																								
400	0.018	0.589	1.145																																																																								
420	0.018	0.565	1.095																																																																								
—	—	—	—																																																																								
—	—	—	—																																																																								
—	—	—	—																																																																								
Note: Slanted line shows the range of the rated input voltage.																																																																											
(注)斜線は定格入力電圧範囲を示す。																																																																											

COSEL

Model	DBS400B28																																																									
Item	Input Current (by Load Current) 入力電流 (負荷特性)	Temperature Testing Circuitry	25°C Figure A																																																							
Object	<hr/>																																																									
1. Graph	<p style="text-align: center;">—△— Input Volt. 200V —□— Input Volt. 280V —○— Input Volt. 400V</p>  <p>The graph shows three sets of curves corresponding to input voltages of 200V, 280V, and 400V. Each set includes a solid line with triangle markers (200V), a dashed line with square markers (280V), and a dotted line with circle markers (400V). All curves show an increase in input current as load current increases. A slanted line is drawn across the graph, starting from approximately (3, 0.4) and ending at (15, 2.2), indicating the rated load current range.</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.020</td><td>0.019</td><td>0.018</td></tr> <tr><td>2.00</td><td>0.345</td><td>0.243</td><td>0.180</td></tr> <tr><td>4.00</td><td>0.643</td><td>0.465</td><td>0.345</td></tr> <tr><td>6.00</td><td>0.942</td><td>0.679</td><td>0.497</td></tr> <tr><td>8.00</td><td>1.244</td><td>0.894</td><td>0.648</td></tr> <tr><td>10.00</td><td>1.550</td><td>1.111</td><td>0.801</td></tr> <tr><td>12.00</td><td>1.861</td><td>1.332</td><td>0.956</td></tr> <tr><td>14.00</td><td>2.178</td><td>1.555</td><td>1.112</td></tr> <tr><td>14.50</td><td>2.254</td><td>1.612</td><td>1.151</td></tr> <tr><td>15.95</td><td>2.490</td><td>1.776</td><td>1.267</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.00	0.020	0.019	0.018	2.00	0.345	0.243	0.180	4.00	0.643	0.465	0.345	6.00	0.942	0.679	0.497	8.00	1.244	0.894	0.648	10.00	1.550	1.111	0.801	12.00	1.861	1.332	0.956	14.00	2.178	1.555	1.112	14.50	2.254	1.612	1.151	15.95	2.490	1.776	1.267	—	—	—	—	—	—	—	—
Load Current [A]	Input Current [A]																																																									
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																							
0.00	0.020	0.019	0.018																																																							
2.00	0.345	0.243	0.180																																																							
4.00	0.643	0.465	0.345																																																							
6.00	0.942	0.679	0.497																																																							
8.00	1.244	0.894	0.648																																																							
10.00	1.550	1.111	0.801																																																							
12.00	1.861	1.332	0.956																																																							
14.00	2.178	1.555	1.112																																																							
14.50	2.254	1.612	1.151																																																							
15.95	2.490	1.776	1.267																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

COSEL

Model	DBS400B28	Temperature	25°C																																																							
Item	Input Power (by Load Current) 入力電力（負荷特性）	Testing Circuitry	Figure A																																																							
Object																																																										
1. Graph	<p style="text-align: center;">△ Input Volt. 200V □ Input Volt. 280V ○ Input Volt. 400V</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>4.00</td><td>5.20</td><td>7.20</td></tr> <tr><td>2.00</td><td>69.00</td><td>68.20</td><td>72.00</td></tr> <tr><td>4.00</td><td>128.70</td><td>130.20</td><td>137.80</td></tr> <tr><td>6.00</td><td>188.50</td><td>190.10</td><td>198.50</td></tr> <tr><td>8.00</td><td>248.90</td><td>250.40</td><td>259.20</td></tr> <tr><td>10.00</td><td>310.00</td><td>311.30</td><td>320.30</td></tr> <tr><td>12.00</td><td>372.30</td><td>373.10</td><td>382.30</td></tr> <tr><td>14.00</td><td>435.50</td><td>435.40</td><td>445.00</td></tr> <tr><td>14.50</td><td>451.00</td><td>451.30</td><td>460.00</td></tr> <tr><td>15.95</td><td>498.00</td><td>497.30</td><td>506.00</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.00	4.00	5.20	7.20	2.00	69.00	68.20	72.00	4.00	128.70	130.20	137.80	6.00	188.50	190.10	198.50	8.00	248.90	250.40	259.20	10.00	310.00	311.30	320.30	12.00	372.30	373.10	382.30	14.00	435.50	435.40	445.00	14.50	451.00	451.30	460.00	15.95	498.00	497.30	506.00	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																									
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																							
0.00	4.00	5.20	7.20																																																							
2.00	69.00	68.20	72.00																																																							
4.00	128.70	130.20	137.80																																																							
6.00	188.50	190.10	198.50																																																							
8.00	248.90	250.40	259.20																																																							
10.00	310.00	311.30	320.30																																																							
12.00	372.30	373.10	382.30																																																							
14.00	435.50	435.40	445.00																																																							
14.50	451.00	451.30	460.00																																																							
15.95	498.00	497.30	506.00																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

COSEL

Model	DBS400B28																																	
Item	Efficiency (by Input Voltage) 効率 (入力電圧特性)																																	
Object																																		
1. Graph		Temperature Testing Circuitry 25°C Figure A																																
<p style="text-align: center;">□ Load 50% △ Load 100%</p> <p>The graph plots Efficiency [%] on the y-axis (70 to 98) against Input Voltage [V] on the x-axis (100 to 500). Two sets of data points are shown: Load 50% (squares) and Load 100% (triangles). Both series show a general downward trend as input voltage increases. Two slanted lines on the graph represent the rated input voltage range.</p>																																		
2. Values																																		
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>170</td><td>85.4</td><td>86.2</td></tr> <tr><td>180</td><td>86.8</td><td>87.1</td></tr> <tr><td>200</td><td>88.1</td><td>88.3</td></tr> <tr><td>220</td><td>88.6</td><td>88.9</td></tr> <tr><td>250</td><td>88.3</td><td>88.7</td></tr> <tr><td>300</td><td>87.1</td><td>88.1</td></tr> <tr><td>350</td><td>85.7</td><td>87.6</td></tr> <tr><td>400</td><td>84.3</td><td>86.6</td></tr> <tr><td>420</td><td>83.8</td><td>86.4</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	170	85.4	86.2	180	86.8	87.1	200	88.1	88.3	220	88.6	88.9	250	88.3	88.7	300	87.1	88.1	350	85.7	87.6	400	84.3	86.6	420	83.8	86.4
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
170	85.4	86.2																																
180	86.8	87.1																																
200	88.1	88.3																																
220	88.6	88.9																																
250	88.3	88.7																																
300	87.1	88.1																																
350	85.7	87.6																																
400	84.3	86.6																																
420	83.8	86.4																																

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	DBS400B28	Temperature	25°C																																																								
Item	Efficiency (by Load Current) 効率(負荷特性)	Testing Circuitry	Figure A																																																								
Object	<hr/>																																																										
1. Graph	<p style="text-align: center;"> △ Input Volt. 200V □ Input Volt. 280V ○ Input Volt. 400V </p> <p>The graph shows efficiency increasing with load current for all input voltages. A slanted line on the right side of the plot indicates the rated load current range.</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency 200V [%]</th> <th>Efficiency 280V [%]</th> <th>Efficiency 400V [%]</th> </tr> </thead> <tbody> <tr><td>2.00</td><td>78.9</td><td>79.8</td><td>75.5</td></tr> <tr><td>4.00</td><td>85.2</td><td>84.2</td><td>79.5</td></tr> <tr><td>6.00</td><td>87.5</td><td>86.7</td><td>83.0</td></tr> <tr><td>8.00</td><td>88.4</td><td>87.9</td><td>84.9</td></tr> <tr><td>10.00</td><td>88.8</td><td>88.4</td><td>85.9</td></tr> <tr><td>12.00</td><td>88.7</td><td>88.6</td><td>86.4</td></tr> <tr><td>14.00</td><td>88.5</td><td>88.5</td><td>86.6</td></tr> <tr><td>14.50</td><td>88.5</td><td>88.5</td><td>86.8</td></tr> <tr><td>15.95</td><td>88.1</td><td>88.3</td><td>86.8</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Efficiency 200V [%]	Efficiency 280V [%]	Efficiency 400V [%]	2.00	78.9	79.8	75.5	4.00	85.2	84.2	79.5	6.00	87.5	86.7	83.0	8.00	88.4	87.9	84.9	10.00	88.8	88.4	85.9	12.00	88.7	88.6	86.4	14.00	88.5	88.5	86.6	14.50	88.5	88.5	86.8	15.95	88.1	88.3	86.8	—	—	—	—	—	—	—	—	—	—	—	—	<hr/>					
Load Current [A]	Efficiency 200V [%]	Efficiency 280V [%]	Efficiency 400V [%]																																																								
2.00	78.9	79.8	75.5																																																								
4.00	85.2	84.2	79.5																																																								
6.00	87.5	86.7	83.0																																																								
8.00	88.4	87.9	84.9																																																								
10.00	88.8	88.4	85.9																																																								
12.00	88.7	88.6	86.4																																																								
14.00	88.5	88.5	86.6																																																								
14.50	88.5	88.5	86.8																																																								
15.95	88.1	88.3	86.8																																																								
—	—	—	—																																																								
—	—	—	—																																																								
—	—	—	—																																																								
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>2.00</td><td>78.9</td><td>79.8</td><td>75.5</td></tr> <tr><td>4.00</td><td>85.2</td><td>84.2</td><td>79.5</td></tr> <tr><td>6.00</td><td>87.5</td><td>86.7</td><td>83.0</td></tr> <tr><td>8.00</td><td>88.4</td><td>87.9</td><td>84.9</td></tr> <tr><td>10.00</td><td>88.8</td><td>88.4</td><td>85.9</td></tr> <tr><td>12.00</td><td>88.7</td><td>88.6</td><td>86.4</td></tr> <tr><td>14.00</td><td>88.5</td><td>88.5</td><td>86.6</td></tr> <tr><td>14.50</td><td>88.5</td><td>88.5</td><td>86.8</td></tr> <tr><td>15.95</td><td>88.1</td><td>88.3</td><td>86.8</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Efficiency [%]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	2.00	78.9	79.8	75.5	4.00	85.2	84.2	79.5	6.00	87.5	86.7	83.0	8.00	88.4	87.9	84.9	10.00	88.8	88.4	85.9	12.00	88.7	88.6	86.4	14.00	88.5	88.5	86.6	14.50	88.5	88.5	86.8	15.95	88.1	88.3	86.8	—	—	—	—	—	—	—	—	—	—	—	—	<hr/>		
Load Current [A]	Efficiency [%]																																																										
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																								
2.00	78.9	79.8	75.5																																																								
4.00	85.2	84.2	79.5																																																								
6.00	87.5	86.7	83.0																																																								
8.00	88.4	87.9	84.9																																																								
10.00	88.8	88.4	85.9																																																								
12.00	88.7	88.6	86.4																																																								
14.00	88.5	88.5	86.6																																																								
14.50	88.5	88.5	86.8																																																								
15.95	88.1	88.3	86.8																																																								
—	—	—	—																																																								
—	—	—	—																																																								
—	—	—	—																																																								

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	DBS400B28	Temperature	25°C																																															
Item	Load Regulation 静的負荷変動	Testing Circuitry	Figure A																																															
Object	+28.0V 14.5A																																																	
1. Graph	<p>—△— Input Volt. 200 V —□— Input Volt. 280 V —○— Input Volt. 400 V</p>																																																	
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>27.915</td><td>27.912</td><td>27.908</td></tr> <tr><td>2.00</td><td>27.909</td><td>27.907</td><td>27.904</td></tr> <tr><td>4.00</td><td>27.906</td><td>27.902</td><td>27.899</td></tr> <tr><td>6.00</td><td>27.901</td><td>27.900</td><td>27.897</td></tr> <tr><td>8.00</td><td>27.896</td><td>27.895</td><td>27.893</td></tr> <tr><td>10.00</td><td>27.888</td><td>27.888</td><td>27.888</td></tr> <tr><td>12.00</td><td>27.878</td><td>27.880</td><td>27.882</td></tr> <tr><td>14.00</td><td>27.867</td><td>27.871</td><td>27.873</td></tr> <tr><td>14.50</td><td>27.864</td><td>27.869</td><td>27.871</td></tr> <tr><td>15.95</td><td>27.857</td><td>27.860</td><td>27.864</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.00	27.915	27.912	27.908	2.00	27.909	27.907	27.904	4.00	27.906	27.902	27.899	6.00	27.901	27.900	27.897	8.00	27.896	27.895	27.893	10.00	27.888	27.888	27.888	12.00	27.878	27.880	27.882	14.00	27.867	27.871	27.873	14.50	27.864	27.869	27.871	15.95	27.857	27.860	27.864
Load Current [A]	Output Voltage [V]																																																	
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																															
0.00	27.915	27.912	27.908																																															
2.00	27.909	27.907	27.904																																															
4.00	27.906	27.902	27.899																																															
6.00	27.901	27.900	27.897																																															
8.00	27.896	27.895	27.893																																															
10.00	27.888	27.888	27.888																																															
12.00	27.878	27.880	27.882																																															
14.00	27.867	27.871	27.873																																															
14.50	27.864	27.869	27.871																																															
15.95	27.857	27.860	27.864																																															

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	DBS400B28	Temperature Testing Circuitry	25°C Figure A																																			
Item	Ripple Voltage(by Load Current) リップル電圧(負荷特性)																																					
Object	+28V14.5A	2. Values																																				
1. Graph	<p>Graph showing Ripple Voltage (mV) vs Load Current (A). The Y-axis ranges from 0 to 140 mV, and the X-axis ranges from 0 to 20 A. Two sets of data points are plotted: Input Volt. 200V (triangles) and Input Volt. 400V (squares). A slanted line indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Output Volt. 200 [mV]</th> <th>Ripple Output Volt. 400 [mV]</th> </tr> </thead> <tbody> <tr><td>0</td><td>10</td><td>10</td></tr> <tr><td>2.9</td><td>20</td><td>25</td></tr> <tr><td>5.8</td><td>25</td><td>30</td></tr> <tr><td>8.7</td><td>25</td><td>30</td></tr> <tr><td>11.6</td><td>25</td><td>30</td></tr> <tr><td>14.5</td><td>25</td><td>30</td></tr> <tr><td>17.4</td><td>25</td><td>35</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Ripple Output Volt. 200 [mV]	Ripple Output Volt. 400 [mV]	0	10	10	2.9	20	25	5.8	25	30	8.7	25	30	11.6	25	30	14.5	25	30	17.4	25	35	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Ripple Output Volt. 200 [mV]	Ripple Output Volt. 400 [mV]																																				
0	10	10																																				
2.9	20	25																																				
5.8	25	30																																				
8.7	25	30																																				
11.6	25	30																																				
14.5	25	30																																				
17.4	25	35																																				
—	—	—																																				
—	—	—																																				
—	—	—																																				
—	—	—																																				
2. Values																																						

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップル電圧は、下図 p - p 値で示される。

(注)斜線は定格負荷電流範囲を示す。




図 リップル波形図

COSEL

Model	DBS400B28	Temperature Testing Circuitry	25°C Figure A																																						
Item	Ripple-Noise リップルノイズ																																								
Object	+28V 14.5A																																								
1. Graph	<p>Y-axis: Ripple-Noise [mV] (0 to 160) X-axis: Load Current [A] (0 to 20)</p>																																								
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 200 [V]</th> <th>Input Volt. 400 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>15</td><td>20</td></tr> <tr><td>2.9</td><td>25</td><td>35</td></tr> <tr><td>5.8</td><td>30</td><td>35</td></tr> <tr><td>8.7</td><td>30</td><td>35</td></tr> <tr><td>11.6</td><td>30</td><td>35</td></tr> <tr><td>14.5</td><td>35</td><td>40</td></tr> <tr><td>17.4</td><td>40</td><td>45</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load current [A]	Ripple-Noise [mV]		Input Volt. 200 [V]	Input Volt. 400 [V]	0	15	20	2.9	25	35	5.8	30	35	8.7	30	35	11.6	30	35	14.5	35	40	17.4	40	45	—	—	—	—	—	—	—	—	—	—	—	—
Load current [A]	Ripple-Noise [mV]																																								
	Input Volt. 200 [V]	Input Volt. 400 [V]																																							
0	15	20																																							
2.9	25	35																																							
5.8	30	35																																							
8.7	30	35																																							
11.6	30	35																																							
14.5	35	40																																							
17.4	40	45																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p> <p>図 リップルノイズ波形図</p>																																									

COSEL

Model	DBS400B28	Temperature Testing Circuitry	25°C Figure A																																																							
Item	Overcurrent Protection 過電流保護																																																									
Object	+28.0V 14.5A																																																									
1. Graph	<p>[V]</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>	2. Values																																																								
			<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>28.00</td><td>17.424</td><td>17.398</td><td>17.894</td></tr> <tr><td>26.60</td><td>17.413</td><td>17.439</td><td>18.021</td></tr> <tr><td>25.20</td><td>17.403</td><td>17.507</td><td>18.130</td></tr> <tr><td>22.40</td><td>17.515</td><td>17.623</td><td>18.312</td></tr> <tr><td>19.60</td><td>17.553</td><td>17.682</td><td>18.452</td></tr> <tr><td>16.80</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>14.00</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>11.20</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>8.40</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>5.60</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>2.80</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>0.00</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	28.00	17.424	17.398	17.894	26.60	17.413	17.439	18.021	25.20	17.403	17.507	18.130	22.40	17.515	17.623	18.312	19.60	17.553	17.682	18.452	16.80	—	—	—	14.00	—	—	—	11.20	—	—	—	8.40	—	—	—	5.60	—	—	—	2.80	—	—	—	0.00	—	—	—
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																							
28.00	17.424	17.398	17.894																																																							
26.60	17.413	17.439	18.021																																																							
25.20	17.403	17.507	18.130																																																							
22.40	17.515	17.623	18.312																																																							
19.60	17.553	17.682	18.452																																																							
16.80	—	—	—																																																							
14.00	—	—	—																																																							
11.20	—	—	—																																																							
8.40	—	—	—																																																							
5.60	—	—	—																																																							
2.80	—	—	—																																																							
0.00	—	—	—																																																							
<p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when the output voltage is from 18V to 0V.</p> <p>(注) 斜線は定格負荷電流範囲を示す。 18V～0V間は、間欠モードとなる。</p>																																																										

COSEL


Model	DBS400B28	Testing Circuitry Figure A																																																					
Item	Overvoltage Protection 過電圧保護																																																						
Object	+28.0 V 14.5 A																																																						
1. Graph	<p>Operating Point [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 0%</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																						
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr> <td>-35</td><td>34.90</td><td>34.90</td><td>34.90</td></tr> <tr> <td>-20</td><td>35.25</td><td>35.32</td><td>35.32</td></tr> <tr> <td>0</td><td>35.81</td><td>35.81</td><td>35.81</td></tr> <tr> <td>15</td><td>36.16</td><td>36.16</td><td>36.16</td></tr> <tr> <td>25</td><td>36.44</td><td>36.44</td><td>36.44</td></tr> <tr> <td>40</td><td>36.79</td><td>36.79</td><td>36.79</td></tr> <tr> <td>55</td><td>37.14</td><td>37.14</td><td>37.14</td></tr> <tr> <td>70</td><td>37.49</td><td>37.48</td><td>37.48</td></tr> <tr> <td>85</td><td>37.84</td><td>37.84</td><td>37.84</td></tr> <tr> <td>90</td><td>37.97</td><td>37.97</td><td>37.97</td></tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Ambient Temperature [°C]	Operating Point [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	-35	34.90	34.90	34.90	-20	35.25	35.32	35.32	0	35.81	35.81	35.81	15	36.16	36.16	36.16	25	36.44	36.44	36.44	40	36.79	36.79	36.79	55	37.14	37.14	37.14	70	37.49	37.48	37.48	85	37.84	37.84	37.84	90	37.97	37.97	37.97	—	—	—	—
Ambient Temperature [°C]	Operating Point [V]																																																						
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																				
-35	34.90	34.90	34.90																																																				
-20	35.25	35.32	35.32																																																				
0	35.81	35.81	35.81																																																				
15	36.16	36.16	36.16																																																				
25	36.44	36.44	36.44																																																				
40	36.79	36.79	36.79																																																				
55	37.14	37.14	37.14																																																				
70	37.49	37.48	37.48																																																				
85	37.84	37.84	37.84																																																				
90	37.97	37.97	37.97																																																				
—	—	—	—																																																				

COSEL

Model	DBS400B28	Temperature Testing Circuitry Figure A	25°C
Item	Dynamic Load Response 動的負荷變動		
Object	+28V 14.5A		

Input Volt. 280 V


Cycle 1000 mS



COSEL


Model	DBS400B28	Temperature Testing Circuitry Figure A	25°C
Item	Rise and Fall Time 立ち上り、立下り時間		
Object	+28.0V 14.5A		

1. Graph



2. Values

Load	Time	T _d	T _r	T _s	T _h	T _f	[mS]
50 %		14.50	6.25	20.75	0.25	8.05	
100 %		14.75	6.00	20.75	0.10	3.95	



COSEL

Model	DBS400B28	Testing Circuitry Figure A																																																					
Item	Ambient Temperature Drift 周囲温度変動																																																						
Object	+28.0V 14.5A																																																						
1. Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																						
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr> <td>-35</td><td>27.837</td><td>27.843</td><td>27.855</td></tr> <tr> <td>-20</td><td>27.843</td><td>27.848</td><td>27.861</td></tr> <tr> <td>0</td><td>27.845</td><td>27.852</td><td>27.868</td></tr> <tr> <td>15</td><td>27.855</td><td>27.861</td><td>27.871</td></tr> <tr> <td>25</td><td>27.859</td><td>27.863</td><td>27.869</td></tr> <tr> <td>40</td><td>27.856</td><td>27.856</td><td>27.857</td></tr> <tr> <td>55</td><td>27.837</td><td>27.836</td><td>27.837</td></tr> <tr> <td>70</td><td>27.805</td><td>27.805</td><td>27.805</td></tr> <tr> <td>85</td><td>27.753</td><td>27.750</td><td>27.744</td></tr> <tr> <td>90</td><td>27.729</td><td>27.723</td><td>27.715</td></tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	-35	27.837	27.843	27.855	-20	27.843	27.848	27.861	0	27.845	27.852	27.868	15	27.855	27.861	27.871	25	27.859	27.863	27.869	40	27.856	27.856	27.857	55	27.837	27.836	27.837	70	27.805	27.805	27.805	85	27.753	27.750	27.744	90	27.729	27.723	27.715	—	—	—	—
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																				
-35	27.837	27.843	27.855																																																				
-20	27.843	27.848	27.861																																																				
0	27.845	27.852	27.868																																																				
15	27.855	27.861	27.871																																																				
25	27.859	27.863	27.869																																																				
40	27.856	27.856	27.857																																																				
55	27.837	27.836	27.837																																																				
70	27.805	27.805	27.805																																																				
85	27.753	27.750	27.744																																																				
90	27.729	27.723	27.715																																																				
—	—	—	—																																																				

COSEL

Model	DBS400B28		
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧		
Object	+28.0V 14.5A		
1. Graph			
[V]	<p>Load 50% Load 100%</p>		
Input Voltage [V]	<p>Load 50% Load 100%</p>		
Ambient Temperature [°C]	<p>Load 50% Load 100%</p>		
2. Values			
Ambient Temperature [°C]	Input Voltage [V]		
	Load 50%	Load 100%	
-35	153	157	
-20	153	158	
0	154	159	
15	154	160	
25	154	161	
40	155	161	
55	155	162	
70	156	163	
85	156	164	
90	156	164	
—	—	—	

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

COSEL

Model	DBS400B28																																								
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)																																								
Object	+28V14.5A																																								
1. Graph																																									
<p>Graph showing Ripple Voltage [mV] vs Ambient Temperature [°C]. The graph shows two sets of data points for Load 50% (squares) and Load 100% (triangles). A slanted line indicates the rated ambient temperature range from -40°C to 100°C.</p>		<p>Testing Circuitry Figure A</p>																																							
2. Values																																									
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temp. [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-40</td><td>120</td><td>120</td></tr> <tr><td>-20</td><td>45</td><td>45</td></tr> <tr><td>0</td><td>25</td><td>25</td></tr> <tr><td>25</td><td>25</td><td>25</td></tr> <tr><td>45</td><td>20</td><td>20</td></tr> <tr><td>65</td><td>25</td><td>25</td></tr> <tr><td>85</td><td>30</td><td>30</td></tr> <tr><td>100</td><td>35</td><td>35</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Ambient Temp. [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-40	120	120	-20	45	45	0	25	25	25	25	25	45	20	20	65	25	25	85	30	30	100	35	35	—	—	—	—	—	—	—	—	—
Ambient Temp. [°C]	Ripple Voltage [mV]																																								
	Load 50%	Load 100%																																							
-40	120	120																																							
-20	45	45																																							
0	25	25																																							
25	25	25																																							
45	20	20																																							
65	25	25																																							
85	30	30																																							
100	35	35																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							

(注)斜線は定格周囲温度範囲を示す。

COSEL

Model	DBS400B28	Temperature Testing Circuitry 25°C Figure A																					
Item	Time Lapse Drift 経時ドリフト																						
Object	+28.0V 14.5A																						
1. Graph		2. Values																					
<p>[V]</p> <table border="1"> <caption>Data points from the graph</caption> <thead> <tr> <th>Time [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>27.842</td></tr> <tr><td>0.5</td><td>27.828</td></tr> <tr><td>1.0</td><td>27.830</td></tr> <tr><td>2.0</td><td>27.831</td></tr> <tr><td>3.0</td><td>27.832</td></tr> <tr><td>4.0</td><td>27.832</td></tr> <tr><td>5.0</td><td>27.832</td></tr> <tr><td>6.0</td><td>27.832</td></tr> <tr><td>7.0</td><td>27.832</td></tr> <tr><td>8.0</td><td>27.832</td></tr> </tbody> </table>		Time [H]	Output Voltage [V]	0.0	27.842	0.5	27.828	1.0	27.830	2.0	27.831	3.0	27.832	4.0	27.832	5.0	27.832	6.0	27.832	7.0	27.832	8.0	27.832
Time [H]	Output Voltage [V]																						
0.0	27.842																						
0.5	27.828																						
1.0	27.830																						
2.0	27.831																						
3.0	27.832																						
4.0	27.832																						
5.0	27.832																						
6.0	27.832																						
7.0	27.832																						
8.0	27.832																						
<p>Output Voltage [V]</p> <p>Input Volt. 280V</p> <p>Load 100%</p>																							



Model	DBS400B28	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	+28.0V 14.5A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20~85 °C

Input Voltage : 200~400 V

Load Current : 0~14.5 A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{ Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -20~85 °C

入力電圧 200~400 V

負荷電流 0~14.5 A

* 定電圧精度(変動値) = ±(出力電圧の最高値-出力電圧の最低値) / 2

$$* \text{ 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-20	200	0.0	27.914		
Minimum Voltage	85	400	14.5	27.728	±94	±0.4



Model	DBS400B28	
Item	Condensation 結露特性	Testing Circuitry Figure A
Object	+28V14.5A	

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	27.731	Input Volt.: 280V, Load Current:14.5A
Line Regulation [mV]	18	Input Volt.: 200~400V, Load Current:14.5A
Load Regulation [mV]	56	Input Volt.: 280V, Load Current:0~14.5A



Model	DBS400B28	Temperature Testing Circuitry 25°C Figure C
Item	Line Noise Tolerance 入力雑音耐量	
Object	+28V 14.5A	

1. Results

Pulse Width [nS]	MODE	No protection failure should occur 保護回路の誤動作がない	DC-like Regulation of Output Voltage 出力電圧の直流的変動
50	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation
1000	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation

Conditions

Input Voltage : 200 V
 Pulse Voltage : ±2000 V
 Pulse Cycle : 10 mS
 Pulse Input Duration: 1 min. or more
 Load : 100 %

COSEL





Figure B (General Electric Characteristic)
一般電気特性





Figure C

Figure D (Line Noise Tolerance)
入力雑音耐量