



TEST DATA OF DBS700B12

Regulated DC Power Supply
January 14, 2010

Approved by : Tatsuya Mano
Tatsuya Mano Design Manager


Prepared by : Takayuki Fukuda
Takayuki Fukuda Design Engineer

COSEL CO.,LTD.

CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	9
10. Ripple-Noise	10
11. Ripple Voltage (by Ambient Temperature)	11
12. Ambient Temperature Drift	12
13. Output Voltage Accuracy	13
14. Time Lapse Drift	14
15. Rise and Fall Time	15
16. Minimum Input Voltage for Regulated Output Voltage	16
17. Overcurrent Protection	17
18. Overvoltage Protection	18
19. Figure of Testing Circuitry	19

(Final Page 19)

Model	DBS700B12	Temperature	25°C																																																																															
Item	Input Current (by Input Voltage)	Testing Circuitry	Figure A																																																																															
Object	_____																																																																																	
1. Graph		—△— Load 100% - -□--- Load 50% - -○--- Load 0%																																																																																
		2. Values																																																																																
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>50</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>100</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>150</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>170</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>180</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>190</td><td>0.035</td><td>2.036</td><td>4.062</td></tr> <tr><td>200</td><td>0.035</td><td>1.928</td><td>3.854</td></tr> <tr><td>250</td><td>0.033</td><td>1.543</td><td>3.080</td></tr> <tr><td>280</td><td>0.030</td><td>1.383</td><td>2.752</td></tr> <tr><td>300</td><td>0.029</td><td>1.294</td><td>2.570</td></tr> <tr><td>350</td><td>0.029</td><td>1.118</td><td>2.210</td></tr> <tr><td>400</td><td>0.028</td><td>0.988</td><td>1.940</td></tr> <tr><td>420</td><td>0.025</td><td>0.945</td><td>1.852</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	50	0.000	0.000	0.000	100	0.000	0.000	0.000	150	0.003	0.003	0.003	170	0.003	0.003	0.003	180	0.003	0.003	0.003	190	0.035	2.036	4.062	200	0.035	1.928	3.854	250	0.033	1.543	3.080	280	0.030	1.383	2.752	300	0.029	1.294	2.570	350	0.029	1.118	2.210	400	0.028	0.988	1.940	420	0.025	0.945	1.852	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0	0.000	0.000	0.000																																																																															
50	0.000	0.000	0.000																																																																															
100	0.000	0.000	0.000																																																																															
150	0.003	0.003	0.003																																																																															
170	0.003	0.003	0.003																																																																															
180	0.003	0.003	0.003																																																																															
190	0.035	2.036	4.062																																																																															
200	0.035	1.928	3.854																																																																															
250	0.033	1.543	3.080																																																																															
280	0.030	1.383	2.752																																																																															
300	0.029	1.294	2.570																																																																															
350	0.029	1.118	2.210																																																																															
400	0.028	0.988	1.940																																																																															
420	0.025	0.945	1.852																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
Note: Slanted line shows the range of the rated input voltage.																																																																																		

COSEL

Model	DBS700B12																																																		
Item	Input Current (by Load Current)	Temperature	25°C																																																
Object	Testing Circuitry	Figure A																																																	
1.Graph	—△— Input Volt. 200V ---□--- Input Volt. 280V -○--- Input Volt. 400V	2.Values																																																	
<p>The graph plots Input Current [A] on the Y-axis against Load Current [A] on the X-axis. Three data series are shown for different input voltages: 200V (triangles), 280V (squares), and 400V (circles). All three series show a linear increase in input current with load current. A slanted line is drawn across the graph, starting from approximately (0, 0.035) and ending at approximately (63, 4.200), representing the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.035</td><td>0.030</td><td>0.004</td></tr> <tr><td>8</td><td>0.584</td><td>0.412</td><td>0.306</td></tr> <tr><td>16</td><td>1.086</td><td>0.778</td><td>0.566</td></tr> <tr><td>24</td><td>1.597</td><td>1.146</td><td>0.823</td></tr> <tr><td>32</td><td>2.116</td><td>1.517</td><td>1.082</td></tr> <tr><td>40</td><td>2.640</td><td>1.894</td><td>1.342</td></tr> <tr><td>48</td><td>3.178</td><td>2.274</td><td>1.606</td></tr> <tr><td>56</td><td>3.720</td><td>2.658</td><td>1.874</td></tr> <tr><td>58</td><td>3.856</td><td>2.754</td><td>1.942</td></tr> <tr><td>63</td><td>4.200</td><td>2.998</td><td>2.112</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0	0.035	0.030	0.004	8	0.584	0.412	0.306	16	1.086	0.778	0.566	24	1.597	1.146	0.823	32	2.116	1.517	1.082	40	2.640	1.894	1.342	48	3.178	2.274	1.606	56	3.720	2.658	1.874	58	3.856	2.754	1.942	63	4.200	2.998	2.112	--	-	-	-			
Load Current [A]	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																
0	0.035	0.030	0.004																																																
8	0.584	0.412	0.306																																																
16	1.086	0.778	0.566																																																
24	1.597	1.146	0.823																																																
32	2.116	1.517	1.082																																																
40	2.640	1.894	1.342																																																
48	3.178	2.274	1.606																																																
56	3.720	2.658	1.874																																																
58	3.856	2.754	1.942																																																
63	4.200	2.998	2.112																																																
--	-	-	-																																																

Note: Slanted line shows the range of the rated load current.

COSEL

Model	DBS700B12	Temperature	25°C																																																			
Item	Input Power (by Load Current)	Testing Circuitry	Figure A																																																			
Object																																																						
1.Graph	<p>—△— Input Volt. 200V - -□-- Input Volt. 280V - -○-- Input Volt. 400V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Power [W] (200V)</th> <th>Input Power [W] (280V)</th> <th>Input Power [W] (400V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>0</td><td>0</td><td>0</td></tr> <tr><td>8</td><td>116.8</td><td>115.3</td><td>122.2</td></tr> <tr><td>16</td><td>217.2</td><td>217.9</td><td>226.2</td></tr> <tr><td>24</td><td>319.4</td><td>320.9</td><td>329.2</td></tr> <tr><td>32</td><td>423.0</td><td>424.9</td><td>433.0</td></tr> <tr><td>40</td><td>528.0</td><td>530.0</td><td>537.0</td></tr> <tr><td>48</td><td>635.0</td><td>637.0</td><td>642.0</td></tr> <tr><td>56</td><td>744.0</td><td>744.0</td><td>750.0</td></tr> <tr><td>58</td><td>771.0</td><td>771.0</td><td>776.0</td></tr> <tr><td>63</td><td>841.0</td><td>839.0</td><td>845.0</td></tr> </tbody> </table>			Load Current [A]	Input Power [W] (200V)	Input Power [W] (280V)	Input Power [W] (400V)	0	0	0	0	8	116.8	115.3	122.2	16	217.2	217.9	226.2	24	319.4	320.9	329.2	32	423.0	424.9	433.0	40	528.0	530.0	537.0	48	635.0	637.0	642.0	56	744.0	744.0	750.0	58	771.0	771.0	776.0	63	841.0	839.0	845.0							
Load Current [A]	Input Power [W] (200V)	Input Power [W] (280V)	Input Power [W] (400V)																																																			
0	0	0	0																																																			
8	116.8	115.3	122.2																																																			
16	217.2	217.9	226.2																																																			
24	319.4	320.9	329.2																																																			
32	423.0	424.9	433.0																																																			
40	528.0	530.0	537.0																																																			
48	635.0	637.0	642.0																																																			
56	744.0	744.0	750.0																																																			
58	771.0	771.0	776.0																																																			
63	841.0	839.0	845.0																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>7.0</td><td>8.4</td><td>0.1</td></tr> <tr><td>8</td><td>116.8</td><td>115.3</td><td>122.2</td></tr> <tr><td>16</td><td>217.2</td><td>217.9</td><td>226.2</td></tr> <tr><td>24</td><td>319.4</td><td>320.9</td><td>329.2</td></tr> <tr><td>32</td><td>423.0</td><td>424.9</td><td>433.0</td></tr> <tr><td>40</td><td>528.0</td><td>530.0</td><td>537.0</td></tr> <tr><td>48</td><td>635.0</td><td>637.0</td><td>642.0</td></tr> <tr><td>56</td><td>744.0</td><td>744.0</td><td>750.0</td></tr> <tr><td>58</td><td>771.0</td><td>771.0</td><td>776.0</td></tr> <tr><td>63</td><td>841.0</td><td>839.0</td><td>845.0</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0	7.0	8.4	0.1	8	116.8	115.3	122.2	16	217.2	217.9	226.2	24	319.4	320.9	329.2	32	423.0	424.9	433.0	40	528.0	530.0	537.0	48	635.0	637.0	642.0	56	744.0	744.0	750.0	58	771.0	771.0	776.0	63	841.0	839.0	845.0	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																			
0	7.0	8.4	0.1																																																			
8	116.8	115.3	122.2																																																			
16	217.2	217.9	226.2																																																			
24	319.4	320.9	329.2																																																			
32	423.0	424.9	433.0																																																			
40	528.0	530.0	537.0																																																			
48	635.0	637.0	642.0																																																			
56	744.0	744.0	750.0																																																			
58	771.0	771.0	776.0																																																			
63	841.0	839.0	845.0																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

Model	DBS700B12	Temperature	25°C																																
Item	Efficiency (by Input Voltage)	Testing Circuitry	Figure A																																
Object	_____																																		
1. Graph			2. Values																																
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: ---□--- Load 50% —△— Load 100%</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>195</td> <td>90.2</td> <td>90.0</td> </tr> <tr> <td>200</td> <td>90.6</td> <td>90.1</td> </tr> <tr> <td>240</td> <td>90.5</td> <td>90.1</td> </tr> <tr> <td>280</td> <td>90.1</td> <td>90.1</td> </tr> <tr> <td>320</td> <td>89.6</td> <td>89.9</td> </tr> <tr> <td>360</td> <td>88.8</td> <td>89.7</td> </tr> <tr> <td>400</td> <td>88.1</td> <td>89.5</td> </tr> <tr> <td>420</td> <td>87.8</td> <td>89.4</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	195	90.2	90.0	200	90.6	90.1	240	90.5	90.1	280	90.1	90.1	320	89.6	89.9	360	88.8	89.7	400	88.1	89.5	420	87.8	89.4	--	-	-
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
195	90.2	90.0																																	
200	90.6	90.1																																	
240	90.5	90.1																																	
280	90.1	90.1																																	
320	89.6	89.9																																	
360	88.8	89.7																																	
400	88.1	89.5																																	
420	87.8	89.4																																	
--	-	-																																	

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	DBS700B12	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Efficiency (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 200V - - □ - - Input Volt. 280V - - ○ - - Input Volt. 400V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [200V] (%)</th> <th>Efficiency [280V] (%)</th> <th>Efficiency [400V] (%)</th> </tr> </thead> <tbody> <tr><td>0</td><td>81.8</td><td>82.9</td><td>78.2</td></tr> <tr><td>8</td><td>88.1</td><td>87.8</td><td>84.5</td></tr> <tr><td>16</td><td>90.0</td><td>89.6</td><td>87.3</td></tr> <tr><td>24</td><td>90.6</td><td>90.2</td><td>88.5</td></tr> <tr><td>32</td><td>90.8</td><td>90.4</td><td>89.2</td></tr> <tr><td>40</td><td>90.6</td><td>90.3</td><td>89.5</td></tr> <tr><td>48</td><td>90.1</td><td>90.1</td><td>89.4</td></tr> <tr><td>56</td><td>90.1</td><td>90.1</td><td>89.5</td></tr> <tr><td>58</td><td>89.7</td><td>89.9</td><td>89.2</td></tr> <tr><td>63</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [200V] (%)	Efficiency [280V] (%)	Efficiency [400V] (%)	0	81.8	82.9	78.2	8	88.1	87.8	84.5	16	90.0	89.6	87.3	24	90.6	90.2	88.5	32	90.8	90.4	89.2	40	90.6	90.3	89.5	48	90.1	90.1	89.4	56	90.1	90.1	89.5	58	89.7	89.9	89.2	63	-	-	-							
Load Current [A]	Efficiency [200V] (%)	Efficiency [280V] (%)	Efficiency [400V] (%)																																																			
0	81.8	82.9	78.2																																																			
8	88.1	87.8	84.5																																																			
16	90.0	89.6	87.3																																																			
24	90.6	90.2	88.5																																																			
32	90.8	90.4	89.2																																																			
40	90.6	90.3	89.5																																																			
48	90.1	90.1	89.4																																																			
56	90.1	90.1	89.5																																																			
58	89.7	89.9	89.2																																																			
63	-	-	-																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>8</td><td>81.8</td><td>82.9</td><td>78.2</td></tr> <tr><td>16</td><td>88.1</td><td>87.8</td><td>84.5</td></tr> <tr><td>24</td><td>90.0</td><td>89.6</td><td>87.3</td></tr> <tr><td>32</td><td>90.6</td><td>90.2</td><td>88.5</td></tr> <tr><td>40</td><td>90.8</td><td>90.4</td><td>89.2</td></tr> <tr><td>48</td><td>90.6</td><td>90.3</td><td>89.5</td></tr> <tr><td>56</td><td>90.1</td><td>90.1</td><td>89.4</td></tr> <tr><td>58</td><td>90.1</td><td>90.1</td><td>89.5</td></tr> <tr><td>63</td><td>89.7</td><td>89.9</td><td>89.2</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0	-	-	-	8	81.8	82.9	78.2	16	88.1	87.8	84.5	24	90.0	89.6	87.3	32	90.6	90.2	88.5	40	90.8	90.4	89.2	48	90.6	90.3	89.5	56	90.1	90.1	89.4	58	90.1	90.1	89.5	63	89.7	89.9	89.2	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																			
0	-	-	-																																																			
8	81.8	82.9	78.2																																																			
16	88.1	87.8	84.5																																																			
24	90.0	89.6	87.3																																																			
32	90.6	90.2	88.5																																																			
40	90.8	90.4	89.2																																																			
48	90.6	90.3	89.5																																																			
56	90.1	90.1	89.4																																																			
58	90.1	90.1	89.5																																																			
63	89.7	89.9	89.2																																																			
--	-	-	-																																																			


Note: Slanted line shows the range of the rated load current.

Model	DBS700B12	Temperature	25°C																																
Item	Line Regulation	Testing Circuitry	Figure A																																
Object	+12V58A																																		
1. Graph																																			
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend:</p> <ul style="list-style-type: none"> Load 50% (Dashed line with squares) Load 100% (Solid line with triangles) 																																			
2. Values																																			
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>195</td> <td>12.046</td> <td>12.043</td> </tr> <tr> <td>200</td> <td>12.046</td> <td>12.042</td> </tr> <tr> <td>240</td> <td>12.046</td> <td>12.041</td> </tr> <tr> <td>280</td> <td>12.045</td> <td>12.040</td> </tr> <tr> <td>320</td> <td>12.044</td> <td>12.038</td> </tr> <tr> <td>360</td> <td>12.044</td> <td>12.038</td> </tr> <tr> <td>400</td> <td>12.043</td> <td>12.038</td> </tr> <tr> <td>420</td> <td>12.042</td> <td>12.037</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	195	12.046	12.043	200	12.046	12.042	240	12.046	12.041	280	12.045	12.040	320	12.044	12.038	360	12.044	12.038	400	12.043	12.038	420	12.042	12.037	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
195	12.046	12.043																																	
200	12.046	12.042																																	
240	12.046	12.041																																	
280	12.045	12.040																																	
320	12.044	12.038																																	
360	12.044	12.038																																	
400	12.043	12.038																																	
420	12.042	12.037																																	
--	-	-																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			

COSEL

Model	DBS700B12	Temperature	25°C																																													
Item	Load Regulation	Testing Circuitry	Figure A																																													
Object	+12V58A																																															
1. Graph																																																
<p>—▲— Input Volt. 200V - - - □ - - Input Volt. 280V - - ○ - - Input Volt. 400V</p> <table border="1"> <caption>Data points from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Output Voltage [V] (Input 200V)</th> <th>Output Voltage [V] (Input 280V)</th> <th>Output Voltage [V] (Input 400V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>12.055</td><td>12.055</td><td>12.055</td></tr> <tr><td>8</td><td>12.051</td><td>12.051</td><td>12.050</td></tr> <tr><td>16</td><td>12.048</td><td>12.048</td><td>12.047</td></tr> <tr><td>24</td><td>12.047</td><td>12.046</td><td>12.044</td></tr> <tr><td>32</td><td>12.046</td><td>12.044</td><td>12.043</td></tr> <tr><td>40</td><td>12.045</td><td>12.043</td><td>12.041</td></tr> <tr><td>48</td><td>12.043</td><td>12.042</td><td>12.040</td></tr> <tr><td>56</td><td>12.042</td><td>12.040</td><td>12.038</td></tr> <tr><td>58</td><td>12.041</td><td>12.039</td><td>12.038</td></tr> <tr><td>63</td><td>12.040</td><td>12.038</td><td>12.036</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V] (Input 200V)	Output Voltage [V] (Input 280V)	Output Voltage [V] (Input 400V)	0	12.055	12.055	12.055	8	12.051	12.051	12.050	16	12.048	12.048	12.047	24	12.047	12.046	12.044	32	12.046	12.044	12.043	40	12.045	12.043	12.041	48	12.043	12.042	12.040	56	12.042	12.040	12.038	58	12.041	12.039	12.038	63	12.040	12.038	12.036	--	-	-	-
Load Current [A]	Output Voltage [V] (Input 200V)	Output Voltage [V] (Input 280V)	Output Voltage [V] (Input 400V)																																													
0	12.055	12.055	12.055																																													
8	12.051	12.051	12.050																																													
16	12.048	12.048	12.047																																													
24	12.047	12.046	12.044																																													
32	12.046	12.044	12.043																																													
40	12.045	12.043	12.041																																													
48	12.043	12.042	12.040																																													
56	12.042	12.040	12.038																																													
58	12.041	12.039	12.038																																													
63	12.040	12.038	12.036																																													
--	-	-	-																																													
2. Values																																																
Load Current [A]	Output Voltage [V]																																															
Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																														
0	12.055	12.055	12.055																																													
8	12.051	12.051	12.050																																													
16	12.048	12.048	12.047																																													
24	12.047	12.046	12.044																																													
32	12.046	12.044	12.043																																													
40	12.045	12.043	12.041																																													
48	12.043	12.042	12.040																																													
56	12.042	12.040	12.038																																													
58	12.041	12.039	12.038																																													
63	12.040	12.038	12.036																																													
--	-	-	-																																													

Note: Slanted line shows the range of the rated load current.

COSEL


Model	DBS700B12	Temperature	25°C																							
Item	Ripple Voltage (by Load Current)	Testing Circuitry	Figure B																							
Object	+12V58A																									
1. Graph			2. Values																							
<table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input Volt. 200V)</th> <th>Ripple Voltage [mV] (Input Volt. 400V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>8</td><td>8</td></tr> <tr><td>12</td><td>18</td><td>30</td></tr> <tr><td>24</td><td>18</td><td>30</td></tr> <tr><td>36</td><td>18</td><td>32</td></tr> <tr><td>48</td><td>18</td><td>32</td></tr> <tr><td>58</td><td>18</td><td>32</td></tr> <tr><td>61</td><td>20</td><td>32</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV] (Input Volt. 200V)	Ripple Voltage [mV] (Input Volt. 400V)	0	8	8	12	18	30	24	18	30	36	18	32	48	18	32	58	18	32	61	20	32
Load Current [A]	Ripple Voltage [mV] (Input Volt. 200V)	Ripple Voltage [mV] (Input Volt. 400V)																								
0	8	8																								
12	18	30																								
24	18	30																								
36	18	32																								
48	18	32																								
58	18	32																								
61	20	32																								
<p>Measured by 250 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>			<p>T1: Due to AC Input Line T2: Due to Switching</p>																							
<p>Fig. Complex Ripple Wave Form</p>			- 9 -																							
			BC-10384																							

COSEL

Model	DBS700B12																																							
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure B																																						
Object	+12V58A																																							
1.Graph																																								
<p>—△— Input Volt. 200V -○- Input Volt. 400V</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple-Noise [mV] (Input Volt. 200V)</th> <th>Ripple-Noise [mV] (Input Volt. 400V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>~25</td><td>~30</td></tr> <tr><td>12</td><td>~30</td><td>~40</td></tr> <tr><td>24</td><td>~30</td><td>~40</td></tr> <tr><td>36</td><td>~30</td><td>~45</td></tr> <tr><td>48</td><td>~30</td><td>~45</td></tr> <tr><td>58</td><td>~30</td><td>~45</td></tr> <tr><td>61</td><td>~30</td><td>~45</td></tr> <tr><td>60</td><td>~30</td><td>~45</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV] (Input Volt. 200V)	Ripple-Noise [mV] (Input Volt. 400V)	0	~25	~30	12	~30	~40	24	~30	~40	36	~30	~45	48	~30	~45	58	~30	~45	61	~30	~45	60	~30	~45											
Load Current [A]	Ripple-Noise [mV] (Input Volt. 200V)	Ripple-Noise [mV] (Input Volt. 400V)																																						
0	~25	~30																																						
12	~30	~40																																						
24	~30	~40																																						
36	~30	~45																																						
48	~30	~45																																						
58	~30	~45																																						
61	~30	~45																																						
60	~30	~45																																						
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 200 [V]</th> <th>Input Volt. 400 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>20</td><td>30</td></tr> <tr><td>12</td><td>25</td><td>40</td></tr> <tr><td>24</td><td>25</td><td>40</td></tr> <tr><td>36</td><td>30</td><td>45</td></tr> <tr><td>48</td><td>30</td><td>45</td></tr> <tr><td>58</td><td>30</td><td>45</td></tr> <tr><td>61</td><td>30</td><td>45</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 200 [V]	Input Volt. 400 [V]	0	20	30	12	25	40	24	25	40	36	30	45	48	30	45	58	30	45	61	30	45	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 200 [V]	Input Volt. 400 [V]																																						
0	20	30																																						
12	25	40																																						
24	25	40																																						
36	30	45																																						
48	30	45																																						
58	30	45																																						
61	30	45																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 250 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple Noise[mVp-p]</p>																																								
Fig.Complex Ripple Noise Wave Form																																								

Model	DBS700B12
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V58A

1. Graph



Testing Circuitry Figure B


2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-50	25	35
-40	25	30
-25	20	20
0	20	20
25	20	20
50	20	20
70	20	20
85	20	20
100	20	20
--	-	-
--	-	-

Measured by 250 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	DBS700B12
Item	Ambient Temperature Drift
Object	+12V58A
1.Graph	<p style="text-align: center;">  Input Volt. 200V Input Volt. 280V Input Volt. 400V </p>  <p style="text-align: center;">Output Voltage [V]</p> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: center;">Load 100%</p>

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
-50	11.960	11.958	11.958
-40	11.975	11.973	11.973
-20	12.002	12.000	11.999
0	12.024	12.021	12.020
25	12.044	12.041	12.039
40	12.053	12.049	12.048
55	12.060	12.057	12.054
70	12.067	12.065	12.063
85	12.077	12.075	12.073
100	12.092	12.090	12.088
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	DBS700B12	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+12V58A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 100°C

Input Voltage : 200 - 400V

Load Current : 0 - 58A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$


$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	100	200	0	12.115	±71	±0.6
Minimum Voltage	-40	400	58	11.973		


COSEL

Model	DBS700B12	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V58A																								
1. Graph			2. Values																						
<p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 280V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.040</td></tr> <tr><td>0.5</td><td>12.039</td></tr> <tr><td>1.0</td><td>12.039</td></tr> <tr><td>2.0</td><td>12.039</td></tr> <tr><td>3.0</td><td>12.039</td></tr> <tr><td>4.0</td><td>12.039</td></tr> <tr><td>5.0</td><td>12.039</td></tr> <tr><td>6.0</td><td>12.039</td></tr> <tr><td>7.0</td><td>12.039</td></tr> <tr><td>8.0</td><td>12.039</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	12.040	0.5	12.039	1.0	12.039	2.0	12.039	3.0	12.039	4.0	12.039	5.0	12.039	6.0	12.039	7.0	12.039	8.0	12.039
Time since start [H]	Output Voltage [V]																								
0.0	12.040																								
0.5	12.039																								
1.0	12.039																								
2.0	12.039																								
3.0	12.039																								
4.0	12.039																								
5.0	12.039																								
6.0	12.039																								
7.0	12.039																								
8.0	12.039																								

COSEL

Model	DBS700B12
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V58A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.


Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-50	171	177
-40	171	177
-20	171	177
0	171	177
25	170	177
40	170	177
55	169	176
70	168	176
85	167	175
100	166	174
--	-	-

COSEL

Model	DBS700B12	Temperature	25°C																																																										
Item	Overcurrent Protection	Testing Circuitry	Figure A																																																										
Object	+12V58A																																																												
1. Graph		Input Volt. 200V Input Volt. 280V Input Volt. 400V																																																											
			2. Values																																																										
<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>59.42</td><td>59.41</td><td>59.40</td></tr> <tr><td>11.4</td><td>70.98</td><td>70.93</td><td>72.18</td></tr> <tr><td>10.8</td><td>71.14</td><td>71.31</td><td>72.54</td></tr> <tr><td>9.6</td><td>71.67</td><td>72.07</td><td>73.77</td></tr> <tr><td>8.4</td><td>72.30</td><td>72.94</td><td>75.20</td></tr> <tr><td>7.2</td><td>72.95</td><td>74.10</td><td>77.17</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	12.0	59.42	59.41	59.40	11.4	70.98	70.93	72.18	10.8	71.14	71.31	72.54	9.6	71.67	72.07	73.77	8.4	72.30	72.94	75.20	7.2	72.95	74.10	77.17	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-		
Output Voltage [V]		Load Current [A]																																																											
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																										
12.0	59.42	59.41	59.40																																																										
11.4	70.98	70.93	72.18																																																										
10.8	71.14	71.31	72.54																																																										
9.6	71.67	72.07	73.77																																																										
8.4	72.30	72.94	75.20																																																										
7.2	72.95	74.10	77.17																																																										
--	-	-	-																																																										
--	-	-	-																																																										
--	-	-	-																																																										
--	-	-	-																																																										
--	-	-	-																																																										
--	-	-	-																																																										
--	-	-	-																																																										
<p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when the output voltage is from 7.2V to 0V.</p>																																																													

Model	DBS700B12	Testing Circuitry Figure A		
Item	Overvoltage Protection			
Object	+12V58A			
1.Graph	<p>—▲— Input Volt. 200V - - - ■ - - Input Volt. 280V - - ○ - - Input Volt. 400V</p>  <p>Operating Point [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 0%</p>	2.Values		

Note: Slanted line shows the range of the rated ambient temperature.

Ambient Temperature [°C]	Operating Point [V]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
-50	15.34	15.34	15.34
-40	15.45	15.45	15.45
-20	15.45	15.45	15.45
0	15.45	15.45	15.45
25	15.45	15.45	15.45
40	15.45	15.45	15.45
55	15.45	15.45	15.45
70	15.45	15.45	15.45
85	15.45	15.45	15.45
100	15.56	15.56	15.56
--	-	-	-




Figure A




Figure B

Co[μF]	
Base plate temperature:	Base plate temperature:
Tc=0°C ~ +100°C	Tc=-40°C ~ +100°C
2200	2200 × 3