

# TEST DATA OF DHS100B05

Regulated DC Power Supply  
May 22, 2009

Approved by : Tatsuya Mano  
Tatsuya Mano Design Manager

Prepared by : Shuuhei Sawada  
Shuuhei Sawada Design Engineer

**COSEL CO.,LTD.**



## CONTENTS

1. Input Current (by Input Voltage) . . . . .	1
2. Input Current (by Load Current) . . . . .	2
3. Input Power (by Load Current) . . . . .	3
4. Efficiency (by Input Voltage) . . . . .	4
5. Efficiency (by Load Current) . . . . .	5
6. Line Regulation . . . . .	6
7. Load Regulation . . . . .	7
8. Dynamic Load Response . . . . .	8
9. Ripple Voltage (by Load Current) . . . . .	9
10. Ripple-Noise . . . . .	10
11. Ripple Voltage (by Ambient Temperature) . . . . .	11
12. Ambient Temperature Drift . . . . .	12
13. Output Voltage Accuracy . . . . .	13
14. Time Lapse Drift . . . . .	14
15. Rise and Fall Time . . . . .	15
16. Minimum Input Voltage for Regulated Output Voltage . . . . .	16
17. Overcurrent Protection . . . . .	17
18. Overvoltage Protection . . . . .	18
19. Figure of Testing Circuitry . . . . .	19

(Final Page 19)

**COSEL**

Model	DHS100B05	Temperature Testing Circuitry	25°C Figure A																																																																															
Item	Input Current (by Input Voltage)																																																																																	
Object	—																																																																																	
1.Graph	<p>—△— Load 100%        - - -□--- Load 50%        - - -○--- Load 0%</p>																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>50</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>100</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>150</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>170</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>180</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>200</td><td>0.024</td><td>0.316</td><td>0.597</td></tr> <tr><td>250</td><td>0.025</td><td>0.243</td><td>0.480</td></tr> <tr><td>280</td><td>0.023</td><td>0.210</td><td>0.430</td></tr> <tr><td>300</td><td>0.022</td><td>0.204</td><td>0.403</td></tr> <tr><td>350</td><td>0.023</td><td>0.179</td><td>0.350</td></tr> <tr><td>400</td><td>0.023</td><td>0.161</td><td>0.309</td></tr> <tr><td>420</td><td>0.023</td><td>0.155</td><td>0.296</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	50	0.000	0.000	0.000	100	0.000	0.000	0.000	150	0.000	0.000	0.000	170	0.002	0.002	0.002	180	0.003	0.003	0.003	200	0.024	0.316	0.597	250	0.025	0.243	0.480	280	0.023	0.210	0.430	300	0.022	0.204	0.403	350	0.023	0.179	0.350	400	0.023	0.161	0.309	420	0.023	0.155	0.296	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0	0.000	0.000	0.000																																																																															
50	0.000	0.000	0.000																																																																															
100	0.000	0.000	0.000																																																																															
150	0.000	0.000	0.000																																																																															
170	0.002	0.002	0.002																																																																															
180	0.003	0.003	0.003																																																																															
200	0.024	0.316	0.597																																																																															
250	0.025	0.243	0.480																																																																															
280	0.023	0.210	0.430																																																																															
300	0.022	0.204	0.403																																																																															
350	0.023	0.179	0.350																																																																															
400	0.023	0.161	0.309																																																																															
420	0.023	0.155	0.296																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															

Note: Slanted line shows the range of the rated input voltage.

**COSEL**

Model	DHS100B05																																																			
Item	Input Current (by Load Current)																																																			
Object	<p>1. Graph</p> <p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.016</td><td>0.013</td><td>0.012</td></tr> <tr><td>4</td><td>0.118</td><td>0.087</td><td>0.065</td></tr> <tr><td>8</td><td>0.231</td><td>0.169</td><td>0.125</td></tr> <tr><td>12</td><td>0.346</td><td>0.251</td><td>0.183</td></tr> <tr><td>16</td><td>0.465</td><td>0.335</td><td>0.242</td></tr> <tr><td>20</td><td>0.588</td><td>0.421</td><td>0.302</td></tr> <tr><td>22</td><td>0.651</td><td>0.467</td><td>0.333</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0	0.016	0.013	0.012	4	0.118	0.087	0.065	8	0.231	0.169	0.125	12	0.346	0.251	0.183	16	0.465	0.335	0.242	20	0.588	0.421	0.302	22	0.651	0.467	0.333	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																			
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																	
0	0.016	0.013	0.012																																																	
4	0.118	0.087	0.065																																																	
8	0.231	0.169	0.125																																																	
12	0.346	0.251	0.183																																																	
16	0.465	0.335	0.242																																																	
20	0.588	0.421	0.302																																																	
22	0.651	0.467	0.333																																																	
--	-	-	-																																																	
--	-	-	-																																																	
--	-	-	-																																																	
--	-	-	-																																																	

Note: Slanted line shows the range of the rated load current.

Temperature 25°C  
Testing Circuitry Figure A

Load Current [A]	Input Current [A]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
0	0.016	0.013	0.012
4	0.118	0.087	0.065
8	0.231	0.169	0.125
12	0.346	0.251	0.183
16	0.465	0.335	0.242
20	0.588	0.421	0.302
22	0.651	0.467	0.333
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

**COSEL**

Model	DHS100B05	Temperature	25°C																																																			
Item	Input Power (by Load Current)	Testing Circuitry	Figure A																																																			
Object	_____																																																					
1. Graph		2. Values																																																				
<p>—▲— Input Volt. 200V        - - - ■ - - Input Volt. 280V        - - ○ - - Input Volt. 400V</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>3.3</td><td>3.8</td><td>4.8</td></tr> <tr><td>4</td><td>23.8</td><td>24.5</td><td>26.2</td></tr> <tr><td>8</td><td>46.3</td><td>47.6</td><td>50.1</td></tr> <tr><td>12</td><td>69.5</td><td>70.6</td><td>73.4</td></tr> <tr><td>16</td><td>93.5</td><td>94.2</td><td>97.2</td></tr> <tr><td>20</td><td>118.1</td><td>118.4</td><td>121.4</td></tr> <tr><td>22</td><td>130.6</td><td>131.3</td><td>133.7</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Power [W]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0	3.3	3.8	4.8	4	23.8	24.5	26.2	8	46.3	47.6	50.1	12	69.5	70.6	73.4	16	93.5	94.2	97.2	20	118.1	118.4	121.4	22	130.6	131.3	133.7	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																			
0	3.3	3.8	4.8																																																			
4	23.8	24.5	26.2																																																			
8	46.3	47.6	50.1																																																			
12	69.5	70.6	73.4																																																			
16	93.5	94.2	97.2																																																			
20	118.1	118.4	121.4																																																			
22	130.6	131.3	133.7																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

Model	DHS100B05	Temperature	25°C																																
Item	Efficiency (by Input Voltage)	Testing Circuitry	Figure A																																
Object	_____																																		
1.Graph			2.Values																																
<p>The graph plots Efficiency [%] on the y-axis (40 to 96) against Input Voltage [V] on the x-axis (100 to 500). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show a general downward trend as input voltage increases. A vertical slanted line is drawn through the data points at approximately 240V, indicating the rated input voltage range.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>195</td> <td>85.9</td> <td>84.8</td> </tr> <tr> <td>200</td> <td>85.8</td> <td>84.7</td> </tr> <tr> <td>240</td> <td>84.6</td> <td>84.4</td> </tr> <tr> <td>280</td> <td>83.3</td> <td>83.8</td> </tr> <tr> <td>320</td> <td>81.9</td> <td>83.0</td> </tr> <tr> <td>360</td> <td>80.3</td> <td>82.1</td> </tr> <tr> <td>400</td> <td>78.6</td> <td>81.3</td> </tr> <tr> <td>420</td> <td>77.0</td> <td>80.3</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	195	85.9	84.8	200	85.8	84.7	240	84.6	84.4	280	83.3	83.8	320	81.9	83.0	360	80.3	82.1	400	78.6	81.3	420	77.0	80.3	--	-	-
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
195	85.9	84.8																																	
200	85.8	84.7																																	
240	84.6	84.4																																	
280	83.3	83.8																																	
320	81.9	83.0																																	
360	80.3	82.1																																	
400	78.6	81.3																																	
420	77.0	80.3																																	
--	-	-																																	

Note: Slanted line shows the range of the rated input voltage.

**COSEL**


Model	DHS100B05	Temperature	25°C																																																			
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																			
Object																																																						
1.Graph	<p>—▲— Input Volt. 200V        - - □ - - Input Volt. 280V        - - ○ - - Input Volt. 400V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4</td><td>81.9</td><td>78.7</td><td>71.7</td></tr> <tr><td>8</td><td>85.2</td><td>81.8</td><td>76.5</td></tr> <tr><td>12</td><td>85.6</td><td>83.3</td><td>79.4</td></tr> <tr><td>16</td><td>85.3</td><td>83.8</td><td>80.4</td></tr> <tr><td>20</td><td>84.7</td><td>83.7</td><td>80.9</td></tr> <tr><td>22</td><td>84.3</td><td>83.2</td><td>80.9</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0	-	-	-	4	81.9	78.7	71.7	8	85.2	81.8	76.5	12	85.6	83.3	79.4	16	85.3	83.8	80.4	20	84.7	83.7	80.9	22	84.3	83.2	80.9	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																			
0	-	-	-																																																			
4	81.9	78.7	71.7																																																			
8	85.2	81.8	76.5																																																			
12	85.6	83.3	79.4																																																			
16	85.3	83.8	80.4																																																			
20	84.7	83.7	80.9																																																			
22	84.3	83.2	80.9																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

**COSEL**

Model	DHS100B05
Item	Line Regulation
Object	+5V20A

Temperature 25°C  
 Testing Circuitry Figure A

## 1. Graph




## 2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
195	5.050	5.048
200	5.050	5.048
240	5.050	5.048
280	5.050	5.048
320	5.050	5.049
360	5.050	5.049
400	5.050	5.049
420	5.050	5.049
--	-	-

Note: Slanted line shows the range of the rated input voltage.

**COSEL**

Model	DHS100B05	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+5V20A																																																					
1.Graph	<p>—△— Input Volt. 200V        - - -□--- Input Volt. 280V        - · -○--- Input Volt. 400V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>5.052</td><td>5.052</td><td>5.053</td></tr> <tr><td>4</td><td>5.050</td><td>5.050</td><td>5.051</td></tr> <tr><td>8</td><td>5.049</td><td>5.050</td><td>5.050</td></tr> <tr><td>12</td><td>5.049</td><td>5.049</td><td>5.050</td></tr> <tr><td>16</td><td>5.048</td><td>5.049</td><td>5.049</td></tr> <tr><td>20</td><td>5.048</td><td>5.048</td><td>5.049</td></tr> <tr><td>22</td><td>5.048</td><td>5.048</td><td>5.049</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0	5.052	5.052	5.053	4	5.050	5.050	5.051	8	5.049	5.050	5.050	12	5.049	5.049	5.050	16	5.048	5.049	5.049	20	5.048	5.048	5.049	22	5.048	5.048	5.049	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																			
0	5.052	5.052	5.053																																																			
4	5.050	5.050	5.051																																																			
8	5.049	5.050	5.050																																																			
12	5.049	5.049	5.050																																																			
16	5.048	5.049	5.049																																																			
20	5.048	5.048	5.049																																																			
22	5.048	5.048	5.049																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

**COSEL**


**COSEL**

Model DHS100B05

Item Ripple Voltage (by Load Current)

Object +5V20A

## 1. Graph



Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C  
Testing Circuitry Figure B

## 2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 200 [V]	Input Volt. 400 [V]
0	25	35
4	25	35
8	25	35
12	25	40
16	30	40
20	35	40
22	35	45
--	-	-
--	-	-
--	-	-
--	-	-

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

**coSEL**

Model	DHS100B05
Item	Ripple-Noise
Object	+5V20A

Temperature 25°C  
Testing Circuitry Figure B

## 1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

## 2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 200 [V]	Input Volt. 400 [V]
0	25	35
4	25	35
8	25	35
12	25	40
16	30	40
20	35	40
22	35	45
--	-	-
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

**COSEL**

Model	DHS100B05
Item	Ripple Voltage (by Ambient Temp.)
Object	+5V20A

## 1. Graph



Input Volt. 280V


Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

## Testing Circuitry Figure B

## 2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-50	40	40
-40	35	35
-20	35	35
0	35	35
25	35	35
40	35	35
55	35	35
70	30	30
85	30	30
100	30	30
--	-	-

**COSEL**

Testing Circuitry Figure A

## 2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
-50	5.039	5.039	5.040
-40	5.041	5.041	5.041
-20	5.043	5.042	5.042
0	5.044	5.044	5.044
25	5.048	5.049	5.049
40	5.050	5.051	5.051
55	5.052	5.052	5.052
70	5.052	5.052	5.052
85	5.051	5.051	5.051
100	5.050	5.050	5.050
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	DHS100B05	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+5V20A	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 100°C

Input Voltage : 200 - 400V

Load Current : 0 - 20A

\* Output Voltage Accuracy =  $\pm$ (Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


### 2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	70	200	0	5.058	±9	±0.2
Minimum Voltage	-40	200	20	5.041		

**COSEL**

Model	DHS100B05
Item	Time Lapse Drift
Object	+5V20A

## 1.Graph


 Temperature 25°C  
 Testing Circuitry Figure A

## 2.Values

Time since start [H]	Output Voltage [V]
0.0	5.049
0.5	5.049
1.0	5.049
2.0	5.049
3.0	5.049
4.0	5.049
5.0	5.049
6.0	5.049
7.0	5.049
8.0	5.049

**coSEL**


Model DHS100B05

Item Rise and Fall Time

Object +5V20A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		24.3	3.8	28.1	0.7	9.7	
100 %		24.3	4.3	28.6	0.6	4.8	



Model	DHS100B05																																								
Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A																																							
Object	+5V20A																																								
1.Graph																																									
			2.Values																																						
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-50</td><td>148</td><td>155</td> </tr> <tr> <td>-40</td><td>149</td><td>156</td> </tr> <tr> <td>-20</td><td>150</td><td>158</td> </tr> <tr> <td>0</td><td>152</td><td>160</td> </tr> <tr> <td>25</td><td>154</td><td>163</td> </tr> <tr> <td>40</td><td>154</td><td>164</td> </tr> <tr> <td>55</td><td>155</td><td>165</td> </tr> <tr> <td>70</td><td>155</td><td>166</td> </tr> <tr> <td>85</td><td>155</td><td>166</td> </tr> <tr> <td>100</td><td>154</td><td>166</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>				Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-50	148	155	-40	149	156	-20	150	158	0	152	160	25	154	163	40	154	164	55	155	165	70	155	166	85	155	166	100	154	166	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-50	148	155																																							
-40	149	156																																							
-20	150	158																																							
0	152	160																																							
25	154	163																																							
40	154	164																																							
55	155	165																																							
70	155	166																																							
85	155	166																																							
100	154	166																																							
--	-	-																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																									

**COSEL**

Model	DHS100B05	Temperature Testing Circuitry	25°C Figure A																																																							
Item	Overcurrent Protection																																																									
Object	+5V20A																																																									
1. Graph	<p>The graph plots Output Voltage [V] on the y-axis (0 to 8) against Load Current [A] on the x-axis (0 to 30). Three curves represent different input voltages: 200V (top), 280V (middle), and 400V (bottom). A horizontal line is drawn at approximately 5V. A slanted line connects points on the curves where the output voltage drops to 2.5V, indicating the range of the rated load current.</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>5.00</td><td>20.20</td><td>20.18</td><td>20.18</td></tr> <tr><td>4.75</td><td>23.95</td><td>24.61</td><td>26.21</td></tr> <tr><td>4.50</td><td>24.18</td><td>24.86</td><td>26.25</td></tr> <tr><td>4.00</td><td>24.63</td><td>25.35</td><td>27.09</td></tr> <tr><td>3.50</td><td>25.06</td><td>26.06</td><td>27.35</td></tr> <tr><td>3.00</td><td>25.62</td><td>26.51</td><td>27.82</td></tr> <tr><td>2.50</td><td>26.30</td><td>27.00</td><td>28.62</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	5.00	20.20	20.18	20.18	4.75	23.95	24.61	26.21	4.50	24.18	24.86	26.25	4.00	24.63	25.35	27.09	3.50	25.06	26.06	27.35	3.00	25.62	26.51	27.82	2.50	26.30	27.00	28.62	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																							
5.00	20.20	20.18	20.18																																																							
4.75	23.95	24.61	26.21																																																							
4.50	24.18	24.86	26.25																																																							
4.00	24.63	25.35	27.09																																																							
3.50	25.06	26.06	27.35																																																							
3.00	25.62	26.51	27.82																																																							
2.50	26.30	27.00	28.62																																																							
--	-	-	-																																																							
--	-	-	-																																																							
--	-	-	-																																																							
--	-	-	-																																																							
--	-	-	-																																																							

Note: Slanted line shows the range of the rated load current.

Intermittent operation occurs when the output voltage is from 2.5V to 0V.

**COSEL**

Model	DHS100B05	Testing Circuitry Figure A																																																					
Item	Ovv Protection																																																						
Object	+5V20A																																																						
1.Graph	<p>Operating Point [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 0%</p> <ul style="list-style-type: none"> <li>— △ — Input Volt. 200V</li> <li>- - □ - - Input Volt. 280V</li> <li>- - ○ - - Input Volt. 400V</li> </ul>																																																						
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr> <td>-50</td><td>6.97</td><td>6.97</td><td>6.97</td></tr> <tr> <td>-40</td><td>6.97</td><td>6.97</td><td>6.97</td></tr> <tr> <td>-20</td><td>6.97</td><td>6.97</td><td>6.97</td></tr> <tr> <td>0</td><td>6.97</td><td>6.97</td><td>6.97</td></tr> <tr> <td>25</td><td>6.97</td><td>6.97</td><td>6.97</td></tr> <tr> <td>40</td><td>6.97</td><td>6.97</td><td>6.97</td></tr> <tr> <td>55</td><td>6.97</td><td>6.97</td><td>6.97</td></tr> <tr> <td>70</td><td>6.97</td><td>6.97</td><td>6.97</td></tr> <tr> <td>85</td><td>6.97</td><td>6.97</td><td>6.97</td></tr> <tr> <td>100</td><td>6.97</td><td>6.97</td><td>6.97</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Ambient Temperature [°C]	Operating Point [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	-50	6.97	6.97	6.97	-40	6.97	6.97	6.97	-20	6.97	6.97	6.97	0	6.97	6.97	6.97	25	6.97	6.97	6.97	40	6.97	6.97	6.97	55	6.97	6.97	6.97	70	6.97	6.97	6.97	85	6.97	6.97	6.97	100	6.97	6.97	6.97	--	-	-	-
Ambient Temperature [°C]	Operating Point [V]																																																						
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																				
-50	6.97	6.97	6.97																																																				
-40	6.97	6.97	6.97																																																				
-20	6.97	6.97	6.97																																																				
0	6.97	6.97	6.97																																																				
25	6.97	6.97	6.97																																																				
40	6.97	6.97	6.97																																																				
55	6.97	6.97	6.97																																																				
70	6.97	6.97	6.97																																																				
85	6.97	6.97	6.97																																																				
100	6.97	6.97	6.97																																																				
--	-	-	-																																																				

Note: Slanted line shows the range of the rated ambient temperature.

COSEL





Figure A



- C1 : DHS100B24 4.7uF  
          DHS100B28 4.7uF  
          Others 10uF
- Co : DHS100B03 2200uF  
          DHS100B05 2200uF  
          DHS100B12 470uF  
          DHS100B15 470uF  
          DHS100B24 220uF  
          DHS100B28 220uF

Figure B