



TEST DATA OF DPF1000 (100V INPUT)

AC-DC Front End Module

Jul 29, 2005

Approved by : Kazuyoshi Shimano
Kazuyoshi Shimano Design Manager

Prepared by : Yukihiro Takehashi
Yukihiro Takehashi Design Engineer

コーセル株式会社
COSEL CO.,LTD.



CONTENTS

1. Output Voltage (by Input Voltage)	1
出力電圧 (入力電圧特性)	
2. Input Current (by Load Power)	2
入力電流 (負荷特性)	
3. Input Power (by Load Power)	3
入力電力 (負荷特性)	
4. Efficiency (by Input Voltage)	4
効率 (入力電圧特性)	
5. Efficiency (by Load Power)	5
効率 (負荷特性)	
6. Power Factor (by Input Voltage)	6
力率 (入力電圧特性)	
7. Power Factor (by Load Power)	7
力率 (負荷特性)	
8. Load Regulation	8
静的負荷変動	
9. Ripple Voltage (by Load Power)	9
リップル電圧 (負荷特性)	
10. Overvoltage Protection	10
過電圧保護	
11. Inrush Current	11
突入電流	
12. Dynamic Load Responce	12
動的負荷変動	
13. Rise and Fall Time	13
立上り、立下り時間	
14. Ambient Temperature Drift	14
周囲温度変動	
15. Minimum Input Voltage for Regulated Output Voltage	15
最低レギュレーション電圧	
16. Ripple Voltage (by Ambient Temperature)	16
リップル電圧 (周囲温度特性)	
17. Time Lapse Drift	17
経時ドリフト	
18. Output Voltage Accuracy	18
定電圧精度	
19. Harmonic Current	19
高調波電流	
20. Condensation	21
結露特性	
21. Leakage Current	22
漏洩電流	
22. Line Noise Tolerance	23
入力雑音耐量	
23. Figure of Testing Circuitry	24
測定回路図	

(Final Page 25)

COSEL


Model DPF1000

Item Output Voltage (by Input Voltage)
出力電圧 (入力電圧特性)

Object +360V 1000W

Temperature 25°C
Testing Circuitry Figure A

1. Graph



(注) 斜線は定格入力電圧範囲を示す。

2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
80	371.5	365.3
85	372.3	367.5
90	372.9	369.0
100	373.8	370.6
110	374.5	372.0
120	375.0	373.0
132	375.5	373.8
140	375.8	374.3
—	—	—

COSEL

COSEL

Model	DPF1000
Item	Input Current (by Load Power) 入力電流 (負荷特性)
Object	—

Temperature 25°C
Testing Circuitry Figure A

1. Graph

—△— Input Volt. 85V
—□— Input Volt. 100V
—○— Input Volt. 132V

Input Current [A]

Load Power [W]

Note: Slanted line shows the range of the rated load power.

(注) 斜線は定格負荷電力範囲を示す。

2. Values

Load Power [W]	Input Current [A]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0	0.24	0.25	0.29
50	0.82	0.75	0.57
150	2.09	1.83	1.38
300	3.99	3.41	2.59
450	5.99	4.98	3.74
600	7.89	6.67	5.00
750	9.91	8.26	6.19
850	11.16	9.39	6.99
1000	13.25	11.11	8.24
1100	14.79	12.19	9.09
—	—	—	—
—	—	—	—

COSEL

ModelDPF1000

ItemInput Power (by Load Power)
入力電力（負荷特性）

Object

1. Graph

△Input Volt. 85V

□Input Volt. 100V

○Input Volt. 132V

Input Power [W]

</

COSEL

Model

DPF1000

Item

Efficiency (by Input Voltage)
効率 (入力電圧特性)

Object


Temperature

25°C

Testing Circuitry

Figure A

1. Graph



Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。

2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
80	90.2	88.4
85	90.4	89.7
90	91.0	90.5
100	91.4	90.8
110	91.6	91.9
120	91.9	92.6
132	92.7	93.0
140	93.1	93.3
—	—	—

COSEL


Model DPF1000

Item Efficiency (by Load Power)
効率 (負荷特性)

Object

Temperature 25°C
Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated load power.

(注) 斜線は定格負荷電力範囲を示す。

2. Values

Load Power [W]	Efficiency [%]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
50	75.1	73.3	78.1
150	86.3	86.0	87.9
300	89.8	89.7	90.6
450	89.8	91.4	92.3
600	90.2	91.6	92.5
750	90.0	91.7	93.2
850	90.3	91.3	93.1
1000	89.7	90.8	93.0
1100	89.0	91.0	92.5
—	—	—	—
—	—	—	—
—	—	—	—

COSEL

Model DPF1000		Temperature 25°C Testing Circuitry Figure A																																
Item	Power Factor (by Input Voltage) 力率 (入力電圧特性)																																	
Object																																		
<p>1. Graph</p> <p>-----□----- Load 50% -----△----- Load 100%</p> <p>Power Factor</p> <p>Input Voltage [V]</p> <p>Note: Slanted line shows power factor correction range.</p> <p>(注) 斜線は力率改善入力電圧範囲を示す。</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th><th colspan="2">Power Factor</th></tr> <tr> <th>Load 50%</th><th>Load 100%</th></tr> </thead> <tbody> <tr><td>80</td><td>0.99</td><td>0.98</td></tr> <tr><td>85</td><td>0.99</td><td>0.99</td></tr> <tr><td>90</td><td>0.99</td><td>0.99</td></tr> <tr><td>100</td><td>0.99</td><td>0.99</td></tr> <tr><td>110</td><td>0.98</td><td>0.99</td></tr> <tr><td>120</td><td>0.98</td><td>0.99</td></tr> <tr><td>132</td><td>0.98</td><td>0.99</td></tr> <tr><td>140</td><td>0.98</td><td>0.99</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Input Voltage [V]	Power Factor		Load 50%	Load 100%	80	0.99	0.98	85	0.99	0.99	90	0.99	0.99	100	0.99	0.99	110	0.98	0.99	120	0.98	0.99	132	0.98	0.99	140	0.98	0.99	—	—	—
Input Voltage [V]	Power Factor																																	
	Load 50%	Load 100%																																
80	0.99	0.98																																
85	0.99	0.99																																
90	0.99	0.99																																
100	0.99	0.99																																
110	0.98	0.99																																
120	0.98	0.99																																
132	0.98	0.99																																
140	0.98	0.99																																
—	—	—																																

COSEL

Model		DPF1000		Temperature		25°C																																																								
Item		Power Factor (by Load Power) 力率 (負荷特性)		Testing Circuitry		Figure A																																																								
Object																																																														
1. Graph				2. Values																																																										
<div><div><div>△</div><div>Input Volt. 85V</div></div><div><div>□</div><div>Input Volt. 100V</div></div><div><div>○</div><div>Input Volt. 132V</div></div></div> <p>Power Factor</p> <p>Load Power [W]</p> <p>Note: Slanted line shows the range of the rated load power.</p> <p>(注)斜線は定格負荷電力範囲を示す。</p>				<table><tr><th rowspan="2">Load Power [W]</th><th colspan="3">Power Factor</th></tr><tr><th>Input Volt. 85[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 132[V]</th></tr><tr><td>50</td><td>0.96</td><td>0.91</td><td>0.85</td></tr><tr><td>150</td><td>0.98</td><td>0.95</td><td>0.94</td></tr><tr><td>300</td><td>0.98</td><td>0.98</td><td>0.97</td></tr><tr><td>450</td><td>0.99</td><td>0.99</td><td>0.98</td></tr><tr><td>600</td><td>0.99</td><td>0.99</td><td>0.98</td></tr><tr><td>750</td><td>0.99</td><td>0.99</td><td>0.99</td></tr><tr><td>850</td><td>0.99</td><td>0.99</td><td>0.99</td></tr><tr><td>1000</td><td>0.99</td><td>0.99</td><td>0.99</td></tr><tr><td>1100</td><td>0.99</td><td>0.99</td><td>0.99</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr></table>				Load Power [W]	Power Factor			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	50	0.96	0.91	0.85	150	0.98	0.95	0.94	300	0.98	0.98	0.97	450	0.99	0.99	0.98	600	0.99	0.99	0.98	750	0.99	0.99	0.99	850	0.99	0.99	0.99	1000	0.99	0.99	0.99	1100	0.99	0.99	0.99	—	—	—	—	—	—	—	—	—	—	—	—
Load Power [W]	Power Factor																																																													
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																											
50	0.96	0.91	0.85																																																											
150	0.98	0.95	0.94																																																											
300	0.98	0.98	0.97																																																											
450	0.99	0.99	0.98																																																											
600	0.99	0.99	0.98																																																											
750	0.99	0.99	0.99																																																											
850	0.99	0.99	0.99																																																											
1000	0.99	0.99	0.99																																																											
1100	0.99	0.99	0.99																																																											
—	—	—	—																																																											
—	—	—	—																																																											
—	—	—	—																																																											


COSEL

Model DPF1000
 Item Load Regulation
 静的負荷変動
 Object +360V1000W

Temperature 25°C
 Testing Circuitry Figure A

1. Graph

—△— Input Volt. 85 V
 -□- Input Volt. 100 V
 —○— Input Volt. 132 V




Note: Slanted line shows the range of the rated load power.

(注) 斜線は定格負荷電力範囲を示す。

2. Values

Load Power [W]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0	376.6	376.8	377.1
50	376.1	376.4	376.9
150	375.2	375.9	376.6
300	374.0	375.0	376.1
450	372.7	374.1	375.7
600	371.3	373.2	375.2
750	370.0	372.2	374.7
850	369.1	371.6	374.4
1000	367.5	370.6	373.8
1100	366.1	370.0	373.4

COSEL




COSEL

Model DPF1000

Item Overvoltage Protection
過電圧保護

Object +360V 1000W

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。


Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Operating Point [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-40	439.4	439.4	439.4
-20	438.4	438.4	438.4
0	438.0	438.0	437.8
25	437.3	437.3	437.4
45	437.0	436.9	436.9
65	436.7	436.6	436.5
85	436.2	436.0	435.8
90	435.8	435.7	435.5
—	—	—	—
—	—	—	—
—	—	—	—

COSEL

Model	DPF1000	Temperature 25°C Testing Circuitry Figure A
Item	Inrush Current 突入電流	
Object		



Input Voltage 100 V


Frequency 50 Hz

Load 100 %

Inrush Current

① 13.60 [A]

② 36.80 [A]





Model	DPF1000	Temperature	25°C
Item	Dynamic Load Response 動的負荷変動	Testing Circuitry	Figure A
Object	+360V1000W		

Input Volt. 100 V


Cycle 10 S

Load Current


Min. Load (0W) \longleftrightarrow

Load 100% (1000W)

20 V/div



200 ms/div




200 ms/div


Min. Load (0W) \longleftrightarrow

Load 50% (500W)

20 V/div



200 ms/div




200 ms/div

COSEL

Model	DPF1000	Temperature	25°C
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	+360V1000W		

1. Graph


Input Volt. 100 V



2. Values

[mS]

Load \ Time	T d	T r	T s	T h	T f
50 %	4.0	226.0	230.0	38.0	596.0
100 %	4.0	232.0	236.0	18.0	306.0



COSEL


Model DPF1000

Item Ambient Temperature Drift
周囲温度変動

Object +360V 1000W

Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-40	369.8	372.3	375.0
-20	368.8	371.4	374.2
0	368.5	371.1	374.0
25	367.6	370.5	373.5
45	367.3	370.2	373.3
65	366.5	369.6	373.1
85	365.8	369.0	372.6
90	365.3	368.8	372.5
—	—	—	—
—	—	—	—
—	—	—	—

COSEL


Model DPF1000

Item Minimum Input Voltage for Regulated Output Voltage
最低レギュレーション電圧

Object +360V 1000W

Testing Circuitry Figure A

1. Graph



2. Values


Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	80	80
-20	79	79
0	78	78
25	76	77
45	75	75
65	74	75
85	73	73
90	73	71
—	—	—
—	—	—
—	—	—

COSEL

Model	DPF1000
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)
Object	+360V1000W

Testing Circuitry Figure A


1. Graph



2. Values

Ambient Temperature [°C]	Ripple Output Voltage [V]	
	Load 50%	Load 100%
-40	6.8	10.0
-20	6.8	10.0
0	6.8	9.8
25	6.8	9.6
45	5.2	8.8
65	5.2	8.8
85	5.2	8.8
90	5.2	8.4
—	—	—
—	—	—
—	—	—

COSEL

COSEL																									
Model	DPF1000	Temperature 25℃ Testing Circuitry Figure A																							
Item	Time Lapse Drift 経時ドリフト																								
Object	+360 V 1000W																								
1. Graph		2.Values																							
<div><div>[V]</div><div></div><div>Output Voltage [V]</div><div>Time [H]</div></div> <div><div>Input Volt.</div><div>100V</div><div>Load</div><div>100%</div></div>		<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>370.60</td></tr><tr><td>0.5</td><td>370.24</td></tr><tr><td>1.0</td><td>370.38</td></tr><tr><td>2.0</td><td>370.55</td></tr><tr><td>3.0</td><td>370.49</td></tr><tr><td>4.0</td><td>370.41</td></tr><tr><td>5.0</td><td>370.39</td></tr><tr><td>6.0</td><td>370.33</td></tr><tr><td>7.0</td><td>370.76</td></tr><tr><td>8.0</td><td>370.60</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	370.60	0.5	370.24	1.0	370.38	2.0	370.55	3.0	370.49	4.0	370.41	5.0	370.39	6.0	370.33	7.0	370.76	8.0	370.60
Time since start [H]	Output Voltage [V]																								
0.0	370.60																								
0.5	370.24																								
1.0	370.38																								
2.0	370.55																								
3.0	370.49																								
4.0	370.41																								
5.0	370.39																								
6.0	370.33																								
7.0	370.76																								
8.0	370.60																								

COSEL

Model		DPF1000	Testing Circuitry Figure A
Item		Output Voltage Accuracy 定電圧精度	
Object		+360V1000W	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20~85 °C

Input Voltage : 85~132 V

Load Power : 0~1000 W

* Output Voltage Accuracy = $\pm (\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

1. 定電圧精度

周囲温度、入力電圧、負荷電力を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -20~85 °C

入力電圧 85~132 V

負荷電力 0~1000 W

* 定電圧精度(変動値) = $\pm (\text{出力電圧の最高値} - \text{出力電圧の最低値}) / 2$

* 定電圧精度(変動率) = $\frac{\text{変動値}}{\text{定格出力電圧}} \times 100$

2. Values


Item	Temperature [°C]	Input Voltage [V]	Output Power [W]	Output Voltage [V]	Output Voltage Accuracy [V]	Output Voltage Accuracy (Ration) [%]
Maximum Voltage	-20	132	0.0	377.18	±6	±1.7
Minimum Voltage	85	85	1000.0	365.30		

Model	DPF1000	Temperature	25°C
Item	Harmonic Current 高調波電流	Testing Circuitry	Figure E
Object			


1. Input Current Waveform

— Input Current
 Envelope of the input current to
 Classify equipment as Class D
 クラスDの機器を決定する為の入力電流包絡線

5A/div



2. Harmonic Current



— Harmonic Current
 高調波電流
 Limits for Class A equipment
 クラスAの機器に対する限度値

Conditions	Values
Input Voltage [V]	95.7
Input Current [A]	11.720
Active Power [W]	1115.5
Apparent Power [VA]	1121.3
Frequency [Hz]	60
Power Factor	0.995
Output Power [W]	1004.9


Harmonics order 高調波次数	Limits 限度値 [A]	Values 測定値 [A]
1	—	11.67000
2	—	0.01000
3	5.52769	0.98000
4	—	0.00000
5	2.73981	0.33000
6	—	0.00000
7	1.85057	0.15000
8	—	0.00000
9	0.96134	0.08000
10	—	0.00000
11	0.79310	0.08000
12	—	0.00000
13	0.50470	0.09000
14	—	0.00000
15	0.36050	0.10000
16	—	0.00000
17	0.31809	0.09000
18	—	0.00000
19	0.28461	0.07000
20	—	0.00000
21	0.25750	0.05000
22	—	0.00000
23	0.23511	0.03000
24	—	0.00000
25	0.21630	0.01000
26	—	0.00000
27	0.20028	0.01000
28	—	0.00000
29	0.18647	0.02000
30	—	0.00000
31	0.17444	0.03000
32	—	0.00000
33	0.16386	0.03000
34	—	0.00000
35	0.15450	0.03000
36	—	0.00000
37	0.14615	0.02000
38	—	0.00000
39	0.13865	0.01000
40	—	0.00000

Model	DPF1000	Temperature	25°C
Item	Harmonic Current 高調波電流	Testing Circuitry	Figure E
Object			


1. Input Current Waveform

— Input Current
 Envelope of the input current to
 Classify equipment as ClassD
 クラスDの機器を決定する為の入力電流包絡線

5A/div



2. Harmonic Current



— Harmonic Current
 高調波電流
 — Limits for Class A equipment
 クラスAの機器に対する限度値

Conditions	Values
Input Voltage [V]	98.2
Input Current [A]	5.710
Active Power [W]	555.3
Apparent Power [VA]	560.6
Frequency [Hz]	60
Power Factor	0.991
Output Power [W]	504.56

Harmonics order 高調波次数	Limits 限度値 [A]	Values 測定値 [A]
1	—	5.66000
2	—	0.01000
3	5.38697	0.69000
4	—	0.00000
5	2.67006	0.23000
6	—	0.00000
7	1.80346	0.17000
8	—	0.00000
9	0.93686	0.04000
10	—	0.00000
11	0.77291	0.04000
12	—	0.00000
13	0.49185	0.04000
14	—	0.00000
15	0.35132	0.07000
16	—	0.00000
17	0.30999	0.03000
18	—	0.00000
19	0.27736	0.02000
20	—	0.00000
21	0.25095	0.03000
22	—	0.00000
23	0.22912	0.04000
24	—	0.00000
25	0.21079	0.04000
26	—	0.00000
27	0.19518	0.02000
28	—	0.00000
29	0.18172	0.01000
30	—	0.00000
31	0.17000	0.01000
32	—	0.00000
33	0.15969	0.02000
34	—	0.00000
35	0.15057	0.03000
36	—	0.00000
37	0.14243	0.03000
38	—	0.00000
39	0.13512	0.03000
40	—	0.00000

COSEL

Model	DPF1000	Temperature	25℃
Item	Leakage Current 漏洩電流	Testing Circuitry	Figure B
Object	_____		

1. Results

Standards	Leakage Current [mA]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
(A) DEN-AN	0.18	0.20	0.27
(B) IEC60950	0.17	0.20	0.26

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 230 [V]	Input Volt. 264 [V]
(B) IEC60950	—	—	—

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

交流入力の高相について測定し、その大きい方を漏洩電流測定値とする。

COSEL




Model	DPF1000	Temperature 25°C Testing Circuitry Figure C
Item	Line Noise Tolerance 入力雑音耐量	
Object	+360V1000W	

1. Results

Pulse Width [nS]	MODE		No protection failure should occur 保護回路の誤動作がない	DC-like Regulation of Output Voltage 出力電圧の直流的変動
		POLARITY		
50	COMMON	+	OK	no fluctuation
		—	OK	no fluctuation
	NORMAL	+	OK	no fluctuation
		—	OK	no fluctuation
1000	COMMON	+	OK	no fluctuation
		—	OK	no fluctuation
	NORMAL	+	OK	no fluctuation
		—	OK	no fluctuation

2. Conditions

Input Voltage : 100 V
 Pulse Voltage : 2000 V
 Pulse Cycle : 10 mS
 Pulse Input Duration : 1 min. or more
 Load : 100 %






Figure C




Figure D




Figure E




Figure F