

COSEL

M T B F

(EIAJ RCR-9102)

|       |            |
|-------|------------|
| Model | EAC-16-472 |
|-------|------------|

| No.                                      | P a r t s              |            | Q' ty of Device | Failure rate [10 <sup>-6</sup> /H] | Reference |
|--|------------------------|------------|-----------------|------------------------------------|-----------|
| 1  | I C                    | Monolithic | 0               | 0. 0000                            |           |
| 2  |                        | Hybrid     | 0               | 0. 0000                            |           |
| 3  | Transistors            |            | 0               | 0. 0000                            |           |
| 4  | Diodes                 |            | 0               | 0. 0000                            |           |
| 5  | LED·Optocouplers       |            | 0               | 0. 0000                            |           |
| 6  | Resistors              |            | 1               | 0. 0031                            |           |
| 7  | Capacitors             |            | 4               | 0. 0314                            |           |
| 8  | Transformer·Choke Coil |            | 1               | 0. 0230                            |           |
| 9  | Connectors             |            | 18              | 0. 0553                            |           |
| 1 0                                      | Others                 |            | 0               | 0. 0000                            |           |
| Total Failure Rate [10 <sup>-6</sup> /H] |                        |            |                 | 0. 1128                            |           |

|                     |      |           |
|---------------------|------|-----------|
| M T B F             | [H]  | 8,870,000 |
| Ambient Temperature | [°C] | —         |
| Load Factor         | [%]  | —         |