

# TEST DATA OF EAM-03-□□□/ESM-03-□□□

## Noise Filter

Nov. 30. 2010

Approved by : Toshio Watanabe  
Toshio Watanabe

Design Manager

Prepared by : Tadayuki Noda  
Tadayuki Noda

Design Engineer

**COSEL CO.,LTD.**





## CONTENTS

1.Attenuation Characteristics .....	1
2.Pulse Attenuation Characteristics .....	4
3.Leakage Current .....	6
4.Figure of Testing Circuitry .....	7

(Final Page 8)



COSEL


Model	EAM-03-□□□/ESM-03-□□□	Temperature Testing Circuitry	25°C Figure A
Item	Attenuation Characteristics		
Object	<hr/>		



COSEL





Model	EAM-03-□□/ESM-03-□□	Temperature Testing Circuitry Figure A
Item	Attenuation Characteristics	
Object	—	




**COSEL**

**COSEL**

Model	EAM-03-□□□/ESM-03-□□□	Temperature Testing Circuitry	25°C Figure B
Item	Pulse Attenuation Characteristics		
Object	_____		



**COSEL**



Model	EAM-03-□□□/ESM-03-□□□	Temperature Testing Circuitry	25°C Figure C	
Item	Leakage Current			
Object	_____			

## 1. Results

[mA]

Model	Standards	Input Volt.				Note
		100 [V]	125 [V]	230 [V]	250 [V]	
EAM-03-000 ESM-03-000	UL1283	0.002	0.002	0.004	0.005	
EAM-03-101 ESM-03-101	UL1283	0.006	0.007	0.013	0.015	
EAM-03-221 ESM-03-221	UL1283	0.011	0.013	0.025	0.028	
EAM-03-331 ESM-03-331	UL1283	0.015	0.019	0.038	0.042	
EAM-03-471 ESM-03-471	UL1283	0.023	0.030	0.061	0.069	

## 2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL




Figure A - 1 Differential mode attenuation measurement




Figure A - 2 Common mode attenuation measurement

COSEL




Figure B Pulse attenuation measurement




Figure C Leakage current measurement ( UL1283 )