

TEST DATA OF EAM-20-□□□

Noise Filter

Mar. 3, 2010

Approved by : Toshio Watanabe Toshio Watanabe Design Manager

Prepared by : Tadayuki Noda
Tadayuki Noda Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Attenuation Characteristics	1
2.Pulse Attenuation Characteristics	4
3.Leakage Current	6
4.Figure of Testing Circuitry	7



(Final Page 8)

COSEL

Model EAM-20-□□□

Temperature 25°C
Testing Circuitry Figure A

Object





COSEL


Model EAM-20-□□□


Temperature 25°C
Testing Circuitry Figure A

Item Attenuation Characteristics

Object _____




COSEL

COSEL

COSEL

Model	EAM-20-□□□	Temperature Testing Circuitry Figure B
Item	Pulse Attenuation Characteristics	
Object	—	





Model	EAM-20-□□□	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure C
Object	_____		

1. Results

[mA]

Model	Standards	Input Volt.				Note
		100 [V]	125 [V]	230 [V]	250 [V]	
EAM-20-000	UL1283	0.002	0.002	0.004	0.005	
EAM-20-101	UL1283	0.006	0.007	0.013	0.015	
EAM-20-221	UL1283	0.011	0.013	0.025	0.028	
EAM-20-331	UL1283	0.015	0.019	0.038	0.042	
EAM-20-471	UL1283	0.023	0.030	0.061	0.069	

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL




Figure A - 1 Differential mode attenuation measurement




Figure A - 2 Common mode attenuation measurement

COSEL




Figure B Pulse attenuation measurement




Figure C Leakage current measurement (UL1283)