

DATA SHEET		Date	Jul.3,2000
Model	FCA75F-24	Temp.	25 °C
Test	Vibration/impact test 振動・衝撃試験	Humid.	45 %Rh
		Tested by	T.Okamoto

1. Method

Vibration/impact test complies with JIS C 0040 (Vibration), JIS C 0041 (Impact)
 JIS C 0040(振動), JIS C 0041(衝撃)に準ずる

(1) Installation method : Mountin screw installation
 取付方法 ねじ取付
2. Conditions

(1) Frequency : 10~55 Hz
 (Vibration) 3 minutes period
 周波数(振動)

(2) Direction・Time : 60 minutes along X, Y and Z axis (Vibration)
 方向・時間 11mS, once each X, Y and Z axis (Impact)
3. Conditions of Acceptability

(1) No degradation of performance or loss of function after test.
 試験後、諸機能が正常であること

(2) No remakably damage of appearance.
 外観上著しい損傷がないこと

(3) No looseness or a crack at solder joint.
 はんだ付け、圧着など電氣的接合部分にクラックや緩みの発生がないこと
4. Result

(1) Vibration limit test

No.	Gravity[G]	Result	Note
1	2	OK	
2		—	
3		—	

All are satisfactory to item 3: OK

(2) Impact test

No.	Gravity[G]	Result	Note
1	20	OK	
2		—	
3		—	

All are satisfactory to item 3: OK