



M T B F

(E I A J R C R - 9 1 0 2)

| | |
|-------|------------|
| Model | FSB-30-324 |
|-------|------------|

| No. | P a r t s | | Q'ty of Device | Failure rate [10 ⁻⁶ /H] | R e f e r e n c e |
|--|------------------------|------------|----------------|------------------------------------|-------------------|
| 1 | I C | Monolithic | 0 | 0.0000 | |
| 2 | | Hybrid | 0 | 0.0000 | |
| 3 | T r a n s i s t o r s | | 0 | 0.0000 | |
| 4 | D i o d e s | | 0 | 0.0000 | |
| 5 | LED•Optocouplers | | 0 | 0.0000 | |
| 6 | R e s i s t o r s | | 6 | 0.0186 | |
| 7 | C a p a c i t o r s | | 13 | 0.1079 | |
| 8 | Transformer•Choke Coil | | 2 | 0.0460 | |
| 9 | C o n n e c t o r s | | 91 | 0.3818 | |
| 10 | O t h e r s | | 2 | 0.0060 | |
| Total Failure Rate [10 ⁻⁶ /H] | | | | 0.5603 | |

| | | |
|---------------------|-----|-----------|
| M T B F | [H] | 1,785,000 |
| Ambient Temperature | [℃] | — |
| Load Factor | [%] | — |