

TEST DATA OF GHA500F-15

Regulated DC Power Supply
April 19, 2013

Approved by : Yoshiaki Shimizu
Yoshiaki Shimizu Design Manager

Prepared by : Soshi Nakamura
Soshi Nakamura Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Load Current)	1
2.Input Power (by Load Current)	2
3.Efficiency (by Input Voltage)	3
4.Efficiency (by Load Current)	4
5.Power Factor (by Input Voltage)	5
6.Power Factor (by Load Current)	6
7.Inrush Current	7
8.Leakage Current	8
9.Line Regulation	9
10.Load Regulation	10
11.Dynamic Load Response	11
12.Ripple Voltage (by Load Current)	12
13.Ripple-Noise	13
14.Ripple Voltage (by Ambient Temperature)	14
15.Ambient Temperature Drift	15
16.Output Voltage Accuracy	16
17.Time Lapse Drift	17
18.Rise and Fall Time	18
19.Hold-Up Time	19
20.Instantaneous Interruption Compensation	20
21.Minimum Input Voltage for Regulated Output Voltage	21
22.Overcurrent Protection	22
23.Ovvoltage Protection	23
24.Figure of Testing Circuitry	24

(Final Page 24)

COSEL

Model	GHA500F-15	Temperature	25°C																																																			
Item	Input Current (by Load Current)	Testing Circuitry	Figure A																																																			
Object	_____																																																					
1.Graph		2.Values																																																				
<p>Input Current [A]</p> <p>Load Current [A]</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 120[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.152</td><td>0.099</td><td>0.086</td></tr> <tr><td>4.4</td><td>0.801</td><td>0.657</td><td>0.449</td></tr> <tr><td>8.8</td><td>1.508</td><td>1.244</td><td>0.711</td></tr> <tr><td>13.4</td><td>2.265</td><td>1.875</td><td>1.028</td></tr> <tr><td>17.7</td><td>2.985</td><td>2.472</td><td>1.322</td></tr> <tr><td>22.0</td><td>3.722</td><td>3.074</td><td>1.622</td></tr> <tr><td>24.0</td><td>4.066</td><td>3.357</td><td>1.764</td></tr> <tr><td>26.7</td><td>4.544</td><td>3.747</td><td>1.957</td></tr> <tr><td>29.4</td><td>5.023</td><td>4.136</td><td>2.152</td></tr> <tr><td>33.4</td><td>5.752</td><td>4.724</td><td>2.444</td></tr> <tr><td>36.7</td><td>-</td><td>5.221</td><td>2.689</td></tr> </tbody> </table>		Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 120[V]	Input Volt. 230[V]	0.0	0.152	0.099	0.086	4.4	0.801	0.657	0.449	8.8	1.508	1.244	0.711	13.4	2.265	1.875	1.028	17.7	2.985	2.472	1.322	22.0	3.722	3.074	1.622	24.0	4.066	3.357	1.764	26.7	4.544	3.747	1.957	29.4	5.023	4.136	2.152	33.4	5.752	4.724	2.444	36.7	-	5.221	2.689
Load Current [A]	Input Current [A]																																																					
	Input Volt. 100[V]	Input Volt. 120[V]	Input Volt. 230[V]																																																			
0.0	0.152	0.099	0.086																																																			
4.4	0.801	0.657	0.449																																																			
8.8	1.508	1.244	0.711																																																			
13.4	2.265	1.875	1.028																																																			
17.7	2.985	2.472	1.322																																																			
22.0	3.722	3.074	1.622																																																			
24.0	4.066	3.357	1.764																																																			
26.7	4.544	3.747	1.957																																																			
29.4	5.023	4.136	2.152																																																			
33.4	5.752	4.724	2.444																																																			
36.7	-	5.221	2.689																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL


Model GHA500F-15

Item Input Power (by Load Current)

Object _____

1. Graph

—△— Input Volt. 100V
 - - -□--- Input Volt. 120V
 - - -○--- Input Volt. 230V



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
 Testing Circuitry Figure A

2. Values

Load Current [A]	Input Power [W]		
	Input Volt. 100[V]	Input Volt. 120[V]	Input Volt. 230[V]
0.0	6.0	6.7	7.3
4.4	78.7	76.8	80.7
8.8	149.8	148.1	152.2
13.4	225.8	224.0	224.7
17.7	297.8	295.2	293.6
22.0	371.4	367.8	363.6
24.0	406.1	401.9	396.4
26.7	453.6	448.4	441.0
29.4	501.7	495.4	486.0
33.4	574.4	565.9	554.0
36.7	-	625.5	610.0

COSEL

Model	GHA500F-15	Temperature	25°C																																																			
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																			
Object																																																						
1.Graph		2.Values																																																				
<p>The graph shows efficiency increasing with load current. At low currents, efficiency is lower (around 84% for 100V at 5A). As load current increases, efficiency rises sharply, reaching nearly 100% around 25A. A slanted line on the right side of the graph marks the rated load current range.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 120[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>4.4</td><td>84.8</td><td>86.9</td><td>82.8</td></tr> <tr> <td>8.8</td><td>89.0</td><td>90.1</td><td>87.6</td></tr> <tr> <td>13.4</td><td>89.9</td><td>90.6</td><td>90.4</td></tr> <tr> <td>17.7</td><td>90.0</td><td>90.8</td><td>91.3</td></tr> <tr> <td>22.0</td><td>89.8</td><td>90.7</td><td>91.7</td></tr> <tr> <td>24.0</td><td>89.6</td><td>90.5</td><td>91.8</td></tr> <tr> <td>26.7</td><td>89.2</td><td>90.3</td><td>91.8</td></tr> <tr> <td>29.4</td><td>88.9</td><td>90.0</td><td>91.7</td></tr> <tr> <td>33.4</td><td>88.1</td><td>89.9</td><td>91.9</td></tr> <tr> <td>36.7</td><td>-</td><td>88.9</td><td>91.2</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 120[V]	Input Volt. 230[V]	0.0	-	-	-	4.4	84.8	86.9	82.8	8.8	89.0	90.1	87.6	13.4	89.9	90.6	90.4	17.7	90.0	90.8	91.3	22.0	89.8	90.7	91.7	24.0	89.6	90.5	91.8	26.7	89.2	90.3	91.8	29.4	88.9	90.0	91.7	33.4	88.1	89.9	91.9	36.7	-	88.9	91.2
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 120[V]	Input Volt. 230[V]																																																			
0.0	-	-	-																																																			
4.4	84.8	86.9	82.8																																																			
8.8	89.0	90.1	87.6																																																			
13.4	89.9	90.6	90.4																																																			
17.7	90.0	90.8	91.3																																																			
22.0	89.8	90.7	91.7																																																			
24.0	89.6	90.5	91.8																																																			
26.7	89.2	90.3	91.8																																																			
29.4	88.9	90.0	91.7																																																			
33.4	88.1	89.9	91.9																																																			
36.7	-	88.9	91.2																																																			

Note: Slanted line shows the range of the rated load current.

COSEL

Model	GHA500F-15																																	
Item	Efficiency (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	_____	_____																																
1.Graph																																		
<p>The graph plots Efficiency [%] on the y-axis (44 to 100) against Input Voltage [V] on the x-axis (50 to 300). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show efficiency increasing slightly with input voltage. Two vertical slanted lines indicate the rated input voltage range.</p>																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>90</td><td>89.8</td><td>88.3 ※1</td> </tr> <tr> <td>100</td><td>90.2</td><td>88.9 ※2</td> </tr> <tr> <td>115</td><td>90.7</td><td>89.2</td> </tr> <tr> <td>120</td><td>90.9</td><td>89.9</td> </tr> <tr> <td>200</td><td>91.3</td><td>91.2</td> </tr> <tr> <td>230</td><td>91.2</td><td>91.9</td> </tr> <tr> <td>264</td><td>91.1</td><td>92.0</td> </tr> <tr> <td>280</td><td>91.2</td><td>91.7</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	90	89.8	88.3 ※1	100	90.2	88.9 ※2	115	90.7	89.2	120	90.9	89.9	200	91.3	91.2	230	91.2	91.9	264	91.1	92.0	280	91.2	91.7	--	-	-
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
90	89.8	88.3 ※1																																
100	90.2	88.9 ※2																																
115	90.7	89.2																																
120	90.9	89.9																																
200	91.3	91.2																																
230	91.2	91.9																																
264	91.1	92.0																																
280	91.2	91.7																																
--	-	-																																
※1:Load 80% ※2:Load 88%																																		
Note: Slanted line shows the range of the rated input voltage.																																		

COSEL




Model	GHA500F-15	Temperature 25°C																																
Item	Power Factor (by Input Voltage)	Testing Circuitry Figure A																																
Object	<hr/>																																	
1.Graph	<p>1. Graph</p>																																	
2.Values	<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>90</td><td>0.999</td><td>0.999 ※1</td> </tr> <tr> <td>100</td><td>0.998</td><td>0.999 ※2</td> </tr> <tr> <td>115</td><td>0.996</td><td>0.999</td> </tr> <tr> <td>120</td><td>0.996</td><td>0.999</td> </tr> <tr> <td>200</td><td>0.976</td><td>0.991</td> </tr> <tr> <td>230</td><td>0.962</td><td>0.986</td> </tr> <tr> <td>264</td><td>0.946</td><td>0.978</td> </tr> <tr> <td>280</td><td>0.934</td><td>0.898</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>		Input Voltage [V]	Power Factor		Load 50%	Load 100%	90	0.999	0.999 ※1	100	0.998	0.999 ※2	115	0.996	0.999	120	0.996	0.999	200	0.976	0.991	230	0.962	0.986	264	0.946	0.978	280	0.934	0.898	--	-	-
Input Voltage [V]	Power Factor																																	
	Load 50%	Load 100%																																
90	0.999	0.999 ※1																																
100	0.998	0.999 ※2																																
115	0.996	0.999																																
120	0.996	0.999																																
200	0.976	0.991																																
230	0.962	0.986																																
264	0.946	0.978																																
280	0.934	0.898																																
--	-	-																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>		※1: Load 80% ※2: Load 88%																																

COSEL

Model	GHA500F-15																																																				
Item	Power Factor (by Load Current)	Temperature 25°C Testing Circuitry Figure A																																																			
Object																																																					
1.Graph																																																					
<p style="text-align: center;"> —△— Input Volt. 100V ---□--- Input Volt. 120V ---○--- Input Volt. 230V </p> <p>Note: Slanted line shows the range of the rated load current.</p>																																																					
2.Values																																																					
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 120[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>0.390</td><td>0.564</td><td>0.368</td></tr> <tr> <td>4.4</td><td>0.981</td><td>0.974</td><td>0.780</td></tr> <tr> <td>8.8</td><td>0.993</td><td>0.991</td><td>0.930</td></tr> <tr> <td>13.4</td><td>0.997</td><td>0.996</td><td>0.950</td></tr> <tr> <td>17.7</td><td>0.998</td><td>0.996</td><td>0.965</td></tr> <tr> <td>22.0</td><td>0.999</td><td>0.997</td><td>0.974</td></tr> <tr> <td>24.0</td><td>0.999</td><td>0.998</td><td>0.977</td></tr> <tr> <td>26.7</td><td>0.999</td><td>0.998</td><td>0.979</td></tr> <tr> <td>29.4</td><td>0.999</td><td>0.999</td><td>0.982</td></tr> <tr> <td>33.4</td><td>0.999</td><td>0.999</td><td>0.986</td></tr> <tr> <td>36.7</td><td>-</td><td>0.999</td><td>0.985</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 120[V]	Input Volt. 230[V]	0.0	0.390	0.564	0.368	4.4	0.981	0.974	0.780	8.8	0.993	0.991	0.930	13.4	0.997	0.996	0.950	17.7	0.998	0.996	0.965	22.0	0.999	0.997	0.974	24.0	0.999	0.998	0.977	26.7	0.999	0.998	0.979	29.4	0.999	0.999	0.982	33.4	0.999	0.999	0.986	36.7	-	0.999	0.985
Load Current [A]	Power Factor																																																				
	Input Volt. 100[V]	Input Volt. 120[V]	Input Volt. 230[V]																																																		
0.0	0.390	0.564	0.368																																																		
4.4	0.981	0.974	0.780																																																		
8.8	0.993	0.991	0.930																																																		
13.4	0.997	0.996	0.950																																																		
17.7	0.998	0.996	0.965																																																		
22.0	0.999	0.997	0.974																																																		
24.0	0.999	0.998	0.977																																																		
26.7	0.999	0.998	0.979																																																		
29.4	0.999	0.999	0.982																																																		
33.4	0.999	0.999	0.986																																																		
36.7	-	0.999	0.985																																																		

COSEL

Model	GHA500F-15	Temperature	25°C
Item	Inrush Current	Testing Circuitry	Figure A
Object	_____		



※1 The specification of the primary inrush current means that the surge current to a built-in noise filter (0.2msec or less:waveform ③) is excluded.



Model	GHA500F-15	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	_____		

1. Results

Standards		Input Volt.			Note
		100 [V]	120 [V]	240 [V]	
IEC60601	Both phases	0.08	0.09	0.17	Operation
	One of phases	0.14	0.15	0.31	Stand by

The value for "One of phases" is the reference value only.


2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSSEL

Model	GHA500F-15																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+15V33.4A																																	
1.Graph																																		
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: - - - Load 50% □ Load 100%</p>																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>90</td><td>15.199</td><td>15.197 ※1</td></tr> <tr><td>100</td><td>15.199</td><td>15.196 ※2</td></tr> <tr><td>115</td><td>15.199</td><td>15.194</td></tr> <tr><td>120</td><td>15.200</td><td>15.196</td></tr> <tr><td>200</td><td>15.199</td><td>15.196</td></tr> <tr><td>230</td><td>15.199</td><td>15.196</td></tr> <tr><td>264</td><td>15.200</td><td>15.196</td></tr> <tr><td>280</td><td>15.199</td><td>15.197</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	90	15.199	15.197 ※1	100	15.199	15.196 ※2	115	15.199	15.194	120	15.200	15.196	200	15.199	15.196	230	15.199	15.196	264	15.200	15.196	280	15.199	15.197	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
90	15.199	15.197 ※1																																
100	15.199	15.196 ※2																																
115	15.199	15.194																																
120	15.200	15.196																																
200	15.199	15.196																																
230	15.199	15.196																																
264	15.200	15.196																																
280	15.199	15.197																																
--	-	-																																
※1: Load 80% ※2: Load 88%																																		
Note: Slanted line shows the range of the rated input voltage.																																		

COSEL

Model	GHA500F-15		
Item	Load Regulation		
Object	+15V33.4A		
1.Graph	<p style="text-align: center;"> —△— Input Volt. 100V ---□--- Input Volt. 120V ---○--- Input Volt. 230V </p> 		
Temperature	25°C		
Testing Circuitry	Figure A		
2.Values			
Load Current [A]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 120[V]	Input Volt. 230[V]
0.0	15.204	15.204	15.204
4.4	15.202	15.202	15.202
8.8	15.201	15.201	15.201
13.4	15.200	15.200	15.200
17.7	15.199	15.199	15.199
22.0	15.198	15.198	15.198
24.0	15.198	15.198	15.198
26.7	15.197	15.197	15.197
29.4	15.197	15.197	15.197
33.4	15.196	15.196	15.196
--	-	-	-


Note: Slanted line shows the range of the rated load current.

COSEL

Model	GHA500F-15	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+15V 33.4A		

Input Volt. 120V
Cycle 1000ms


Load Current




33.4A / 50μs

Min.Load (0A)↔
Load 100%(33.4A)

500 mV/div




1 ms/div




1 ms/div

Min.Load (0A)↔
Load 50%(16.7A)

200 mV/div




1 ms/div




1 ms/div

Load 50% (16.7A)↔
Load 100% (33.4A)

200 mV/div



1 ms/div




1 ms/div

COSEL

Model	GHA500F-15
Item	Ripple Voltage (by Load Current)
Object	+15V33.4A

Temperature 25°C
Testing Circuitry Figure A

1.Graph



2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 120 [V]	Input Volt. 230 [V]
0.0	10	10
4.4	40	45
8.8	45	45
13.4	60	60
17.7	70	70
22.0	75	80
24.0	80	80
26.7	95	100
29.4	100	100
33.4	100	105
36.7	105	115

Measured by 20 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

COSEL

Model	GHA500F-15
Item	Ripple-Noise
Object	+15V33.4A

 Temperature 25°C
 Testing Circuitry Figure A

1. Graph



2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 120 [V]	Input Volt. 230 [V]
0.0	15	15
4.4	45	50
8.8	55	60
13.4	70	70
17.7	80	85
22.0	90	90
24.0	90	90
26.7	100	100
29.4	120	120
33.4	125	125
36.7	130	130

Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.





Fig.Complex Ripple Noise Wave Form

COSEL

Model	GHA500F-15
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V33.4A

1. Graph



Measured by 20 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 120 [V]	Input Volt. 230 [V]
-30	130	140
-20	130	130
0	120	130
25	100	105
50	95	95
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	GHA500F-15
Item	Ambient Temperature Drift
Object	+15V33.4A
1.Graph	
<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Input Volt. 100V</p> <p>Input Volt. 120V</p> <p>Input Volt. 230V</p>	
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>	

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 120[V]	Input Volt. 230[V]
-20	15.148	15.150	15.149
-10	15.166	15.167	15.167
0	15.176	15.176	15.177
10	15.189	15.186	15.190
20	15.197	15.198	15.198
25	15.201	15.202	15.203
30	15.205	15.206	15.206
40	15.211	15.211	15.212
50	15.214	15.214	15.214
60	15.215	15.215	15.215
--	-	-	-

Note: In case of Input Volt. 100V, Load 88%.
Other case Load 100%.



Model	GHA500F-15	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+15V33.4A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 50°C

Input Voltage : 115 - 264V

Load Current : 0 - 33.4A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	50	230	0	15.223	±38	±0.3
Minimum Voltage	-20	115	33.4	15.148		


COSEL

Model	GHA500F-15	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+15V33.4A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 230V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.196</td></tr> <tr><td>0.5</td><td>15.211</td></tr> <tr><td>1.0</td><td>15.211</td></tr> <tr><td>2.0</td><td>15.211</td></tr> <tr><td>3.0</td><td>15.211</td></tr> <tr><td>4.0</td><td>15.211</td></tr> <tr><td>5.0</td><td>15.211</td></tr> <tr><td>6.0</td><td>15.211</td></tr> <tr><td>7.0</td><td>15.211</td></tr> <tr><td>8.0</td><td>15.210</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	15.196	0.5	15.211	1.0	15.211	2.0	15.211	3.0	15.211	4.0	15.211	5.0	15.211	6.0	15.211	7.0	15.211	8.0	15.210
Time since start [H]	Output Voltage [V]																								
0.0	15.196																								
0.5	15.211																								
1.0	15.211																								
2.0	15.211																								
3.0	15.211																								
4.0	15.211																								
5.0	15.211																								
6.0	15.211																								
7.0	15.211																								
8.0	15.210																								
<p>* The characteristic of AC120V is equal.</p>																									

COSEL


Model	GHA500F-15	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+15V33.4A		

1. Graph



2. Values

Input Volt.	Time	Td	Tr	Ts	Th	Tf	[ms]
120 V		473.0	16.5	489.5	17.8	1.4	
230 V		471.0	16.5	487.5	17.6	1.4	




COSEL

Model	GHA500F-15
Item	Hold-Up Time
Object	+15V33.4A

Temperature 25°C
Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
90	34	20 ※1
100	34	16 ※2
115	34	16
120	34	16
200	34	16
230	34	16
264	34	16
280	34	16
--	-	-

※1: Load 80%

※2: Load 88%

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
Note: Slanted line shows the range of the rated input voltage.

COSEL


Model	GHA500F-15																																																					
Item	Instantaneous Interruption Compensation																																																					
Object	+15V33.4A																																																					
1.Graph	<p style="text-align: center;"> —△— Input Volt. 100V ---□--- Input Volt. 120V ---○--- Input Volt. 230V </p>																																																					
2.Values	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 120[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>4.4</td><td>115</td><td>115</td><td>119</td></tr> <tr> <td>8.8</td><td>60</td><td>60</td><td>61</td></tr> <tr> <td>13.4</td><td>39</td><td>39</td><td>39</td></tr> <tr> <td>17.7</td><td>30</td><td>30</td><td>30</td></tr> <tr> <td>22.0</td><td>22</td><td>22</td><td>23</td></tr> <tr> <td>24.0</td><td>21</td><td>22</td><td>22</td></tr> <tr> <td>26.7</td><td>17</td><td>20</td><td>20</td></tr> <tr> <td>29.4</td><td>16</td><td>18</td><td>17</td></tr> <tr> <td>33.4</td><td>13</td><td>16</td><td>16</td></tr> <tr> <td>36.7</td><td>-</td><td>14</td><td>14</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 120[V]	Input Volt. 230[V]	0.0	-	-	-	4.4	115	115	119	8.8	60	60	61	13.4	39	39	39	17.7	30	30	30	22.0	22	22	23	24.0	21	22	22	26.7	17	20	20	29.4	16	18	17	33.4	13	16	16	36.7	-	14	14
Load Current [A]	Time [ms]																																																					
	Input Volt. 100[V]	Input Volt. 120[V]	Input Volt. 230[V]																																																			
0.0	-	-	-																																																			
4.4	115	115	119																																																			
8.8	60	60	61																																																			
13.4	39	39	39																																																			
17.7	30	30	30																																																			
22.0	22	22	23																																																			
24.0	21	22	22																																																			
26.7	17	20	20																																																			
29.4	16	18	17																																																			
33.4	13	16	16																																																			
36.7	-	14	14																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						



Model	GHA500F-15
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V33.4A

Testing Circuitry Figure A

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	73	83
-10	73	79
0	74	82
10	74	85
20	74	87
25	74	87
30	73	87
40	73	87
50	73	89
60	74	89
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

COSEL


Model	GHA500F-15																																																									
Item	Overcurrent Protection	Temperature 25°C Testing Circuitry Figure A																																																								
Object	+15V33.4A																																																									
1.Graph																																																										
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 120V</p> <p>Input Volt. 230V</p>																																																										
<p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when overcurrent protection is activated.</p>																																																										
2.Values																																																										
<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="2">Load Current [A]</th> </tr> <tr> <th>Input Volt. 120[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>15</td><td>38.41</td><td>38.40</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]		Input Volt. 120[V]	Input Volt. 230[V]	15	38.41	38.40	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 120[V]	Input Volt. 230[V]																																																								
15	38.41	38.40																																																								
--	-	-																																																								
--	-	-																																																								
--	-	-																																																								
--	-	-																																																								
--	-	-																																																								
--	-	-																																																								
--	-	-																																																								
--	-	-																																																								
--	-	-																																																								
--	-	-																																																								
--	-	-																																																								
--	-	-																																																								
--	-	-																																																								
--	-	-																																																								
--	-	-																																																								
--	-	-																																																								

COSEL

Model	GHA500F-15
Item	Overvoltage Protection
Object	+15V33.4A

Testing Circuitry Figure A

1.Graph



2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 120[V]	Input Volt. 230[V]
-20	19.04	19.04
-10	19.27	19.27
0	19.39	19.39
10	19.57	19.57
20	19.74	19.74
25	19.74	19.74
30	19.86	19.86
40	20.03	20.03
50	20.15	20.15
60	20.38	20.27
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

COSEL




Figure A




Figure B (IEC60601-1)