

TEST DATA OF GHA700F-12-J1

Regulated DC Power Supply
March 26, 2024

Approved by : _____
Jun Uchida
Design Manager

Prepared by : _____
Kasumi Izumi
Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Load Current)	1
2.Efficiency (by Load Current)	2
3.Power Factor (by Load Current)	3
4.Inrush Current	4
5.Leakage Current	5
6.Line Regulation	6
7.Load Regulation	7
8.Ripple-Noise	7
9.Dynamic Load Response	8
10.Rise and Fall Time	9
11.Hold-Up Time	10
12.Instantaneous Interruption Compensation	11
13.Overcurrent Protection	12
14.Ambient Temperature Drift	13
15.Minimum Input Voltage for Regulated Output Voltage	13
16.Overvoltage Protection	13
17.Figure of Testing Circuitry	14

(Final Page 15)

COSEL

Model	GHA700F-12-J1																																																					
Item	Input Current (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object	_____																																																					
1.Graph		—▲— Input Volt. 100V - - □--- Input Volt. 115V - - ○--- Input Volt. 230V																																																				
		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>0.096</td><td>0.090</td><td>0.130</td></tr> <tr> <td>8.00</td><td>1.073</td><td>0.952</td><td>0.632</td></tr> <tr> <td>16.00</td><td>2.059</td><td>1.811</td><td>1.071</td></tr> <tr> <td>24.00</td><td>3.153</td><td>2.710</td><td>1.493</td></tr> <tr> <td>32.00</td><td>4.225</td><td>3.668</td><td>1.928</td></tr> <tr> <td>40.00</td><td>5.310</td><td>4.607</td><td>2.379</td></tr> <tr> <td>48.00</td><td>6.429</td><td>5.569</td><td>2.835</td></tr> <tr> <td>54.20</td><td>-</td><td>6.324</td><td>3.175</td></tr> <tr> <td>59.62</td><td>-</td><td>6.992</td><td>3.469</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	0.096	0.090	0.130	8.00	1.073	0.952	0.632	16.00	2.059	1.811	1.071	24.00	3.153	2.710	1.493	32.00	4.225	3.668	1.928	40.00	5.310	4.607	2.379	48.00	6.429	5.569	2.835	54.20	-	6.324	3.175	59.62	-	6.992	3.469	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.00	0.096	0.090	0.130																																																			
8.00	1.073	0.952	0.632																																																			
16.00	2.059	1.811	1.071																																																			
24.00	3.153	2.710	1.493																																																			
32.00	4.225	3.668	1.928																																																			
40.00	5.310	4.607	2.379																																																			
48.00	6.429	5.569	2.835																																																			
54.20	-	6.324	3.175																																																			
59.62	-	6.992	3.469																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						

COSEL

Model	GHA700F-12-J1																																																			
Item	Efficiency (by Load Current)	Temperature	25°C																																																	
Object	Testing Circuitry Figure A																																																			
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 100V Input Volt. 115V Input Volt. 230V <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>100[V] (%)</th> <th>115[V] (%)</th> <th>230[V] (%)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>8.00</td><td>92.7</td><td>93.2</td><td>95.2</td></tr> <tr><td>16.00</td><td>94.3</td><td>94.4</td><td>96.3</td></tr> <tr><td>24.00</td><td>93.7</td><td>94.3</td><td>96.1</td></tr> <tr><td>32.00</td><td>93.2</td><td>93.8</td><td>95.5</td></tr> <tr><td>40.00</td><td>92.7</td><td>93.4</td><td>95.2</td></tr> <tr><td>48.00</td><td>92.1</td><td>92.8</td><td>94.7</td></tr> <tr><td>54.20</td><td>-</td><td>92.4</td><td>94.4</td></tr> <tr><td>59.62</td><td>-</td><td>91.9</td><td>94.1</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	100[V] (%)	115[V] (%)	230[V] (%)	0.00	-	-	-	8.00	92.7	93.2	95.2	16.00	94.3	94.4	96.3	24.00	93.7	94.3	96.1	32.00	93.2	93.8	95.5	40.00	92.7	93.4	95.2	48.00	92.1	92.8	94.7	54.20	-	92.4	94.4	59.62	-	91.9	94.1	--	-	-	-	--	-	-	-	2.Values		
Load Current [A]	100[V] (%)	115[V] (%)	230[V] (%)																																																	
0.00	-	-	-																																																	
8.00	92.7	93.2	95.2																																																	
16.00	94.3	94.4	96.3																																																	
24.00	93.7	94.3	96.1																																																	
32.00	93.2	93.8	95.5																																																	
40.00	92.7	93.4	95.2																																																	
48.00	92.1	92.8	94.7																																																	
54.20	-	92.4	94.4																																																	
59.62	-	91.9	94.1																																																	
--	-	-	-																																																	
--	-	-	-																																																	
2.	Load Current [A]	Efficiency [%]																																																		
		Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																




Note: Slanted line shows the range of the rated load current.

COSEL

Model	GHA700F-12-J1																																																					
Item	Power Factor (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object																																																						
1.Graph	—△— Input Volt. 100V - - □--- Input Volt. 115V - - ○--- Input Volt. 230V																																																					
	<p>Note: Slanted line shows the range of the rated load current.</p>	2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>0.387</td><td>0.257</td><td>0.073</td></tr> <tr> <td>8.00</td><td>0.962</td><td>0.943</td><td>0.717</td></tr> <tr> <td>16.00</td><td>0.991</td><td>0.977</td><td>0.830</td></tr> <tr> <td>24.00</td><td>0.983</td><td>0.986</td><td>0.891</td></tr> <tr> <td>32.00</td><td>0.986</td><td>0.981</td><td>0.920</td></tr> <tr> <td>40.00</td><td>0.989</td><td>0.983</td><td>0.939</td></tr> <tr> <td>48.00</td><td>0.989</td><td>0.986</td><td>0.949</td></tr> <tr> <td>54.20</td><td>-</td><td>0.986</td><td>0.957</td></tr> <tr> <td>59.62</td><td>-</td><td>0.986</td><td>0.961</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	0.387	0.257	0.073	8.00	0.962	0.943	0.717	16.00	0.991	0.977	0.830	24.00	0.983	0.986	0.891	32.00	0.986	0.981	0.920	40.00	0.989	0.983	0.939	48.00	0.989	0.986	0.949	54.20	-	0.986	0.957	59.62	-	0.986	0.961	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.00	0.387	0.257	0.073																																																			
8.00	0.962	0.943	0.717																																																			
16.00	0.991	0.977	0.830																																																			
24.00	0.983	0.986	0.891																																																			
32.00	0.986	0.981	0.920																																																			
40.00	0.989	0.983	0.939																																																			
48.00	0.989	0.986	0.949																																																			
54.20	-	0.986	0.957																																																			
59.62	-	0.986	0.961																																																			
--	-	-	-																																																			
--	-	-	-																																																			

COSEL

Model	GHA700F-12-J1	Temperature	25°C
Item	Inrush Current	Testing Circuitry	Figure A
Object	_____		





Model	GHA700F-12-J1	Temperature Testing Circuitry	25°C Figure C	
Item	Leakage Current			
Object	_____			

1. Results

[mA]

Standards	Testing Circuitry	Measuring Method	Input Volt.			Note
			100 [V]	240 [V]	264 [V]	
DEN-AN	Figure C-1	Both phases	0.06	0.15	0.17	Operation
		One of phases	0.09	0.24	0.26	Stand by
IEC62368-1	Figure C-2	Both phases	0.06	0.15	0.17	Operation
		One of phases	0.09	0.24	0.25	Stand by
	Figure C-3	Both phases	0.06	0.15	0.17	Operation
		One of phases	0.09	0.23	0.26	Stand by
IEC60601-1	Figure C-4	Both phases	0.06	0.15	0.17	Operation
		One of phases	0.09	0.24	0.26	Stand by

The value for "One of phases" is the reference value only.

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model	GHA700F-12-J1																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+12V54.2A																																	
1.Graph																																		
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td><td>12.104</td><td>12.096 ※1</td> </tr> <tr> <td>100</td><td>12.104</td><td>12.096 ※2</td> </tr> <tr> <td>115</td><td>12.104</td><td>12.096</td> </tr> <tr> <td>200</td><td>12.103</td><td>12.096</td> </tr> <tr> <td>230</td><td>12.103</td><td>12.096</td> </tr> <tr> <td>264</td><td>12.103</td><td>12.097</td> </tr> <tr> <td>280</td><td>12.103</td><td>12.096</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	85	12.104	12.096 ※1	100	12.104	12.096 ※2	115	12.104	12.096	200	12.103	12.096	230	12.103	12.096	264	12.103	12.097	280	12.103	12.096	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
85	12.104	12.096 ※1																																
100	12.104	12.096 ※2																																
115	12.104	12.096																																
200	12.103	12.096																																
230	12.103	12.096																																
264	12.103	12.097																																
280	12.103	12.096																																
--	-	-																																
--	-	-																																
※1: Load 75% ※2: Load 87.5%																																		


COSEL

Model	GHA700F-12-J1	Temperature	25°C																																																
Item	Load Regulation	Testing Circuitry	Figure A																																																
Object	+12V54.2A	2.Values																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 100V Input Volt. 115V Input Volt. 230V <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Output Voltage [V] (100V)</th> <th>Output Voltage [V] (115V)</th> <th>Output Voltage [V] (230V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>12.118</td><td>12.117</td><td>12.118</td></tr> <tr><td>8.00</td><td>12.115</td><td>12.114</td><td>12.114</td></tr> <tr><td>16.00</td><td>12.112</td><td>12.112</td><td>12.112</td></tr> <tr><td>24.00</td><td>12.109</td><td>12.109</td><td>12.109</td></tr> <tr><td>32.00</td><td>12.106</td><td>12.107</td><td>12.107</td></tr> <tr><td>40.00</td><td>12.104</td><td>12.104</td><td>12.104</td></tr> <tr><td>48.00</td><td>12.101</td><td>12.101</td><td>12.102</td></tr> <tr><td>54.20</td><td>-</td><td>12.099</td><td>12.099</td></tr> <tr><td>59.62</td><td>-</td><td>12.097</td><td>12.097</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V] (100V)	Output Voltage [V] (115V)	Output Voltage [V] (230V)	0.00	12.118	12.117	12.118	8.00	12.115	12.114	12.114	16.00	12.112	12.112	12.112	24.00	12.109	12.109	12.109	32.00	12.106	12.107	12.107	40.00	12.104	12.104	12.104	48.00	12.101	12.101	12.102	54.20	-	12.099	12.099	59.62	-	12.097	12.097	--	--	--	--	--	--	--	--
Load Current [A]	Output Voltage [V] (100V)	Output Voltage [V] (115V)	Output Voltage [V] (230V)																																																
0.00	12.118	12.117	12.118																																																
8.00	12.115	12.114	12.114																																																
16.00	12.112	12.112	12.112																																																
24.00	12.109	12.109	12.109																																																
32.00	12.106	12.107	12.107																																																
40.00	12.104	12.104	12.104																																																
48.00	12.101	12.101	12.102																																																
54.20	-	12.099	12.099																																																
59.62	-	12.097	12.097																																																
--	--	--	--																																																
--	--	--	--																																																
Item	Ripple-Noise	Temperature	25°C																																																
Object	+12V54.2A	Testing Circuitry	Figure B																																																
1.Graph	<p>Input Voltage 230V Load 100%</p> <p>100[mV/div]</p> <p>20[μs/div]</p>																																																		

COSEL

Model	GHA700F-12-J1	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+12V54.2A		

Input Volt. 115 V
 Cycle 1000 ms

Response. $t_1=t_2=50\mu s$. Typ

Load 0%(0A) \longleftrightarrow
 Load 100%(54.2A)

500[mV/div]

10[ms/div]

10[ms/div]

Load 50%(27.1A) \longleftrightarrow
 Load 100%(54.2A)

500[mV/div]


10[ms/div]

10[ms/div]

COSEL


Model	GHA700F-12-J1	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+12V54.2A		

1. Graph



2. Values

Input Volt.	Time	Td	Tr	Ts	Th	Tf	[ms]
115 V		462.0	13.5	475.5	12.0	1.0	
230 V		461.5	13.5	475.0	12.0	1.0	



COSEL

Model	GHA700F-12-J1																																	
Item	Hold-Up Time	Temperature 25°C Testing Circuitry Figure A																																
Object	+12V54.2A																																	
1. Graph																																		
<p>Legend: --- □--- Load 50% —△— Load 100%</p>																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td><td>24</td><td>12 ※1</td> </tr> <tr> <td>100</td><td>24</td><td>12 ※2</td> </tr> <tr> <td>115</td><td>24</td><td>12</td> </tr> <tr> <td>200</td><td>24</td><td>12</td> </tr> <tr> <td>230</td><td>24</td><td>12</td> </tr> <tr> <td>264</td><td>24</td><td>12</td> </tr> <tr> <td>280</td><td>24</td><td>12</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	85	24	12 ※1	100	24	12 ※2	115	24	12	200	24	12	230	24	12	264	24	12	280	24	12	--	-	-	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																	
	Load 50%	Load 100%																																
85	24	12 ※1																																
100	24	12 ※2																																
115	24	12																																
200	24	12																																
230	24	12																																
264	24	12																																
280	24	12																																
--	-	-																																
--	-	-																																
※1: Load 75% ※2: Load 87.5%																																		
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy. Note: Slanted line shows the range of the rated input voltage.</p>																																		

COSEL

Model	GHA700F-12-J1																																																					
Item	Instantaneous Interruption Compensation	Temperature Testing Circuitry	25°C Figure A																																																			
Object	+12V54.2A																																																					
1.Graph																																																						
<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 100V Input Volt. 115V Input Volt. 230V 																																																						
2.Values																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>8.00</td><td>84</td><td>83</td><td>83</td></tr> <tr> <td>16.00</td><td>44</td><td>44</td><td>44</td></tr> <tr> <td>24.00</td><td>29</td><td>29</td><td>28</td></tr> <tr> <td>32.00</td><td>21</td><td>21</td><td>21</td></tr> <tr> <td>40.00</td><td>15</td><td>15</td><td>16</td></tr> <tr> <td>48.00</td><td>13</td><td>14</td><td>14</td></tr> <tr> <td>54.20</td><td>-</td><td>11</td><td>11</td></tr> <tr> <td>59.62</td><td>-</td><td>8</td><td>7</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	-	-	-	8.00	84	83	83	16.00	44	44	44	24.00	29	29	28	32.00	21	21	21	40.00	15	15	16	48.00	13	14	14	54.20	-	11	11	59.62	-	8	7	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
8.00	84	83	83																																																			
16.00	44	44	44																																																			
24.00	29	29	28																																																			
32.00	21	21	21																																																			
40.00	15	15	16																																																			
48.00	13	14	14																																																			
54.20	-	11	11																																																			
59.62	-	8	7																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						



COSEL

Model	GHA700F-12-J1	Testing Circuitry Figure A
Item	Ambient Temperature Drift	
Object	+12V54.2A	

1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]		
	Input Volt. 100V	Input Volt. 115V	Input Volt. 230V
-20	12.083	12.086	12.086
25	12.104	12.102	12.101
50	12.099	12.099	12.101

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A	
Object	+12V54.2A		

1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	77	77
25	76	78
50	76	77




Item	Overvoltage Protection	Testing Circuitry Figure A	
Object	+12V54.2A		

1.Values

Load 0%

Ambient Temperature[°C]	Operating Point [V]	
	Input Volt. 115V	Input Volt. 230V
-20	15.47	15.47
25	15.58	15.58
50	15.64	15.64

COSEL



COSEL




Figure C-2 (IEC62368-1 refer to IEC60990 Fig.4)




Figure C-3 (IEC62368-1 refer to IEC60990 Fig.5)




Figure C-4 (IEC60601-1)