



M T B F

(E I A J R C R - 9 1 0 2 B)

Model	GT2-24
-------	--------

No.	Parts		Q'ty of Device	Failure rate [$10^{-6}/H$]	Reference
1	IC	Linear	2	0.0480	
2	Transistors	NPN/PNP	0	0.0000	
3	Transistors	Power NPN/PNP	1	0.0420	
4	FET	MOS FET	1	0.0990	
5	Diodes	FR	2	0.0440	
6	Diodes	Zener	2	0.0480	
7	Diodes	bridge	2	0.1320	
8	Resistors	Metal Film	19	0.3040	
9	Resistors	Power Film	3	0.1230	
10	Resistors	variable	1	0.0160	
11	Capacitors	Aluminum Electrolytic	8	0.1520	
12	Capacitors	Film	5	0.0420	
13	Transformer	Power	1	0.3600	
14	Fuses		1	0.0200	
15	Connectors	Printed Crcuit Board	7	0.3640	
16	Connection	Hand Solder	10	0.0260	
17	Connection	Flow Solder	246	0.1279	
18	Connection	Crimp	31	0.0192	
19	Connection	Screw	8	0.0080	
20	Printed Crcuit Board	Through Hole	2	0.0900	
Total Failure Rate [$10^{-6}/H$]				2.0651	

M T B F	[H]	484,000
Ambient Temperature	[°C]	-
Load Factor	[%]	-