

TEST DATA OF GT2.5W-12

Regulated DC Power Supply
November 2, 2010

Approved by : Eiyoshi Wakamatsu
Eiyoshi Wakamatsu Design Manager

Prepared by : Satoshi Kinoshita
Satoshi Kinoshita Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Load Current) 1

2.Input Power (by Load Current) 2

3.Efficiency (by Input Voltage) 3

4.Efficiency (by Load Current) 4

5.Power Factor (by Input Voltage) 5

6.Power Factor (by Load Current) 6

7.Inrush Current 7

8.Line Regulation 8

9.Load Regulation 9

10.Dynamic Load Response 10

11.Ripple Voltage (by Load Current) 12

12.Ripple Voltage (by Ambient Temperature) 14

13.Ambient Temperature Drift 15

14.Output Voltage Accuracy 16

15.Time Lapse Drift 17

16.Rise and Fall Time 18

17.Hold-Up Time 20

18.Instantaneous Interruption Compensation 22

19.Minimum Input Voltage for Regulated Output Voltage 24

20.Overcurrent Protection 25

21.Figure of Testing Circuitry 26

(Final Page 26)



Model		GT2.5W-12		Temperature 25°C																																																				
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																				
Object																																																								
1.Graph		<p>—△— Input Volt. 90V</p> <p>- - □ - - Input Volt. 100V</p> <p>- · ○ · - - Input Volt. 110V</p>		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 90[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 110[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.020</td><td>0.023</td><td>0.026</td></tr> <tr><td>20</td><td>0.175</td><td>0.179</td><td>0.183</td></tr> <tr><td>40</td><td>0.303</td><td>0.309</td><td>0.315</td></tr> <tr><td>60</td><td>0.420</td><td>0.429</td><td>0.437</td></tr> <tr><td>80</td><td>0.531</td><td>0.542</td><td>0.552</td></tr> <tr><td>100</td><td>0.637</td><td>0.650</td><td>0.662</td></tr> <tr><td>110</td><td>0.688</td><td>0.702</td><td>0.715</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Ration [%]	Input Current [A]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0	0.020	0.023	0.026	20	0.175	0.179	0.183	40	0.303	0.309	0.315	60	0.420	0.429	0.437	80	0.531	0.542	0.552	100	0.637	0.650	0.662	110	0.688	0.702	0.715	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Current [A]																																																							
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																					
0	0.020	0.023	0.026																																																					
20	0.175	0.179	0.183																																																					
40	0.303	0.309	0.315																																																					
60	0.420	0.429	0.437																																																					
80	0.531	0.542	0.552																																																					
100	0.637	0.650	0.662																																																					
110	0.688	0.702	0.715																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					



<p>Model GT2.5W-12</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
<p>Item</p>	<p>Input Power (by Load Current)</p>																																																				
<p>Object</p>	<p>_____</p>	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 90[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 110[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>1.20</td><td>1.40</td><td>1.70</td></tr> <tr><td>20</td><td>9.80</td><td>11.10</td><td>12.30</td></tr> <tr><td>40</td><td>18.40</td><td>20.50</td><td>22.80</td></tr> <tr><td>60</td><td>26.80</td><td>30.00</td><td>33.10</td></tr> <tr><td>80</td><td>35.10</td><td>39.20</td><td>43.40</td></tr> <tr><td>100</td><td>43.40</td><td>48.40</td><td>53.50</td></tr> <tr><td>110</td><td>47.50</td><td>53.00</td><td>58.60</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Input Power [W]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0	1.20	1.40	1.70	20	9.80	11.10	12.30	40	18.40	20.50	22.80	60	26.80	30.00	33.10	80	35.10	39.20	43.40	100	43.40	48.40	53.50	110	47.50	53.00	58.60	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Power [W]																																																				
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																		
0	1.20	1.40	1.70																																																		
20	9.80	11.10	12.30																																																		
40	18.40	20.50	22.80																																																		
60	26.80	30.00	33.10																																																		
80	35.10	39.20	43.40																																																		
100	43.40	48.40	53.50																																																		
110	47.50	53.00	58.60																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
<p>1.Graph</p> <p> —△— Input Volt. 90V - - □ - - Input Volt. 100V ···○··· Input Volt. 110V </p> <p>Input Power [W]</p> <p>Load Ration [%]</p>																																																					



Model		GT2.5W-12																																	
Item		Efficiency (by Input Voltage)																																	
Object		Temperature 25°C Testing Circuitry Figure A																																	
1.Graph		2.Values																																	
<p>---□--- Load 50% —△— Load 100%</p> <p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>62.2</td> <td>64.9</td> </tr> <tr> <td>90</td> <td>58.6</td> <td>61.0</td> </tr> <tr> <td>100</td> <td>52.5</td> <td>54.6</td> </tr> <tr> <td>110</td> <td>47.5</td> <td>49.5</td> </tr> <tr> <td>115</td> <td>45.2</td> <td>47.2</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	85	62.2	64.9	90	58.6	61.0	100	52.5	54.6	110	47.5	49.5	115	45.2	47.2	--	-	-	--	-	-	--	-	-	--	-	-
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
85	62.2	64.9																																	
90	58.6	61.0																																	
100	52.5	54.6																																	
110	47.5	49.5																																	
115	45.2	47.2																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	



Model		GT2.5W-12		Temperature 25°C																																																																																
Item		Efficiency (by Load Current)		Testing Circuitry Figure A																																																																																
Object		_____																																																																																		
1.Graph			2.Values																																																																																	
<p> —△— Input Volt. 90V - - □ - - Input Volt. 100V - - ○ - - Input Volt. 110V </p> <table border="1"> <caption>Graph Data</caption> <thead> <tr> <th>Load Ration [%]</th> <th>90V Efficiency [%]</th> <th>100V Efficiency [%]</th> <th>110V Efficiency [%]</th> </tr> </thead> <tbody> <tr><td>20</td><td>54.1</td><td>47.7</td><td>43.1</td></tr> <tr><td>40</td><td>57.6</td><td>51.7</td><td>46.4</td></tr> <tr><td>60</td><td>59.3</td><td>53.0</td><td>48.0</td></tr> <tr><td>80</td><td>60.4</td><td>54.1</td><td>48.8</td></tr> <tr><td>100</td><td>61.0</td><td>54.7</td><td>49.5</td></tr> <tr><td>110</td><td>61.4</td><td>55.0</td><td>49.7</td></tr> </tbody> </table>			Load Ration [%]	90V Efficiency [%]	100V Efficiency [%]	110V Efficiency [%]	20	54.1	47.7	43.1	40	57.6	51.7	46.4	60	59.3	53.0	48.0	80	60.4	54.1	48.8	100	61.0	54.7	49.5	110	61.4	55.0	49.7	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 90[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 110[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>54.1</td><td>47.7</td><td>43.1</td></tr> <tr><td>40</td><td>57.6</td><td>51.7</td><td>46.4</td></tr> <tr><td>60</td><td>59.3</td><td>53.0</td><td>48.0</td></tr> <tr><td>80</td><td>60.4</td><td>54.1</td><td>48.8</td></tr> <tr><td>100</td><td>61.0</td><td>54.7</td><td>49.5</td></tr> <tr><td>110</td><td>61.4</td><td>55.0</td><td>49.7</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Efficiency [%]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0	-	-	-	20	54.1	47.7	43.1	40	57.6	51.7	46.4	60	59.3	53.0	48.0	80	60.4	54.1	48.8	100	61.0	54.7	49.5	110	61.4	55.0	49.7	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	90V Efficiency [%]	100V Efficiency [%]	110V Efficiency [%]																																																																																	
20	54.1	47.7	43.1																																																																																	
40	57.6	51.7	46.4																																																																																	
60	59.3	53.0	48.0																																																																																	
80	60.4	54.1	48.8																																																																																	
100	61.0	54.7	49.5																																																																																	
110	61.4	55.0	49.7																																																																																	
Load Ration [%]	Efficiency [%]																																																																																			
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																																																	
0	-	-	-																																																																																	
20	54.1	47.7	43.1																																																																																	
40	57.6	51.7	46.4																																																																																	
60	59.3	53.0	48.0																																																																																	
80	60.4	54.1	48.8																																																																																	
100	61.0	54.7	49.5																																																																																	
110	61.4	55.0	49.7																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	




Model		GT2.5W-12																																	
Item		Power Factor (by Input Voltage)																																	
Object		_____																																	
1.Graph		Temperature 25°C Testing Circuitry Figure A																																	
<p>1.Graph</p> <p>---□--- Load 50% —△— Load 100%</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>0.701</td> <td>0.763</td> </tr> <tr> <td>90</td> <td>0.693</td> <td>0.757</td> </tr> <tr> <td>100</td> <td>0.681</td> <td>0.747</td> </tr> <tr> <td>110</td> <td>0.674</td> <td>0.736</td> </tr> <tr> <td>115</td> <td>0.670</td> <td>0.732</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Input Voltage [V]	Power Factor		Load 50%	Load 100%	85	0.701	0.763	90	0.693	0.757	100	0.681	0.747	110	0.674	0.736	115	0.670	0.732	--	-	-	--	-	-	--	-	-	--	-	-
Input Voltage [V]	Power Factor																																		
	Load 50%	Load 100%																																	
85	0.701	0.763																																	
90	0.693	0.757																																	
100	0.681	0.747																																	
110	0.674	0.736																																	
115	0.670	0.732																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	



Model		GT2.5W-12		Temperature 25°C																																																				
Item		Power Factor (by Load Current)		Testing Circuitry Figure A																																																				
Object																																																								
1.Graph		<p>—△— Input Volt. 90V</p> <p>- - □ - - Input Volt. 100V</p> <p>- · ○ · - - Input Volt. 110V</p>		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 90[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 110[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>20</td> <td>0.620</td> <td>0.620</td> <td>0.609</td> </tr> <tr> <td>40</td> <td>0.676</td> <td>0.663</td> <td>0.657</td> </tr> <tr> <td>60</td> <td>0.709</td> <td>0.699</td> <td>0.690</td> </tr> <tr> <td>80</td> <td>0.734</td> <td>0.723</td> <td>0.715</td> </tr> <tr> <td>100</td> <td>0.757</td> <td>0.746</td> <td>0.735</td> </tr> <tr> <td>110</td> <td>0.767</td> <td>0.755</td> <td>0.746</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Load Ration [%]	Power Factor			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0	-	-	-	20	0.620	0.620	0.609	40	0.676	0.663	0.657	60	0.709	0.699	0.690	80	0.734	0.723	0.715	100	0.757	0.746	0.735	110	0.767	0.755	0.746	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Power Factor																																																							
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																					
0	-	-	-																																																					
20	0.620	0.620	0.609																																																					
40	0.676	0.663	0.657																																																					
60	0.709	0.699	0.690																																																					
80	0.734	0.723	0.715																																																					
100	0.757	0.746	0.735																																																					
110	0.767	0.755	0.746																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					




Model		GT2.5W-12	
Item		Inrush Current	
Object		_____	
		Temperature	25°C
		Testing Circuitry	Figure A



Input Voltage 100 V
 Frequency 60 Hz
 Load 100 %

Primary inrush current 10.1 A






COSEL																																			
Model	GT2.5W-12	Temperature	25°C																																
Item	Line Regulation	Testing Circuitry	Figure A																																
Object	+12V1.1A																																		
<p>1.Graph</p> <p style="text-align: right;"> ---□--- Load 50% —△— Load 100% </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>85</td><td>12.038</td><td>12.036</td></tr> <tr><td>90</td><td>12.038</td><td>12.036</td></tr> <tr><td>100</td><td>12.038</td><td>12.036</td></tr> <tr><td>110</td><td>12.038</td><td>12.036</td></tr> <tr><td>115</td><td>12.038</td><td>12.036</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	85	12.038	12.036	90	12.038	12.036	100	12.038	12.036	110	12.038	12.036	115	12.038	12.036	--	-	-	--	-	-	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
85	12.038	12.036																																	
90	12.038	12.036																																	
100	12.038	12.036																																	
110	12.038	12.036																																	
115	12.038	12.036																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
Object	-12V1.1A																																		
<p>1.Graph</p> <p style="text-align: right;"> ---□--- Load 50% —△— Load 100% </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>85</td><td>-12.035</td><td>-12.034</td></tr> <tr><td>90</td><td>-12.035</td><td>-12.034</td></tr> <tr><td>100</td><td>-12.035</td><td>-12.034</td></tr> <tr><td>110</td><td>-12.035</td><td>-12.035</td></tr> <tr><td>115</td><td>-12.035</td><td>-12.035</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	85	-12.035	-12.034	90	-12.035	-12.034	100	-12.035	-12.034	110	-12.035	-12.035	115	-12.035	-12.035	--	-	-	--	-	-	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
85	-12.035	-12.034																																	
90	-12.035	-12.034																																	
100	-12.035	-12.034																																	
110	-12.035	-12.035																																	
115	-12.035	-12.035																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			



Model	GT2.5W-12
Item	Load Regulation
Object	+12V1.1A


Temperature 25°C
Testing Circuitry Figure A



2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]
0.00	12.039	12.039	12.039
0.20	12.039	12.039	12.039
0.40	12.038	12.038	12.038
0.60	12.038	12.038	12.038
0.80	12.037	12.037	12.037
1.00	12.037	12.037	12.037
1.10	12.036	12.036	12.036
1.21	12.036	12.036	12.036
--	-	-	-
--	-	-	-
--	-	-	-

Object	-12V1.1A
--------	----------



2.Values


Load Current [A]	Output Voltage [V]		
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]
0.00	-12.036	-12.036	-12.036
0.20	-12.036	-12.036	-12.036
0.40	-12.036	-12.036	-12.035
0.60	-12.035	-12.035	-12.035
0.80	-12.035	-12.035	-12.035
1.00	-12.035	-12.035	-12.034
1.10	-12.034	-12.034	-12.034
1.21	-12.034	-12.034	-12.034
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.




Model		GT2.5W-12	
Item		Dynamic Load Response	
Object		+12V1.1A	
		Temperature	25°C
		Testing Circuitry	Figure A

Input Volt. 100 V
 Cycle 1000 ms




Min. Load (0A) ←→
 Load 100% (1.1A)

50 mV/div




100 μs/div




100 μs/div

Load 50% (0.55A) ←→
 Load 100% (1.1A)

50 mV/div



100 μs/div




100 μs/div



Model		GT2.5W-12	
Item		Temperature	25°C
Object		Testing Circuitry	Figure A
		-12V1.1A	


Input Volt. 100 V
 Cycle 1000 ms

Load Current




Min. Load (0A) ←→
 Load 100% (1.1A)

50 mV/div




100 μs/div




100 μs/div

Load 50% (0.55A) ←→
 Load 100% (1.1A)

50 mV/div



100 μs/div



100 μs/div



Model	GT2.5W-12	Temperature	25°C																																									
Item	Ripple Voltage (by Load Current)	Testing Circuitry	Figure A																																									
Object	+12V1.1A																																											
<p>1.Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 90V</p> <p>-·-○-·- Input Volt. 110V</p> </div> <p>Measured by 20 MHz Oscilloscope. Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 90 [V]</th> <th>Input Volt. 110 [V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>0.6</td> <td>0.6</td> </tr> <tr> <td>0.55</td> <td>0.6</td> <td>0.6</td> </tr> <tr> <td>1.10</td> <td>0.6</td> <td>0.6</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 90 [V]	Input Volt. 110 [V]	0.00	0.6	0.6	0.55	0.6	0.6	1.10	0.6	0.6	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																											
	Input Volt. 90 [V]	Input Volt. 110 [V]																																										
0.00	0.6	0.6																																										
0.55	0.6	0.6																																										
1.10	0.6	0.6																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										




<p>Model GT2.5W-12</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																									
<p>Item</p>	<p>Ripple Voltage (by Load Current)</p>																																										
<p>Object</p>	<p>-12V1.1A</p>																																										
<p>1.Graph</p> <div style="display: flex; justify-content: space-around;"> <div> <p>—△— Input Volt. 90V</p> <p>-·-○-·- Input Volt. 110V</p> </div> </div> <p>Measured by 20 MHz Oscilloscope. Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 90 [V]</th> <th>Input Volt. 110 [V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>0.6</td> <td>0.6</td> </tr> <tr> <td>0.55</td> <td>0.6</td> <td>0.6</td> </tr> <tr> <td>1.10</td> <td>0.6</td> <td>0.6</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 90 [V]	Input Volt. 110 [V]	0.00	0.6	0.6	0.55	0.6	0.6	1.10	0.6	0.6	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																										
	Input Volt. 90 [V]	Input Volt. 110 [V]																																									
0.00	0.6	0.6																																									
0.55	0.6	0.6																																									
1.10	0.6	0.6																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									



Model	GT2.5W-12
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V1.1A


Testing Circuitry Figure A



2.Values


Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-20	1.0	1.0
-10	0.6	0.6
25	0.6	0.6
50	0.6	0.6
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

Object	-12V1.1A
--------	----------



2.Values


Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-20	0.8	1.0
-10	0.6	0.6
25	0.6	0.6
50	0.6	0.6
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]
-20	12.026	12.026	12.026
-10	12.031	12.031	12.031
0	12.034	12.034	12.034
10	12.035	12.035	12.035
20	12.035	12.035	12.036
25	12.035	12.035	12.035
30	12.035	12.035	12.035
40	12.033	12.033	12.033
50	12.030	12.030	12.030
60	12.025	12.025	12.025
--	-	-	-



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]
-20	-12.023	-12.023	-12.023
-10	-12.030	-12.030	-12.030
0	-12.033	-12.033	-12.033
10	-12.035	-12.035	-12.035
20	-12.037	-12.037	-12.037
25	-12.037	-12.037	-12.037
30	-12.036	-12.036	-12.036
40	-12.032	-12.032	-12.032
50	-12.028	-12.028	-12.028
60	-12.023	-12.023	-12.023
--	-	-	-



COSEL		
Model	GT2.5W-12	
Item	Output Voltage Accuracy	Testing Circuitry Figure A

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 - 50°C

Input Voltage : 90 - 110V

Load Current (AVR 1) : 0 - 1.1A (AVR 2) : 0 - 1.1A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) =
$$\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object		+12V1.1A					
Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy		
			Current[A]	Voltage[V]	Value [mV]	Ration [%]	
Maximum Voltage	20	110	0	12.038	±5	±0.1	
Minimum Voltage	50	110	1.1	12.028			

Object		-12V1.1A					
Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy		
			Current[A]	Voltage[V]	Value [mV]	Ration [%]	
Maximum Voltage	20	110	0	-12.039	±6	±0.1	
Minimum Voltage	50	110	1.1	-12.027			




COSEL																									
Model	GT2.5W-12	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V1.1A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p style="text-align: center;">Input Volt. 100V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.037</td></tr> <tr><td>0.5</td><td>12.036</td></tr> <tr><td>1.0</td><td>12.036</td></tr> <tr><td>2.0</td><td>12.036</td></tr> <tr><td>3.0</td><td>12.036</td></tr> <tr><td>4.0</td><td>12.036</td></tr> <tr><td>5.0</td><td>12.036</td></tr> <tr><td>6.0</td><td>12.036</td></tr> <tr><td>7.0</td><td>12.036</td></tr> <tr><td>8.0</td><td>12.036</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	12.037	0.5	12.036	1.0	12.036	2.0	12.036	3.0	12.036	4.0	12.036	5.0	12.036	6.0	12.036	7.0	12.036	8.0	12.036
Time since start [H]	Output Voltage [V]																								
0.0	12.037																								
0.5	12.036																								
1.0	12.036																								
2.0	12.036																								
3.0	12.036																								
4.0	12.036																								
5.0	12.036																								
6.0	12.036																								
7.0	12.036																								
8.0	12.036																								
Object	-12V1.1A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p style="text-align: center;">Input Volt. 100V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-12.035</td></tr> <tr><td>0.5</td><td>-12.034</td></tr> <tr><td>1.0</td><td>-12.034</td></tr> <tr><td>2.0</td><td>-12.034</td></tr> <tr><td>3.0</td><td>-12.034</td></tr> <tr><td>4.0</td><td>-12.034</td></tr> <tr><td>5.0</td><td>-12.034</td></tr> <tr><td>6.0</td><td>-12.034</td></tr> <tr><td>7.0</td><td>-12.034</td></tr> <tr><td>8.0</td><td>-12.034</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	-12.035	0.5	-12.034	1.0	-12.034	2.0	-12.034	3.0	-12.034	4.0	-12.034	5.0	-12.034	6.0	-12.034	7.0	-12.034	8.0	-12.034
Time since start [H]	Output Voltage [V]																								
0.0	-12.035																								
0.5	-12.034																								
1.0	-12.034																								
2.0	-12.034																								
3.0	-12.034																								
4.0	-12.034																								
5.0	-12.034																								
6.0	-12.034																								
7.0	-12.034																								
8.0	-12.034																								



Model	GT2.5W-12	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+12V1.1A		


1. Graph

Input Volt. 100 V



2. Values

		[ms]				
Load \ Time	Td	Tr	Ts	Th	Tf	
50 %	10.8	27.8	38.6	46.0	187.5	
100 %	11.3	27.3	38.6	19.0	96.0	






Model	GT2.5W-12	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	-12V1.1A		


1. Graph

Input Volt. 100 V



2. Values

Load	Time	[ms]				
		T _d	T _r	T _s	T _h	T _f
50 %		10.5	27.8	38.3	46.0	185.0
100 %		10.5	27.8	38.3	18.5	94.5





<p>Model GT2.5W-12</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																
<p>Item Hold-Up Time</p>																																		
<p>Object +12V1.1A</p>	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>19</td> <td>6</td> </tr> <tr> <td>90</td> <td>25</td> <td>9</td> </tr> <tr> <td>100</td> <td>39</td> <td>15</td> </tr> <tr> <td>110</td> <td>52</td> <td>22</td> </tr> <tr> <td>115</td> <td>59</td> <td>25</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	85	19	6	90	25	9	100	39	15	110	52	22	115	59	25	--	-	-	--	-	-	--	-	-	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																	
	Load 50%	Load 100%																																
85	19	6																																
90	25	9																																
100	39	15																																
110	52	22																																
115	59	25																																
--	-	-																																
--	-	-																																
--	-	-																																
--	-	-																																
<p>1.Graph</p> <p>---□--- Load 50% —△— Load 100%</p> <p>Hold-Up Time [ms]</p> <p>Input Voltage [V]</p> <p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy. Note: Slanted line shows the range of the rated input voltage.</p>																																		



Model		GT2.5W-12		Temperature 25°C Testing Circuitry Figure A																																
Item		Hold-Up Time																																		
Object		-12V1.1A																																		
1.Graph			2.Values																																	
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>20</td> <td>6</td> </tr> <tr> <td>90</td> <td>26</td> <td>9</td> </tr> <tr> <td>100</td> <td>39</td> <td>15</td> </tr> <tr> <td>110</td> <td>53</td> <td>22</td> </tr> <tr> <td>115</td> <td>59</td> <td>25</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	85	20	6	90	26	9	100	39	15	110	53	22	115	59	25	--	-	-	--	-	-	--	-	-	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																			
	Load 50%	Load 100%																																		
85	20	6																																		
90	26	9																																		
100	39	15																																		
110	53	22																																		
115	59	25																																		
--	-	-																																		
--	-	-																																		
--	-	-																																		
--	-	-																																		
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy. Note: Slanted line shows the range of the rated input voltage.</p>																																				



<p>Model GT2.5W-12</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
<p>Item Instantaneous Interruption Compensation</p>																																																					
<p>Object +12V1.1A</p>																																																					
<p>1.Graph</p> <p> —△— Input Volt. 90V - - □ - - Input Volt. 100V ···○··· Input Volt. 110V </p> <p>Instantaneous Compensation Time [ms]</p> <p>Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 90[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 110[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.20</td><td>72</td><td>106</td><td>153</td></tr> <tr><td>0.40</td><td>36</td><td>54</td><td>72</td></tr> <tr><td>0.60</td><td>21</td><td>23</td><td>39</td></tr> <tr><td>0.80</td><td>5</td><td>22</td><td>23</td></tr> <tr><td>1.00</td><td>5</td><td>6</td><td>22</td></tr> <tr><td>1.10</td><td>4</td><td>5</td><td>22</td></tr> <tr><td>1.21</td><td>4</td><td>5</td><td>19</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Time [ms]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.00	-	-	-	0.20	72	106	153	0.40	36	54	72	0.60	21	23	39	0.80	5	22	23	1.00	5	6	22	1.10	4	5	22	1.21	4	5	19	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																				
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																		
0.00	-	-	-																																																		
0.20	72	106	153																																																		
0.40	36	54	72																																																		
0.60	21	23	39																																																		
0.80	5	22	23																																																		
1.00	5	6	22																																																		
1.10	4	5	22																																																		
1.21	4	5	19																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
<p>Note: Slanted line shows the range of the rated load current.</p>																																																					




<p>Model GT2.5W-12</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
<p>Item Instantaneous Interruption Compensation</p>																																																					
<p>Object -12V1.1A</p>																																																					
<p>1.Graph</p> <p> —△— Input Volt. 90V - - □ - - Input Volt. 100V ···○··· Input Volt. 110V </p> <p>Instantaneous Compensation Time [ms]</p> <p>Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 90[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 110[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.20</td><td>72</td><td>106</td><td>154</td></tr> <tr><td>0.40</td><td>37</td><td>55</td><td>72</td></tr> <tr><td>0.60</td><td>21</td><td>23</td><td>39</td></tr> <tr><td>0.80</td><td>5</td><td>22</td><td>23</td></tr> <tr><td>1.00</td><td>5</td><td>6</td><td>22</td></tr> <tr><td>1.10</td><td>4</td><td>5</td><td>22</td></tr> <tr><td>1.21</td><td>4</td><td>5</td><td>19</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Time [ms]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.00	-	-	-	0.20	72	106	154	0.40	37	55	72	0.60	21	23	39	0.80	5	22	23	1.00	5	6	22	1.10	4	5	22	1.21	4	5	19	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																				
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																		
0.00	-	-	-																																																		
0.20	72	106	154																																																		
0.40	37	55	72																																																		
0.60	21	23	39																																																		
0.80	5	22	23																																																		
1.00	5	6	22																																																		
1.10	4	5	22																																																		
1.21	4	5	19																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
<p>Note: Slanted line shows the range of the rated load current.</p>																																																					



Model	GT2.5W-12
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V1.1A


Testing Circuitry Figure A



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	69	75
-10	69	75
0	69	75
10	69	75
20	69	75
25	69	75
30	69	75
40	69	77
50	69	77
60	69	77
--	-	-

Object	-12V1.1A
--------	----------



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	69	75
-10	69	75
0	69	75
10	69	75
20	69	75
25	69	77
30	69	77
40	71	77
50	71	77
60	71	77
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.



COSEL																																																										
Model	GT2.5W-12	Temperature	25°C																																																							
Item	Overcurrent Protection	Testing Circuitry	Figure A																																																							
Object	+12V1.1A																																																									
<p>1.Graph</p> <p> Input Volt. 90V Input Volt. 100V Input Volt. 110V </p> <p style="text-align: center;">Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 90[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 110[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>1.39</td><td>1.39</td><td>1.39</td></tr> <tr><td>11.4</td><td>1.35</td><td>1.35</td><td>1.35</td></tr> <tr><td>10.8</td><td>1.31</td><td>1.31</td><td>1.31</td></tr> <tr><td>9.6</td><td>1.24</td><td>1.24</td><td>1.24</td></tr> <tr><td>8.4</td><td>1.16</td><td>1.16</td><td>1.16</td></tr> <tr><td>7.2</td><td>1.08</td><td>1.08</td><td>1.08</td></tr> <tr><td>6.0</td><td>1.00</td><td>1.00</td><td>1.00</td></tr> <tr><td>4.8</td><td>0.92</td><td>0.92</td><td>0.92</td></tr> <tr><td>3.6</td><td>0.84</td><td>0.84</td><td>0.84</td></tr> <tr><td>2.4</td><td>0.76</td><td>0.76</td><td>0.76</td></tr> <tr><td>1.2</td><td>0.68</td><td>0.68</td><td>0.68</td></tr> <tr><td>0.0</td><td>0.60</td><td>0.60</td><td>0.60</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	12.0	1.39	1.39	1.39	11.4	1.35	1.35	1.35	10.8	1.31	1.31	1.31	9.6	1.24	1.24	1.24	8.4	1.16	1.16	1.16	7.2	1.08	1.08	1.08	6.0	1.00	1.00	1.00	4.8	0.92	0.92	0.92	3.6	0.84	0.84	0.84	2.4	0.76	0.76	0.76	1.2	0.68	0.68	0.68	0.0	0.60	0.60	0.60
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																							
12.0	1.39	1.39	1.39																																																							
11.4	1.35	1.35	1.35																																																							
10.8	1.31	1.31	1.31																																																							
9.6	1.24	1.24	1.24																																																							
8.4	1.16	1.16	1.16																																																							
7.2	1.08	1.08	1.08																																																							
6.0	1.00	1.00	1.00																																																							
4.8	0.92	0.92	0.92																																																							
3.6	0.84	0.84	0.84																																																							
2.4	0.76	0.76	0.76																																																							
1.2	0.68	0.68	0.68																																																							
0.0	0.60	0.60	0.60																																																							
Object	-12V1.1A																																																									
<p>1.Graph</p> <p> Input Volt. 90V Input Volt. 100V Input Volt. 110V </p> <p style="text-align: center;">Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 90[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 110[V]</th> </tr> </thead> <tbody> <tr><td>-12.0</td><td>1.39</td><td>1.39</td><td>1.39</td></tr> <tr><td>-11.4</td><td>1.35</td><td>1.35</td><td>1.35</td></tr> <tr><td>-10.8</td><td>1.31</td><td>1.31</td><td>1.31</td></tr> <tr><td>-9.6</td><td>1.24</td><td>1.24</td><td>1.24</td></tr> <tr><td>-8.4</td><td>1.16</td><td>1.16</td><td>1.16</td></tr> <tr><td>-7.2</td><td>1.08</td><td>1.08</td><td>1.08</td></tr> <tr><td>-6.0</td><td>1.00</td><td>1.00</td><td>1.00</td></tr> <tr><td>-4.8</td><td>0.92</td><td>0.92</td><td>0.92</td></tr> <tr><td>-3.6</td><td>0.85</td><td>0.85</td><td>0.85</td></tr> <tr><td>-2.4</td><td>0.77</td><td>0.77</td><td>0.77</td></tr> <tr><td>-1.2</td><td>0.69</td><td>0.69</td><td>0.69</td></tr> <tr><td>0.0</td><td>0.60</td><td>0.60</td><td>0.60</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	-12.0	1.39	1.39	1.39	-11.4	1.35	1.35	1.35	-10.8	1.31	1.31	1.31	-9.6	1.24	1.24	1.24	-8.4	1.16	1.16	1.16	-7.2	1.08	1.08	1.08	-6.0	1.00	1.00	1.00	-4.8	0.92	0.92	0.92	-3.6	0.85	0.85	0.85	-2.4	0.77	0.77	0.77	-1.2	0.69	0.69	0.69	0.0	0.60	0.60	0.60
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																							
-12.0	1.39	1.39	1.39																																																							
-11.4	1.35	1.35	1.35																																																							
-10.8	1.31	1.31	1.31																																																							
-9.6	1.24	1.24	1.24																																																							
-8.4	1.16	1.16	1.16																																																							
-7.2	1.08	1.08	1.08																																																							
-6.0	1.00	1.00	1.00																																																							
-4.8	0.92	0.92	0.92																																																							
-3.6	0.85	0.85	0.85																																																							
-2.4	0.77	0.77	0.77																																																							
-1.2	0.69	0.69	0.69																																																							
0.0	0.60	0.60	0.60																																																							




Figure A