

TEST DATA OF GT2.5W-15

Regulated DC Power Supply
November 2, 2010

Approved by : Eiyoshi Wakamatsu
Eiyoshi Wakamatsu Design Manager

Prepared by : Satoshi Kinoshita
Satoshi Kinoshita Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Load Current)	1
2.Input Power (by Load Current)	2
3.Efficiency (by Input Voltage)	3
4.Efficiency (by Load Current)	4
5.Power Factor (by Input Voltage)	5
6.Power Factor (by Load Current)	6
7.Inrush Current	7
8.Line Regulation	8
9.Load Regulation	9
10.Dynamic Load Response	10
11.Ripple Voltage (by Load Current)	12
12.Ripple Voltage (by Ambient Temperature)	14
13.Ambient Temperature Drift	15
14.Output Voltage Accuracy	16
15.Time Lapse Drift	17
16.Rise and Fall Time	18
17.Hold-Up Time	20
18.Instantaneous Interruption Compensation	22
19.Minimum Input Voltage for Regulated Output Voltage	24
20.Overcurrent Protection	25
21.Figure of Testing Circuitry	26

(Final Page 26)

COSEL

Model		GT2.5W-15		Temperature 25°C																																																	
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																	
Object		_____																																																			
1.Graph		<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>110V</div></div></div> <table><thead><tr><th>Load Ration [%]</th><th>Input Current [A] (90V)</th><th>Input Current [A] (100V)</th><th>Input Current [A] (110V)</th></tr></thead><tbody><tr><td>0</td><td>0.022</td><td>0.025</td><td>0.028</td></tr><tr><td>20</td><td>0.167</td><td>0.169</td><td>0.175</td></tr><tr><td>40</td><td>0.288</td><td>0.292</td><td>0.299</td></tr><tr><td>60</td><td>0.398</td><td>0.406</td><td>0.413</td></tr><tr><td>80</td><td>0.503</td><td>0.512</td><td>0.521</td></tr><tr><td>100</td><td>0.603</td><td>0.614</td><td>0.626</td></tr><tr><td>110</td><td>0.652</td><td>0.665</td><td>0.677</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></tbody></table>		Load Ration [%]	Input Current [A] (90V)	Input Current [A] (100V)	Input Current [A] (110V)	0	0.022	0.025	0.028	20	0.167	0.169	0.175	40	0.288	0.292	0.299	60	0.398	0.406	0.413	80	0.503	0.512	0.521	100	0.603	0.614	0.626	110	0.652	0.665	0.677	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	2.Values	
Load Ration [%]	Input Current [A] (90V)	Input Current [A] (100V)	Input Current [A] (110V)																																																		
0	0.022	0.025	0.028																																																		
20	0.167	0.169	0.175																																																		
40	0.288	0.292	0.299																																																		
60	0.398	0.406	0.413																																																		
80	0.503	0.512	0.521																																																		
100	0.603	0.614	0.626																																																		
110	0.652	0.665	0.677																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		



COSEL																																																						
Model	GT2.5W-15																																																					
Item	Input Power (by Load Current)	Temperature	25°C																																																			
Object	_____	Testing Circuitry	Figure A																																																			
1.Graph		2.Values																																																				
<div><div><div><div><div></div><div>△</div></div><div>—</div><div>Input Volt. 90V</div></div><div><div><div></div><div>□</div></div><div>- - -</div><div>Input Volt. 100V</div></div><div><div><div></div><div>○</div></div><div>- · - · -</div><div>Input Volt. 110V</div></div></div><div><p>Input Power [W]</p><p>Load Ratio [%]</p></div></div> <table><tr><th rowspan="2">Load Ration [%]</th><th colspan="3">Input Power [W]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>0</td><td>1.30</td><td>1.60</td><td>1.90</td></tr><tr><td>20</td><td>9.30</td><td>10.40</td><td>11.60</td></tr><tr><td>40</td><td>17.10</td><td>19.20</td><td>21.20</td></tr><tr><td>60</td><td>24.90</td><td>27.90</td><td>30.80</td></tr><tr><td>80</td><td>32.60</td><td>36.40</td><td>40.30</td></tr><tr><td>100</td><td>40.30</td><td>45.00</td><td>49.70</td></tr><tr><td>110</td><td>44.10</td><td>49.30</td><td>54.50</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Ration [%]	Input Power [W]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0	1.30	1.60	1.90	20	9.30	10.40	11.60	40	17.10	19.20	21.20	60	24.90	27.90	30.80	80	32.60	36.40	40.30	100	40.30	45.00	49.70	110	44.10	49.30	54.50	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-		
Load Ration [%]	Input Power [W]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0	1.30	1.60	1.90																																																			
20	9.30	10.40	11.60																																																			
40	17.10	19.20	21.20																																																			
60	24.90	27.90	30.80																																																			
80	32.60	36.40	40.30																																																			
100	40.30	45.00	49.70																																																			
110	44.10	49.30	54.50																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Model	GT2.5W-15																																		
Item	Efficiency (by Input Voltage)	Temperature	25°C																																
Object		Testing Circuitry	Figure A																																
1.Graph		2.Values																																	
<div><div><div>---</div><div>□</div><div>---</div></div><div>Load 50%</div></div> <div><div>—</div><div>△</div><div>—</div></div> <div>Load 100%</div> <table><thead><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Efficiency [%]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>85</td><td>68.4</td><td>71.3</td></tr><tr><td>90</td><td>64.5</td><td>67.2</td></tr><tr><td>100</td><td>57.6</td><td>60.2</td></tr><tr><td>110</td><td>52.1</td><td>54.4</td></tr><tr><td>115</td><td>49.6</td><td>51.9</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table> <p>Note: Slanted line shows the range of the rated input voltage.</p>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	85	68.4	71.3	90	64.5	67.2	100	57.6	60.2	110	52.1	54.4	115	49.6	51.9	--	-	-	--	-	-	--	-	-	--	-	-		
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
85	68.4	71.3																																	
90	64.5	67.2																																	
100	57.6	60.2																																	
110	52.1	54.4																																	
115	49.6	51.9																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	

COSEL

Model	GT2.5W-15																																																					
Item	Efficiency (by Load Current)	Temperature	25°C																																																			
Object	_____	Testing Circuitry	Figure A																																																			
1.Graph		2.Values																																																				
<div><div>—△— Input Volt. 90V</div><div>- - -□- - Input Volt. 100V</div><div>- · -○- · - Input Volt. 110V</div></div> <p>Efficiency [%]</p> <p>Load Ration [%]</p>		<table><tr><th rowspan="2">Load Ration [%]</th><th colspan="3">Efficiency [%]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>0</td><td>-</td><td>-</td><td>-</td></tr><tr><td>20</td><td>58.3</td><td>52.2</td><td>46.8</td></tr><tr><td>40</td><td>63.4</td><td>56.4</td><td>51.1</td></tr><tr><td>60</td><td>65.3</td><td>58.2</td><td>52.8</td></tr><tr><td>80</td><td>66.5</td><td>59.5</td><td>53.8</td></tr><tr><td>100</td><td>67.2</td><td>60.2</td><td>54.5</td></tr><tr><td>110</td><td>67.6</td><td>60.4</td><td>54.7</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Ration [%]	Efficiency [%]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0	-	-	-	20	58.3	52.2	46.8	40	63.4	56.4	51.1	60	65.3	58.2	52.8	80	66.5	59.5	53.8	100	67.2	60.2	54.5	110	67.6	60.4	54.7	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Efficiency [%]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0	-	-	-																																																			
20	58.3	52.2	46.8																																																			
40	63.4	56.4	51.1																																																			
60	65.3	58.2	52.8																																																			
80	66.5	59.5	53.8																																																			
100	67.2	60.2	54.5																																																			
110	67.6	60.4	54.7																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Model	GT2.5W-15																																
Item	Power Factor (by Input Voltage)	Temperature	25°C																														
		Testing Circuitry	Figure A																														
Object																																	
1.Graph		2.Values																															
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th>Input Voltage [V]</th><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>85</td><td>0.685</td><td>0.750</td></tr><tr><td>90</td><td>0.677</td><td>0.744</td></tr><tr><td>100</td><td>0.671</td><td>0.732</td></tr><tr><td>110</td><td>0.663</td><td>0.722</td></tr><tr><td>115</td><td>0.659</td><td>0.718</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table>		Input Voltage [V]	Load 50%	Load 100%	85	0.685	0.750	90	0.677	0.744	100	0.671	0.732	110	0.663	0.722	115	0.659	0.718	--	-	-	--	-	-	--	-	-	--	-	-		
Input Voltage [V]	Load 50%	Load 100%																															
85	0.685	0.750																															
90	0.677	0.744																															
100	0.671	0.732																															
110	0.663	0.722																															
115	0.659	0.718																															
--	-	-																															
--	-	-																															
--	-	-																															
--	-	-																															
Note: Slanted line shows the range of the rated input voltage.																																	

COSEL


Model		GT2.5W-15		Temperature 25°C																																																				
Item		Power Factor (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>110V</div></div></div> <table><thead><tr><th>Load Ration [%]</th><th>90V</th><th>100V</th><th>110V</th></tr></thead><tbody><tr><td>0</td><td>-</td><td>-</td><td>-</td></tr><tr><td>20</td><td>0.616</td><td>0.615</td><td>0.604</td></tr><tr><td>40</td><td>0.660</td><td>0.658</td><td>0.644</td></tr><tr><td>60</td><td>0.697</td><td>0.689</td><td>0.678</td></tr><tr><td>80</td><td>0.721</td><td>0.711</td><td>0.703</td></tr><tr><td>100</td><td>0.744</td><td>0.733</td><td>0.723</td></tr><tr><td>110</td><td>0.753</td><td>0.742</td><td>0.733</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></tbody></table>		Load Ration [%]	90V	100V	110V	0	-	-	-	20	0.616	0.615	0.604	40	0.660	0.658	0.644	60	0.697	0.689	0.678	80	0.721	0.711	0.703	100	0.744	0.733	0.723	110	0.753	0.742	0.733	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	2.Values				
Load Ration [%]	90V	100V	110V																																																					
0	-	-	-																																																					
20	0.616	0.615	0.604																																																					
40	0.660	0.658	0.644																																																					
60	0.697	0.689	0.678																																																					
80	0.721	0.711	0.703																																																					
100	0.744	0.733	0.723																																																					
110	0.753	0.742	0.733																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
		<table><thead><tr><th rowspan="2">Load Ration [%]</th><th colspan="3">Power Factor</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr></thead><tbody><tr><td>0</td><td>-</td><td>-</td><td>-</td></tr><tr><td>20</td><td>0.616</td><td>0.615</td><td>0.604</td></tr><tr><td>40</td><td>0.660</td><td>0.658</td><td>0.644</td></tr><tr><td>60</td><td>0.697</td><td>0.689</td><td>0.678</td></tr><tr><td>80</td><td>0.721</td><td>0.711</td><td>0.703</td></tr><tr><td>100</td><td>0.744</td><td>0.733</td><td>0.723</td></tr><tr><td>110</td><td>0.753</td><td>0.742</td><td>0.733</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></tbody></table>				Load Ration [%]	Power Factor			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0	-	-	-	20	0.616	0.615	0.604	40	0.660	0.658	0.644	60	0.697	0.689	0.678	80	0.721	0.711	0.703	100	0.744	0.733	0.723	110	0.753	0.742	0.733	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Power Factor																																																							
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																					
0	-	-	-																																																					
20	0.616	0.615	0.604																																																					
40	0.660	0.658	0.644																																																					
60	0.697	0.689	0.678																																																					
80	0.721	0.711	0.703																																																					
100	0.744	0.733	0.723																																																					
110	0.753	0.742	0.733																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					



Model	GT2.5W-15	Temperature 25°C Testing Circuitry Figure A	
Item	Inrush Current		
Object	_____		


Input
Current
[20A/div]



Input
Voltage
[100V/div]





Input Voltage 100 V
Frequency 60 Hz
Load 100 %

Primary inrush current 10.1 A



Model	GT2.5W-15																																		
Item	Line Regulation	Temperature	25°C																																
		Testing Circuitry	Figure A																																
Object	+15V0.9A																																		
1.Graph		2.Values																																	
<div><div>---□--- Load 50%</div><div>—△— Load 100%</div></div>		<table><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Output Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>85</td><td>15.048</td><td>15.047</td></tr><tr><td>90</td><td>15.048</td><td>15.047</td></tr><tr><td>100</td><td>15.048</td><td>15.047</td></tr><tr><td>110</td><td>15.048</td><td>15.047</td></tr><tr><td>115</td><td>15.048</td><td>15.047</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	85	15.048	15.047	90	15.048	15.047	100	15.048	15.047	110	15.048	15.047	115	15.048	15.047	--	-	-	--	-	-	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
85	15.048	15.047																																	
90	15.048	15.047																																	
100	15.048	15.047																																	
110	15.048	15.047																																	
115	15.048	15.047																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
Object	-15V0.9A																																		
1.Graph		2.Values																																	
<div><div>---□--- Load 50%</div><div>—△— Load 100%</div></div> <div>Note: Slanted line shows the range of the rated input voltage.</div>		<table><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Output Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>85</td><td>-15.045</td><td>-15.044</td></tr><tr><td>90</td><td>-15.045</td><td>-15.044</td></tr><tr><td>100</td><td>-15.045</td><td>-15.044</td></tr><tr><td>110</td><td>-15.045</td><td>-15.044</td></tr><tr><td>115</td><td>-15.045</td><td>-15.044</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	85	-15.045	-15.044	90	-15.045	-15.044	100	-15.045	-15.044	110	-15.045	-15.044	115	-15.045	-15.044	--	-	-	--	-	-	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
85	-15.045	-15.044																																	
90	-15.045	-15.044																																	
100	-15.045	-15.044																																	
110	-15.045	-15.044																																	
115	-15.045	-15.044																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	



Model	GT2.5W-15																																																					
Item	Load Regulation	Temperature	25°C																																																			
		Testing Circuitry	Figure A																																																			
Object	+15V0.9A																																																					
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt. 90V</div></div><div><div>---□---</div><div>Input Volt. 100V</div></div><div><div>---○---</div><div>Input Volt. 110V</div></div></div> 		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>0.00</td><td>15.049</td><td>15.049</td><td>15.049</td></tr><tr><td>0.15</td><td>15.048</td><td>15.048</td><td>15.048</td></tr><tr><td>0.30</td><td>15.048</td><td>15.048</td><td>15.048</td></tr><tr><td>0.45</td><td>15.048</td><td>15.048</td><td>15.048</td></tr><tr><td>0.60</td><td>15.047</td><td>15.047</td><td>15.047</td></tr><tr><td>0.75</td><td>15.047</td><td>15.047</td><td>15.047</td></tr><tr><td>0.90</td><td>15.047</td><td>15.047</td><td>15.047</td></tr><tr><td>0.99</td><td>15.046</td><td>15.046</td><td>15.046</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Output Voltage [V]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.00	15.049	15.049	15.049	0.15	15.048	15.048	15.048	0.30	15.048	15.048	15.048	0.45	15.048	15.048	15.048	0.60	15.047	15.047	15.047	0.75	15.047	15.047	15.047	0.90	15.047	15.047	15.047	0.99	15.046	15.046	15.046	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0.00	15.049	15.049	15.049																																																			
0.15	15.048	15.048	15.048																																																			
0.30	15.048	15.048	15.048																																																			
0.45	15.048	15.048	15.048																																																			
0.60	15.047	15.047	15.047																																																			
0.75	15.047	15.047	15.047																																																			
0.90	15.047	15.047	15.047																																																			
0.99	15.046	15.046	15.046																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Object	-15V0.9A																																																					
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt. 90V</div></div><div><div>---□---</div><div>Input Volt. 100V</div></div><div><div>---○---</div><div>Input Volt. 110V</div></div></div> 		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>0.00</td><td>-15.045</td><td>-15.045</td><td>-15.045</td></tr><tr><td>0.15</td><td>-15.045</td><td>-15.045</td><td>-15.045</td></tr><tr><td>0.30</td><td>-15.045</td><td>-15.045</td><td>-15.045</td></tr><tr><td>0.45</td><td>-15.045</td><td>-15.045</td><td>-15.045</td></tr><tr><td>0.60</td><td>-15.044</td><td>-15.044</td><td>-15.044</td></tr><tr><td>0.75</td><td>-15.044</td><td>-15.044</td><td>-15.044</td></tr><tr><td>0.90</td><td>-15.044</td><td>-15.044</td><td>-15.044</td></tr><tr><td>0.99</td><td>-15.044</td><td>-15.044</td><td>-15.044</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Output Voltage [V]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.00	-15.045	-15.045	-15.045	0.15	-15.045	-15.045	-15.045	0.30	-15.045	-15.045	-15.045	0.45	-15.045	-15.045	-15.045	0.60	-15.044	-15.044	-15.044	0.75	-15.044	-15.044	-15.044	0.90	-15.044	-15.044	-15.044	0.99	-15.044	-15.044	-15.044	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0.00	-15.045	-15.045	-15.045																																																			
0.15	-15.045	-15.045	-15.045																																																			
0.30	-15.045	-15.045	-15.045																																																			
0.45	-15.045	-15.045	-15.045																																																			
0.60	-15.044	-15.044	-15.044																																																			
0.75	-15.044	-15.044	-15.044																																																			
0.90	-15.044	-15.044	-15.044																																																			
0.99	-15.044	-15.044	-15.044																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						

-

9

-


BC-10218

COSEL

Model	GT2.5W-15	Temperature Testing Circuitry	25°C Figure A
Item	Dynamic Load Response		
Object	+15V0.9A		


Input Volt. 100 V
Cycle 1000 ms

Load Current




Min. Load (0A) \longleftrightarrow
Load 100% (0.9A)

50 mV/div




100 μs/div




100 μs/div

Load 50% (0.45A) \longleftrightarrow
Load 100% (0.9A)

50 mV/div



100 μs/div




100 μs/div



Model	GT2.5W-15	Temperature Testing Circuitry	25°C Figure A
Item	Dynamic Load Response		
Object	-15V0.9A		


Input Volt. 100 V
Cycle 1000 ms

Load Current




Min. Load (0A) \longleftrightarrow
Load 100% (0.9A)

50 mV/div




100 μ s/div




100 μ s/div

Load 50% (0.45A) \longleftrightarrow
Load 100% (0.9A)

50 mV/div



100 μ s/div



100 μ s/div

Model	GT2.5W-15																																											
Item	Ripple Voltage (by Load Current)	Temperature	25°C																																									
Object	+15V0.9A	Testing Circuitry	Figure A																																									
1.Graph		2.Values																																										
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>110V</div></div></div> <p>Measured by 20 MHz Oscilloscope. Note: Slanted line shows the range of the rated load current.</p>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="2">Ripple Voltage [mV]</th></tr><tr><th>Input Volt. 90 [V]</th><th>Input Volt. 110 [V]</th></tr><tr><td>0.00</td><td>0.8</td><td>0.8</td></tr><tr><td>0.45</td><td>0.8</td><td>0.8</td></tr><tr><td>0.90</td><td>1.0</td><td>1.0</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 90 [V]	Input Volt. 110 [V]	0.00	0.8	0.8	0.45	0.8	0.8	0.90	1.0	1.0	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																											
	Input Volt. 90 [V]	Input Volt. 110 [V]																																										
0.00	0.8	0.8																																										
0.45	0.8	0.8																																										
0.90	1.0	1.0																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										

Model	GT2.5W-15																																											
Item	Ripple Voltage (by Load Current)	Temperature	25°C																																									
		Testing Circuitry	Figure A																																									
Object	-15V0.9A																																											
1.Graph		2.Values																																										
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>110V</div></div></div> <p>Measured by 20 MHz Oscilloscope. Note: Slanted line shows the range of the rated load current.</p>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="2">Ripple Voltage [mV]</th></tr><tr><th>Input Volt. 90 [V]</th><th>Input Volt. 110 [V]</th></tr><tr><td>0.00</td><td>0.6</td><td>0.6</td></tr><tr><td>0.45</td><td>1.2</td><td>1.2</td></tr><tr><td>0.90</td><td>1.4</td><td>1.4</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 90 [V]	Input Volt. 110 [V]	0.00	0.6	0.6	0.45	1.2	1.2	0.90	1.4	1.4	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																											
	Input Volt. 90 [V]	Input Volt. 110 [V]																																										
0.00	0.6	0.6																																										
0.45	1.2	1.2																																										
0.90	1.4	1.4																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										

Model	GT2.5W-15																																									
Item	Ripple Voltage (by Ambient Temp.)	Testing Circuitry Figure A																																								
Object	+15V0.9A																																									
1.Graph		2.Values																																								
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th>Ambient Temperature [°C]</th><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>-20</td><td>1.0</td><td>1.0</td></tr><tr><td>-10</td><td>0.8</td><td>1.0</td></tr><tr><td>25</td><td>0.8</td><td>1.0</td></tr><tr><td>50</td><td>0.8</td><td>1.0</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table> <p>Input Volt. 100V</p>		Ambient Temperature [°C]	Load 50%	Load 100%	-20	1.0	1.0	-10	0.8	1.0	25	0.8	1.0	50	0.8	1.0	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-		
Ambient Temperature [°C]	Load 50%	Load 100%																																								
-20	1.0	1.0																																								
-10	0.8	1.0																																								
25	0.8	1.0																																								
50	0.8	1.0																																								
--	-	-																																								
--	-	-																																								
--	-	-																																								
--	-	-																																								
--	-	-																																								
--	-	-																																								
--	-	-																																								
--	-	-																																								
Object	-15V0.9A																																									
1.Graph		2.Values																																								
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th>Ambient Temperature [°C]</th><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>-20</td><td>1.6</td><td>1.6</td></tr><tr><td>-10</td><td>1.2</td><td>1.4</td></tr><tr><td>25</td><td>1.2</td><td>1.4</td></tr><tr><td>50</td><td>1.2</td><td>1.4</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table> <p>Input Volt. 100V</p> <p>Measured by 20 MHz Oscilloscope.</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>		Ambient Temperature [°C]	Load 50%	Load 100%	-20	1.6	1.6	-10	1.2	1.4	25	1.2	1.4	50	1.2	1.4	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-		
Ambient Temperature [°C]	Load 50%	Load 100%																																								
-20	1.6	1.6																																								
-10	1.2	1.4																																								
25	1.2	1.4																																								
50	1.2	1.4																																								
--	-	-																																								
--	-	-																																								
--	-	-																																								
--	-	-																																								
--	-	-																																								
--	-	-																																								
--	-	-																																								
--	-	-																																								

- 14 -



BC-10218

Model	GT2.5W-15																																																					
Item	Ambient Temperature Drift	Testing Circuitry Figure A																																																				
Object	+15V0.9A																																																					
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>---○---</div><div>Input Volt.</div><div>110V</div></div></div> <table><thead><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr></thead><tbody><tr><td>-20</td><td>15.022</td><td>15.023</td><td>15.023</td></tr><tr><td>-10</td><td>15.033</td><td>15.033</td><td>15.033</td></tr><tr><td>0</td><td>15.041</td><td>15.041</td><td>15.041</td></tr><tr><td>10</td><td>15.047</td><td>15.047</td><td>15.047</td></tr><tr><td>20</td><td>15.049</td><td>15.049</td><td>15.049</td></tr><tr><td>25</td><td>15.050</td><td>15.050</td><td>15.050</td></tr><tr><td>30</td><td>15.050</td><td>15.050</td><td>15.050</td></tr><tr><td>40</td><td>15.048</td><td>15.048</td><td>15.048</td></tr><tr><td>50</td><td>15.045</td><td>15.045</td><td>15.045</td></tr><tr><td>60</td><td>15.038</td><td>15.038</td><td>15.038</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></tbody></table>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	-20	15.022	15.023	15.023	-10	15.033	15.033	15.033	0	15.041	15.041	15.041	10	15.047	15.047	15.047	20	15.049	15.049	15.049	25	15.050	15.050	15.050	30	15.050	15.050	15.050	40	15.048	15.048	15.048	50	15.045	15.045	15.045	60	15.038	15.038	15.038	--	-	-	-		
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
-20	15.022	15.023	15.023																																																			
-10	15.033	15.033	15.033																																																			
0	15.041	15.041	15.041																																																			
10	15.047	15.047	15.047																																																			
20	15.049	15.049	15.049																																																			
25	15.050	15.050	15.050																																																			
30	15.050	15.050	15.050																																																			
40	15.048	15.048	15.048																																																			
50	15.045	15.045	15.045																																																			
60	15.038	15.038	15.038																																																			
--	-	-	-																																																			
Object	-15V0.9A																																																					
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>---○---</div><div>Input Volt.</div><div>110V</div></div></div> <table><thead><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr></thead><tbody><tr><td>-20</td><td>-15.025</td><td>-15.025</td><td>-15.025</td></tr><tr><td>-10</td><td>-15.033</td><td>-15.033</td><td>-15.033</td></tr><tr><td>0</td><td>-15.040</td><td>-15.040</td><td>-15.040</td></tr><tr><td>10</td><td>-15.043</td><td>-15.043</td><td>-15.043</td></tr><tr><td>20</td><td>-15.046</td><td>-15.046</td><td>-15.046</td></tr><tr><td>25</td><td>-15.047</td><td>-15.047</td><td>-15.047</td></tr><tr><td>30</td><td>-15.047</td><td>-15.047</td><td>-15.047</td></tr><tr><td>40</td><td>-15.046</td><td>-15.046</td><td>-15.046</td></tr><tr><td>50</td><td>-15.043</td><td>-15.043</td><td>-15.043</td></tr><tr><td>60</td><td>-15.038</td><td>-15.038</td><td>-15.038</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></tbody></table>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	-20	-15.025	-15.025	-15.025	-10	-15.033	-15.033	-15.033	0	-15.040	-15.040	-15.040	10	-15.043	-15.043	-15.043	20	-15.046	-15.046	-15.046	25	-15.047	-15.047	-15.047	30	-15.047	-15.047	-15.047	40	-15.046	-15.046	-15.046	50	-15.043	-15.043	-15.043	60	-15.038	-15.038	-15.038	--	-	-	-		
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
-20	-15.025	-15.025	-15.025																																																			
-10	-15.033	-15.033	-15.033																																																			
0	-15.040	-15.040	-15.040																																																			
10	-15.043	-15.043	-15.043																																																			
20	-15.046	-15.046	-15.046																																																			
25	-15.047	-15.047	-15.047																																																			
30	-15.047	-15.047	-15.047																																																			
40	-15.046	-15.046	-15.046																																																			
50	-15.043	-15.043	-15.043																																																			
60	-15.038	-15.038	-15.038																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated ambient temperature.																																																						

- 15 -

BC-10218

COSEL


Model	GT2.5W-15																								
Item	Time Lapse Drift	Temperature	25°C																						
Object	+15V0.9A	Testing Circuitry	Figure A																						
1.Graph		2.Values																							
<div><p>Input Volt. 100V Load 100%</p></div>		<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>15.047</td></tr><tr><td>0.5</td><td>15.046</td></tr><tr><td>1.0</td><td>15.046</td></tr><tr><td>2.0</td><td>15.046</td></tr><tr><td>3.0</td><td>15.046</td></tr><tr><td>4.0</td><td>15.046</td></tr><tr><td>5.0</td><td>15.046</td></tr><tr><td>6.0</td><td>15.046</td></tr><tr><td>7.0</td><td>15.046</td></tr><tr><td>8.0</td><td>15.046</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	15.047	0.5	15.046	1.0	15.046	2.0	15.046	3.0	15.046	4.0	15.046	5.0	15.046	6.0	15.046	7.0	15.046	8.0	15.046
Time since start [H]	Output Voltage [V]																								
0.0	15.047																								
0.5	15.046																								
1.0	15.046																								
2.0	15.046																								
3.0	15.046																								
4.0	15.046																								
5.0	15.046																								
6.0	15.046																								
7.0	15.046																								
8.0	15.046																								
Object	-15V0.9A																								
1.Graph		2.Values																							
<div><p>Input Volt. 100V Load 100%</p></div>		<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>-15.045</td></tr><tr><td>0.5</td><td>-15.044</td></tr><tr><td>1.0</td><td>-15.044</td></tr><tr><td>2.0</td><td>-15.044</td></tr><tr><td>3.0</td><td>-15.044</td></tr><tr><td>4.0</td><td>-15.044</td></tr><tr><td>5.0</td><td>-15.044</td></tr><tr><td>6.0</td><td>-15.044</td></tr><tr><td>7.0</td><td>-15.044</td></tr><tr><td>8.0</td><td>-15.044</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	-15.045	0.5	-15.044	1.0	-15.044	2.0	-15.044	3.0	-15.044	4.0	-15.044	5.0	-15.044	6.0	-15.044	7.0	-15.044	8.0	-15.044
Time since start [H]	Output Voltage [V]																								
0.0	-15.045																								
0.5	-15.044																								
1.0	-15.044																								
2.0	-15.044																								
3.0	-15.044																								
4.0	-15.044																								
5.0	-15.044																								
6.0	-15.044																								
7.0	-15.044																								
8.0	-15.044																								

- 17 -

BC-10218


Model	GT2.5W-15	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+15V0.9A		

1.Graph




2.Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		11.5	27.0	38.5	57.5	285.5
100 %		11.5	27.0	38.5	23.5	145.0




Model	GT2.5W-15	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	-15V0.9A		

1.Graph



2.Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		11.3	26.8	38.1	56.5	282.5
100 %		11.8	26.5	38.3	23.5	143.0



Model	GT2.5W-15																																
Item	Hold-Up Time	Temperature	25°C																														
		Testing Circuitry	Figure A																														
Object	+15V0.9A																																
1.Graph		2.Values																															
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <p>The graph shows Hold-Up Time [ms] on a logarithmic y-axis (1 to 1000) versus Input Voltage [V] on a linear x-axis (80 to 120). Two data series are plotted: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show an increasing trend. A vertical shaded region is present between approximately 90V and 110V.</p> <table border="1"><thead><tr><th>Input Voltage [V]</th><th>Load 50% [ms]</th><th>Load 100% [ms]</th></tr></thead><tbody><tr><td>85</td><td>20</td><td>5</td></tr><tr><td>90</td><td>29</td><td>9</td></tr><tr><td>100</td><td>47</td><td>18</td></tr><tr><td>110</td><td>65</td><td>27</td></tr><tr><td>115</td><td>75</td><td>32</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table>		Input Voltage [V]	Load 50% [ms]	Load 100% [ms]	85	20	5	90	29	9	100	47	18	110	65	27	115	75	32	--	-	-	--	-	-	--	-	-	--	-	-		
Input Voltage [V]	Load 50% [ms]	Load 100% [ms]																															
85	20	5																															
90	29	9																															
100	47	18																															
110	65	27																															
115	75	32																															
--	-	-																															
--	-	-																															
--	-	-																															
--	-	-																															
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																	

Model	GT2.5W-15																																		
Item	Hold-Up Time	Temperature	25°C																																
		Testing Circuitry	Figure A																																
Object	-15V0.9A																																		
1.Graph		2.Values																																	
<div><div><div>---</div><div>□</div><div>---</div><div>Load 50%</div></div><div><div>—</div><div>△</div><div>—</div><div>Load 100%</div></div></div> <p>Hold-Up Time [ms]</p> <p>Input Voltage [V]</p> <p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy. Note: Slanted line shows the range of the rated input voltage.</p>		<table><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Hold-Up Time [ms]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>85</td><td>19</td><td>5</td></tr><tr><td>90</td><td>28</td><td>9</td></tr><tr><td>100</td><td>46</td><td>18</td></tr><tr><td>110</td><td>65</td><td>27</td></tr><tr><td>115</td><td>74</td><td>32</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	85	19	5	90	28	9	100	46	18	110	65	27	115	74	32	--	-	-	--	-	-	--	-	-	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																		
	Load 50%	Load 100%																																	
85	19	5																																	
90	28	9																																	
100	46	18																																	
110	65	27																																	
115	74	32																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	



Model	GT2.5W-15																																																					
Item	Instantaneous Interruption Compensation	Temperature	25°C																																																			
Object	+15V0.9A	Testing Circuitry	Figure A																																																			
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>- - □ - -</div><div>Input Volt.</div><div>100V</div></div><div><div>- · ○ - ·</div><div>Input Volt.</div><div>110V</div></div></div> <p>Instantaneous Compensation Time [ms]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Time [ms]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr><tr><td>0.15</td><td>89</td><td>139</td><td>206</td></tr><tr><td>0.30</td><td>38</td><td>71</td><td>89</td></tr><tr><td>0.45</td><td>22</td><td>39</td><td>56</td></tr><tr><td>0.60</td><td>5</td><td>22</td><td>39</td></tr><tr><td>0.75</td><td>5</td><td>22</td><td>23</td></tr><tr><td>0.90</td><td>4</td><td>6</td><td>22</td></tr><tr><td>0.99</td><td>4</td><td>5</td><td>22</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Time [ms]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.00	-	-	-	0.15	89	139	206	0.30	38	71	89	0.45	22	39	56	0.60	5	22	39	0.75	5	22	23	0.90	4	6	22	0.99	4	5	22	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0.00	-	-	-																																																			
0.15	89	139	206																																																			
0.30	38	71	89																																																			
0.45	22	39	56																																																			
0.60	5	22	39																																																			
0.75	5	22	23																																																			
0.90	4	6	22																																																			
0.99	4	5	22																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Model	GT2.5W-15																																																					
Item	Instantaneous Interruption Compensation	Temperature	25°C																																																			
Object	-15V0.9A	Testing Circuitry	Figure A																																																			
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt.</div><div>90V</div></div><div><div>---□---</div><div>Input Volt.</div><div>100V</div></div><div><div>---○---</div><div>Input Volt.</div><div>110V</div></div></div> <div>Instantaneous Compensation Time [ms]</div> <div>Load Current [A]</div> <div>Note: Slanted line shows the range of the rated load current.</div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Time [ms]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr><tr><td>0.15</td><td>89</td><td>139</td><td>204</td></tr><tr><td>0.30</td><td>38</td><td>71</td><td>89</td></tr><tr><td>0.45</td><td>21</td><td>39</td><td>56</td></tr><tr><td>0.60</td><td>5</td><td>22</td><td>39</td></tr><tr><td>0.75</td><td>5</td><td>21</td><td>23</td></tr><tr><td>0.90</td><td>4</td><td>6</td><td>22</td></tr><tr><td>0.99</td><td>4</td><td>5</td><td>22</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Time [ms]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.00	-	-	-	0.15	89	139	204	0.30	38	71	89	0.45	21	39	56	0.60	5	22	39	0.75	5	21	23	0.90	4	6	22	0.99	4	5	22	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0.00	-	-	-																																																			
0.15	89	139	204																																																			
0.30	38	71	89																																																			
0.45	21	39	56																																																			
0.60	5	22	39																																																			
0.75	5	21	23																																																			
0.90	4	6	22																																																			
0.99	4	5	22																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Model	GT2.5W-15																																								
Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A																																							
Object	+15V0.9A																																								
1.Graph		2.Values																																							
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="2">Input Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>-20</td><td>72</td><td>78</td></tr><tr><td>-10</td><td>73</td><td>79</td></tr><tr><td>0</td><td>73</td><td>79</td></tr><tr><td>10</td><td>73</td><td>79</td></tr><tr><td>20</td><td>73</td><td>79</td></tr><tr><td>25</td><td>73</td><td>79</td></tr><tr><td>30</td><td>73</td><td>79</td></tr><tr><td>40</td><td>73</td><td>79</td></tr><tr><td>50</td><td>73</td><td>79</td></tr><tr><td>60</td><td>73</td><td>79</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-20	72	78	-10	73	79	0	73	79	10	73	79	20	73	79	25	73	79	30	73	79	40	73	79	50	73	79	60	73	79	--	-	-		
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-20	72	78																																							
-10	73	79																																							
0	73	79																																							
10	73	79																																							
20	73	79																																							
25	73	79																																							
30	73	79																																							
40	73	79																																							
50	73	79																																							
60	73	79																																							
--	-	-																																							
Object	-15V0.9A																																								
1.Graph		2.Values																																							
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="2">Input Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>-20</td><td>72</td><td>78</td></tr><tr><td>-10</td><td>73</td><td>79</td></tr><tr><td>0</td><td>73</td><td>79</td></tr><tr><td>10</td><td>73</td><td>79</td></tr><tr><td>20</td><td>73</td><td>79</td></tr><tr><td>25</td><td>73</td><td>79</td></tr><tr><td>30</td><td>73</td><td>79</td></tr><tr><td>40</td><td>73</td><td>79</td></tr><tr><td>50</td><td>73</td><td>79</td></tr><tr><td>60</td><td>73</td><td>79</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-20	72	78	-10	73	79	0	73	79	10	73	79	20	73	79	25	73	79	30	73	79	40	73	79	50	73	79	60	73	79	--	-	-		
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-20	72	78																																							
-10	73	79																																							
0	73	79																																							
10	73	79																																							
20	73	79																																							
25	73	79																																							
30	73	79																																							
40	73	79																																							
50	73	79																																							
60	73	79																																							
--	-	-																																							
Note: Slanted line shows the range of the rated ambient temperature.																																									

- 24 -

BC-10218

Model	GT2.5W-15	Temperature Testing Circuitry	25°C Figure A																																																							
Item	Overcurrent Protection																																																									
Object	+15V0.9A																																																									
1.Graph		2.Values																																																								
<div><div></div>Input Volt. 90V</div> <div><div></div>Input Volt. 100V</div> <div><div></div>Input Volt. 110V</div> 																																																										
		<table><tr><th rowspan="2">Output Voltage [V]</th><th colspan="3">Load Current [A]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>15.0</td><td>1.15</td><td>1.15</td><td>1.15</td></tr><tr><td>14.3</td><td>1.11</td><td>1.11</td><td>1.11</td></tr><tr><td>13.5</td><td>1.08</td><td>1.08</td><td>1.08</td></tr><tr><td>12.0</td><td>1.02</td><td>1.02</td><td>1.02</td></tr><tr><td>10.5</td><td>0.95</td><td>0.95</td><td>0.95</td></tr><tr><td>9.0</td><td>0.89</td><td>0.89</td><td>0.89</td></tr><tr><td>7.5</td><td>0.82</td><td>0.82</td><td>0.82</td></tr><tr><td>6.0</td><td>0.76</td><td>0.76</td><td>0.76</td></tr><tr><td>4.5</td><td>0.69</td><td>0.69</td><td>0.69</td></tr><tr><td>3.0</td><td>0.63</td><td>0.63</td><td>0.63</td></tr><tr><td>1.5</td><td>0.56</td><td>0.56</td><td>0.56</td></tr><tr><td>0.0</td><td>0.49</td><td>0.49</td><td>0.49</td></tr></table>	Output Voltage [V]	Load Current [A]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	15.0	1.15	1.15	1.15	14.3	1.11	1.11	1.11	13.5	1.08	1.08	1.08	12.0	1.02	1.02	1.02	10.5	0.95	0.95	0.95	9.0	0.89	0.89	0.89	7.5	0.82	0.82	0.82	6.0	0.76	0.76	0.76	4.5	0.69	0.69	0.69	3.0	0.63	0.63	0.63	1.5	0.56	0.56	0.56	0.0	0.49	0.49	0.49	
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																							
15.0	1.15	1.15	1.15																																																							
14.3	1.11	1.11	1.11																																																							
13.5	1.08	1.08	1.08																																																							
12.0	1.02	1.02	1.02																																																							
10.5	0.95	0.95	0.95																																																							
9.0	0.89	0.89	0.89																																																							
7.5	0.82	0.82	0.82																																																							
6.0	0.76	0.76	0.76																																																							
4.5	0.69	0.69	0.69																																																							
3.0	0.63	0.63	0.63																																																							
1.5	0.56	0.56	0.56																																																							
0.0	0.49	0.49	0.49																																																							
Object	-15V0.9A																																																									
1.Graph				2.Values																																																						
<div><div></div>Input Volt. 90V</div> <div><div></div>Input Volt. 100V</div> <div><div></div>Input Volt. 110V</div> 																																																										
Note: Slanted line shows the range of the rated load current.		<table><tr><th rowspan="2">Output Voltage [V]</th><th colspan="3">Load Current [A]</th></tr><tr><th>Input Volt. 90[V]</th><th>Input Volt. 100[V]</th><th>Input Volt. 110[V]</th></tr><tr><td>-15.00</td><td>1.16</td><td>1.16</td><td>1.16</td></tr><tr><td>-14.25</td><td>1.13</td><td>1.13</td><td>1.13</td></tr><tr><td>-13.50</td><td>1.09</td><td>1.09</td><td>1.09</td></tr><tr><td>-12.00</td><td>1.03</td><td>1.03</td><td>1.03</td></tr><tr><td>-10.50</td><td>0.96</td><td>0.96</td><td>0.96</td></tr><tr><td>-9.00</td><td>0.90</td><td>0.90</td><td>0.90</td></tr><tr><td>-7.50</td><td>0.83</td><td>0.83</td><td>0.83</td></tr><tr><td>-6.00</td><td>0.76</td><td>0.76</td><td>0.76</td></tr><tr><td>-4.50</td><td>0.70</td><td>0.70</td><td>0.70</td></tr><tr><td>-3.00</td><td>0.63</td><td>0.63</td><td>0.63</td></tr><tr><td>-1.50</td><td>0.57</td><td>0.57</td><td>0.57</td></tr><tr><td>0.00</td><td>0.50</td><td>0.50</td><td>0.50</td></tr></table>		Output Voltage [V]	Load Current [A]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	-15.00	1.16	1.16	1.16	-14.25	1.13	1.13	1.13	-13.50	1.09	1.09	1.09	-12.00	1.03	1.03	1.03	-10.50	0.96	0.96	0.96	-9.00	0.90	0.90	0.90	-7.50	0.83	0.83	0.83	-6.00	0.76	0.76	0.76	-4.50	0.70	0.70	0.70	-3.00	0.63	0.63	0.63	-1.50	0.57	0.57	0.57	0.00	0.50	0.50	0.50
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																							
-15.00	1.16	1.16	1.16																																																							
-14.25	1.13	1.13	1.13																																																							
-13.50	1.09	1.09	1.09																																																							
-12.00	1.03	1.03	1.03																																																							
-10.50	0.96	0.96	0.96																																																							
-9.00	0.90	0.90	0.90																																																							
-7.50	0.83	0.83	0.83																																																							
-6.00	0.76	0.76	0.76																																																							
-4.50	0.70	0.70	0.70																																																							
-3.00	0.63	0.63	0.63																																																							
-1.50	0.57	0.57	0.57																																																							
0.00	0.50	0.50	0.50																																																							

- 25 -

BC-10218




Figure A