

# TEST DATA OF GT2W-12

Regulated DC Power Supply  
October 26, 2010

Approved by : Eiyoshi Wakamatsu  
Eiyoshi Wakamatsu                          Design Manager

Prepared by : Satoshi Kinoshita  
Satoshi Kinoshita                          Design Engineer


**COSEL CO.,LTD.**

## CONTENTS

1.Input Current (by Load Current) · · · · ·	1
2.Input Power (by Load Current) · · · · ·	2
3.Efficiency (by Input Voltage) · · · · ·	3
4.Efficiency (by Load Current) · · · · ·	4
5.Power Factor (by Input Voltage) · · · · ·	5
6.Power Factor (by Load Current) · · · · ·	6
7.Inrush Current · · · · ·	7
8.Line Regulation · · · · ·	8
9.Load Regulation · · · · ·	9
10.Dynamic Load Response · · · · ·	10
11.Ripple Voltage (by Load Current) · · · · ·	12
12.Ripple Voltage (by Ambient Temperature) · · · · ·	14
13.Ambient Temperature Drift · · · · ·	15
14.Output Voltage Accuracy · · · · ·	16
15.Time Lapse Drift · · · · ·	17
16.Rise and Fall Time · · · · ·	18
17.Hold-Up Time · · · · ·	20
18.Instantaneous Interruption Compensation · · · · ·	22
19.Minimum Input Voltage for Regulated Output Voltage · · · · ·	24
20.Overcurrent Protection · · · · ·	25
21.Figure of Testing Circuitry · · · · ·	26


(Final Page 26)

**COSEL**

Model	GT2W-12																																																					
Item	Input Current (by Load Current)																																																					
Object	<u> </u>																																																					
1.Graph																																																						
<p style="text-align: center;"> <span style="display: inline-block; width: 15px; height: 15px; border: 1px solid black; border-radius: 50%; background-color: white;"></span> Input Volt. 90V  <span style="display: inline-block; width: 15px; height: 15px; border: 1px dashed black; border-radius: 50%; background-color: white;"></span> Input Volt. 100V  <span style="display: inline-block; width: 15px; height: 15px; border: 1px dashed black; border-radius: 50%; border: 1px solid black; background-color: white;"></span> Input Volt. 110V     </p>  <table border="1" style="margin-left: auto; margin-right: auto;"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>90V [A]</th> <th>100V [A]</th> <th>110V [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.017</td><td>0.019</td><td>0.021</td></tr> <tr><td>20</td><td>0.117</td><td>0.120</td><td>0.123</td></tr> <tr><td>40</td><td>0.200</td><td>0.205</td><td>0.209</td></tr> <tr><td>60</td><td>0.278</td><td>0.283</td><td>0.289</td></tr> <tr><td>80</td><td>0.350</td><td>0.357</td><td>0.364</td></tr> <tr><td>100</td><td>0.420</td><td>0.428</td><td>0.436</td></tr> <tr><td>110</td><td>0.453</td><td>0.463</td><td>0.471</td></tr> </tbody> </table>				Load Ration [%]	90V [A]	100V [A]	110V [A]	0	0.017	0.019	0.021	20	0.117	0.120	0.123	40	0.200	0.205	0.209	60	0.278	0.283	0.289	80	0.350	0.357	0.364	100	0.420	0.428	0.436	110	0.453	0.463	0.471																			
Load Ration [%]	90V [A]	100V [A]	110V [A]																																																			
0	0.017	0.019	0.021																																																			
20	0.117	0.120	0.123																																																			
40	0.200	0.205	0.209																																																			
60	0.278	0.283	0.289																																																			
80	0.350	0.357	0.364																																																			
100	0.420	0.428	0.436																																																			
110	0.453	0.463	0.471																																																			
2.Values																																																						
<table border="1" style="width: 100%;"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 90[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 110[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.017</td><td>0.019</td><td>0.021</td></tr> <tr><td>20</td><td>0.117</td><td>0.120</td><td>0.123</td></tr> <tr><td>40</td><td>0.200</td><td>0.205</td><td>0.209</td></tr> <tr><td>60</td><td>0.278</td><td>0.283</td><td>0.289</td></tr> <tr><td>80</td><td>0.350</td><td>0.357</td><td>0.364</td></tr> <tr><td>100</td><td>0.420</td><td>0.428</td><td>0.436</td></tr> <tr><td>110</td><td>0.453</td><td>0.463</td><td>0.471</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Ration [%]	Input Current [A]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0	0.017	0.019	0.021	20	0.117	0.120	0.123	40	0.200	0.205	0.209	60	0.278	0.283	0.289	80	0.350	0.357	0.364	100	0.420	0.428	0.436	110	0.453	0.463	0.471	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Current [A]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0	0.017	0.019	0.021																																																			
20	0.117	0.120	0.123																																																			
40	0.200	0.205	0.209																																																			
60	0.278	0.283	0.289																																																			
80	0.350	0.357	0.364																																																			
100	0.420	0.428	0.436																																																			
110	0.453	0.463	0.471																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

**COSEL**

Model	GT2W-12
Item	Input Power (by Load Current)
Object	_____



Temperature 25°C  
Testing Circuitry Figure A

## 2.Values


Load Ration [%]	Input Power [W]		
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]
0	0.90	1.10	1.30
20	6.50	7.30	8.10
40	11.90	13.40	14.80
60	17.40	19.40	21.50
80	22.70	25.40	28.10
100	28.10	31.30	34.60
110	30.70	34.30	37.90
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

**COSEL**

Model	GT2W-12																																	
Item	Efficiency (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	—	—																																
1.Graph																																		
<p>The graph plots Efficiency [%] on the y-axis (22 to 78) against Input Voltage [V] on the x-axis (80 to 120). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show a general downward trend as input voltage increases. A slanted line on the graph indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>65.4</td> <td>68.4</td> </tr> <tr> <td>90</td> <td>61.4</td> <td>64.2</td> </tr> <tr> <td>100</td> <td>55.0</td> <td>57.5</td> </tr> <tr> <td>110</td> <td>49.6</td> <td>52.2</td> </tr> <tr> <td>115</td> <td>47.5</td> <td>49.7</td> </tr> </tbody> </table>			Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	85	65.4	68.4	90	61.4	64.2	100	55.0	57.5	110	49.6	52.2	115	47.5	49.7														
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																																
85	65.4	68.4																																
90	61.4	64.2																																
100	55.0	57.5																																
110	49.6	52.2																																
115	47.5	49.7																																
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>65.4</td> <td>68.4</td> </tr> <tr> <td>90</td> <td>61.4</td> <td>64.2</td> </tr> <tr> <td>100</td> <td>55.0</td> <td>57.5</td> </tr> <tr> <td>110</td> <td>49.6</td> <td>52.2</td> </tr> <tr> <td>115</td> <td>47.5</td> <td>49.7</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	85	65.4	68.4	90	61.4	64.2	100	55.0	57.5	110	49.6	52.2	115	47.5	49.7	--	-	-	--	-	-	--	-	-	--	-	-
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
85	65.4	68.4																																
90	61.4	64.2																																
100	55.0	57.5																																
110	49.6	52.2																																
115	47.5	49.7																																
--	-	-																																
--	-	-																																
--	-	-																																
--	-	-																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

**COSEL**

Model	GT2W-12
Item	Efficiency (by Load Current)
Object	_____



Temperature 25°C  
Testing Circuitry Figure A

2.Values

Load Ration [%]	Efficiency [%]		
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]
0	-	-	-
20	55.6	49.5	44.5
40	60.6	53.8	48.7
60	62.2	55.8	50.3
80	63.6	56.8	51.4
100	64.2	57.7	52.2
110	64.7	57.9	52.4
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-


**COSEL**

Model	GT2W-12																																	
Item	Power Factor (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	—	—																																
1.Graph																																		
<p>Graph showing Power Factor vs Input Voltage for GT2W-12 at 25°C. The x-axis is Input Voltage [V] from 80 to 120. The y-axis is Power Factor from 0.2 to 0.8. Two sets of data points are shown: Load 50% (dashed line, squares) and Load 100% (solid line, triangles). Both series show a slight decrease in power factor as input voltage increases. A slanted line indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 50% Power Factor</th> <th>Load 100% Power Factor</th> </tr> </thead> <tbody> <tr><td>85</td><td>0.687</td><td>0.748</td></tr> <tr><td>90</td><td>0.684</td><td>0.745</td></tr> <tr><td>100</td><td>0.672</td><td>0.734</td></tr> <tr><td>110</td><td>0.664</td><td>0.722</td></tr> <tr><td>115</td><td>0.655</td><td>0.719</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Load 50% Power Factor	Load 100% Power Factor	85	0.687	0.748	90	0.684	0.745	100	0.672	0.734	110	0.664	0.722	115	0.655	0.719	--	-	-	--	-	-	--	-	-	--	-	-		
Input Voltage [V]	Load 50% Power Factor	Load 100% Power Factor																																
85	0.687	0.748																																
90	0.684	0.745																																
100	0.672	0.734																																
110	0.664	0.722																																
115	0.655	0.719																																
--	-	-																																
--	-	-																																
--	-	-																																
--	-	-																																
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>85</td><td>0.687</td><td>0.748</td></tr> <tr><td>90</td><td>0.684</td><td>0.745</td></tr> <tr><td>100</td><td>0.672</td><td>0.734</td></tr> <tr><td>110</td><td>0.664</td><td>0.722</td></tr> <tr><td>115</td><td>0.655</td><td>0.719</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Power Factor		Load 50%	Load 100%	85	0.687	0.748	90	0.684	0.745	100	0.672	0.734	110	0.664	0.722	115	0.655	0.719	--	-	-	--	-	-	--	-	-	--	-	-
Input Voltage [V]	Power Factor																																	
	Load 50%	Load 100%																																
85	0.687	0.748																																
90	0.684	0.745																																
100	0.672	0.734																																
110	0.664	0.722																																
115	0.655	0.719																																
--	-	-																																
--	-	-																																
--	-	-																																
--	-	-																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

Model	GT2W-12	Temperature Testing Circuitry      25°C Figure A																																																				
Item	Power Factor (by Load Current)																																																					
Object	_____	2.Values																																																				
1.Graph	_____	<p>—△— Input Volt. 90V        - - □ - - Input Volt. 100V        - - ○ - - Input Volt. 110V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>90V [Power Factor]</th> <th>100V [Power Factor]</th> <th>110V [Power Factor]</th> </tr> </thead> <tbody> <tr><td>30</td><td>0.60</td><td>0.61</td><td>0.60</td></tr> <tr><td>40</td><td>0.65</td><td>0.66</td><td>0.65</td></tr> <tr><td>50</td><td>0.68</td><td>0.69</td><td>0.68</td></tr> <tr><td>60</td><td>0.70</td><td>0.71</td><td>0.70</td></tr> <tr><td>70</td><td>0.72</td><td>0.73</td><td>0.72</td></tr> <tr><td>80</td><td>0.73</td><td>0.74</td><td>0.73</td></tr> <tr><td>90</td><td>0.74</td><td>0.75</td><td>0.74</td></tr> <tr><td>100</td><td>0.75</td><td>0.76</td><td>0.75</td></tr> </tbody> </table>			Load Ration [%]	90V [Power Factor]	100V [Power Factor]	110V [Power Factor]	30	0.60	0.61	0.60	40	0.65	0.66	0.65	50	0.68	0.69	0.68	60	0.70	0.71	0.70	70	0.72	0.73	0.72	80	0.73	0.74	0.73	90	0.74	0.75	0.74	100	0.75	0.76	0.75														
Load Ration [%]	90V [Power Factor]	100V [Power Factor]	110V [Power Factor]																																																			
30	0.60	0.61	0.60																																																			
40	0.65	0.66	0.65																																																			
50	0.68	0.69	0.68																																																			
60	0.70	0.71	0.70																																																			
70	0.72	0.73	0.72																																																			
80	0.73	0.74	0.73																																																			
90	0.74	0.75	0.74																																																			
100	0.75	0.76	0.75																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 90[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 110[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>0.613</td><td>0.608</td><td>0.596</td></tr> <tr><td>40</td><td>0.661</td><td>0.654</td><td>0.643</td></tr> <tr><td>60</td><td>0.696</td><td>0.686</td><td>0.676</td></tr> <tr><td>80</td><td>0.721</td><td>0.711</td><td>0.703</td></tr> <tr><td>100</td><td>0.743</td><td>0.731</td><td>0.721</td></tr> <tr><td>110</td><td>0.752</td><td>0.742</td><td>0.732</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Power Factor			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0	-	-	-	20	0.613	0.608	0.596	40	0.661	0.654	0.643	60	0.696	0.686	0.676	80	0.721	0.711	0.703	100	0.743	0.731	0.721	110	0.752	0.742	0.732	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Power Factor																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0	-	-	-																																																			
20	0.613	0.608	0.596																																																			
40	0.661	0.654	0.643																																																			
60	0.696	0.686	0.676																																																			
80	0.721	0.711	0.703																																																			
100	0.743	0.731	0.721																																																			
110	0.752	0.742	0.732																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			


**COSEL**

Model	GT2W-12	Temperature Testing Circuitry 25°C Figure A
Item	Inrush Current	
Object	_____	



Input Voltage      100 V  
 Frequency          60 Hz  
 Load                100 %

Primary inrush current      7.3 A




**COSEL**

Model	GT2W-12
Item	Line Regulation
Object	+12V0.75A

Temperature 25°C  
Testing Circuitry Figure A

## 1.Graph




## 2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
85	12.024	12.023
90	12.024	12.023
100	12.024	12.023
110	12.024	12.023
115	12.024	12.023
--	-	-
--	-	-
--	-	-
--	-	-

Object	-12V0.75A
--------	-----------

## 1.Graph




## 2.Values


Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
85	-12.024	-12.023
90	-12.024	-12.023
100	-12.024	-12.023
110	-12.024	-12.023
115	-12.024	-12.023
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated input voltage.



Model	GT2W-12	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+12V0.75A																																																					
1.Graph	<p>—△— Input Volt. 90V        - - -□--- Input Volt. 100V        - - -○--- Input Volt. 110V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 90[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 110[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>12.025</td><td>12.025</td><td>12.025</td></tr> <tr><td>0.150</td><td>12.024</td><td>12.025</td><td>12.024</td></tr> <tr><td>0.300</td><td>12.024</td><td>12.024</td><td>12.024</td></tr> <tr><td>0.450</td><td>12.024</td><td>12.024</td><td>12.024</td></tr> <tr><td>0.600</td><td>12.023</td><td>12.023</td><td>12.023</td></tr> <tr><td>0.750</td><td>12.023</td><td>12.023</td><td>12.023</td></tr> <tr><td>0.825</td><td>12.023</td><td>12.023</td><td>12.023</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.000	12.025	12.025	12.025	0.150	12.024	12.025	12.024	0.300	12.024	12.024	12.024	0.450	12.024	12.024	12.024	0.600	12.023	12.023	12.023	0.750	12.023	12.023	12.023	0.825	12.023	12.023	12.023	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0.000	12.025	12.025	12.025																																																			
0.150	12.024	12.025	12.024																																																			
0.300	12.024	12.024	12.024																																																			
0.450	12.024	12.024	12.024																																																			
0.600	12.023	12.023	12.023																																																			
0.750	12.023	12.023	12.023																																																			
0.825	12.023	12.023	12.023																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Object	-12V0.75A	2.Values																																																				
1.Graph	<p>—△— Input Volt. 90V        - - -□--- Input Volt. 100V        - - -○--- Input Volt. 110V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 90[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 110[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-12.025</td><td>-12.025</td><td>-12.025</td></tr> <tr><td>0.150</td><td>-12.025</td><td>-12.025</td><td>-12.025</td></tr> <tr><td>0.300</td><td>-12.024</td><td>-12.024</td><td>-12.024</td></tr> <tr><td>0.450</td><td>-12.024</td><td>-12.024</td><td>-12.024</td></tr> <tr><td>0.600</td><td>-12.024</td><td>-12.024</td><td>-12.024</td></tr> <tr><td>0.750</td><td>-12.023</td><td>-12.023</td><td>-12.023</td></tr> <tr><td>0.825</td><td>-12.023</td><td>-12.023</td><td>-12.023</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.000	-12.025	-12.025	-12.025	0.150	-12.025	-12.025	-12.025	0.300	-12.024	-12.024	-12.024	0.450	-12.024	-12.024	-12.024	0.600	-12.024	-12.024	-12.024	0.750	-12.023	-12.023	-12.023	0.825	-12.023	-12.023	-12.023	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0.000	-12.025	-12.025	-12.025																																																			
0.150	-12.025	-12.025	-12.025																																																			
0.300	-12.024	-12.024	-12.024																																																			
0.450	-12.024	-12.024	-12.024																																																			
0.600	-12.024	-12.024	-12.024																																																			
0.750	-12.023	-12.023	-12.023																																																			
0.825	-12.023	-12.023	-12.023																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

**COSEL**

**COSEL**

**COSEL**

Model	GT2W-12																																										
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure A																																									
Object	+12V0.75A																																										
1.Graph																																											
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0.0 to 4.0 mV, and the X-axis ranges from 0.0 to 1.0 A. Two curves are plotted: one for Input Volt. 90V (solid line with open circles) and one for Input Volt. 110V (dashed line with open triangles). Both curves show a slight increase in ripple voltage as load current increases. A slanted line indicates the range of rated load current.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input Volt. 90V)</th> <th>Ripple Voltage [mV] (Input Volt. 110V)</th> </tr> </thead> <tbody> <tr> <td>0.000</td> <td>0.6</td> <td>0.6</td> </tr> <tr> <td>0.375</td> <td>0.8</td> <td>0.8</td> </tr> <tr> <td>0.750</td> <td>0.9</td> <td>0.9</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV] (Input Volt. 90V)	Ripple Voltage [mV] (Input Volt. 110V)	0.000	0.6	0.6	0.375	0.8	0.8	0.750	0.9	0.9	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-		
Load Current [A]	Ripple Voltage [mV] (Input Volt. 90V)	Ripple Voltage [mV] (Input Volt. 110V)																																									
0.000	0.6	0.6																																									
0.375	0.8	0.8																																									
0.750	0.9	0.9																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
2.Values																																											
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 90 [V]</th> <th>Input Volt. 110 [V]</th> </tr> </thead> <tbody> <tr> <td>0.000</td> <td>0.6</td> <td>0.6</td> </tr> <tr> <td>0.375</td> <td>0.8</td> <td>0.8</td> </tr> <tr> <td>0.750</td> <td>0.9</td> <td>0.9</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 90 [V]	Input Volt. 110 [V]	0.000	0.6	0.6	0.375	0.8	0.8	0.750	0.9	0.9	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																										
	Input Volt. 90 [V]	Input Volt. 110 [V]																																									
0.000	0.6	0.6																																									
0.375	0.8	0.8																																									
0.750	0.9	0.9																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
<p>Measured by 20 MHz Oscilloscope. Note: Slanted line shows the range of the rated load current.</p>																																											


**COSEL**

Model	GT2W-12																																										
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure A																																									
Object	-12V0.75A																																										
1.Graph																																											
<p>—△— Input Volt. 90V    -·○--- Input Volt. 110V</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input Volt. 90V)</th> <th>Ripple Voltage [mV] (Input Volt. 110V)</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>0.5</td><td>0.5</td></tr> <tr><td>0.375</td><td>0.6</td><td>0.6</td></tr> <tr><td>0.750</td><td>0.6</td><td>0.6</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV] (Input Volt. 90V)	Ripple Voltage [mV] (Input Volt. 110V)	0.000	0.5	0.5	0.375	0.6	0.6	0.750	0.6	0.6	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-			
Load Current [A]	Ripple Voltage [mV] (Input Volt. 90V)	Ripple Voltage [mV] (Input Volt. 110V)																																									
0.000	0.5	0.5																																									
0.375	0.6	0.6																																									
0.750	0.6	0.6																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
2.Values																																											
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 90 [V]</th> <th>Input Volt. 110 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>0.5</td><td>0.5</td></tr> <tr><td>0.375</td><td>0.6</td><td>0.6</td></tr> <tr><td>0.750</td><td>0.6</td><td>0.6</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 90 [V]	Input Volt. 110 [V]	0.000	0.5	0.5	0.375	0.6	0.6	0.750	0.6	0.6	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																										
	Input Volt. 90 [V]	Input Volt. 110 [V]																																									
0.000	0.5	0.5																																									
0.375	0.6	0.6																																									
0.750	0.6	0.6																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
<p>Measured by 20 MHz Oscilloscope.    Note: Slanted line shows the range of the rated load current.</p>																																											

**COSEL**

Model	GT2W-12
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V0.75A

## 1.Graph




Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-20	1.0	1.0
-10	0.9	0.9
25	0.8	0.9
50	0.8	0.9
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

## 1.Graph



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-20	0.6	0.7
-10	0.6	0.6
25	0.6	0.6
50	0.6	0.6
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 20 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.



Model	GT2W-12	Testing Circuitry Figure A		
Item	Ambient Temperature Drift			
Object	+12V0.75A			
1.Graph	<p style="text-align: center;"> <span style="color: black;">—△—</span> Input Volt. 90V  <span style="color: gray;">---□---</span> Input Volt. 100V  <span style="color: gray;">---○---</span> Input Volt. 110V         </p> <p style="text-align: center;">Output Voltage [V]</p> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: center;">Load 100%</p>	2.Values		
2.Values				
Object	-12V0.75A	2.Values		
1.Graph	<p style="text-align: center;"> <span style="color: black;">—△—</span> Input Volt. 90V  <span style="color: gray;">---□---</span> Input Volt. 100V  <span style="color: gray;">---○---</span> Input Volt. 110V         </p> <p style="text-align: center;">Output Voltage [V]</p> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: center;">Load 100%</p>			
2.Values				

Note: Slanted line shows the range of the rated ambient temperature.



Model	GT2W-12	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 - 50°C

Input Voltage : 90 - 110V

Load Current (AVR 1) : 0 - 0.75A (AVR 2) : 0 - 0.75A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$



$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values

Object	+12V0.75A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	10	100	0	12.030	$\pm 7$	$\pm 0.1$
Minimum Voltage	50	110	0.75	12.016		

Object	-12V0.75A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	10	90	0	-12.029	$\pm 7$	$\pm 0.1$
Minimum Voltage	50	90	0.75	-12.016		

**COSEL**


Model	GT2W-12	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V0.75A																								
1.Graph		2.Values																							
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V</p> <p>Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th><th>Output Voltage [V]</th></tr> </thead> <tbody> <tr><td>0.0</td><td>12.023</td></tr> <tr><td>0.5</td><td>12.023</td></tr> <tr><td>1.0</td><td>12.023</td></tr> <tr><td>2.0</td><td>12.023</td></tr> <tr><td>3.0</td><td>12.023</td></tr> <tr><td>4.0</td><td>12.023</td></tr> <tr><td>5.0</td><td>12.023</td></tr> <tr><td>6.0</td><td>12.023</td></tr> <tr><td>7.0</td><td>12.023</td></tr> <tr><td>8.0</td><td>12.023</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	12.023	0.5	12.023	1.0	12.023	2.0	12.023	3.0	12.023	4.0	12.023	5.0	12.023	6.0	12.023	7.0	12.023	8.0	12.023
Time since start [H]	Output Voltage [V]																								
0.0	12.023																								
0.5	12.023																								
1.0	12.023																								
2.0	12.023																								
3.0	12.023																								
4.0	12.023																								
5.0	12.023																								
6.0	12.023																								
7.0	12.023																								
8.0	12.023																								
Object -12V0.75A		2.Values																							
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V</p> <p>Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th><th>Output Voltage [V]</th></tr> </thead> <tbody> <tr><td>0.0</td><td>-12.024</td></tr> <tr><td>0.5</td><td>-12.023</td></tr> <tr><td>1.0</td><td>-12.023</td></tr> <tr><td>2.0</td><td>-12.023</td></tr> <tr><td>3.0</td><td>-12.023</td></tr> <tr><td>4.0</td><td>-12.023</td></tr> <tr><td>5.0</td><td>-12.023</td></tr> <tr><td>6.0</td><td>-12.023</td></tr> <tr><td>7.0</td><td>-12.023</td></tr> <tr><td>8.0</td><td>-12.023</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	-12.024	0.5	-12.023	1.0	-12.023	2.0	-12.023	3.0	-12.023	4.0	-12.023	5.0	-12.023	6.0	-12.023	7.0	-12.023	8.0	-12.023
Time since start [H]	Output Voltage [V]																								
0.0	-12.024																								
0.5	-12.023																								
1.0	-12.023																								
2.0	-12.023																								
3.0	-12.023																								
4.0	-12.023																								
5.0	-12.023																								
6.0	-12.023																								
7.0	-12.023																								
8.0	-12.023																								

**COSEL**

Model	GT2W-12
Item	Rise and Fall Time
Object	+12V0.75A


Temperature 25°C  
Testing Circuitry Figure A

## 1.Graph



## 2.Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		12.3	26.8	39.1	58.5	273.0
100 %		12.5	26.5	39.0	24.5	141.5




**COSEL**

Model	GT2W-12
Item	Rise and Fall Time
Object	-12V0.75A


Temperature 25°C  
Testing Circuitry Figure A

## 1.Graph



## 2.Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		12.0	27.0	39.0	58.5	272.5	
100 %		12.3	26.8	39.1	24.0	139.5	




**COSEL**

Model	GT2W-12
Item	Hold-Up Time
Object	+12V0.75A

 Temperature 25°C  
 Testing Circuitry Figure A

## 1.Graph



## 2.Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
85	21	5
90	30	10
100	48	19
110	67	28
115	76	33
--	-	-
--	-	-
--	-	-
--	-	-


This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.  
 Note: Slanted line shows the range of the rated input voltage.

**COSEL**

Model	GT2W-12
Item	Hold-Up Time
Object	-12V0.75A

 Temperature 25°C  
 Testing Circuitry Figure A

## 1.Graph



## 2.Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
85	21	5
90	30	10
100	48	19
110	67	28
115	76	33
--	-	-
--	-	-
--	-	-
--	-	-

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.  
 Note: Slanted line shows the range of the rated input voltage.

Model	GT2W-12	Temperature Testing Circuitry      25°C Figure A																																																				
Item	Instantaneous Interruption Compensation																																																					
Object	+12V0.75A																																																					
1.Graph	<p>—△— Input Volt. 90V      - - -□- - Input Volt. 100V      - - -○- - Input Volt. 110V</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>90[V] [ms]</th> <th>100[V] [ms]</th> <th>110[V] [ms]</th> </tr> </thead> <tbody> <tr><td>0.150</td><td>73</td><td>123</td><td>173</td></tr> <tr><td>0.300</td><td>38</td><td>56</td><td>73</td></tr> <tr><td>0.450</td><td>21</td><td>37</td><td>53</td></tr> <tr><td>0.600</td><td>5</td><td>22</td><td>37</td></tr> <tr><td>0.750</td><td>5</td><td>6</td><td>22</td></tr> <tr><td>0.825</td><td>4</td><td>5</td><td>22</td></tr> </tbody> </table>	Load Current [A]	90[V] [ms]	100[V] [ms]	110[V] [ms]	0.150	73	123	173	0.300	38	56	73	0.450	21	37	53	0.600	5	22	37	0.750	5	6	22	0.825	4	5	22																									
Load Current [A]	90[V] [ms]	100[V] [ms]	110[V] [ms]																																																			
0.150	73	123	173																																																			
0.300	38	56	73																																																			
0.450	21	37	53																																																			
0.600	5	22	37																																																			
0.750	5	6	22																																																			
0.825	4	5	22																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 90[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 110[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.150</td><td>73</td><td>123</td><td>173</td></tr> <tr><td>0.300</td><td>38</td><td>56</td><td>73</td></tr> <tr><td>0.450</td><td>21</td><td>37</td><td>53</td></tr> <tr><td>0.600</td><td>5</td><td>22</td><td>37</td></tr> <tr><td>0.750</td><td>5</td><td>6</td><td>22</td></tr> <tr><td>0.825</td><td>4</td><td>5</td><td>22</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.000	-	-	-	0.150	73	123	173	0.300	38	56	73	0.450	21	37	53	0.600	5	22	37	0.750	5	6	22	0.825	4	5	22	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0.000	-	-	-																																																			
0.150	73	123	173																																																			
0.300	38	56	73																																																			
0.450	21	37	53																																																			
0.600	5	22	37																																																			
0.750	5	6	22																																																			
0.825	4	5	22																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

Model	GT2W-12	Temperature Testing Circuitry      25°C Figure A																																																				
Item	Instantaneous Interruption Compensation																																																					
Object	-12V0.75A																																																					
1.Graph	<p>—△— Input Volt. 90V        - - -□- - Input Volt. 100V        - - -○- - Input Volt. 110V</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>90[V] [ms]</th> <th>100[V] [ms]</th> <th>110[V] [ms]</th> </tr> </thead> <tbody> <tr><td>0.150</td><td>73</td><td>123</td><td>173</td></tr> <tr><td>0.300</td><td>38</td><td>56</td><td>73</td></tr> <tr><td>0.450</td><td>21</td><td>37</td><td>53</td></tr> <tr><td>0.600</td><td>5</td><td>22</td><td>37</td></tr> <tr><td>0.750</td><td>4</td><td>6</td><td>22</td></tr> <tr><td>0.825</td><td>4</td><td>5</td><td>22</td></tr> </tbody> </table>	Load Current [A]	90[V] [ms]	100[V] [ms]	110[V] [ms]	0.150	73	123	173	0.300	38	56	73	0.450	21	37	53	0.600	5	22	37	0.750	4	6	22	0.825	4	5	22																									
Load Current [A]	90[V] [ms]	100[V] [ms]	110[V] [ms]																																																			
0.150	73	123	173																																																			
0.300	38	56	73																																																			
0.450	21	37	53																																																			
0.600	5	22	37																																																			
0.750	4	6	22																																																			
0.825	4	5	22																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 90[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 110[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.150</td><td>73</td><td>123</td><td>173</td></tr> <tr><td>0.300</td><td>38</td><td>56</td><td>73</td></tr> <tr><td>0.450</td><td>21</td><td>37</td><td>53</td></tr> <tr><td>0.600</td><td>5</td><td>22</td><td>37</td></tr> <tr><td>0.750</td><td>4</td><td>6</td><td>22</td></tr> <tr><td>0.825</td><td>4</td><td>5</td><td>22</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	0.000	-	-	-	0.150	73	123	173	0.300	38	56	73	0.450	21	37	53	0.600	5	22	37	0.750	4	6	22	0.825	4	5	22	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																			
0.000	-	-	-																																																			
0.150	73	123	173																																																			
0.300	38	56	73																																																			
0.450	21	37	53																																																			
0.600	5	22	37																																																			
0.750	4	6	22																																																			
0.825	4	5	22																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.




Model	GT2W-12
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V0.75A

Testing Circuitry Figure A

## 1.Graph

---□--- Load 50%  
—△— Load 100%




## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	73	79
-10	73	79
0	73	79
10	73	79
20	73	79
25	73	79
30	73	79
40	73	79
50	73	79
60	73	79
--	-	-

Object	-12V0.75A
--------	-----------

## 1.Graph

---□--- Load 50%  
—△— Load 100%



## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	73	79
-10	73	79
0	73	79
10	73	79
20	73	79
25	73	79
30	73	79
40	73	79
50	73	79
60	73	79
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

**COSSEL**

Model	GT2W-12	Temperature Testing Circuitry	25°C Figure A																																																							
Item	Overcurrent Protection																																																									
Object	+12V0.75A																																																									
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 90V Input Volt. 100V Input Volt. 110V</p>	2.Values																																																								
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 90[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 110[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>0.94</td><td>0.94</td><td>0.94</td></tr> <tr><td>11.4</td><td>0.92</td><td>0.92</td><td>0.92</td></tr> <tr><td>10.8</td><td>0.89</td><td>0.89</td><td>0.89</td></tr> <tr><td>9.6</td><td>0.84</td><td>0.84</td><td>0.84</td></tr> <tr><td>8.4</td><td>0.79</td><td>0.79</td><td>0.79</td></tr> <tr><td>7.2</td><td>0.74</td><td>0.74</td><td>0.74</td></tr> <tr><td>6.0</td><td>0.69</td><td>0.68</td><td>0.68</td></tr> <tr><td>4.8</td><td>0.64</td><td>0.64</td><td>0.64</td></tr> <tr><td>3.6</td><td>0.58</td><td>0.58</td><td>0.58</td></tr> <tr><td>2.4</td><td>0.53</td><td>0.53</td><td>0.53</td></tr> <tr><td>1.2</td><td>0.48</td><td>0.48</td><td>0.48</td></tr> <tr><td>0.0</td><td>0.42</td><td>0.42</td><td>0.42</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	12.0	0.94	0.94	0.94	11.4	0.92	0.92	0.92	10.8	0.89	0.89	0.89	9.6	0.84	0.84	0.84	8.4	0.79	0.79	0.79	7.2	0.74	0.74	0.74	6.0	0.69	0.68	0.68	4.8	0.64	0.64	0.64	3.6	0.58	0.58	0.58	2.4	0.53	0.53	0.53	1.2	0.48	0.48	0.48	0.0	0.42	0.42	0.42	
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																							
12.0	0.94	0.94	0.94																																																							
11.4	0.92	0.92	0.92																																																							
10.8	0.89	0.89	0.89																																																							
9.6	0.84	0.84	0.84																																																							
8.4	0.79	0.79	0.79																																																							
7.2	0.74	0.74	0.74																																																							
6.0	0.69	0.68	0.68																																																							
4.8	0.64	0.64	0.64																																																							
3.6	0.58	0.58	0.58																																																							
2.4	0.53	0.53	0.53																																																							
1.2	0.48	0.48	0.48																																																							
0.0	0.42	0.42	0.42																																																							
Object	-12V0.75A	2.Values																																																								
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 90V Input Volt. 100V Input Volt. 110V</p>	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 90[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 110[V]</th> </tr> </thead> <tbody> <tr><td>-12.0</td><td>0.96</td><td>0.96</td><td>0.96</td></tr> <tr><td>-11.4</td><td>0.94</td><td>0.94</td><td>0.94</td></tr> <tr><td>-10.8</td><td>0.91</td><td>0.91</td><td>0.91</td></tr> <tr><td>-9.6</td><td>0.86</td><td>0.86</td><td>0.86</td></tr> <tr><td>-8.4</td><td>0.81</td><td>0.81</td><td>0.81</td></tr> <tr><td>-7.2</td><td>0.75</td><td>0.75</td><td>0.75</td></tr> <tr><td>-6.0</td><td>0.70</td><td>0.70</td><td>0.70</td></tr> <tr><td>-4.8</td><td>0.65</td><td>0.65</td><td>0.65</td></tr> <tr><td>-3.6</td><td>0.60</td><td>0.60</td><td>0.60</td></tr> <tr><td>-2.4</td><td>0.55</td><td>0.54</td><td>0.54</td></tr> <tr><td>-1.2</td><td>0.50</td><td>0.50</td><td>0.50</td></tr> <tr><td>0.0</td><td>0.44</td><td>0.44</td><td>0.44</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]	-12.0	0.96	0.96	0.96	-11.4	0.94	0.94	0.94	-10.8	0.91	0.91	0.91	-9.6	0.86	0.86	0.86	-8.4	0.81	0.81	0.81	-7.2	0.75	0.75	0.75	-6.0	0.70	0.70	0.70	-4.8	0.65	0.65	0.65	-3.6	0.60	0.60	0.60	-2.4	0.55	0.54	0.54	-1.2	0.50	0.50	0.50	0.0	0.44	0.44	0.44	
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 90[V]	Input Volt. 100[V]	Input Volt. 110[V]																																																							
-12.0	0.96	0.96	0.96																																																							
-11.4	0.94	0.94	0.94																																																							
-10.8	0.91	0.91	0.91																																																							
-9.6	0.86	0.86	0.86																																																							
-8.4	0.81	0.81	0.81																																																							
-7.2	0.75	0.75	0.75																																																							
-6.0	0.70	0.70	0.70																																																							
-4.8	0.65	0.65	0.65																																																							
-3.6	0.60	0.60	0.60																																																							
-2.4	0.55	0.54	0.54																																																							
-1.2	0.50	0.50	0.50																																																							
0.0	0.44	0.44	0.44																																																							
	Note: Slanted line shows the range of the rated load current.																																																									




Figure A