

Temperature increase of main components: 主要部品温度上昇

Model: GT3

1. Conditions

- (1) Input : AC 90 ~ 110 [V]
- (2) Output : Rated output
- (3) Mounting method : Shown as Fig.1.1

2. Result

	Parts name	Symbol	Increase (T)						Rated temp. []	Reference
			[deg]							
			5V	12V	15V	24V				
1	Rectifier(Main-Input)	SS1	49	51	46	39			150	Junction Temp.
2	Rectifier(Sub-Input)	SS21	25	25	24	23			150	Junction Temp.
3	Transformer	T1	43	41	41	43			120	
4	Input Capacitor(Main)	C2	30	26	25	23			105	
5	Input Capacitor(Sub)	C21	26	25	24	23			105	
6	Fet(Main)	TR1	59	63	60	59			150	Junction Temp.
7	Transistor(Sub)	TR21	29	29	28	27			150	Junction Temp.
8	Voltage Regulator	IC21	26	26	25	24			150	Junction Temp.
9	Power Control Ic	IC22	37	37	36	35			150	Junction Temp.
10	Output Capacitor	C6	24	22	22	21			105	
11										
12										
13										
14										
15										
16										
17										
18										
19										
20										




Fig.1.1 Mounting method (Normal position)

*All information presented herein are not guaranteed.
 *本資料は参考資料であり、その内容を保証するものではありません。